

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

Telephone: +86-755-26648640 Fax: +86-755-26648637

Website: <u>www.cqa-cert.com</u>

. . .

Report Template Version: V04

Report Template Revision Date: 2018-07-06

RF Exposure Evaluation Report

Report No.: CQASZ20220601018E-02

Applicant: TOPWAY EM ENTERPRISE LTD.

Address of Applicant: 8F BLOCK B BUILDING 6 BAONENG S & T PARK LONG HUA, SHENZHEN

GD, China 518109

Equipment Under Test (EUT):

EUT Name: BLUETOOTH HEADPHONES

Model No.: 19BF18, Z01, TP-BF02

Test Model No.: 19BF18

Brand Name: N/A

 FCC ID:
 2AKI8-TP-BF02

 Standards:
 47 CFR Part 1.1307

 47 CFR Part 2.1093

KDB447498D01 General RF Exposure Guidance v06

Date of Receipt: 2020-06-12

Date of Test: 2020-06-12 to 2020-06-24

Date of Issue: 2022-8-19
Test Result: PASS*

*In the configuration tested, the EUT complied with the standards specified above

Tested By:

(Timo Lei)

Reviewed By:

(K Liao)

Approved By: (Jack Ai)

TESTING TECHNOLOGY
LESTING TECHNOLOGY
LESTING TECHNOLOGY
APPROVED
APPROVED

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of CQA, this report can't be reproduced except in full.



Report No.: CQASZ20220601018E-02

Version

Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ20220601018E-02	Rev.01	Initial report	2022-8-19

Note:

This test report (Ref. No.: CQASZ20220601018E-02)

All test data comes from source test reports (Ref. No.: CQASZ20200600522E-02).

Only on the basis of the original report Change EUT Name, Model No.. The tested samples have not been changed.





Report No.: CQASZ20220601018E-02

1 Contents

		Page
1	VERSION	2
2	2 CONTENTS	3
3	B GENERAL INFORMATION	4
	3.1 CLIENT INFORMATION	4
4	SAR EVALUATION	5
	4.1 RF EXPOSURE COMPLIANCE REQUIREMENT	5 5
	4.1.3 EUT RF Exposure	6



Report No.: CQASZ20220601018E-02

2 General Information

2.1 Client Information

Applicant:	TOPWAY EM ENTERPRISE LTD.	
Address of Applicant:	8F BLOCK B BUILDING 6 BAONENG S & T PARK LONG HUA, SHENZHEN GD, China 518109	
Manufacturer:	TOPWAY EM ENTERPRISE LTD.	
Address of Manufacturer:	8F BLOCK B BUILDING 6 BAONENG S & T PARK LONG HUA, SHENZHEN GD, China 518109	
Factory:	Shenzhen Jia Hua Li Dian Zi You Xian Gong Si	
Address of Factory:	NO 101,201, BUILDING E, NEW INDUSTRIAL ZONE, SHENZHU ROAD, LIUYUE SHENKENG VILLAGE, HENGGANG, LONGGANG DISTRICT, SHENZHEN CHINA.	

2.2 General Description of EUT

Product Name:	BLUETOOTH HEADPHONES	
Model No.:	19BF18, Z01, TP-BF02	
Test Model No.:	19BF18	
Trade Mark:	N/A	
Hardware Version:	V1.2	
Software Version:	Vesion 1_V35	
Operation Frequency:	2402MHz~2480MHz	
Bluetooth Version:	V5.0	
Modulation Technique:	Frequency Hopping Spread Spectrum(FHSS)	
Modulation Type:	GFSK, π/4DQPSK, 8DPSK	
Number of Channel:	79	
Transfer Rate:	1Mbps/2Mbps/3Mbps	
Hopping Channel Type:	Adaptive Frequency Hopping systems	
Sample Type:	☐ Mobile ☐ Portable ☐ Fix Location	
Test Software of EUT:	Blue test3 (manufacturer declare)	
Antenna Type:	PCB antenna	
Antenna Gain:	4dBi	
Power Supply:	lithium battery:DC 3.7V, 410mAh, Charge by DC 5.0V	

Note:

Model No.: 19BF18, Z01, TP-BF02.

Only the model 19BF18 was tested, since the electrical circuit design, layout, components used and internal wiring were identical for the above models, with difference being color of appearance and model name.



Report No.: CQASZ20220601018E-02

3 SAR Evaluation

3.1 RF Exposure Compliance Requirement

3.1.1 Standard Requirement

According to KDB447498D01 General RF Exposure Guidance v06

4.3.1. Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

3.1.2 Limits

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] $\sqrt{f(GHz)} \le 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

f(GHz) is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation¹⁷

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is \leq 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is \leq 5 mm, a distance of 5 mm is applied to determine SAR test exclusion



Report No.: CQASZ20220601018E-02

3.1.3 EUT RF Exposure

Measurement Data

GFSK mode						
Test channel	Peak Output Power	Tune up tolerance	Maximum tune-up Power			
	(dBm)	(dBm)	(dBm)	(mW)		
Lowest(2402MHz)	-3.960	-4.5±1	-3.5	0.447		
Middle(2441MHz)	-3.310	-4.0±1	-3.0	0.501		
Highest(2480MHz)	-2.890	-3.5±1	-2.5	0.562		
	π/4DQPSK mode					
Test channel	Peak Output Power	Tune up tolerance	Maximum tur	ne-up Power		
	(dBm)	(dBm)	(dBm)	(mW)		
Lowest(2402MHz)	-2.630	-3.5±1	-2.5	0.562		
Middle(2441MHz)	-2.060	-3.0±1	-2.0	0.708		
Highest(2480MHz)	-1.610	-2.5±1	-1.5	0.708		
	8DPSK	mode				
Test channel	Peak Output Power	Tune up tolerance	Maximum tune-up Powe			
	(dBm)	(dBm)	(dBm)	(mW)		
Lowest(2402MHz)	-2.420	-3.0±1	-2.0	0.631		
Middle(2441MHz)	-1.810	-2.5±1	5±1 -1.5			
Highest(2480MHz)	-1.380	-2.0±1	-1.0	0.794		

Worst case: 8DPSK						
Channel	Maximum Peak Conducted Tune up tolerance	Maximum tune- up Power		Calculated	Exclusion	
	Output Power (dBm)	(dBm)	(dBm)	(mW)	value	threshold
Lowest (2402MHz)	-2.420	-3.0±1	-2.0	0.562	0.174	
Middle (2441MHz)	-1.810	-2.5±1	-1.5	0.708	0.221	3.0
Highest (2480MHz)	-1.380	-2.0±1	-1.0	0.708	0.223	
Conclusion: the calculated value ≤3.0, SAR is exempted.						

Remark: The Max Conducted Peak Output Power data refer to report Report No.: CQASZ20220601018E-01.