



Excellence in Compliance Testing

---

## **Certification Exhibit**

**FCC ID: 2AKILBX050  
IC: 22194-BX050**

**FCC Rule Part: 15.247  
ISED Canada Radio Standards Specification: RSS-247**

**ACS Project Number: 16-2074**

**Manufacturer: Creed Monarch, Inc.  
Model: BX050**

## **RF Exposure**

**General Information:**

Applicant: Creed Monarch, Inc.  
 ACS Project: 16-2074  
 Device Category: Mobile  
 Environment: General Population/Uncontrolled Exposure

**Technical Information:**

Antenna Type: Helical SMD Antenna  
 Antenna Gain: 0.8 dBi  
 Maximum Transmitter Conducted Power: 7.92 dBm, 6.2 mW  
 Maximum System EIRP: 8.72 dBm, 7.45 mW  
 Exposure Conditions: Greater than 20 centimeters

**MPE Calculation**

The Power Density (mW/cm<sup>2</sup>) is calculated as follows:

$$S = \frac{PG}{4\pi R^2}$$

Where:

- S = power density (in appropriate units, e.g. mW/cm<sup>2</sup>)
- P = power input to the antenna (in appropriate units, e.g., mW)
- G = power gain of the antenna in the direction of interest relative to an isotropic radiator
- R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

**Table 1: FCC Requirements**

MPE Calculator for Mobile Equipment Limits for General Population/Uncontrolled Exposure*							
Transmit Frequency (MHz)	Radio Power (dBm)	Power Density Limit (mW/Cm2)	Radio Power (mW)	Antenna Gain (dBi)	Antenna Gain (mW eq.)	Distance (cm)	Power Density (mW/cm^2)
922.4	7.92	0.61	6.19	0.8	1.202	20	0.001

**Table 2: Innovation Science Economic Development Canada Requirements**

MPE Calculator for Mobile Equipment Limits for General Population/Uncontrolled Exposure*							
Transmit Frequency (MHz)	Radio Power (dBm)	Power Density Limit (W/m2)	Radio Power (mW)	Antenna Gain (dBi)	Antenna Gain (mW eq.)	Distance (cm)	Power Density (W/m^2)
922.4	7.92	2.78	6.19	0.8	1.202	20	0.015

**Installation Guidelines**

The installation manual should contain text similar to the following advising how to install the equipment to maintain compliance with the FCC RF exposure requirements:

**RF Exposure**

In accordance with FCC requirements of human exposure to radio frequency fields, the radiating element shall be installed such that a minimum separation distance of 20 centimeters will be maintained.

**Conclusion**

This device complies with the MPE requirements by providing adequate separation between the device, any radiating structure and the general population.