

# Test Report

Verified code: 614324

Report No.: E20240129370001-10

Customer: Lumi United Technology Co., Ltd

Address: B1, Chongwen Park, Nanshan iPark, Liuxian Avenue, Taoyuan Residential District, Nanshan District, Shenzhen, China

Sample Name: Aqara Smart Lock U200

Sample Model: EL-D02D

Receive Sample Date: Feb.01,2024

Test Date: Feb.02,2024 ~ Feb.29,2024

Reference Document: 47 CFR, FCC Part 2.1091 Radio frequency radiation exposure evaluation: mobile devices

Test Result: Pass

Prepared by: Chen Xiacong  
Chen Xiacong

Reviewed by: Jiang Tao  
Jiang Tao

Approved by: Xiao Liang  
Xiao Liang

GRG METROLOGY & TEST GROUP CO., LTD.

Issued Date: 2024-04-01

GRG METROLOGY & TEST GROUP CO., LTD.

Address: No.163,Pingyun Road, West of Huangpu Avenue, Guangzhou, Guangdong, China  
Tel: (+86) 400-602-0999 FAX: (+86) 020-38698685 Web: <http://www.grgtest.com>



## Statement

1. The report is invalid without "special seal for inspection and testing"; some copies are invalid; The report is invalid if it is altered or missing; The report is invalid without the signature of the person who prepared, reviewed and approved it.
2. The sample information is provided by the client and responsible for its authenticity; The content of the report is only valid for the samples sent this time.
3. When there are reports in both Chinese and English, the Chinese version will prevail when the language problems are inconsistent.
4. If there is any objection concerning the report, please inform us within 15 days from the date of receiving the report.
5. Without the agreement of the laboratory, the client is not authorized to use the test results for unapproved propaganda.

----- The following blanks -----

## TABLE OF CONTENTS

1.	GENERAL DESCRIPTION OF EUT.....	5
1.1	APPLICANT.....	5
1.2	MANUFACTURER.....	5
1.3	BASIC DESCRIPTION OF EQUIPMENT UNDER TEST.....	5
2.	LABORATORY.....	6
2.1	LABORATORY.....	6
2.2	ACCREDITATIONS.....	6
3.	LIMITS FOR GENERAL POPULATION/UNCONTROLLED EXPOSURE.....	7
4.	CALCULATION METHOD.....	8
5.	ESTIMATION RESULT.....	9
5.1	MEASUREMENT RESULTS.....	9
6.	CONCLUSION.....	10

----- The following blanks -----

**REPORT ISSUED HISTORY**

Report Version	Report No.	Description	Compile Date
1.0	E20240129370001-10	Original Issue	2024-03-11

----- The following blanks -----

**1. GENERAL DESCRIPTION OF EUT**

**1.1 APPLICANT**

Name: Lumi United Technology Co., Ltd  
 Address: B1, Chongwen Park, Nanshan iPark, Liuxian Avenue, Taoyuan Residential District, Nanshan District, Shenzhen, China

**1.2 MANUFACTURER**

Name: Lumi United Technology Co., Ltd  
 Address: B1, Chongwen Park, Nanshan iPark, Liuxian Avenue, Taoyuan Residential District, Nanshan District, Shenzhen, China

**1.3 BASIC DESCRIPTION OF EQUIPMENT UNDER TEST**

Equipment: Aqara Smart Lock U200  
 Model No.: EL-D02D  
 Adding Model: EL-D02E

The model NO. EL-D02D & EL-D02E have the same technical construction including circuit diagram, PCB LAYOUT, hardware version and software version identical, except the model name and powered are different due to the sales area .

Models Difference:

Product Name	Model No.	Powered	Sales Area
Aqara Smart Lock U200	EL-D02D	Dry Battery+ Lithium battery	Sales entities
	EL-D02E	Lithium battery	Sales on line

Trade Name: Aqara  
 FCC ID: 2AKIT-ELD02  
 Power supply: 4 LR6 AA 1.5V Batteries(Dry Battery, DC 6V) or 7.4V battery(Lithium battery)  
 Frequency Band: 2402MHz - 2480MHz for Bluetooth LE with 1M&2M  
 2405MHz - 2480MHz for Thread  
 Transmit Power: BLE for 1Mbps:7.73dBm, BLE for 2Mbps:7.73dBm,Thread: 7.23dBm  
 Modulation type: GFSK for BLE, O-QPSK for Thread  
 Antenna Specification: BLE:Antenna 1: 0.82dBi gain (Max)  
 Thread:Antenna 1: 0.82dBi gain (Max)  
 Temperature Range: -15 °C ~ 66 °C  
 Hardware Version: V2.1  
 Software Version: V0019  
 Sample No: E20240129370001-0007

Note 1: The EUT antenna gain is provided by the applicant. This report is made solely on the basis of such data and/or information. We accept no responsibility for the authenticity and completeness of the above data and information and the validity of the results and/or conclusions.

Note 2: The Maximum peak output power were performed on the EL-D02D model.

## 2. LABORATORY

### 2.1 LABORATORY

The tests & measurements refer to this report were performed by Shenzhen EMC Laboratory of GRG METROLOGY & TEST GROUP CO., LTD.

Add.: No.1301 Guanguang Road Xinlan Community, Guanlan Street, Longhua District  
Shenzhen, 518110, People's Republic of China.

P.C.: 518110

Tel : 0755-61180008

Fax: 0755-61180008

### 2.2 ACCREDITATIONS

Our laboratories are accredited and approved by the following approval agencies according to GB/T 27025(ISO/IEC 17025:2017)

**USA** A2LA(Certificate #2861.01)

The measuring facility of laboratories has been authorized or registered by the following approval agencies.

**Canada** ISED (Company Number: 24897, CAB identifier:CN0069)

**USA** FCC (Registration Number: 759402, Designation Number:CN1198)

Copies of granted accreditation certificates are available for downloading from our web site,

<http://www.grgtest.com>

----- The following blanks -----

### 3. LIMITS FOR GENERAL POPULATION/UNCONTROLLEDEXPOSURE

#### General

According to the KDB 447498 D04 Interim General RF Exposure Guidance v01, General frequency and separation-distance dependent MPE-based effective radiated power (ERP) thresholds are in Table 4.1 to support an exemption from further evaluation from 300 kHz through 100 GHz.

TABLE 4.1—THRESHOLDS FOR SINGLE RF SOURCES SUBJECT TO ROUTINE ENVIRONMENTAL EVALUATION

RF Source Frequency			Minimum Distance			Threshold ERP
$f_L$ MHz		$f_H$ MHz	$\lambda_L / 2\pi$		$\lambda_H / 2\pi$	W
0.3	–	1.34	159 m	–	35.6 m	$1,920 R^2$
1.34	–	30	35.6 m	–	1.6 m	$3,450 R^2/f^2$
30	–	300	1.6 m	–	159 mm	$3.83 R^2$
300	–	1,500	159 mm	–	31.8 mm	$0.0128 R^2 f$
1,500	–	100,000	31.8 mm	–	0.5 mm	$19.2 R^2$

Subscripts L and H are low and high;  $\lambda$  is wavelength.  
From § 1.1307(b)(3)(i)(C), modified by adding Minimum Distance columns.

For mobile devices that are not exempt per Table 4.1 at distances from 20 cm to 40 cm and in 0.3 GHz to 6 GHz, evaluation of compliance with the exposure limits in §1.1310 is necessary if the ERP of the device is greater than  $ERP_{20\text{cm}}$  in Formula (4.1).

Formula (4.1):

$$P_{\text{th}} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

#### 4. CALCULATION METHOD

Predication of MPE limit at a given distance

$EIRP(dBm) = \text{Maximum Tune-up Output power (dBm)} + \text{Maximum antenna gain(dBi)}$

$ERP(dBm) = EIRP(dBm) - 2.15$

R=minimum distance to the center of radiation of the antenna

From the EUT RF output power, the minimum mobile separation distance,  $d=20\text{cm}$ , as well as the maximum gain of the used as following information, the RF power ERP can be obtained.

**Table 1 Antenna Specification**

Mode	Antenna type	Internal Identification	Maximum antenna gain
BLE 1M	PIFA antenna	Antenna 1	0.82dBi
BLE 2M	PIFA antenna	Antenna 1	0.82dBi
Thread	PIFA antenna	Antenna 1	0.82dBi

**Table 2 Transmit Power**

Mode	Maximum Output Power (dBm)	Maximum Tune-up Output power (dBm)
BLE 1M	7.73	$7.00 \pm 1.00$
BLE 2M	7.73	$7.00 \pm 1.00$
Thread	7.23	$7.00 \pm 1.00$

----- The following blanks -----



## 5. ESTIMATION RESULT

### 5.1 MEASUREMENT RESULTS

#### STANDALONE MPE

Mode	Frequency (MHz)	Maximum Tune-up Output power (dBm)	Antenna Gain (dBi)	Maximum Tune-up EIRP (dBm)	ERP (dBm)	Maximum Tune-up ERP (W)	Threshold ERP(W)
BLE 1M	2402- 2480	8.00	0.82	8.82	6.67	0.00465	0.768
BLE 2M	2402- 2480	8.00	0.82	8.82	6.67	0.00465	0.768
Thread	2405-2480	8.00	0.82	8.82	6.67	0.00465	0.768

Remark:

1. RF Exposure use distance is 20cm from manufacturer declaration of user manual.
2. Threshold  $ERP(W) = 19.2R^2(W) = 19.2 * 0.2^2(W) = 0.768(W)$ .
3. The BLE and Thread do not support simultaneous transmission.
4.  $ERP(dBm) = EIRP(dBm) - 2.15$ .

----- The following blanks -----

## 6. CONCLUSION

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.

----- End of Report -----

5/17/24