

# TEST REPORT

Reference No..... : WTX20X06041391W-1  
FCC ID ..... : 2AKIT-HM1S-G01  
Applicant ..... : Lumi United Technology Co., Ltd  
Address ..... : 8th Floor, JinQi Wisdom Valley, No.1 Tangling Road, Liuxian Ave, Taoyuan Residential District, Nanshan District, Shenzhen.China.  
Product Name ..... : Hub M1S  
Test Model. .... : HM1S-G01  
Standards ..... : FCC Part 15C  
Date of Receipt sample .... : Jun.30, 2020  
Date of Test..... : Jun.30, 2020 to Jul.27, 2020  
Date of Issue ..... : Jul.27, 2020  
Test Result..... : **Pass**

Remarks:

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

**Prepared By:**

**Waltek Testing Group (Shenzhen) Co., Ltd.**

Address: 1/F., Room 101, Building 1, Hongwei Industrial Park, Liuxian 2nd Road,  
Block 70 Bao'an District, Shenzhen, Guangdong, China

Tel.: +86-755-33663308

Fax.: +86-755-33663309

Tested by:

*Jack Huang*

Jack Huang / Project Engineer

Reviewed By:

*Lion Cai*

Lion Cai / RF Manager

Approved & Authorized By:

*Silin Chen*

Silin Chen / Manager

**TABLE OF CONTENTS**

<b>1. GENERAL INFORMATION</b>	<b>4</b>
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
1.2 TEST STANDARDS	5
1.3 TEST METHODOLOGY	5
1.4 TEST FACILITY	5
1.5 EUT SETUP AND TEST MODE	6
1.6 MEASUREMENT UNCERTAINTY	7
1.7 TEST EQUIPMENT LIST AND DETAILS	8
<b>2. SUMMARY OF TEST RESULTS</b>	<b>10</b>
<b>3. RF EXPOSURE</b>	<b>11</b>
3.1 STANDARD APPLICABLE	11
3.2 TEST RESULT	11
<b>4. ANTENNA REQUIREMENT</b>	<b>12</b>
4.1 STANDARD APPLICABLE	12
4.2 EVALUATION INFORMATION	12
<b>5. POWER SPECTRAL DENSITY</b>	<b>13</b>
5.1 STANDARD APPLICABLE	13
5.2 TEST SETUP BLOCK DIAGRAM	13
5.3 TEST PROCEDURE	13
5.4 SUMMARY OF TEST RESULTS/PLOTS	13
<b>6. DTS BANDWIDTH</b>	<b>23</b>
6.1 STANDARD APPLICABLE	23
6.2 TEST SETUP BLOCK DIAGRAM	23
6.3 TEST PROCEDURE	23
6.4 SUMMARY OF TEST RESULTS/PLOTS	23
<b>7. RF OUTPUT POWER</b>	<b>33</b>
7.1 STANDARD APPLICABLE	33
7.2 TEST SETUP BLOCK DIAGRAM	33
7.3 TEST PROCEDURE	33
7.4 SUMMARY OF TEST RESULTS/PLOTS	33
<b>8. FIELD STRENGTH OF SPURIOUS EMISSIONS</b>	<b>43</b>
8.1 STANDARD APPLICABLE	43
8.2 TEST PROCEDURE	43
8.3 CORRECTED AMPLITUDE & MARGIN CALCULATION	45
8.4 SUMMARY OF TEST RESULTS/PLOTS	45
<b>9. OUT OF BAND EMISSIONS</b>	<b>53</b>
9.1 STANDARD APPLICABLE	53
9.2 TEST PROCEDURE	53
9.3 SUMMARY OF TEST RESULTS/PLOTS	54
<b>10. CONDUCTED EMISSIONS</b>	<b>87</b>
10.1 TEST PROCEDURE	87
10.2 BASIC TEST SETUP BLOCK DIAGRAM	87
10.3 TEST RECEIVER SETUP	87
10.4 SUMMARY OF TEST RESULTS/PLOTS	87

**Report version**

Version No.	Date of issue	Description
Rev.00	Jul.27, 2020	Original
/	/	/

## 1. GENERAL INFORMATION

---

### 1.1 Product Description for Equipment Under Test (EUT)

#### Client Information

Applicant: Lumi United Technology Co., Ltd  
 Address of applicant: 8th Floor, JinQi Wisdom Valley, No.1 Tangling Road, Liuxian Ave, Taoyuan Residential District, Nanshan District, Shenzhen.China.

Manufacturer: Lumi United Technology Co., Ltd  
 Address of manufacturer: 8th Floor, JinQi Wisdom Valley, No.1 Tangling Road, Liuxian Ave, Taoyuan Residential District, Nanshan District, Shenzhen.China.

General Description of EUT	
Product Name:	Hub M1S
Trade Name:	Aqara
Model No.:	HM1S-G01
Adding Model(s):	/
Rated Voltage:	AC 120V, 60Hz, 0.2A
Power Adapter Model:	/
Software Version:	V1.0.0
Hardware Version:	LM19-SGY-CN-T2
<i>Note: The test data is gathered from a production sample provided by the manufacturer.</i>	

Technical Characteristics of EUT	
Support Standards:	802.11b, 802.11g, 802.11n
Frequency Range:	2412-2462MHz for 802.11b/g/n(HT20) 2422-2452MHz for 802.11n(HT40)
RF Output Power:	18.45dBm (Conducted)
Type of Modulation:	DBPSK,BPSK,DQPSK,QPSK,16QAM,64QAM
Data Rate:	1-11Mbps, 6-54Mbps, up to 300Mbps
Quantity of Channels:	11 for 802.11b/g/n(HT20); 7 for 802.11n(HT40)
Channel Separation:	5MHz
Type of Antenna:	ANT1: FPC Antenna ANT2: PCB Antenna
Antenna Gain:	2.0dBi

## 1.2 Test Standards

The tests were performed according to following standards:

**FCC Rules Part 15.247**: Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz.

**558074 D01 15.247 Meas Guidance v05r02**: Guidance for Compliance Measurements on Digital Transmission System, Frequency Hopping Spread Spectrum System, and Hybrid System Devices Operating under section 15.247 of the Fcc rules.

**662911 D01 Multiple Transmitter Output v02r01**: Emissions Testing of Transmitters with Multiple Outputs in the Same Band.

**ANSI C63.10-2013**: American National Standard for Testing Unlicensed Wireless Devices.

**Maintenance of compliance** is the responsibility of the manufacturer. Any modification of the product, which result in lowering the emission, should be checked to ensure compliance has been maintained.

## 1.3 Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, KDB 558074 D01 15.247 Meas Guidance v05r02, KDB 662911 D01 Multiple Transmitter Output v02r01

The equipment under test (EUT) was configured to measure its highest possible emission level. The test modes were adapted accordingly in reference to the Operating Instructions.

## 1.4 Test Facility

### Address of the test laboratory

Laboratory: Waltek Testing Group (Shenzhen) Co., Ltd.

Address: 1/F., Room 101, Building 1, Hongwei Industrial Park, Liuxian 2nd Road, Block 70 Bao'an District, Shenzhen, Guangdong, China

### FCC – Registration No.: 125990

Waltek Testing Group (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. The Designation Number is CN5010, and Test Firm Registration Number is 125990.

### Industry Canada (IC) Registration No.: 11464A

The 3m Semi-anechoic chamber of Waltek Testing Group (Shenzhen) Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 11464A.

## 1.5 EUT Setup and Test Mode

Use “QCOM\_V1.0.exe” and follow the instructions given by the manufacturer, you can start to test. During testing, Channel and Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. Test use the customer default power level, with a duty cycle equal to 100%, and to measure its highest possible emissions level, more detailed description as follows:

Test Mode List		
Test Mode	Description	Remark
TM1	802.11b	Low:2412MHz, Middle:2437MHz,High:2462MHz
TM2	802.11g	Low:2412MHz, Middle:2437MHz,High:2462MHz
TM3	802.11n-HT20	Low:2412MHz, Middle:2437MHz,High:2462MHz
TM4	802.11n-HT40	Low:2422MHz, Middle:2437MHz,High:2452MHz

Test Conditions	
Temperature:	22~25 °C
Relative Humidity:	50~55 %.
ATM Pressure:	1019 mbar

EUT Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
/	/	/	/

Special Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
/	/	/	/

Auxiliary Equipment List and Details			
Description	Manufacturer	Model	Serial Number
Wireless switch T1	Lumi	WXKG13LM	/
Mobile phone	HUAWEI	VOG-AL00	/
Notebook	Lenovo	E445	EB12648265

## 1.6 Measurement Uncertainty

Measurement uncertainty		
Parameter	Conditions	Uncertainty
RF Output Power	Conducted	$\pm 0.42\text{dB}$
Occupied Bandwidth	Conducted	$\pm 1.5\%$
Power Spectral Density	Conducted	$\pm 1.8\text{dB}$
Conducted Spurious Emission	Conducted	$\pm 2.17\text{dB}$
Conducted Emissions	Conducted	9-150kHz $\pm 3.74\text{dB}$
		0.15-30MHz $\pm 3.34\text{dB}$
Transmitter Spurious Emissions	Radiated	30-200MHz $\pm 4.52\text{dB}$
		0.2-1GHz $\pm 5.56\text{dB}$
		1-6GHz $\pm 3.84\text{dB}$
		6-18GHz $\pm 3.92\text{dB}$

**1.7 Test Equipment List and Details**

No.	Description	Manufacturer	Model	Serial No.	Cal Date	Due Date
SEMT-1072	Spectrum Analyzer	Agilent	E4407B	MY41440400	2020-04-28	2021-04-27
SEMT-1031	Spectrum Analyzer	Rohde & Schwarz	FSP30	836079/035	2020-04-28	2021-04-27
SEMT-1007	EMI Test Receiver	Rohde & Schwarz	ESVB	825471/005	2020-04-28	2021-04-27
SEMT-1008	Amplifier	Agilent	8447F	3113A06717	2020-04-28	2021-04-27
SEMT-1043	Amplifier	C&D	PAP-1G18	2002	2020-04-28	2021-04-27
SEMT-1011	Broadband Antenna	Schwarz beck	VULB9163	9163-333	2019-05-05	2021-05-04
SEMT-1042	Horn Antenna	ETS	3117	00086197	2019-05-05	2021-05-04
SEMT-1121	Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170582	2019-05-05	2021-05-04
SEMT-1069	Loop Antenna	Schwarz beck	FMZB 1516	9773	2019-05-05	2021-05-04
SEMT-1001	EMI Test Receiver	Rohde & Schwarz	ESPI	101611	2020-04-28	2021-04-27
SEMT-1003	L.I.S.N	Schwarz beck	NSLK8126	8126-224	2020-04-28	2021-04-27
SEMT-1002	Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100911	2020-04-28	2021-04-27
SEMT-1168	Pre-amplifier	Direction Systems Inc.	PAP-0126	14141-12838	2020-04-28	2021-04-27
SEMT-1169	Pre-amplifier	Direction Systems Inc.	PAP-2640	14145-14153	2020-04-28	2021-04-27
SEMT-1163	Spectrum Analyzer	Rohde & Schwarz	FSP40	100612	2020-04-28	2021-04-27
SEMT-1170	DRG Horn Antenna	A.H. SYSTEMS	SAS-574	571	2019-05-05	2021-05-04
SEMT-1166	Power Limiter	Agilent	N9356B	MY45450376	2020-04-28	2021-04-27
SEMT-1048	RF Limiter	ATTEN	AT-BSF-2400~2500	/	2020-04-28	2021-04-27
SEMT-1076	RF Switcher	Top Precision	RCS03-A2	/	2020-04-28	2021-04-27
SEMT-C001	Cable	Zheng DI	LL142-07-07-10M(A)	/	2020-03-17	2021-03-16
SEMT-C002	Cable	Zheng DI	ZT40-2.92J-2.92J-6M	/	2020-03-17	2021-03-16
SEMT-C003	Cable	Zheng DI	ZT40-2.92J-2.92J-2.5M	/	2020-03-17	2021-03-16
SEMT-C004	Cable	Zheng DI	2M0RFC	/	2020-03-17	2021-03-16
SEMT-C005	Cable	Zheng DI	1M0RFC	/	2020-03-17	2021-03-16
SEMT-C006	Cable	Zheng DI	1M0RFC	/	2020-03-17	2021-03-16



<b>Software List</b>			
<b>Description</b>	<b>Manufacturer</b>	<b>Model</b>	<b>Version</b>
EMI Test Software (Radiated Emission)*	Farad	EZ-EMC	RA-03A1
EMI Test Software (Conducted Emission)*	Farad	EZ-EMC	RA-03A1

\*Remark: indicates software version used in the compliance certification testing

## 2. SUMMARY OF TEST RESULTS

---

<b>FCC Rules</b>	<b>Description of Test Item</b>	<b>Result</b>
§2.1091	RF Exposure	Compliant
§15.203; §15.247(b)(4)(i)	Antenna Requirement	Compliant
§15.205	Restricted Band of Operation	Compliant
§15.207(a)	Conducted Emission	Compliant
§15.247(e)	Power Spectral Density	Compliant
§15.247(a)(2)	DTS Bandwidth	Compliant
§15.247(b)(3)	RF Output Power	Compliant
§15.209(a)	Radiated Emission	Compliant
§15.247(d)	Band Edge (Out of Band Emissions)	Compliant

N/A: Not applicable

### **3. RF Exposure**

---

#### **3.1 Standard Applicable**

According to §1.1307 and §2.1091, the mobile transmitter must comply the RF exposure requirements.

#### **3.2 Test Result**

This product complied with the requirement of the RF exposure, please see the RF Exposure Report.

## **4. Antenna Requirement**

---

### **4.1 Standard Applicable**

According to FCC Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

### **4.2 Evaluation Information**

This product has two antennas; a FPC Antenna and a PCB Antenna, fulfill the requirement of this section.


## 5. Power Spectral Density

---

### 5.1 Standard Applicable

According to 15.247(a)(1)(iii), for digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

### 5.2 Test Setup Block Diagram



### 5.3 Test Procedure

According to the KDB 558074 D01 v05r02 Subclause 8.4 and ANSI C63.10-2013 Subclause 11.10.3, such specifications require that the same method as used to determine the conducted output power shall also be used to determine the power spectral density. The test method of power spectral density as below:




- Set instrument center frequency to DTS channel center frequency.
- Set span to at least 1.5 times the OBW.
- Set RBW to:  $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$ .
- Set VBW  $\geq 3 \times \text{RBW}$ .
- Detector = power averaging (RMS) or sample detector (when RMS not available).
- Ensure that the number of measurement points in the sweep  $\geq 2 \times \text{span}/\text{RBW}$ .
- Sweep time = auto couple.
- Employ trace averaging (RMS) mode over a minimum of 100 traces.
- Use the peak marker function to determine the maximum amplitude level.
- If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat (note that this may require zooming in on the emission of interest and reducing the span in order to meet the minimum measurement point requirement as the RBW is reduced).

### 5.4 Summary of Test Results/Plots


Test Mode	Test Channel MHz	Test Result(dBm/3kHz)		Total dBm	Limit dBm/3kHz
		Antenna A	Antenna B		
802.11b_11Mbps	2412	-19.82	-19.40	/	8
	2437	-19.43	-19.42	/	8
	2462	-19.64	-19.66	/	8
802.11g_54Mbps	2412	-21.88	-21.07	/	8
	2437	-22.10	-21.12	/	8
	2462	-21.25	-20.83	/	8
802.11n-HT20_MCS7	2412	-20.38	-20.17	-17.26	8
	2437	-20.23	-20.31	-17.26	8
	2462	-20.36	-19.91	-17.12	8
802.11n-HT40_MCS7	2422	-26.62	-25.82	-23.19	8
	2437	-25.88	-25.70	-22.78	8
	2452	-25.83	-25.42	-22.61	8

Please refer to the following test plots:

➤ Antenna A


<p>802.11b-Low</p>	 <p>The plot shows a spectrum centered at 2.412 GHz with a 30 MHz span. The y-axis represents power in dBm, ranging from -90 to 10. The signal is a multi-carrier waveform with a peak level of -19.82 dBm. Parameters include RBW 3 kHz, VBW 10 kHz, Att 20 dB, and SWT 3.4 s. A marker is placed at the peak.</p> <p>Date: 13.JUL.2020 14:26:25</p>
<p>802.11b-Middle</p>	 <p>The plot shows a spectrum centered at 2.437 GHz with a 30 MHz span. The y-axis represents power in dBm, ranging from -90 to 10. The signal is a multi-carrier waveform with a peak level of -19.43 dBm. Parameters include RBW 3 kHz, VBW 10 kHz, Att 20 dB, and SWT 3.4 s. A marker is placed at the peak.</p> <p>Date: 13.JUL.2020 14:36:03</p>
<p>802.11b-High</p>	 <p>The plot shows a spectrum centered at 2.462 GHz with a 30 MHz span. The y-axis represents power in dBm, ranging from -90 to 10. The signal is a multi-carrier waveform with a peak level of -19.64 dBm. Parameters include RBW 3 kHz, VBW 10 kHz, Att 20 dB, and SWT 3.4 s. A marker is placed at the peak.</p> <p>Date: 13.JUL.2020 14:43:08</p>

802.11g-Low




Date: 20.JUL.2020 16:55:09

802.11g-Middle



Date: 20.JUL.2020 17:01:36


802.11g-High



Date: 13.JUL.2020 15:04:31




802.11n-HT20-Low




Date: 20.JUL.2020 16:48:32

802.11n-HT20-Middle




Date: 13.JUL.2020 15:19:24

802.11n-HT20-High




Date: 13.JUL.2020 15:26:24

802.11n-HT40-Low




Date: 20.JUL.2020 16:41:22

802.11n-HT40-Middle






Date: 20.JUL.2020 16:29:15

802.11n-HT40-High




Date: 20.JUL.2020 16:16:59

➤ Antenna B


<p>802.11b-Low</p>	 <p>Ref 10 dBm Att 20 dB RBW 3 kHz Marker 1 [T1] -19.40 dBm VBW 10 kHz SWT 3.4 s 2.411280000 GHz</p> <p>10 Offset 1 dB</p> <p>Center 2.412 GHz 3 MHz/ Span 30 MHz</p> <p>Date: 20.JUL.2020 17:19:01</p>
<p>802.11b-Middle</p>	 <p>Ref 10 dBm Att 20 dB RBW 3 kHz Marker 1 [T1] -19.42 dBm VBW 10 kHz SWT 3.4 s 2.436310000 GHz</p> <p>10 Offset 1 dB</p> <p>Center 2.437 GHz 3 MHz/ Span 30 MHz</p> <p>Date: 20.JUL.2020 17:25:45</p>
<p>802.11b-High</p>	 <p>Ref 10 dBm Att 20 dB RBW 3 kHz Marker 1 [T1] -19.66 dBm VBW 10 kHz SWT 3.4 s 2.461280000 GHz</p> <p>10 Offset 1 dB</p> <p>Center 2.462 GHz 3 MHz/ Span 30 MHz</p> <p>Date: 20.JUL.2020 17:33:23</p>

802.11g-Low




Date: 20.JUL.2020 17:39:55

802.11g-Middle




Date: 20.JUL.2020 17:46:14

802.11g-High




Date: 20.JUL.2020 17:52:38

802.11n-HT20-Low




Date: 20.JUL.2020 17:59:10

802.11n-HT20-Middle




Date: 20.JUL.2020 18:05:42

802.11n-HT20-High




Date: 20.JUL.2020 19:08:58

802.11n-HT40-Low




Date: 20.JUL.2020 19:21:46

802.11n-HT40-Middle



Date: 20.JUL.2020 19:34:14

802.11n-HT40-High



Date: 20.JUL.2020 19:47:14


## 6. DTS Bandwidth

---

### 6.1 Standard Applicable

According to 15.247(a)(2), systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

### 6.2 Test Setup Block Diagram



### 6.3 Test Procedure

According to the KDB 558074 D01 v05r02 Subclause 8.2 and ANSI C63.10-2013 Subclause 11.8.1, the test method of DTS Bandwidth as below:

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW)  $\geq 3 \times$  RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.




### 6.4 Summary of Test Results/Plots

Test Mode	Test Channel MHz	Test Result(MHz)		Limit kHz
		Antenna A	Antenna B	
802.11b_11Mbps	2412	10.08	10.02	$\geq 500$
	2437	10.08	10.08	$\geq 500$
	2462	10.08	10.08	$\geq 500$
802.11g_54Mbps	2412	16.50	16.50	$\geq 500$
	2437	16.50	16.50	$\geq 500$
	2462	16.50	16.50	$\geq 500$
802.11n-HT20_MCS7	2412	17.58	17.58	$\geq 500$
	2437	17.58	17.58	$\geq 500$
	2462	17.58	17.58	$\geq 500$
802.11n-HT40_MCS7	2422	36.60	36.60	$\geq 500$
	2437	36.48	36.60	$\geq 500$
	2452	36.60	36.60	$\geq 500$


Please refer to the following test plots:



➤ Antenna A


<p>802.11b-Low</p>	 <p>Ref 20 dBm Att 30 dB RBW 100 kHz Delta 1 [T1] 1.21 dB VBW 300 kHz SWT 5 ms 10.08000000 MHz</p> <p>Marker 1 [T1] -3.67 dBm 0.406830000 GHz</p> <p>Offset 1 dB d1 -3.08 dBm</p> <p>Center 2.412 GHz 3 MHz/ Span 30 MHz</p> <p>Date: 13.JUL.2020 11:55:33</p>
<p>802.11b-Middle</p>	 <p>Ref 20 dBm Att 30 dB RBW 100 kHz Delta 1 [T1] 1.20 dB VBW 300 kHz SWT 5 ms 10.08000000 MHz</p> <p>Marker 1 [T1] -3.30 dBm 0.431930000 GHz</p> <p>Offset 1 dB d1 -2.88 dBm</p> <p>Center 2.437 GHz 3 MHz/ Span 30 MHz</p> <p>Date: 13.JUL.2020 11:56:54</p>
<p>802.11b-High</p>	 <p>Ref 20 dBm Att 30 dB RBW 100 kHz Delta 1 [T1] 0.98 dB VBW 300 kHz SWT 5 ms 10.08000000 MHz</p> <p>Marker 1 [T1] -3.38 dBm 0.456930000 GHz</p> <p>Offset 1 dB d1 -3.09 dBm</p> <p>Center 2.462 GHz 3 MHz/ Span 30 MHz</p> <p>Date: 13.JUL.2020 11:57:44</p>

802.11g-Low




Date: 13.JUL.2020 13:36:54

802.11g-Middle




Date: 13.JUL.2020 13:38:45

802.11g-High




Date: 13.JUL.2020 13:40:21

802.11n-HT20-Low




Date: 13.JUL.2020 13:44:36

802.11n-HT20-Middle




Date: 13.JUL.2020 13:46:17

802.11n-HT20-High




Date: 13.JUL.2020 13:47:18

802.11n-HT40-Low




Date: 13.JUL.2020 13:54:20

802.11n-HT40-Middle






Date: 13.JUL.2020 13:55:14

802.11n-HT40-High




Date: 13.JUL.2020 13:56:10

➤ Antenna B


<p>802.11b-Low</p>	 <p>Date: 13.JUL.2020 16:45:22</p>
<p>802.11b-Middle</p>	 <p>Date: 13.JUL.2020 16:46:33</p>
<p>802.11b-High</p>	 <p>Date: 13.JUL.2020 16:48:02</p>

802.11g-Low




Date: 13.JUL.2020 16:48:59

802.11g-Middle




Date: 13.JUL.2020 16:49:46

802.11g-High




Date: 13.JUL.2020 16:50:47

802.11n-HT20-Low




Date: 13.JUL.2020 16:52:11

802.11n-HT20-Middle




Date: 13.JUL.2020 16:53:03

802.11n-HT20-High




Date: 13.JUL.2020 16:54:17

802.11n-HT40-Low




Date: 13.JUL.2020 16:55:34

802.11n-HT40-Middle



Date: 13.JUL.2020 16:57:05

802.11n-HT40-High



Date: 13.JUL.2020 16:58:08




## 7. RF Output Power

---

### 7.1 Standard Applicable

According to 15.247(b)(3), for systems using digital modulation in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands: 1 Watt.

### 7.2 Test Setup Block Diagram



### 7.3 Test Procedure

According to the KDB-558074 D01 v05r02 Subclause 8.3.2.2 and ANSI C63.10-2013 Subclause 11.9.2.2, when this option is exercised, the measured power is to be referenced to the OBW rather than the DTS bandwidth




- Set span to at least 1.5 times the OBW.
- Set RBW = 1-5% of the OBW, not to exceed 1 MHz.
- Set VBW  $\geq 3 \times$  RBW.
- Number of points in sweep  $\geq 2 \times$  span / RBW. (This gives bin-to-bin spacing  $\leq$  RBW/2, so that narrowband signals are not lost between frequency bins.)
- Sweep time = auto.
- Detector = RMS (i.e., power averaging), if available. Otherwise, use sample detector mode.
- If transmit duty cycle < 98 %, use a sweep trigger with the level set to enable triggering only on full power pulses. The transmitter shall operate at maximum power control level for the entire duration of every sweep. If the EUT transmits continuously (i.e., with no off intervals) or at duty cycle  $\geq 98$  %, and if each transmission is entirely at the maximum power control level, then the trigger shall be set to “free run” .
- Trace average at least 100 traces in power averaging (i.e., RMS) mode.
- Compute power by integrating the spectrum across the OBW of the signal using the instrument’s band power measurement function, with band limits set equal to the OBW band edges. If the instrument does not have a band power function, sum the spectrum levels (in power units) at intervals equal to the RBW extending across the entire OBW of the spectrum.

### 7.4 Summary of Test Results/Plots


Test Mode	Test Channel MHz	Test Result(dBm)		Total dBm	Output Power mW	Limit mW
		Antenna A	Antenna B			
802.11b	2412	16.58	15.60	/	45.50	1000
	2437	16.84	15.71	/	48.31	1000
	2462	16.56	16.03	/	45.29	1000
802.11g	2412	15.89	15.18	/	38.82	1000
	2437	15.60	15.29	/	36.31	1000
	2462	15.80	15.42	/	38.02	1000
802.11n HT20	2412	16.09	14.67	18.45	69.98	1000
	2437	15.52	14.80	18.19	65.92	1000
	2462	15.34	14.96	18.16	65.46	1000
802.11n HT40	2422	13.48	13.42	16.46	44.26	1000
	2437	14.32	13.78	17.07	50.93	1000
	2452	13.74	14.17	16.97	49.77	1000

Please refer to the following test plots:

➤ Antenna A


<p>802.11b-Low 11Mbps</p>	 <p>Ref 20 dBm    Att 30 dB    RBW 300 kHz VBM 1 MHz    SWT 5 ms</p> <p>Offset 1 dB</p> <p>Center 2.412 GHz    3 MHz/    Span 30 MHz</p> <p>Tx Channel Bandwidth    20 MHz    Power    16.58 dBm</p> <p>Date: 13.JUL.2020 10:04:59</p>
<p>802.11b-Middle 11Mbps</p>	 <p>Ref 20 dBm    Att 30 dB    RBW 300 kHz VBM 1 MHz    SWT 5 ms</p> <p>Offset 1 dB</p> <p>Center 2.437 GHz    3 MHz/    Span 30 MHz</p> <p>Tx Channel Bandwidth    20 MHz    Power    16.84 dBm</p> <p>Date: 13.JUL.2020 10:06:51</p>
<p>802.11b-High 11Mbps</p>	 <p>Ref 20 dBm    Att 30 dB    RBW 300 kHz VBM 1 MHz    SWT 5 ms</p> <p>Offset 1 dB</p> <p>Center 2.462 GHz    3 MHz/    Span 30 MHz</p> <p>Tx Channel Bandwidth    20 MHz    Power    16.56 dBm</p> <p>Date: 13.JUL.2020 10:07:24</p>

802.11g-Low  
54Mbps




Date: 20.JUL.2020 14:49:27

802.11g-Middle  
54Mbps






Date: 20.JUL.2020 14:50:14


802.11g-High  
54Mbps



Date: 13.JUL.2020 10:10:42


<p>802.11n-HT20-Low MCS7</p>	 <p>Ref 20 dBm Att 30 dB RBW 300 kHz VSM 1 MHz SWT 5 ms</p> <p>Offset 1 dB</p> <p>Center 2.412 GHz 3 MHz/ Span 30 MHz</p> <p>Tx Channel1 Bandwidth 20 MHz Power 16.09 dBm</p> <p>Date: 20.JUL.2020 15:50:05</p>
<p>802.11n-HT20-Middle MCS7</p>	 <p>Ref 20 dBm Att 30 dB RBW 300 kHz VSM 1 MHz SWT 5 ms</p> <p>Offset 1 dB</p> <p>Center 2.437 GHz 3 MHz/ Span 30 MHz</p> <p>Tx Channel1 Bandwidth 20 MHz Power 15.52 dBm</p> <p>Date: 13.JUL.2020 10:13:49</p>
<p>802.11n-HT20-High MCS7</p>	 <p>Ref 20 dBm Att 30 dB RBW 300 kHz VSM 1 MHz SWT 5 ms</p> <p>Offset 1 dB</p> <p>Center 2.462 GHz 3 MHz/ Span 30 MHz</p> <p>Tx Channel1 Bandwidth 20 MHz Power 15.34 dBm</p> <p>Date: 13.JUL.2020 10:14:20</p>

802.11n-HT40-Low  
MCS7




Date: 20.JUL.2020 15:52:15

802.11n-HT40-Middle  
MCS7






Date: 20.JUL.2020 16:00:24

802.11n-HT40-High  
MCS7




Date: 20.JUL.2020 16:03:23

➤ Antenna B


<p>802.11b-Low 11Mbps</p>	 <p>Date: 13.JUL.2020 16:11:22</p>
<p>802.11b-Middle 11Mbps</p>	 <p>Date: 13.JUL.2020 16:12:20</p>
<p>802.11b-High 11Mbps</p>	 <p>Date: 13.JUL.2020 16:14:29</p>

802.11g-Low  
54Mbps




Date: 13.JUL.2020 16:15:32

802.11g-Middle  
54Mbps



Date: 13.JUL.2020 16:17:13


802.11g-High  
54Mbps



Date: 13.JUL.2020 16:17:47




802.11n-HT20-Low  
MCS7




Date: 13.JUL.2020 16:18:22

802.11n-HT20-Middle  
MCS7




Date: 13.JUL.2020 16:18:47

802.11n-HT20-High  
MCS7




Date: 13.JUL.2020 16:19:12

802.11n-HT40-Low  
MCS7




Date: 13.JUL.2020 16:20:15

802.11n-HT40-Middle  
MCS7



Date: 13.JUL.2020 16:21:04

802.11n-HT40-High  
MCS7



Date: 13.JUL.2020 16:22:17

## 8. Field Strength of Spurious Emissions

### 8.1 Standard Applicable

According to §15.247(d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

The emission limit in this paragraph is based on measurement instrumentation employing an average detector. The provisions in §15.35 for limiting peak emissions apply. Spurious Radiated Emissions measurements starting below or at the lowest crystal frequency.


### 8.2 Test Procedure

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.205 15.247(a) and FCC Part 15.209 Limit.


The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.


The test setup for emission measurement below 30MHz..



The test setup for emission measurement from 30 MHz to 1 GHz..



The test setup for emission measurement above 1 GHz..



Frequency :9kHz-30MHz

RBW=10KHz,

VBW =30KHz

Sweep time= Auto

Trace = max hold

Detector function = peak

Frequency :30MHz-1GHz

RBW=120KHz,

VBW=300KHz

Sweep time= Auto

Trace = max hold

Detector function = peak, QP

Frequency :Above 1GHz

RBW=1MHz,

VBW=3MHz(Peak), 10Hz(AV)

Sweep time= Auto

Trace = max hold

Detector function = peak, AV

### 8.3 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and the Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Ant. Factor} + \text{Cable Loss} - \text{Ampl. Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -6dB $\mu$ V means the emission is 6dB $\mu$ V below the maximum limit. The equation for margin calculation is as follows:


$$\text{Margin} = \text{Corr. Ampl.} - \text{FCC Part 15 Limit}$$

### 8.4 Summary of Test Results/Plots

*Note: 1. This EUT was tested in 3 orthogonal positions and the worst case position data was reported. All test modes (different data rate and different modulation) are performed, but only the worst case (802.11b\_11Mbps) is recorded in this report.*


- Spurious Emissions Below 1GHz
- Worst case Antenna A

802.11b_11Mbps			
Test Channel	Low	Polarity:	Horizontal




No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ( )	Height (cm)	Remark
1	39.0245	37.65	-12.35	25.30	40.00	-14.70	-	-	peak
2	100.9340	34.29	-13.32	20.97	43.50	-22.53	-	-	peak
3	227.6906	33.33	-12.00	21.33	46.00	-24.67	-	-	peak
4	483.9094	35.06	-4.53	30.53	46.00	-15.47	-	-	peak
5	900.1474	31.27	1.55	32.82	46.00	-13.18	-	-	peak

802.11b_11Mbps			
Test Channel	Low	Polarity:	Vertical



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ( )	Height (cm)	Remark
1	44.5868	37.29	-11.82	25.47	40.00	-14.53	-	-	peak
2	97.1148	35.61	-13.80	21.81	43.50	-21.69	-	-	peak
3	257.4222	34.79	-10.87	23.92	46.00	-22.08	-	-	peak
4	495.9344	32.20	-4.17	28.03	46.00	-17.97	-	-	peak
5	922.5157	31.62	1.83	33.45	46.00	-12.55	-	-	peak


802.11b_11Mbps			
Test Channel	Middle	Polarity:	Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ( )	Height (cm)	Remark
1	40.4172	36.73	-11.97	24.76	40.00	-15.24	-	-	peak
2	73.1025	36.23	-15.50	20.73	40.00	-19.27	-	-	peak
3	240.8304	33.16	-11.37	21.79	46.00	-24.21	-	-	peak
4	494.1984	34.06	-4.22	29.84	46.00	-16.16	-	-	peak
5	893.8567	31.23	1.30	32.53	46.00	-13.47	-	-	peak




802.11b_11Mbps			
Test Channel	Middle	Polarity:	Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ( )	Height (cm)	Remark
1	39.4372	37.81	-12.19	25.62	40.00	-14.38	-	-	peak
2	71.8320	38.64	-15.15	23.49	40.00	-16.51	-	-	peak
3	245.0900	32.81	-11.18	21.63	46.00	-24.37	-	-	peak
4	432.5457	32.68	-5.79	26.89	46.00	-19.11	-	-	peak
5	696.8567	32.75	-1.86	30.89	46.00	-15.11	-	-	peak

802.11b_11Mbps			
Test Channel	High	Polarity:	Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ( )	Height (cm)	Remark
1	30.2111	48.86	-14.14	34.72	40.00	-5.28	-	-	peak
2	34.1561	48.37	-13.92	34.45	40.00	-5.55	-	-	peak
3	43.0505	44.01	-11.87	32.14	40.00	-7.86	-	-	peak
4	520.8882	34.58	-4.15	30.43	46.00	-15.57	-	-	peak
5	875.2470	31.02	0.55	31.57	46.00	-14.43	-	-	peak

802.11b_11Mbps			
Test Channel	High	Polarity:	Vertical



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ( )	Height (cm)	Remark
1	38.6161	37.70	-12.51	25.19	40.00	-14.81	-	-	peak
2	96.0986	35.70	-13.96	21.74	43.50	-21.76	-	-	peak
3	416.1791	32.63	-6.08	26.55	46.00	-19.45	-	-	peak
4	771.4486	31.69	-1.12	30.57	46.00	-15.43	-	-	peak
5	922.5157	32.22	1.83	34.05	46.00	-11.95	-	-	peak

Remark: ‘-’Means’ the test Degree and Height are not recorded by the test software and only show the worst case in the test report.

- Spurious Emissions Above 1GHz
- Worst case ant A
- Test Mode: 802.11b\_11Mbps(Worst case)

Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Polar H/V	Detector
Low Channel-2412MHz							
3923.367	52.49	-6.81	45.68	74.00	-28.32	H	PK
5490.177	53.40	-4.15	49.25	74.00	-24.75	H	PK
8250.266	52.89	-0.39	52.50	74.00	-21.50	H	PK
3135.986	52.38	-8.24	44.14	74.00	-29.86	V	PK
5338.579	52.15	-4.23	47.92	74.00	-26.08	V	PK
7860.737	51.80	-0.96	50.84	74.00	-23.16	V	PK
Middle Channel-2437MHz							
3308.185	52.46	-7.75	44.71	74.00	-29.29	H	PK
4559.152	52.45	-4.67	47.78	74.00	-26.22	H	PK
8747.716	52.88	0.29	53.17	74.00	-20.83	H	PK
3923.367	54.60	-6.81	47.79	74.00	-26.21	V	PK
6299.178	52.64	-2.56	50.08	74.00	-23.92	V	PK
8250.266	52.81	-0.39	52.42	74.00	-21.58	V	PK
High Channel-2462MHz							
3598.087	53.23	-7.11	46.12	74.00	-27.88	H	PK
4688.616	53.22	-4.59	48.63	74.00	-25.37	H	PK
8083.954	53.22	-0.47	52.75	74.00	-21.25	H	PK
2995.538	53.28	-8.64	44.64	74.00	-29.36	V	PK
4797.271	52.70	-4.52	48.18	74.00	-25.82	V	PK
6886.154	52.84	-2.28	50.56	74.00	-23.44	V	PK

Note: 1. Testing is carried out with frequency rang 9kHz to the tenth harmonics, other than listed in the table above are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

2. Average measurement was not performed if peak level is lower than average limit(54 dBuV/m).

## 9. Out of Band Emissions

---

### 9.1 Standard Applicable

According to §15.247(d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

### 9.2 Test Procedure

According to the KDB 558074D01 v05r02 Subclause 8.4 and ANSI C63.10-2013 Subclause 11.11, the Emissions in nonrestricted frequency bands test method as follows:

- a) Set the center frequency and span to encompass frequency range to be measured.
- b) Set the RBW = 100 kHz.
- c) Set the VBW  $\geq [3 \times \text{RBW}]$ .
- d) Detector = peak.
- e) Sweep time = auto couple.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use the peak marker function to determine the maximum amplitude level.

According to the KDB 558074 D01 v05r02 Subclause 8.5 and ANSI C63.10-2013 Subclause 11.12, the Emissions in restricted frequency bands test method as follows:

#### A. Radiated emission measurements:

Set span = wide enough to capture the peak level of the emission operating on the channel closest to the bandedge, as well as any modulation products which fall outside of the authorized band of operation (2310MHz to 2420MHz for low bandedge, 2460MHz to 2500MHz for the high bandedge)

RBW = 1MHz, VBW = 1MHz for peak value measured

RBW = 1MHz, VBW = 10Hz for average value measured

Sweep = auto; Detector function = peak/average; Trace = max hold

All the trace to stabilize, set the marker on the emission at the bandedge, or on the highest modulation product outside of the band, if this level is greater than that at the bandedge. Enable the marker-delta function, then use the marker-to-peak function to move the marker to the peak of the in-band emission. Those emission must comply with the 15.209 limit for fall in the restricted bands listed in section 15.205. Note that the method of measurement

KDB publication number: 913591 may be used for the radiated bandedge measurements.

#### B. Antenna-port conducted measurements

Peak emission levels are measured by setting the instrument as follows:

- a) RBW = as specified in Table 9.
- b) VBW  $\geq$   $[3 \times \text{RBW}]$ .
- c) Detector = peak.
- d) Sweep time = auto.
- e) Trace mode = max hold.
- f) Allow sweeps to continue until the trace stabilizes. (Note that the required measurement time may be lengthened for low-duty-cycle applications.)

**Table 9—RBW as a function of frequency**

Frequency	RBW
9 kHz to 150 kHz	200 Hz to 300 Hz
0.15 MHz to 30 MHz	9 kHz to 10 kHz
30 MHz to 1000 MHz	100 kHz to 120 kHz
>1000 MHz	1 MHz


If the peak-detected amplitude can be shown to comply with the average limit, then it is not necessary to perform a separate average measurement.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements specified in section 8.1. Report the three highest emissions relative to the limit.

### 9.3 Summary of Test Results/Plots


- Radiated test
- Worst case ant A

802.11b_11Mbps			
Test Channel	Low	Polarity:	Horizontal (worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	41.24	-9.66	31.58	54.00	-22.42	Average Detector
	2310.000	53.63	-9.66	43.97	74.00	-30.03	Peak Detector
2	2390.000	42.92	-9.50	33.42	54.00	-20.58	Average Detector
	2390.000	54.90	-9.50	45.40	74.00	-28.60	Peak Detector
3	2412.343	103.73	-9.46	94.27	/	/	Average Detector
	2412.710	108.55	-9.46	99.09	/	/	Peak Detector


802.11b_11Mbps			
Test Channel	High	Polarity:	Horizontal (worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2461.162	104.78	-9.36	95.42	/	/	Average Detector
	2460.764	109.30	-9.36	99.94	/	/	Peak Detector
2	2483.500	41.68	-9.31	32.37	54.00	-21.63	Average Detector
	2483.500	53.60	-9.31	44.29	74.00	-29.71	Peak Detector
3	2500.000	41.27	-9.28	31.99	54.00	-22.01	Average Detector
	2500.000	53.21	-9.28	43.93	74.00	-30.07	Peak Detector




802.11g_54Mbps			
Test Channel	Low	Polarity:	Horizontal (worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	40.50	-9.66	30.84	54.00	-23.16	Average Detector
		51.80	-9.66	42.14	74.00	-31.86	Peak Detector
2	2390.000	45.47	-9.50	35.97	54.00	-18.03	Average Detector
		64.05	-9.50	54.55	74.00	-19.45	Peak Detector
3	2418.600	95.93	-9.44	86.49	/	/	Average Detector
		106.63	-9.44	97.19	/	/	Peak Detector

802.11g_54Mbps			
Test Channel	High	Polarity:	Horizontal (worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2461.063	99.83	-9.36	90.47	/	/	Average Detector
	2460.864	110.26	-9.36	100.90	/	/	Peak Detector
2	2483.500	50.51	-9.31	41.20	54.00	-12.80	Average Detector
	2483.500	70.10	-9.31	60.79	74.00	-13.21	Peak Detector
3	2500.000	41.78	-9.28	32.50	54.00	-21.50	Average Detector
	2500.000	54.72	-9.28	45.44	74.00	-28.56	Peak Detector

802.11n-HT20_MCS7			
Test Channel	Low	Polarity:	Horizontal (worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	41.57	-9.66	31.91	54.00	-22.09	Average Detector
	2310.000	54.36	-9.66	44.70	74.00	-29.30	Peak Detector
2	2390.000	42.88	-9.50	33.38	54.00	-20.62	Average Detector
	2390.000	62.72	-9.50	53.22	74.00	-20.78	Peak Detector
3	2418.600	85.87	-9.44	76.43	/	/	Average Detector
	2418.120	97.23	-9.44	87.79	/	/	Peak Detector

802.11n-HT20_MCS7			
Test Channel	High	Polarity:	Horizontal (worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2468.950	99.26	-9.34	89.92	/	/	Average Detector
	2468.400	109.98	-9.34	100.64	/	/	Peak Detector
2	2483.500	56.44	-9.31	47.13	54.00	-6.87	Average Detector
	2483.500	78.28	-9.31	68.97	74.00	-5.03	Peak Detector
3	2500.000	41.67	-9.28	32.39	54.00	-21.61	Average Detector
	2500.000	53.14	-9.28	43.86	74.00	-30.14	Peak Detector

802.11n-HT40_MCS7			
Test Channel	Low	Polarity:	Horizontal (worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	42.61	-9.66	32.95	54.00	-21.05	Average Detector
		54.53	-9.66	44.87	74.00	-29.13	Peak Detector
2	2390.000	55.24	-9.50	45.74	54.00	-8.26	Average Detector
		68.42	-9.50	58.92	74.00	-15.08	Peak Detector
3	2428.860	93.98	-9.42	84.56	/	/	Average Detector
		105.22	-9.43	95.79	/	/	Peak Detector

802.11n-HT40_MCS7			
Test Channel	High	Polarity:	Horizontal (worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2438.750	94.88	-9.41	85.47	/	/	Average Detector
	2438.540	105.86	-9.41	96.45	/	/	Peak Detector
2	2483.500	53.07	-9.31	43.76	54.00	-10.24	Average Detector
	2483.500	66.10	-9.31	56.79	74.00	-17.21	Peak Detector
3	2500.000	44.70	-9.28	35.42	54.00	-18.58	Average Detector
	2500.000	60.49	-9.28	51.21	74.00	-22.79	Peak Detector


➤ Antenna A

802.11b\_11Mbps

Low




Date: 13.JUL.2020 14:00:48




Date: 13.JUL.2020 14:01:17

802.11b\_11Mbps

Middle



Date: 13.JUL.2020 14:02:27




Date: 13.JUL.2020 14:03:01




802.11b\_11Mbps

High




Date: 13.JUL.2020 14:03:50




Date: 13.JUL.2020 14:04:08

802.11g\_54Mbps

Low




Date: 13.JUL.2020 14:05:04




Date: 13.JUL.2020 14:05:19

802.11g\_54Mbps

Middle




Date: 13.JUL.2020 14:06:04




Date: 13.JUL.2020 14:06:18

802.11g\_54Mbps

High




Date: 13.JUL.2020 14:07:04




Date: 13.JUL.2020 14:07:17

802.11n-HT20\_MCS7

Low




Date: 13.JUL.2020 14:08:32




Date: 13.JUL.2020 14:08:49

802.11n-HT20\_MCS7

Middle




Date: 13.JUL.2020 14:09:44




Date: 13.JUL.2020 14:10:01

802.11n-HT20\_MCS7

High




Date: 13.JUL.2020 14:12:58




Date: 13.JUL.2020 14:13:45

802.11n-HT40\_MCS7

Low



Date: 13.JUL.2020 14:14:27




Date: 13.JUL.2020 14:14:43




802.11n-HT40\_MCS7

Middle




Date: 13.JUL.2020 14:15:23




Date: 13.JUL.2020 14:15:38

802.11n-HT40\_MCS7

High



Date: 13.JUL.2020 14:16:27




Date: 13.JUL.2020 14:16:45


➤ Antenna B

802.11b\_11Mbps

Low




Date: 13.JUL.2020 17:05:15




Date: 13.JUL.2020 17:05:29

802.11b\_11Mbps

Middle




Date: 13.JUL.2020 17:06:13




Date: 13.JUL.2020 17:06:28

802.11b\_11Mbps

High




Date: 13.JUL.2020 17:07:34




Date: 13.JUL.2020 17:07:49

802.11g\_54Mbps

Low




Date: 13.JUL.2020 17:08:35




Date: 13.JUL.2020 17:08:49

802.11g\_54Mbps

Middle




Date: 13.JUL.2020 17:09:36




Date: 13.JUL.2020 17:09:48

802.11g\_54Mbps

High



Date: 13.JUL.2020 17:10:36




Date: 13.JUL.2020 17:10:49




802.11n-HT20\_MCS7

Low




Date: 13.JUL.2020 17:11:38




Date: 13.JUL.2020 17:11:52

802.11n-HT20\_MCS7

Middle




Date: 13.JUL.2020 17:12:25




Date: 13.JUL.2020 17:12:37

802.11n-HT20\_MCS7

High




Date: 13.JUL.2020 17:13:40




Date: 13.JUL.2020 17:13:54

802.11n-HT40\_MCS7

Low




Date: 13.JUL.2020 17:14:31




Date: 13.JUL.2020 17:14:45

802.11n-HT40\_MCS7

Middle




Date: 13.JUL.2020 17:15:19




Date: 13.JUL.2020 17:15:31

802.11n-HT40\_MCS7

High



Date: 13.JUL.2020 17:16:05



Date: 13.JUL.2020 17:16:31


## 10. Conducted Emissions

### 10.1 Test Procedure

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle. The spacing between the peripherals was 10 cm.

### 10.2 Basic Test Setup Block Diagram




### 10.3 Test Receiver Setup

During the conducted emission test, the test receiver was set with the following configurations:

Start Frequency .....	150 kHz
Stop Frequency .....	30 MHz
Sweep Speed .....	Auto
IF Bandwidth.....	10 kHz
Quasi-Peak Adapter Bandwidth .....	9 kHz
Quasi-Peak Adapter Mode .....	Normal

### 10.4 Summary of Test Results/Plots


Test Mode	Communication	AC120V 60Hz	Polarity:	Neutral
-----------	---------------	-------------	-----------	---------



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.6220	32.46	10.05	42.51	56.00	-13.49	QP
2*	0.6220	24.35	10.05	34.40	46.00	-11.60	AVG
3	2.4220	15.52	10.37	25.89	46.00	-20.11	AVG
4	2.4820	26.14	10.37	36.51	56.00	-19.49	QP
5	5.3900	28.66	10.41	39.07	60.00	-20.93	QP
6	5.5780	17.35	10.42	27.77	50.00	-22.23	AVG



Test Mode	Communication	AC120V 60Hz	Polarity:	Line
-----------	---------------	-------------	-----------	------



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.6220	31.24	10.05	41.29	56.00	-14.71	QP
2*	0.6220	21.27	10.05	31.32	46.00	-14.68	AVG
3	1.8620	23.18	10.37	33.55	56.00	-22.45	QP
4	1.8620	16.37	10.37	26.74	46.00	-19.26	AVG
5	5.5460	28.78	10.42	39.20	60.00	-20.80	QP
6	5.5860	17.29	10.42	27.71	50.00	-22.29	AVG

\*\*\*\*\* END OF REPORT \*\*\*\*\*