

Test Report

Verified code: 227481

Report No.: E20240311968201-5

Customer: Lumi United Technology Co., Ltd.

Address: B1,Chongwe Park,Nanshan iPark, Liuxian Avenue, Taoyuan Residential District, Nanshan District, Shenzhen, China.

Sample Name: Smart Lock U100, Smart Lock U50

Sample Model: SDL-D01, DL-D05D

Receive Sample Date: Jan.18,2023

Test Date: Jan.30,2023 ~ Feb.17,2023

Reference Document: CFR 47, FCC Part 2.1091 Radio frequency radiation exposure evaluation: mobile devices.

Test Result: Pass

Prepared by: Huang Lifang
Huang Lifang

Reviewed by: Wu Haoting
Wu Haoting

Approved by: Xiao Liang
Xiao Liang

GUANGZHOU GRG METROLOGY & TEST CO., LTD

Issued Date: 2024-04-15

GUANGZHOU GRG METROLOGY & TEST CO., LTD.

Address: No.163, Pingyun Road, West of Huangpu Avenue, Guangzhou, Guangdong, China
Tel: (+86) 400-602-0999 FAX: (+86) 020-38698685 Web: <http://www.grgtest.com>



Statement

1. The report is invalid without "special seal for inspection and testing"; some copies are invalid; The report is invalid if it is altered or missing; The report is invalid without the signature of the person who prepared, reviewed and approved it.
2. The sample information is provided by the client and responsible for its authenticity; The content of the report is only valid for the samples sent this time.
3. When there are reports in both Chinese and English, the Chinese version will prevail when the language problems are inconsistent.
4. If there is any objection concerning the report, please inform us within 15 days from the date of receiving the report.
5. Without the agreement of the laboratory, the client is not authorized to use the test results for unapproved propaganda.

----- The following blanks -----

TABLE OF CONTENTS

1.	GENERAL DESCRIPTION OF EUT.....	5
1.1	APPLICANT.....	5
1.2	MANUFACTURER.....	5
1.3	BASIC DESCRIPTION OF EQUIPMENT UNDER TEST.....	5
2.	LABORATORY AND ACCREDITATIONS.....	7
2.1	LABORATORY.....	7
2.2	ACCREDITATIONS.....	7
3.	LIMITS FOR GENERAL POPULATION/UNCONTROLLED EXPOSURE.....	8
4.	CALCULATION METHOD.....	9
5.	ESTIMATION RESULT.....	10
5.1	MEASUREMENT RESULTS.....	10
6.	CONCLUSION.....	12

----- The following blanks -----

REPORT ISSUED HISTORY

Report Version	Report No.	Description	Compile Date
1.0	E20240311968201-5	Original Issue	2024-03-25

Note:

The new EUT (Smart Lock U50) model numbers DL-D05D & DL-D05E (they have the same technical construction including circuit diagram PCB layout, hardware version and software version identical, except the model name) and the old EUT (Smart Lock U100) model numbers SDL-D01 & DL-D01D have the same technical construction including circuit diagram and PCB layout in the rear lock, it didn't affect bluetooth and zigbee RF chip performance. The differences in the new front lock on the basis of the old as below:

- a. The new front lock was canceled the fingerprint.
- b. The new front lock C board PCB layout and PIC type were changed.
- c. The new front lock B board PCB added 1pc LED 0603 White, 1pc LED 0603 RED and 2pcs 180R 5% 0402, connector P6B type was changed, deleted devices as below:
 - a) 150R 0402 1/16W: R104B, R107B;
 - b) 51R 0402 1/16W: R105B, R106B, R108B, R110B;
 - c) 100K 0402 1/16W: R109B;
 - d) 10nF/6.3V 0402 X5R: C107B;
 - e) 100nF/16V 0402 X5R: C83B;
 - f) 1uF/6.3V 0402 X5R: C82B;
 - g) BEAD\300Ω@100MHZ\250mA\0402: L7B;
 - h) ESD\Bi\±25/20KV\VRWM=3.3V, VBR=6.5V, Ir=0.1uA, CJ=12pF;
 - i) Ipp=6A\ SOD-882: D23B, D24B, D25B, D26B, D27B, D28B;
 - j) CONN: P4B.

Evaluate according to the above description, the difference about the report E20240311968201-5 and E20230117700901-5 are as follows:

- 1) Adding the equipment Smart Lock U50, the models DL-D05D in the page 1.
- 2) Adding the equipment Smart Lock U50, the models DL-D05D & DL-D05E, model difference description and hardware version in the section 1.3.
- 3) Adding the EUT photos of the models DL-D05D in the APPENDIX B.
- 4) This report does not need to be retested, all test datas come from E20230117700901-5.

1. GENERAL DESCRIPTION OF EUT

1.1 APPLICANT

Name: Lumi United Technology Co., Ltd
Address: B1,Chongwe Park,Nanshan iPark, Liuxian Avenue, Taoyuan Residential District, Nanshan District, Shenzhen, China.

1.2 MANUFACTURER

Name: Lumi United Technology Co., Ltd
Address: B1,Chongwe Park,Nanshan iPark, Liuxian Avenue, Taoyuan Residential District, Nanshan District, Shenzhen, China.

1.3 BASIC DESCRIPTION OF EQUIPMENT UNDER TEST

Equipment: Smart Lock U100
Adding Equipment: Smart Lock U50
Model No.: SDL-D01
Adding Model: DL-D01D, DL-D05D, DL-D05E
Models Difference: 1).That EUT (Smart Lock U100) Model Numbers SDL-D01 and DL-D01D have the same technical construction including circuit diagram PCB layout, hardware version and software version identical, except sales area, packaging and accessories are different, and all the tests were performed on the model SDL-D01.
2).The adding EUT (Smart Lock U50) model numbers DL-D05D & DL-D05E (they have the same technical construction including circuit diagram PCB layout, hardware version and software version identical, except the model name) and the EUT (Smart Lock U100) model numbers SDL-D01 & DL-D01D have the same technical construction including circuit diagram and PCB layout in the rear lock, it didn't affect bluetooth and zigbee RF chip performance. The differences in the new front lock on the basis of the old as below:
a.The new front lock was canceled the fingerprint.
b.The new front lock C board PCB layout and PIC type were changed.
c.The new front lock B board PCB added 1pc LED 0603 White, 1pc LED 0603 RED and 2pcs 180R 5% 0402, connector P6B type was changed, deleted devices as below:
150R 0402 1/16W: R104B,R107B;
51R 0402 1/16W: R105B, R106B, R108B, R110B;
100K 0402 1/16W: R109B;
10nF/6.3V 0402 X5R: C107B;
100nF/16V 0402 X5R: C83B;
1uF/6.3V 0402 X5R: C82B;
BEAD\300Ω@100MHZ\250mA\0402: L7B;
ESD\Bi\±25/20KV\VRWM=3.3V, VBR=6.5V, Ir=0.1uA, CJ=12pF;
Ipp=6A\ SOD-882: D23B,D24B,D25B,D26B,D27B,D28B;
CONN: P4B.

Trade Name: Aqara

FCC ID: 2AKIT-SDLD01

Power supply: DC 6V power supplied by 4 AA batteries,DC 5V power supplied by USB-C emergency port

Frequency Band: 2402MHz-2480MHz for BLE, 2405MHz-2475MHz for Zigbee,13.65MHz for NFC

Maximum Transmit Power: BLE for 1Mbps:7.75dBm, BLE for 2Mbps:7.75dBm, Zigbee: 7.71dBm,NFC:-47.90dBm

Modulation type: GFSK for BLE, O-QPSK for Zigbee

Antenna Specification: BLE&Zigbee: FPC antenna with 2dBi gain (Max)
NFC:PCB antenna with 2dBi gain(Max)

Temperature Range: -35 °C~66 °C

Hardware Version: V2.1 for SDL-D01 & DL-D01D;
V3.1 for DL-D05D & DL-D05E.

Software Version: 1.0.4_0007

Sample No: E20230117700901-0003, E20230117700901-0004, E20230117700901-0007

Note: The basic description of the EUT is provided by the applicant. This report is made Solely on the basis of such data and/or information.We accept no responsibility for the authenticity and completeness of the above data and information and the validity of the results and/or conclusions.

----- The following blanks -----

2. LABORATORY AND ACCREDITATIONS

2.1 LABORATORY

The tests & measurements refer to this report were performed by Shenzhen EMC Laboratory of Guangzhou GRG Metrology & Test Co., Ltd.

Add.: No.1301 Guanguang Road Xinlan Community, Guanlan Street, Longhua District
Shenzhen, 518110, People's Republic of China.
P.C.: 518110
Tel : 0755-61180008
Fax: 0755-61180008

2.2 ACCREDITATIONS

Our laboratories are accredited and approved by the following approval agencies according to ISO/IEC 17025.

USA A2LA(Certificate #2861.01)

The measuring facility of laboratories has been authorized or registered by the following approval agencies.

Canada ISED (Company Number: 24897, CAB identifier:CN0069)

USA FCC (Registration Number: 759402, Designation Number:CN1198)

Copies of granted accreditation certificates are available for downloading from our web site,
<http://www.grgtest.com>

----- The following blanks -----

3. LIMITS FOR GENERAL POPULATION/UNCONTROLLED EXPOSURE

General

According to the KDB 447498 D04 Interim General RF Exposure Guidance v01, General frequency and separation-distance dependent MPE-based effective radiated power (ERP) thresholds are in Table 4.1 to support an exemption from further evaluation from 300 kHz through 100 GHz.

TABLE 4.1—THRESHOLDS FOR SINGLE RF SOURCES SUBJECT TO ROUTINE ENVIRONMENTAL EVALUATION

RF Source Frequency			Minimum Distance			Threshold ERP
f_L MHz		f_H MHz	$\lambda_L / 2\pi$		$\lambda_H / 2\pi$	W
0.3	–	1.34	159 m	–	35.6 m	1,920 R ²
1.34	–	30	35.6 m	–	1.6 m	3,450 R ² /f ²
30	–	300	1.6 m	–	159 mm	3.83 R ²
300	–	1,500	159 mm	–	31.8 mm	0.0128 R ² f
1,500	–	100,000	31.8 mm	–	0.5 mm	19.2R ²

Subscripts L and H are low and high; λ is wavelength.
From § 1.1307(b)(3)(i)(C), modified by adding Minimum Distance columns.

For mobile devices that are not exempt per Table 4.1 at distances from 20 cm to 40 cm and in 0.3 GHz to 6 GHz, evaluation of compliance with the exposure limits in §1.1310 is necessary if the ERP of the device is greater than ERP_{20cm} in Formula (4.1).

$$P_{th} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases} \quad (4.1)$$

In accordance with KDB447498D04 Either SAR-based or MPE-based exemption may be considered for test exemption for fixed, mobile, or portable device exposure conditions; therefore, the contributions from each exemption in conjunction with the measured SAR (Evaluated_k term) shall be used to determine exemption for simultaneous transmission according to Formula

$$\text{MPE Ratio} = \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} < 1$$

ERP_j: the available maximum time-averaged power or the ERP, whichever is greater, of fixed, mobile, or portable RF source j.

ERP_{th,j}: exemption threshold ERP for fixed, mobile, or portable RF source j, at a distance of at least $\lambda/2\pi$, according to the applicable § 1.1307(b)(3)(i)(C) Table 1 formula at the location in question.

the sum of the ratios of the applicable terms for SAR-based, MPE-based and measured SAR or MPE shall be less than 1, to determine simultaneous transmission exposure compliance

4. CALCULATION METHOD

Predication of MPE limit at a given distance

$EIRP(dBm) = \text{Maximum Tune-up Output power (dBm)} + \text{Maximum antenna gain (dBi)}$

$ERP(dBm) = EIRP(dBm) - 2.15$

R= minimum distance to the center of radiation of the antenna

From the EUT RF output power, the minimum mobile separation distance, $d=20\text{cm}$, as well as the maximum gain of the used as following information, the RF power ERP can be obtained.

Table 1 Antenna Specification

Mode	Antenna type	Internal Identification	Maximum antenna gain
BLE 1M	FPC antenna	Antenna 1	2dBi
BLE 2M	FPC antenna	Antenna 1	2dBi
Zigbee	FPC antenna	Antenna 1	2dBi
NFC	PCB antenna	Antenna 2	2dBi

Table 2 Transmit Power

Mode	Maximum Output Power (dBm)	Tune-up Output Power (dBm)
BLE 1M	7.75	8.00±1
BLE 2M	7.75	8.00±1
Zigbee	7.71	8.00±1

Mode	Maximum EIRP (dBm)	Tune-up EIRP (dBm)
NFC	-36.07	-36.00±1

Remark:

1) NFC Maximum EIRP(dBm) =NFC maximum output electric field

intensity(dBuV/m)+20log(d)-104.7=59.09dBuV/m +20log(3m)- 104.7= -36.07dBm

5. ESTIMATION RESULT

5.1 MEASUREMENT RESULTS

STANDALONE MPE

Mode	Frequency (MHz)	Maximum Tune-up Output power (dBm)	Antenna Gain (dBi)	Maximum Tune-up EIRP (dBm)	Maximum Tune-up ERP (dBm)	Maximum Tune-up ERP (W)	Threshold ERP (W)
BLE 1M	2402- 2480	9.00	2	11.00	8.85	0.008	0.768
BLE 2M	2402- 2480	9.00	2	11.00	8.85	0.008	0.768
Zigbee	2405-0475	9.00	2	11.00	8.85	0.008	0.768

Mode	Frequency (MHz)	Maximum Tune-up EIRP (dBm)	Maximum Tune-up ERP (dBm)	Maximum Tune-up ERP (W)	Threshold ERP (W)
NFC	13.56	-35.00	-37.15	0.00000019	0.751

Remark:

- 1) RF Exposure use distance is 20cm from manufacturer declaration of user manual.
- 2) $1.34 \text{ MHz} < f \leq 30 \text{ MHz}$ Threshold ERP(W)= $3450R^2 f^2$ (W)= $3450*0.2*0.2/(13.56*13.56)$ (W)=0.751(W),
 $1500 \text{ MHz} < f \leq 100 \text{ GHz}$ Threshold ERP(W)= $19.2R^2$ (W)= $19.2*0.2*0.2$ (W)=0.768(W) (where f is in MHz).
- 3) ERP(dBm)= EIRP(dBm)-2.15

----- The following blanks -----

Maximum Simultaneous transmission MPE ratio for BLE and NFC

Maximum MPE ratio Zigbee	Maximum MPE ratio NFC	Σ MPE ratios	Limit	Results
0.01040000	0.00000025	0.01040025	1.00000	Pass

Note:

1. The BLE and zigbee do not support simultaneous transmission, the BLE and NFC do not support simultaneous transmission, the zigbee and NFC support simultaneous.
2. ERP_j : the available maximum time-averaged power or the ERP, whichever is greater, of fixed, mobile, or portable RF source j.
3. $ERP_{th,j}$: exemption threshold ERP for fixed, mobile, or portable RF source j, at a distance of at least $\lambda/2\pi$, according to the applicable § 1.1307(b)(3)(i)(C) Table 1 formula at the location in question.
4. Maximum MPE Ratio (Zigbee) = Maximum Tune-up ERP/ Threshold ERP = $0.008W/0.768W = 0.0104$;
Maximum MPE Ratio (NFC) = Maximum Tune-up ERP/ Threshold ERP = $0.00000019W/0.751W = 0.00000025$;
 Σ MPE ratios = Maximum MPE Ratio (Zigbee) + Maximum MPE Ratio (NFC) = $0.0104 + 0.00000025 = 0.01040025$

----- The following blanks -----

6. CONCLUSION

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.

----- End of Report -----