

**RF EXPOSURE EVALUATION METHOD**

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

**EUT Specification**

<b>EUT</b>	POLAR 3D PRINTER
<b>Frequency band (Operating)</b>	<input checked="" type="checkbox"/> WLAN: 2.412GHz ~ 2.462GHz <input checked="" type="checkbox"/> WLAN: 5.150GHz ~ 5.250GHz <input checked="" type="checkbox"/> WLAN: 5.725GHz ~ 5.850GHz <input type="checkbox"/> Others
<b>Device category</b>	<input type="checkbox"/> Portable (<20cm separation) <input checked="" type="checkbox"/> Mobile (>20cm separation) <input type="checkbox"/> Others
<b>Exposure classification</b>	<input type="checkbox"/> Occupational/Controlled exposure (S = 5mW/cm2) <input checked="" type="checkbox"/> General Population/Uncontrolled exposure (S=1mW/cm2)
<b>Antenna diversity</b>	<input checked="" type="checkbox"/> Single antenna <input type="checkbox"/> Multiple antennas <input type="checkbox"/> Tx diversity <input type="checkbox"/> Rx diversity <input type="checkbox"/> Tx/Rx diversity
<b>Max. output power</b>	18.61dBm (0.0726W)
<b>Antenna gain (Max)</b>	0 dBi
<b>Evaluation applied</b>	<input checked="" type="checkbox"/> MPE Evaluation <input type="checkbox"/> SAR Evaluation

**Limits for Maximum Permissible Exposure(MPE)**

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density(mW/cm2)	Average Time
(A) Limits for Occupational/Control Exposures				
300-1500	--	--	F/300	6
1500-100000	--	--	5	6
(B) Limits for General Population/Uncontrol Exposures				
300-1500	--	--	F/1500	6
1500-100000	--	--	1	30

**transmission formula:  $Pd=(Pout \cdot G)/(4 \cdot \pi \cdot R^2)$**

Where

Pd= Power density in mW/cm2

Pout=output power to antenna in mW

G= gain of antenna in linear scale

Pi=3.1415

R= distance between observation point and center of the radiator in cm

Pd the limit of MPE, 1mW/cm2. If we know the maximum gain of the antenna and

total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

**SAR Test Exclusion Thresholds for 100 MHz - 6 GHz and  $\leq$  50 mm**

Approximate SAR Test Exclusion Power Thresholds at Selected Frequencies and Test Separation Distances are illustrated in the following Table.

MHz	5	10	15	20	25	mm
150	39	77	116	155	194	SAR Test Exclusion Threshold (mW)
300	27	55	82	110	137	
450	22	45	67	89	112	
835	16	33	49	66	82	
900	16	32	47	63	79	
1500	12	24	37	49	61	
1900	11	22	33	44	54	
2450	10	19	29	38	48	
3600	8	16	24	32	40	
5200	7	13	20	26	33	
5400	6	13	19	26	32	
5800	6	12	19	25	31	

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq$  50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where  $f(\text{GHz})$  is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is  $\leq$  50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $<$  5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

**Measurement Result**

Operating Mode	Frequency	Measured Power	Tune up tolerance	Max. Tune up Power	Antenna Gain	Power density at 20cm	Power density Limits
	(MHz)	(dBm)	(dBm)	(dBm)	(dBi)	(mW/ cm <sup>2</sup> )	(mW/ cm <sup>2</sup> )
802.11b	2412	17.97	18±1	19.00	0.0	0.0158	1
	2437	18.20	18±1	19.00	0.0	0.0158	1
	2462	18.61	18±1	19.00	0.0	0.0158	1
802.11g	2412	18.48	18±1	19.00	0.0	0.0158	1
	2437	18.34	18±1	19.00	0.0	0.0158	1
	2462	18.49	18±1	19.00	0.0	0.0158	1
802.11n (HT20)	2412	16.56	16±1	17.00	0.0	0.0100	1
	2437	16.44	16±1	17.00	0.0	0.0100	1
	2462	16.60	16±1	17.00	0.0	0.0100	1
802.11a	5180	9.79	9±1	10.00	0.0	0.0020	1
	5220	9.27	9±1	10.00	0.0	0.0020	1
	5240	9.36	9±1	10.00	0.0	0.0020	1
	5745	8.27	9±1	10.00	0.0	0.0020	1
	5765	8.56	9±1	10.00	0.0	0.0020	1
	5805	8.34	9±1	10.00	0.0	0.0020	1

Note: The estimation distance is 20cm.

This device support 802.11abgn 2.4g+5g mode. This device is not supported simultaneous transmission(2.4G WIFI+5GWIFI), When used 2,4g wifi, the 5g wifi is unactivated. and vice versa.

**Conclusion**

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device