




2DH5 Left side 2480\_30~1000




2DH5 Left side 2480\_1000~26500




2DH5 Right side 2480\_0~Reference




2DH5 Right side 2480 30~1000




2DH5 Right side 2480 1000~26500




3DH5 Left side 2402 0~Reference




3DH5 Left side 2402 30~1000




3DH5 Left side 2402 1000~26500




3DH5 Right side 2402 0~Reference




3DH5 Right side 2402 30~1000




3DH5 Right side 2402 1000~26500




3DH5 Left side 2441 0~Reference




3DH5 Left side 2441 30~1000




3DH5 Left side 2441 1000~26500




3DH5 Right side 2441 0~Reference






3DH5 Right side 2441 30~1000




3DH5 Right side 2441 1000~26500




3DH5 Left side 2480 0~Reference






3DH5 Right side 2480 30~1000




3DH5 Right side 2480 1000~26500





## 12. Duty cycle

### 12.1. Block diagram of test setup



### 12.2. Limit

Just for Report.

### 12.3. Test procedure

(1) Connected the EUT's antenna port to the Spectrum Analyzer by suitable attenuator, The cable loss and attenuator loss have been put into spectrum analyzer as amplitude offset.

set the Spectrum Analyzer as below:

Centre Frequency: The centre frequency of the middle hopping channel.

Resolution BW: 10 MHz.

Video BW: 10 MHz.

Span: Zero span.

Detector: Peak.

Trace Mode: Clear Write.

Sweep: Video Trigger

(2) When the trace is complete, measure the sending time of 1 burst and the duty cycle of 1 burst cycle.

(3) Calculate dwell time follow below formula:

Duty cycle= Pulse's on time / Burst cycle


## 12.4. Test result

Test Engineer:	Zhongyao	Test Site:	RF Measurement System 3#
Ambient Condition:	24.4°C,38.7%RH	Test Date:	2024.06.06-2024.06.07
Test Power Supply:	Battery	Sample Number:	S24050810-010


Test Mode	Antenna	Frequency [MHz]	ON Time [ms]	Period [ms]	Duty Cycle [%]	Duty Cycle Factor[dB]
DH5	Left side	2402	2.90	3.76	77.13	1.13
	Right side	2402	2.89	3.75	77.07	1.13
	Left side	2441	2.89	3.75	77.07	1.13
	Right side	2441	2.89	3.75	77.07	1.13
	Left side	2480	2.89	3.75	77.07	1.13
	Right side	2480	2.89	3.75	77.07	1.13
2DH5	Left side	2402	2.90	3.75	77.33	1.12
	Right side	2402	2.89	3.75	77.07	1.13
	Left side	2441	2.90	3.76	77.13	1.13
	Right side	2441	2.89	3.75	77.07	1.13
	Left side	2480	2.90	3.76	77.13	1.13
	Right side	2480	2.89	3.75	77.07	1.13
3DH5	Left side	2402	2.89	3.75	77.07	1.13
	Right side	2402	2.90	3.75	77.33	1.12
	Left side	2441	2.89	3.75	77.07	1.13
	Right side	2441	2.90	3.75	77.33	1.12
	Left side	2480	2.91	3.76	77.39	1.11
	Right side	2480	2.91	3.76	77.39	1.11

### 12.5. Test graphs







DH5 Left side 2480




DH5 Right side 2480




2DH5 Left side 2402




2DH5\_Right side\_2402




2DH5\_Left side\_2441




2DH5\_Right side\_2402




2DH5 Left side 2480




2DH5 Right side 2480




3DH5 Left side 2402






3DH5\_Right side\_2402



3DH5\_Left side\_2441



3DH5\_Right side\_2441





## 13. Antenna Requirements

### 13.1. Limit

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For intentional device, according to RSS-Gen issue 5 section 6.8.

The applicant for equipment certification shall provide a list of all antenna types that may be used with the transmitter, where applicable (i.e. for transmitters with detachable antenna), indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna. The test report shall demonstrate the compliance of the transmitter with the limit for maximum equivalent isotropically radiated power (e.i.r.p.) specified in the applicable RSS, when the transmitter is equipped with any antenna type, selected from this list.

### 13.2. Result



The antenna used for this product as Antenna information described in section 2.1 of the report, and there is no other antenna than that furnished by the responsible party shall be used with the device.


## 14.Radiated Emission

### 14.1. Test equipment

Equipment	Manufacturer	Model No.	Serial No.	Cal Due To
Micro-Tronics filters	REBES	BRM50716	DDT-ZC03240	/
Pre-amplifier	COM-POWER	PAM-118A	DDT-ZC01293	2024/07/14
Trilog Broadband Antenna	Schwarzbeck	VULB 9163	DDT-ZC02050	2024/07/11
EMI TEST RECEIVER	R&S	ESU26	DDT-ZC01909	2025/03/31
RF cable	Yuhu Technology	JCTB810-NJ-NJ-9M	DDT-ZC02538	2025/03/31
Broad-Band Horn Antenna	Schwarzbeck	BBHA 9170	DDT-ZC00506	2025/04/26
RF Cable	N/A	W13.02 AP1-X2	DDT-ZC04023	2025/03/31
Hochgewinn-Hornantenne	SCHWARZBEC K	BBHA 9120 D	DDT-ZC02129	2025/09/18
High pass filter	Micro-Tronics	HPM50108	DDT-ZC00560	2025/04/22
PSA Series Spectrum Analyzer	Agilent	E4447A	DDT-ZC00517	2025/03/31
Micro-Tronics filters	REBES	BRM50702	DDT-ZC03242	/
High Pass filter	Xi'an Xingbo	XBLBQ-GTA67	DDT-ZC02179	2025/04/22
RF cable	Zhongke Junchuang	JCT26S-NJ-NJ-1.5M	DDT-ZC02762	2025/03/31
RF cable	Yuhu Technology	ZT26S-SMAJ-SMAJ-1M	DDT-ZC02037	2025/03/31
ELECTRIC AND MAGNETIC FIELD ANALYZER	Narda	EHP-200A	DDT-ZC01401	2024/09/20
Pre-amplifier	COM-POWER	PAM-840A	DDT-ZC01693	2025/03/31
RF Cable	N/A	W24.02 HL-562	DDT-ZC04022	2025/03/31
Active Loop Antenna	Schwarzbeck	FMZB1519	DDT-ZC00524	2025/09/11
High pass filter	Micro-Tronics	HPM50102	DDT-ZC00561	2025/04/22

### 14.2. Block diagram of test setup





**14.3. Limits**

(1) FCC 15.205 Restricted frequency band

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
10.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.1772&4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.2072&4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(2)
13.36-13.41			

1Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz

2Above 38.6

RSS-Gen section 8.10 Restricted frequency bands\*

MHz	MHz	MHz	GHz
0.090-0.110	12.51975-12.52025	240-285	3.5-4.4
0.495-0.505	12.57675-12.57725	322-335.4	4.5-5.15
2.1735-2.1905	13.36-13.41	399.9-410	5.35-5.46
3.020-3.026	16.42-16.423	608-614	7.25-7.75
4.125-4.128	16.69475-16.69525	960-1427	8.025-8.5
4.1772&4.17775	16.80425-16.80475	1435-1626.5	9.0-9.2
4.2072&4.20775	25.5-25.67	1645.5-1646.5	9.3-9.5
5.677-5.683	37.5-38.25	1660-1710	10.6-12.7
6.215-6.218	73-74.6	1718.8-1722.2	13.25-13.4
6.26775-6.26825	74.8-75.2	2200-2300	14.47-14.5
6.31175-6.31225	108-138	2310-2390	15.35-16.2
8.291-8.294	149.9-150.05	2483.5-2500	17.7-21.4
8.362-8.366	156.52475-156.52525	2655-2900	22.01-23.12
8.37625-8.38675	156.7-156.9	3260-3267	23.6-24.0
8.41425-8.41475	162.0125-167.17	3332-3339	31.2-31.8
12.29-12.293	167.72-173.2	3345.8-3358	36.43-36.5
			Above 38.6

\* Certain frequency bands listed in table and in bands above 38.6 GHz are designated for licence-exempt applications. These frequency bands and the requirements that apply to related devices are set out in the 200 and 300 series of RSSs.

(2) FCC 15.209 Limit & RSS-Gen section 8.9 Limit

FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMIT	
		mV/m	dB(mV)/m
0.009 ~ 0.490	300	2400/F(kHz)	67.6-20log(F)
0.490 ~ 1.705	30	24000/F(kHz)	87.6-20log(F)
1.705 ~ 30.0	30	30	29.54
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0
Above 1000	3	74.0 dB(mV)/m (Peak) 54.0 dB(mV)/m (Average)	

Note:

(1) The emission limits shown in the above table are based on measurements employing a CISPR QP detector except for the frequency bands 9 - 90 kHz, 110 - 490 kHz and above 1000 MHz, radiated emissions limits in these three bands are based on measurements employing an average detector.

(2) At frequencies below 30 MHz, measurement may be performed at a distance closer than that specified, and the limit at closer measurement distance can be extrapolated by below formula:

$$\text{Limit}_{3\text{m}}(\text{dBuV/m}) = \text{Limit}_{30\text{m}}(\text{dBuV/m}) + 40\text{Log}(30\text{m}/3\text{m})$$

### (3) Limit for this EUT

The emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209, and the emissions appearing within RSS-Gen section 8.10 Restricted frequency bands shall not exceed the limits shown in RSS-Gen section 8.9, all the other emissions shall be at least 20 dB below the fundamental emissions or comply with 15.209 limits and RSS-Gen section 8.9 limits.

### 14.4. Assistant equipment used for test

Assistant equipment	Manufacturer	Model number	Description	other
/	/	/	/	/

### 14.5. Test procedure

- (1) EUT was placed on a non-metallic table, 80 cm above the ground plane inside a semi-anechoic chamber for below 1G and 150 cm above the ground plane inside a fully-anechoic chamber for above 1G.
- (2) Test antenna was located 3 m from the EUT on an adjustable mast, and the antenna used as below table.

Test frequency range	Test antenna used	Test antenna distance
9 kHz - 30 MHz	Active Loop antenna	3 m
30 MHz - 1 GHz	Trilog Broadband Antenna	3 m
1 GHz - 18 GHz	Double Ridged Horn Antenna(1 GHz-18 GHz)	3 m
18 GHz - 40 GHz	Horn Antenna(18 GHz-40 GHz)	1 m

According ANSI C63.10:2013 clause 6.4.6 and 6.5.3, for measurements below 30 MHz, Antenna was located 3 m from EUT, the loop antenna was positioned in three antenna orientations (parallel, perpendicular, and round-parallel), for each measurement antenna alignment, the EUT shall be rotated through 0° to 360° on a turntable, and the lowest height of the magnetic antenna shall be 1 m above the ground. For measurement above 30MHz, the trilog Broadband Antenna or Horn Antenna was located 3m from EUT, Measurements were made with the antenna positioned in both the horizontal and vertical planes of Polarization, and the measurement antenna was varied from 1 m to 4 m. in height above the reference ground plane to obtain the maximum signal strength.

(3) Below pre-scan procedure was first performed in order to find prominent frequency spectrum radiated emissions from 9 kHz to 25 GHz:

(a) Scanning the peak frequency spectrum with the antenna specified in step (3), and the EUT was rotated 360 degree, the antenna height was varied from 1 m to 4 m (Except loop antenna, it's fixed 1 m above ground.)

(b) Change work frequency or channel of device if practicable.

(c) Change modulation type of device if practicable.

(d) Change power supply range from 85% to 115% of the rated supply voltage

(e) Rotated EUT through three orthogonal axes to determine the attitude of EUT arrangement produces highest emissions.

Spectrum frequency from 9 kHz to 25 GHz (tenth harmonic of fundamental frequency) was investigated, and no any obvious emission were detected from 18 GHz to 25 GHz, so below final test was performed with frequency range from 9 kHz to 18 GHz.

(4) For final emissions measurements at each frequency of interest, the EUT was rotated and the antenna height was varied between 1 m and 4 m in order to maximize the emission. Measurements in both horizontal and vertical polarities were made and the data was recorded. In order to find the maximum emission, the relative positions of equipment and all of the interface cables were changed according to ANSI C63.10:2013 on Radiated Emission test.

(5) The emissions from 9 kHz to 1 GHz were measured based on CISPR QP detector except for the frequency bands 9 - 90 kHz, 110 - 490 kHz, for emissions from 9 kHz - 90 kHz, 110 kHz - 490 kHz and above 1 GHz were measured based on average detector, for emissions above 1 GHz, peak emissions also be measured and need comply with Peak limit.

(6) The emissions from 9 kHz to 1 GHz, QP or average values were measured with EMI receiver with below RBW.

Frequency band	RBW
9 kHz - 150 kHz	200 Hz
150 kHz - 30 MHz	9 kHz
30 MHz - 1 GHz	120 kHz

(7) For emissions above 1GHz, both Peak and Average level were measured with Spectrum Analyzer, and the RBW is set at 1 MHz, VBW is set at 3 MHz for Peak measure; According ANSI C63.10:2013 clause 4.1.4.2.2 procedure for average measure.

(8) For portable device, X axis, Y axis, Z axis are tested, and worse setup is reported.

(9) According exploratory test, the emission levels are 20 dB below the limit detected from 9 kHz to 30 MHz and 18 GHz to 25 GHz, so the final test was performed with frequency range from 30 MHz to 18 GHz and recorded in below.

(10) For 30 MHz ~ 25 GHz: (Scan with GFSK,  $\pi/4$ -DQPSK and 8DPSK, the worst case is record and reported)

(11) For emissions below 1 GHz, according exploratory explorer test, when change Tx mode and channel, have no distinct influence on emissions level, so for emissions below 1 GHz, the final test was only performed with EUT working in worst mode.


#### 14.6. Test result

**PASS. (See below detailed test result)**

14.7. Test data

## TR-4-E-009 Radiated Emission Test Result

**Test Date:** 2024-06-07 **Tested By:** Junchang Du  
**EUT:** WIRELESS HEADPHONES **Model Number:** HA-NP40T  
**Test Mode:** BT TX **Power Supply:** Battery  
**Condition:** Temp:22.9°C;Humi:60.0% **Test Site:** DDT 3# Chamber  
**File Path:** d:\ts\2024 report data\Q24050810-1E\FCC BELOW 1G\20240607-220612\_H  
**Memo:** L Sample Number:S24050810-011



Data List										
NO.	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable Loss [dB]	AMP [dB]	Result [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	30.983	32.11	10.40	3.77	-30.99	15.29	40.00	24.71	QP	Horizontal
2	53.687	28.48	12.71	3.91	-30.68	14.42	40.00	25.58	QP	Horizontal
3	69.784	29.27	9.95	4.02	-30.57	12.67	40.00	27.33	QP	Horizontal
4	300.018	23.34	13.70	5.22	-30.30	11.96	46.00	34.04	QP	Horizontal
5	690.099	23.17	19.50	6.66	-29.90	19.43	46.00	26.57	QP	Horizontal
6	901.430	23.28	21.90	7.20	-28.99	23.39	46.00	22.61	QP	Horizontal


Note:

1. Result Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.
3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.



# TR-4-E-009 Radiated Emission Test Result

**Test Date:** 2024-06-07      **Tested By:** Junchang Du  
**EUT:** WIRELESS HEADPHONES      **Model Number:** HA-NP40T  
**Test Mode:** BT TX      **Power Supply:** Battery  
**Condition:** Temp:22.9°C;Humi:60.0%      **Test Site:** DDT 3# Chamber  
**File Path:** d:\ts\2024 report data\Q24050810-1E\FCC BELOW 1G\20240607-220654\_V  
**Memo:** L Sample Number:S24050810-011




Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable Loss [dB]	AMP [dB]	Result [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	44.241	31.21	13.05	3.85	-30.79	17.32	40.00	22.68	QP	Vertical
2	54.331	33.11	12.43	3.91	-30.67	18.78	40.00	21.22	QP	Vertical
3	69.735	40.84	9.99	4.02	-30.57	24.28	40.00	15.72	QP	Vertical
4	242.254	23.18	11.66	4.95	-30.47	9.32	46.00	36.68	QP	Vertical
5	608.274	23.6	19.26	6.40	-29.90	19.36	46.00	26.64	QP	Vertical
6	994.406	24.26	22.54	7.45	-28.15	26.10	54.00	27.90	QP	Vertical

**Note:**

1. Result Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.
3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

# TR-4-E-009 Radiated Emission Test Result

**Test Date:** 2024-06-07 **Tested By:** Junchang Du  
**EUT:** WIRELESS HEADPHONES **Model Number:** HA-NP40T  
**Test Mode:** BT TX **Power Supply:** Battery  
**Condition:** Temp:22.9°C;Humi:60.0% **Test Site:** DDT 3# Chamber  
**File Path:** d:\ts\2024 report data\Q24050810-1E\FCC BELOW 1G\20240607-215416\_H  
**Memo:** R Sample Number:S24050810-011




Data List										
NO.	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable Loss [dB]	AMP [dB]	Result [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	30.810	31.43	10.38	3.76	-30.99	14.58	40.00	25.42	QP	Horizontal
2	54.141	28.2	12.36	3.91	-30.67	13.80	40.00	26.20	QP	Horizontal
3	70.473	27.86	9.66	4.02	-30.56	10.98	40.00	29.02	QP	Horizontal
4	269.121	23.63	12.36	5.08	-30.39	10.68	46.00	35.32	QP	Horizontal
5	453.109	24.44	15.92	5.82	-29.99	16.19	46.00	29.81	QP	Horizontal
6	951.436	23.14	22.38	7.33	-28.54	24.31	46.00	21.69	QP	Horizontal

**Note:**

1. Result Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.
3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

# TR-4-E-009 Radiated Emission Test Result

**Test Date:** 2024-06-07 **Tested By:** Junchang Du  
**EUT:** WIRELESS HEADPHONES **Model Number:** HA-NP40T  
**Test Mode:** BT TX **Power Supply:** Battery  
**Condition:** Temp:22.9°C;Humi:60.0% **Test Site:** DDT 3# Chamber  
**File Path:** d:\ts\2024 report data\Q24050810-1E\FCC BELOW 1G\20240607-215459\_V  
**Memo:** R Sample Number:S24050810-011



Data List										
NO.	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable Loss [dB]	AMP [dB]	Result [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	32.542	33.61	10.53	3.78	-30.96	16.96	40.00	23.04	QP	Vertical
2	44.179	31.55	13.04	3.85	-30.79	17.65	40.00	22.35	QP	Vertical
3	54.828	32.48	12.63	3.92	-30.67	18.36	40.00	21.64	QP	Vertical
4	69.784	40.14	9.95	4.02	-30.57	23.54	40.00	16.46	QP	Vertical
5	308.120	23.26	13.45	5.25	-30.28	11.68	46.00	34.32	QP	Vertical
6	701.811	26.16	19.64	6.69	-29.90	22.59	46.00	23.41	QP	Vertical


**Note:**

1. Result Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.
3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

# TR-4-E-009 Radiated Emission Test Result

**Test Date:** 2024-06-07 **Tested By:** Junchang Du  
**EUT:** WIRELESS HEADPHONES **Model Number:** HA-NP40T  
**Test Mode:** DH5 TX 2402MHz **Power Supply:** Battery  
**Condition:** Temp:22.9°C;Humi:60.0% **Test Site:** DDT 3# Chamber  
**File Path:** d:\ts\2024 report data\Q24050810-1E\FCC ABOVE 1G\1  
**Memo:** L Sample Number:S24050810-011 Power Setting:10

## Test Graph



Data List										
NO	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	2224.000	44.93	27.56	4.73	-37.64	39.58	74.00	34.42	PK	Horizontal
2	3822.000	46.12	30.79	5.08	-40.34	41.65	74.00	32.35	PK	Horizontal
3	4804.600	50.75	32.62	5.53	-40.15	48.75	74.00	25.25	PK	Horizontal
4	7412.400	43.93	36.68	6.66	-41.73	45.54	74.00	28.46	PK	Horizontal
5	11319.000	41.38	39.22	8.33	-39.24	49.69	74.00	24.31	PK	Horizontal
6	15796.800	39.62	38.31	10.01	-39.24	48.70	74.00	25.30	PK	Horizontal


**Note:**

- Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

# TR-4-E-009 Radiated Emission Test Result

**Test Date:** 2024-06-07 **Tested By:** Junchang Du  
**EUT:** WIRELESS HEADPHONES **Model Number:** HA-NP40T  
**Test Mode:** DH5 TX 2402MHz **Power Supply:** Battery  
**Condition:** Temp:22.9°C;Humi:60.0% **Test Site:** DDT 3# Chamber  
**File Path:** d:\ts\2024 report data\Q24050810-1E\FCC ABOVE 1G\2  
**Memo:** L Sample Number:S24050810-011 Power Setting:10

## Test Graph



Data List										
NO	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	2278.400	47.13	27.02	4.77	-37.80	41.12	74.00	32.88	PK	Vertical
2	3680.900	46.32	30.32	5.10	-40.26	41.48	74.00	32.52	PK	Vertical
3	4830.100	44.93	33.28	5.55	-40.14	43.62	74.00	30.38	PK	Vertical
4	7473.600	44.40	36.55	6.69	-41.88	45.76	74.00	28.24	PK	Vertical
5	11234.000	41.98	39.20	8.28	-39.20	50.26	74.00	23.74	PK	Vertical
6	15820.600	40.67	38.26	10.03	-39.25	49.71	74.00	24.29	PK	Vertical


**Note:**

- Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

# TR-4-E-009 Radiated Emission Test Result

**Test Date:** 2024-06-07 **Tested By:** Junchang Du  
**EUT:** WIRELESS HEADPHONES **Model Number:** HA-NP40T  
**Test Mode:** DH5 TX 2441MHz **Power Supply:** Battery  
**Condition:** Temp:22.9°C;Humi:60.0% **Test Site:** DDT 3# Chamber  
**File Path:** d:\ts\2024 report data\Q24050810-1E\FCC ABOVE 1G\3  
**Memo:** L Sample Number:S24050810-011 Power Setting:10

## Test Graph



Data List										
NO	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	2218.900	45.23	27.61	4.73	-37.63	39.94	74.00	34.06	PK	Horizontal
2	3929.100	46.19	31.14	5.06	-40.41	41.98	74.00	32.02	PK	Horizontal
3	4882.800	49.54	33.28	5.58	-40.12	48.28	74.00	25.72	PK	Horizontal
4	7351.200	42.32	36.80	6.63	-41.58	44.17	74.00	29.83	PK	Horizontal
5	11509.400	41.57	39.18	8.45	-39.33	49.87	74.00	24.13	PK	Horizontal
6	15723.700	39.30	38.45	9.96	-39.19	48.52	74.00	25.48	PK	Horizontal


**Note:**

- Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

# TR-4-E-009 Radiated Emission Test Result

**Test Date:** 2024-06-07 **Tested By:** Junchang Du  
**EUT:** WIRELESS HEADPHONES **Model Number:** HA-NP40T  
**Test Mode:** DH5 TX 2441MHz **Power Supply:** Battery  
**Condition:** Temp:22.9°C;Humi:60.0% **Test Site:** DDT 3# Chamber  
**File Path:** d:\ts\2024 report data\Q24050810-1E\FCC ABOVE 1G\4  
**Memo:** L Sample Number:S24050810-011 Power Setting:10

## Test Graph



Data List										
NO	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	2208.700	44.85	27.71	4.72	-37.60	39.68	74.00	34.32	PK	Vertical
2	4105.900	46.15	31.11	5.11	-40.41	41.96	74.00	32.04	PK	Vertical
3	4872.600	43.93	33.44	5.57	-40.13	42.81	74.00	31.19	PK	Vertical
4	7373.300	43.34	36.75	6.64	-41.63	45.10	74.00	28.90	PK	Vertical
5	11150.700	42.03	39.25	8.22	-39.16	50.34	74.00	23.66	PK	Vertical
6	15592.800	38.81	38.61	9.88	-39.12	48.18	74.00	25.82	PK	Vertical


**Note:**

- Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

# TR-4-E-009 Radiated Emission Test Result

**Test Date:** 2024-06-07 **Tested By:** Junchang Du  
**EUT:** WIRELESS HEADPHONES **Model Number:** HA-NP40T  
**Test Mode:** DH5 TX 2480MHz **Power Supply:** Battery  
**Condition:** Temp:22.9°C;Humi:60.0% **Test Site:** DDT 3# Chamber  
**File Path:** d:\ts\2024 report data\Q24050810-1E\FCC ABOVE 1G\5  
**Memo:** L Sample Number:S24050810-011 Power Setting:10

## Test Graph



Data List										
NO	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	2280.100	45.25	27.00	4.77	-37.80	39.22	74.00	34.78	PK	Horizontal
2	3832.200	45.91	30.83	5.08	-40.35	41.47	74.00	32.53	PK	Horizontal
3	4959.300	48.21	33.12	5.63	-40.10	46.86	74.00	27.14	PK	Horizontal
4	7439.600	44.87	36.62	6.67	-41.80	46.36	74.00	27.64	PK	Horizontal
5	11504.300	41.33	39.19	8.45	-39.33	49.64	74.00	24.36	PK	Horizontal
6	15487.400	39.72	38.83	9.81	-39.05	49.31	74.00	24.69	PK	Horizontal

**Note:**


- Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.



# TR-4-E-009 Radiated Emission Test Result

**Test Date:** 2024-06-07 **Tested By:** Junchang Du  
**EUT:** WIRELESS HEADPHONES **Model Number:** HA-NP40T  
**Test Mode:** DH5 TX 2480MHz **Power Supply:** Battery  
**Condition:** Temp:22.9°C;Humi:60.0% **Test Site:** DDT 3# Chamber  
**File Path:** d:\ts\2024 report data\Q24050810-1E\FCC ABOVE 1G\6  
**Memo:** L Sample Number:S24050810-011 Power Setting:10

## Test Graph



Data List										
NO	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	2210.400	45.18	27.70	4.72	-37.61	39.99	74.00	34.01	PK	Vertical
2	3839.000	46.82	30.86	5.08	-40.35	42.41	74.00	31.59	PK	Vertical
3	5039.200	44.85	33.28	5.67	-40.07	43.73	74.00	30.27	PK	Vertical
4	7439.600	45.97	36.62	6.67	-41.80	47.46	74.00	26.54	PK	Vertical
5	11823.900	42.24	38.90	8.65	-39.48	50.31	74.00	23.69	PK	Vertical
6	15580.900	39.61	38.64	9.87	-39.11	49.01	74.00	24.99	PK	Vertical


**Note:**

- Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

# TR-4-E-009 Radiated Emission Test Result

**Test Date:** 2024-06-07 **Tested By:** Junchang Du  
**EUT:** WIRELESS HEADPHONES **Model Number:** HA-NP40T  
**Test Mode:** DH5 TX 2402MHz **Power Supply:** Battery  
**Condition:** Temp:22.9°C;Humi:60.0% **Test Site:** DDT 3# Chamber  
**File Path:** d:\ts\2024 report data\Q24050810-1E\FCC ABOVE 1G\19  
**Memo:** R Sample Number:S24050810-011 Power Setting:10

## Test Graph



Data List										
NO	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	2261.400	45.05	27.19	4.75	-37.75	39.24	74.00	34.76	PK	Horizontal
2	3818.600	45.29	30.77	5.08	-40.34	40.80	74.00	33.20	PK	Horizontal
3	4804.600	45.82	32.62	5.53	-40.15	43.82	74.00	30.18	PK	Horizontal
4	7431.100	43.36	36.64	6.67	-41.78	44.89	74.00	29.11	PK	Horizontal
5	12038.100	41.78	39.24	8.78	-39.57	50.23	74.00	23.77	PK	Horizontal
6	15764.500	39.41	38.37	9.99	-39.22	48.55	74.00	25.45	PK	Horizontal


**Note:**

- Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

# TR-4-E-009 Radiated Emission Test Result

**Test Date:** 2024-06-07 **Tested By:** Junchang Du  
**EUT:** WIRELESS HEADPHONES **Model Number:** HA-NP40T  
**Test Mode:** DH5 TX 2402MHz **Power Supply:** Battery  
**Condition:** Temp:22.9°C;Humi:60.0% **Test Site:** DDT 3# Chamber  
**File Path:** d:\ts\2024 report data\Q24050810-1E\FCC ABOVE 1G\20  
**Memo:** R Sample Number:S24050810-011 Power Setting:10

## Test Graph



Data List										
NO	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	2210.400	45.91	27.70	4.72	-37.61	40.72	74.00	33.28	PK	Vertical
2	4141.600	45.67	31.18	5.13	-40.40	41.58	74.00	32.42	PK	Vertical
3	4804.600	45.65	32.62	5.53	-40.15	43.65	74.00	30.35	PK	Vertical
4	7398.800	43.17	36.70	6.65	-41.70	44.82	74.00	29.18	PK	Vertical
5	11497.500	42.17	39.20	8.44	-39.32	50.49	74.00	23.51	PK	Vertical
6	15750.900	39.27	38.40	9.98	-39.21	48.44	74.00	25.56	PK	Vertical


**Note:**

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

# TR-4-E-009 Radiated Emission Test Result

**Test Date:** 2024-06-07 **Tested By:** Junchang Du  
**EUT:** WIRELESS HEADPHONES **Model Number:** HA-NP40T  
**Test Mode:** DH5 TX 2441MHz **Power Supply:** Battery  
**Condition:** Temp:22.9°C;Humi:60.0% **Test Site:** DDT 3# Chamber  
**File Path:** d:\ts\2024 report data\Q24050810-1E\FCC ABOVE 1G\21  
**Memo:** R Sample Number:S24050810-011 Power Setting:10

## Test Graph



Data List										
NO	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	2264.800	46.64	27.15	4.76	-37.76	40.79	74.00	33.21	PK	Horizontal
2	3903.600	46.09	31.19	5.07	-40.39	41.96	74.00	32.04	PK	Horizontal
3	4882.800	47.44	33.28	5.58	-40.12	46.18	74.00	27.82	PK	Horizontal
4	7449.800	43.11	36.60	6.68	-41.82	44.57	74.00	29.43	PK	Horizontal
5	11375.100	41.37	39.28	8.37	-39.27	49.75	74.00	24.25	PK	Horizontal
6	15703.300	39.14	38.49	9.95	-39.18	48.40	74.00	25.60	PK	Horizontal


**Note:**

- Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

# TR-4-E-009 Radiated Emission Test Result

**Test Date:** 2024-06-07 **Tested By:** Junchang Du  
**EUT:** WIRELESS HEADPHONES **Model Number:** HA-NP40T  
**Test Mode:** DH5 TX 2441MHz **Power Supply:** Battery  
**Condition:** Temp:22.9°C;Humi:60.0% **Test Site:** DDT 3# Chamber  
**File Path:** d:\ts\2024 report data\Q24050810-1E\FCC ABOVE 1G\22  
**Memo:** R Sample Number:S24050810-011 Power Setting:10

## Test Graph



Data List										
NO	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	2266.500	45.34	27.14	4.76	-37.76	39.48	74.00	34.52	PK	Vertical
2	3653.700	46.87	30.21	5.11	-40.24	41.95	74.00	32.05	PK	Vertical
3	4882.800	44.82	33.28	5.58	-40.12	43.56	74.00	30.44	PK	Vertical
4	7322.300	43.80	36.86	6.61	-41.51	45.76	74.00	28.24	PK	Vertical
5	11517.900	41.66	39.16	8.46	-39.33	49.95	74.00	24.05	PK	Vertical
6	15902.200	39.75	38.10	10.08	-39.30	48.63	74.00	25.37	PK	Vertical


**Note:**

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

# TR-4-E-009 Radiated Emission Test Result

**Test Date:** 2024-06-07 **Tested By:** Junchang Du  
**EUT:** WIRELESS HEADPHONES **Model Number:** HA-NP40T  
**Test Mode:** DH5 TX 2480MHz **Power Supply:** Battery  
**Condition:** Temp:22.9°C;Humi:60.0% **Test Site:** DDT 3# Chamber  
**File Path:** d:\ts\2024 report data\Q24050810-1E\FCC ABOVE 1G\23  
**Memo:** R Sample Number:S24050810-011 Power Setting:10

## Test Graph



Data List										
NO	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	2288.600	46.55	26.91	4.77	-37.83	40.40	74.00	33.60	PK	Horizontal
2	3920.600	45.80	31.16	5.06	-40.40	41.62	74.00	32.38	PK	Horizontal
3	4959.300	50.00	33.12	5.63	-40.10	48.65	74.00	25.35	PK	Horizontal
4	7424.300	43.17	36.65	6.66	-41.76	44.72	74.00	29.28	PK	Horizontal
5	11529.800	42.34	39.14	8.46	-39.34	50.60	74.00	23.40	PK	Horizontal
6	15614.900	39.37	38.59	9.89	-39.13	48.72	74.00	25.28	PK	Horizontal


**Note:**

- Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

# TR-4-E-009 Radiated Emission Test Result

**Test Date:** 2024-06-07 **Tested By:** Junchang Du  
**EUT:** WIRELESS HEADPHONES **Model Number:** HA-NP40T  
**Test Mode:** DH5 TX 2480MHz **Power Supply:** Battery  
**Condition:** Temp:22.9°C;Humi:60.0% **Test Site:** DDT 3# Chamber  
**File Path:** d:\ts\2024 report data\Q24050810-1E\FCC ABOVE 1G\24  
**Memo:** R Sample Number:S24050810-011 Power Setting:10

## Test Graph



Data List										
NO	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	2222.300	44.69	27.58	4.73	-37.64	39.36	74.00	34.64	PK	Vertical
2	3641.800	45.92	30.17	5.11	-40.23	40.97	74.00	33.03	PK	Vertical
3	4959.300	46.25	33.12	5.63	-40.10	44.90	74.00	29.10	PK	Vertical
4	7439.600	44.85	36.62	6.67	-41.80	46.34	74.00	27.66	PK	Vertical
5	11336.000	42.30	39.24	8.34	-39.25	50.63	74.00	23.37	PK	Vertical
6	15659.100	38.66	38.54	9.92	-39.16	47.96	74.00	26.04	PK	Vertical

**Note:**

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

## 15. Band Edge Compliance

### 15.1. Test equipment

Equipment	Manufacturer	Model No.	Serial No.	Cal Due To
PSA Series Spectrum Analyzer	Agilent	E4447A	DDT-ZC00517	2025/03/31
RF cable	Yuhu Technology	ZT26S-SMAJ-SMAJ-1M	DDT-ZC02037	2025/03/31
Broad-Band Horn Antenna	Schwarzbeck	BBHA 9170	DDT-ZC00506	2025/04/26
RF Cable	N/A	W13.02 AP1-X2	DDT-ZC04023	2025/03/31
RF cable	Yuhu Technology	JCTB810-NJ-NJ-9M	DDT-ZC02538	2025/03/31
Trilog Broadband Antenna	Schwarzbeck	VULB 9163	DDT-ZC02050	2024/07/11
Active Loop Antenna	Schwarzbeck	FMZB1519	DDT-ZC00524	2025/09/11
RF cable	Zhongke Junchuang	JCT26S-NJ-NJ-1.5M	DDT-ZC02762	2025/03/31
High pass filter	Micro-Tronics	HPM50102	DDT-ZC00561	2025/04/22
Micro-Tronics filters	REBES	BRM50702	DDT-ZC03242	/
Pre-amplifier	COM-POWER	PAM-118A	DDT-ZC01293	2024/07/14
Hochgewinn-Hornantenne	SCHWARZBECK	BBHA 9120 D	DDT-ZC02129	2025/09/18
Pre-amplifier	COM-POWER	PAM-840A	DDT-ZC01693	2025/03/31
High pass filter	Micro-Tronics	HPM50108	DDT-ZC00560	2025/04/22
RF Cable	N/A	W24.02 HL-562	DDT-ZC04022	2025/03/31
Micro-Tronics filters	REBES	BRM50716	DDT-ZC03240	/
EMI TEST RECEIVER	R&S	ESU26	DDT-ZC01909	2025/03/31
High Pass filter	Xi'an Xingbo	XBLBQ-GTA67	DDT-ZC02179	2025/04/22
ELECTRIC AND MAGNETIC FIELD ANALYZER	Narda	EHP-200A	DDT-ZC01401	2024/09/20