

FCC SAR Exclusion Report

Report No. : SF200117C14

Applicant : Nuheara Limited

Address : 190 Aberdeen St, Northbridge, Western Australia 6003

Product : IQbuds² Max

Brand : Nuheara Limited

FCC ID : 2AKMG00000NU318

Model No. : NU318

Standards : FCC 47 CFR Part 2 (2.1093), IEEE C95.1:1992, IEEE Std 1528:2013

KDB 865664 D01 v01r04, KDB 865664 D02 v01r02, KDB 447498 D01 v06

Sample Received Date : Jan. 17, 2020

Date of Evaluation : Mar. 06, 2020

Lab Address : No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

Test Location : No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City, Taiwan

CERTIFICATION: The above equipment have been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch – Lin Kou Laboratories**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's SAR characteristics under the conditions specified in this report. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product certification, approval, or endorsement by TAF or any government agencies.

Prepared By:

Lena Wang / Specialist

Approved By:

Gordon Lin / Manager





This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.

Report Format Version 5.0.0 Page No. : 1 of 8



FCC SAR Exclusion Report

Table of Contents

Rel	Release Control Record				
	Summary of Maximum SAR Value4				
2.	Description of Equipment Under Test5				
3.	SAR Measurement Evaluation				
		Maximum Output Power			
		3.1.1 Maximum Target Conducted Power			
		3.1.2 Time-Avg. Power calculation.			
	3.2	SAR Testing Exclusions			
	Information on the Testing Laboratories				

Appendix A. Photographs of EUT and Setup

Report Format Version 5.0.0 Page No. : 2 of 8



Release Control Record

Issue No.	Reason for Change	Date Issued
SF200117C14	Initial release	Mar. 10, 2020

Report Format Version 5.0.0 Page No. : 3 of 8



1. Summary of Maximum SAR Value

Equipment Class	Mode	Highest Reported SAR _{1g} (W/kg)
DSS	Bluetooth	Not Required

Note:

1. The SAR limit (Head & Body: SAR_{1g} 1.6 W/kg) for general population / uncontrolled exposure is specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1-1992.

Report Format Version 5.0.0 Page No. : 4 of 8



2. <u>Description of Equipment Under Test</u>

EUT Type	IQbuds ² Max
Brand Name	Nuheara Limited
FCC ID	2AKMG00000NU318
Model Name	NU318
Tx Frequency Bands (Unit: MHz)	Bluetooth : 2402 ~ 2480
Uplink Modulations	Bluetooth : GFSK, π/4-DQPSK, 8-DPSK
Maximum Tune-up Conducted Power (Unit: dBm)	Please refer to section 3.1 of this report
Antenna Type	PIFA Antenna
EUT Stage	Engineering Sample

Note:

- 1. The above EUT information is declared by manufacturer and for more detailed features description please refers to the manufacturer's specifications or User's Manual.
- 2. Only left earbud has RF function.

Report Format Version 5.0.0 Page No. : 5 of 8



3. SAR Measurement Evaluation

3.1 Maximum Output Power

3.1.1 Maximum Target Conducted Power

The maximum conducted average power (Unit: dBm) including tune-up tolerance is shown as below.

<Bluetooth>


Mode	Channel	Frequency (MHz)	Tune-up Power
	0	2402	6.5
Bluetooth EDR	39	2441	6.5
	78	2480	6.5
	0	2402	3.5
Bluetooth LE	19	2440	3.5
	39	2480	3.5

3.1.2 Time-Avg. Power calculation.

The calculation of time-avg. power (Unit: dBm) Including duty cycle.

<The calculated average power with duty cycle>

Mode	Max Tune-up Power	Duty cycle (%)	Calculated Time-Avg. Power
BT EDR	6.5	77.0	5.36



Time-domain plot for Bluetooth transmission signal

The duty factor of Bluetooth signal has been calculated as following.

Duty Factor = Pulse Width / Total Period = (7.30 - 4.42) / (8.16 - 4.42) = 77 %

Report Format Version 5.0.0 Page No. : 6 of 8



3.2 SAR Testing Exclusions

According to KDB 447498 D01, the SAR test exclusion condition is based on source-based time-averaged maximum conducted output power, adjusted for tune-up tolerance, and the minimum test separation distance required for the exposure conditions. The SAR exclusion threshold is determined by the following formula.

1. For the test separation distance <= 50 mm

$$\frac{\text{Max. Tune up Power}_{(mW)}}{\text{Min. Test Separation Distance}_{(mm)}} \times \sqrt{f_{(GHz)}} \leq 3.0$$

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

2. For the test separation distance > 50 mm, and the frequency at 100 MHz to 1500 MHz

$$\left[\text{(Threshold at 50 mm in Step 1)} + \text{(Test Separation Distance} - 50 \text{ mm)} \times \left(\frac{f_{\text{(MHz)}}}{150} \right) \right]_{\text{(mW)}}$$

3. For the test separation distance > 50 mm, and the frequency at > 1500 MHz to 6 GHz $[(Threshold at 50 mm in Step 1) + (Test Separation Distance - 50 mm) \times 10]_{(mW)}$

	Time Ave		Separation Distance (mm)		
Mode	Time-Avg. Power (dBm)	Time-Avg. Power (mW)	Ant. to Surface (mm)	Calculated Result	Require SAR Testing?
ВТ	5.36	3.44	5	1.08	No

Note:

- 1. When separation distance <= 50 mm and the calculated result shown in above table is <= 3.0, the SAR testing exclusion is applied.
- 2. When separation distance > 50 mm and the device output power is less than the calculated result (power threshold, mW) shown in above table, the SAR testing exclusion is applied.
- 3. Please refer distance a and b on antenna location in appendix a.

Summary:

Since the SAR testing for all device orientations apply SAR test exclusion per KDB 447498, SAR testing for this device is not required.

Report Format Version 5.0.0 Page No. : 7 of 8



4. Information on the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Taiwan Huaya Lab:

Add: No. 19, Huaya 2nd Rd., Guishan Dist., Taoyuan City 333, Taiwan

Tel: +886-(0)3-318-3232 Fax: +886-(0)3-211-5834

Taiwan Linkou Lab:

Add: No. 47-2, Baodoucuokeng, Linkou Dist., New Taipei City 244, Taiwan

Tel: +886-(0)2-2605-2180 Fax: +886-(0)2-2605-2943

Taiwan Hsinchu Lab1:

Add: E-2, No. 1, Lixing 1st Rd., East Dist., Hsinchu City 300, Taiwan

Tel: +886-(0)3-666-8565 Fax: +886-(0)3-666-8323

Taiwan Hsinchu Lab2:

Add: No. 49, Ln. 206, Wende Rd., Qionglin Township, Hsinchu County 307, Taiwan

Tel: +886-(0)3-512-0595 Fax: +886-(0)3-512-0568

Taiwan Xindian Lab:

Add: B2F., No. 215, Sec. 3, Beixin Rd., Xindian Dist., New Taipei City 231, Taiwan

Tel: +886-(0)2-8914-5882 Fax: +886-(0)2-8914-5840

Email: service.adt@tw.bureauveritas.com

Web Site: https://ee.bureauveritas.com.tw/BVInternet/Default

The road map of all our labs can be found in our web site also.

---END---

Report Format Version 5.0.0 Page No. : 8 of 8



Appendix A. Photographs of EUT and Setup

Report Format Version 5.0.0 Issued Date : Mar. 10, 2020

Report No. : SF200117C14