



**SGS-CSTC Standards Technical Services Co., Ltd.**  
**Shenzhen Branch**

No. 1 Workshop, M-10, Middle section, Science & Technology Park,  
Shenzhen, Guangdong, China 518057

Telephone: +86 (0) 755 2601 2053  
Fax: +86 (0) 755 2671 0594  
Email: ee.shenzhen@sgs.com

Report No.: SZEM170400292602  
Page: 1 of 53

## **TEST REPORT**

**Application No.:** SZEM1704002926CR (GZEM1704000223EM)  
**Applicant:** Shenzhen Dongdixin Technology Co., Ltd.  
**Address of Applicant:** No.3 Building XiliBaimang Xusheng Industrial Estate 518108 Nanshan, Shenzhen, China  
**Manufacturer:** Shenzhen Dongdixin Technology Co., Ltd.  
**Address of Manufacturer:** No.3 Building XiliBaimang Xusheng Industrial Estate 518108 Nanshan, Shenzhen, China  
**Factory:** Shenzhen Dongdixin Technology Co., Ltd.  
**Address of Factory:** No.3 Building XiliBaimang Xusheng Industrial Estate 518108 Nanshan, Shenzhen, China  
**Equipment Under Test (EUT):**  
**EUT Name:** Incontinence Treatment Device  
**Model No.:** LT2061  
**FCC ID:** 2AKMI-LT2061  
**Standards:** 47 CFR Part 15, Subpart C 15.247  
**Date of Receipt:** 2017-04-10  
**Date of Test:** 2017-04-11 to 2017-04-15  
**Date of Issue:** 2017-04-24

<b>Test Result :</b>	<b>Pass*</b>
----------------------	--------------

\* In the configuration tested, the EUT complied with the standards specified above.



Jack Zhang  
EMC Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



Revision Record				
Version	Chapter	Date	Modifier	Remark
01		2017-04-24		Original

Authorized for issue by:			
Tested By			
	Hank Yan /Project Engineer	2017-04-15	Date
Checked By			
	Eric Fu /Reviewer	2017-04-24	Date



## 2 Test Summary

Radio Spectrum Technical Requirement				
Item	Standard	Method	Requirement	Result
Antenna Requirement	47 CFR Part 15, Subpart C 15.247	N/A	47 CFR Part 15, Subpart C 15.203 & 15.247(c)	Pass

Radio Spectrum Matter Part				
Item	Standard	Method	Requirement	Result
Conducted Peak Output Power	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 11.9.1.1	47 CFR Part 15, Subpart C 15.247(b)(3)	Pass
Minimum 6dB Bandwidth	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 11.8.1	47 CFR Part 15, Subpart C 15.247a(2)	Pass
Power Spectrum Density	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 11.10.2	47 CFR Part 15, Subpart C 15.247(e)	Pass
Conducted Spurious Emissions	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 11.11	47 CFR Part 15, Subpart C 15.247(d)	Pass
Radiated Spurious Emissions	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.4,6.5,6.6	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Radiated Emissions which fall in the restricted bands	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.10.5	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Conducted Band Edges Measurement	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 11.12.2.4	47 CFR Part 15, Subpart C 15.247(d)	Pass



### 3 Contents

	Page
<b>1 COVER PAGE .....</b>	<b>1</b>
<b>2 TEST SUMMARY .....</b>	<b>3</b>
<b>3 CONTENTS .....</b>	<b>4</b>
<b>4 GENERAL INFORMATION .....</b>	<b>6</b>
4.1 DETAILS OF E.U.T. ....	6
4.2 DESCRIPTION OF SUPPORT UNITS .....	8
4.3 MEASUREMENT UNCERTAINTY .....	8
4.4 TEST LOCATION .....	9
4.5 TEST FACILITY .....	9
4.6 DEVIATION FROM STANDARDS .....	9
4.7 ABNORMALITIES FROM STANDARD CONDITIONS .....	9
<b>5 EQUIPMENT LIST .....</b>	<b>10</b>
<b>6 RADIO SPECTRUM TECHNICAL REQUIREMENT .....</b>	<b>12</b>
6.1 ANTENNA REQUIREMENT .....	12
6.1.1 Test Requirement: .....	12
6.1.2 Conclusion .....	12
<b>7 RADIO SPECTRUM MATTER TEST RESULTS .....</b>	<b>13</b>
7.1 CONDUCTED PEAK OUTPUT POWER .....	13
7.1.1 E.U.T. Operation .....	14
7.1.2 Test Setup Diagram .....	14
7.1.3 Measurement Data .....	14
7.2 MINIMUM 6dB BANDWIDTH .....	15
7.2.1 E.U.T. Operation .....	15
7.2.2 Test Setup Diagram .....	15
7.2.3 Measurement Data .....	15
7.3 POWER SPECTRUM DENSITY .....	16
7.3.1 E.U.T. Operation .....	16
7.3.2 Test Setup Diagram .....	16
7.3.3 Measurement Data .....	16
7.4 CONDUCTED SPURIOUS EMISSIONS .....	17
7.4.1 E.U.T. Operation .....	17
7.4.2 Test Setup Diagram .....	17
7.4.3 Measurement Data .....	17
7.5 RADIATED SPURIOUS EMISSIONS .....	18
7.5.1 E.U.T. Operation .....	19
7.5.2 Test Setup Diagram .....	19
7.5.3 Measurement Data .....	20
7.6 RADIATED EMISSIONS WHICH FALL IN THE RESTRICTED BANDS .....	23
7.6.1 E.U.T. Operation .....	23
7.6.2 Test Setup Diagram .....	23
7.6.3 Measurement Data .....	24
7.7 CONDUCTED BAND EDGES MEASUREMENT .....	29
7.7.1 E.U.T. Operation .....	29
7.7.2 Test Setup Diagram .....	29
7.7.3 Measurement Data .....	29



<b>8</b>	<b>PHOTOGRAPHS.....</b>	<b>30</b>
8.1	RADIATED SPURIOUS EMISSIONS TEST SETUP.....	30
8.2	EUT CONSTRUCTIONAL DETAILS .....	31
<b>9</b>	<b>APPENDIX.....</b>	<b>32</b>
9.1	APPENDIX 15.247.....	32-53



## 4 General Information

### 4.1 Details of E.U.T.

Frequency Range:	2402MHz to 2480MHz
Bluetooth Version:	V4.0 BLE
Modulation Type:	GFSK
Number of Channels:	40
Sample Type:	Portable production
Antenna Type:	Integral Antenna
Antenna Gain:	2dBi
Power supply:	DC 3.7V Li-ion Battery Battery Charger: Model: AKN1G-0500030VU Input: AC 100-240V, 50/60Hz, 0.2A Output: DC 5.0V, 0.3A



Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
0	2402MHz	10	2422MHz	20	2442MHz	30	2462MHz
1	2404MHz	11	2424MHz	21	2444MHz	31	2464MHz
2	2406MHz	12	2426MHz	22	2446MHz	32	2466MHz
3	2408MHz	13	2428MHz	23	2448MHz	33	2468MHz
4	2410MHz	14	2430MHz	24	2450MHz	34	2470MHz
5	2412MHz	15	2432MHz	25	2452MHz	35	2472MHz
6	2414MHz	16	2434MHz	26	2454MHz	36	2474MHz
7	2416MHz	17	2436MHz	27	2456MHz	37	2476MHz
8	2418MHz	18	2438MHz	28	2458MHz	38	2478MHz
9	2420MHz	19	2440MHz	29	2460MHz	39	2480MHz

**Note:**

In section 15.31(m), regards to the operating frequency range over 10 MHz, the lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Channel	Frequency
The lowest channel (CH0)	2402MHz
The middle channel (CH19)	2440MHz
The highest channel (CH39)	2480MHz

## 4.2 Description of Support Units

The EUT has been tested as an independent unit.

## 4.3 Measurement Uncertainty

No.	Item	Measurement Uncertainty
1	Radio Frequency	7.25 x 10 <sup>-8</sup>
2	Duty cycle	0.37%
3	Occupied Bandwidth	3%
4	RF conducted power	0.75dB
5	RF power density	2.84dB
6	Conducted Spurious emissions	0.75dB
7	RF Radiated power	4.5dB (below 1GHz)
		4.8dB (above 1GHz)
8	Radiated Spurious emission test	4.5dB (30MHz-1GHz)
		4.8dB (1GHz-18GHz)
9	Temperature test	1 °C
10	Humidity test	3%
11	Supply voltages	1.5%
12	Time	3%





#### **4.4 Test Location**

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, Guangdong, China.  
518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.

#### **4.5 Test Facility**

The test facility is recognized, certified, or accredited by the following organizations:

- **CNAS (No. CNAS L2929)**

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

- **A2LA (Certificate No. 3816.01)**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

- **VCCI**

The 10m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-823, R-4188, T-1153 and C-2383 respectively.

- **FCC – Registration No.: 556682**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No.: 556682.

- **Industry Canada (IC)**

Two 3m Semi-anechoic chambers and the 10m Semi-anechoic chamber of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab have been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-1, 4620C-2, 4620C-3.

#### **4.6 Deviation from Standards**

None

#### **4.7 Abnormalities from Standard Conditions**

None



## 5 Equipment List

Conducted Peak Output Power					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
DC Power Supply	ZhaoXin	RXN-305D	SEM011-02	2016-10-09	2017-10-09
Spectrum Analyzer	Rohde & Schwarz	FSP	SEM004-06	2016-10-09	2017-10-09
Power Meter	Rohde & Schwarz	NRVS	SEM014-02	2016-10-09	2017-10-09

Minimum 6dB Bandwidth					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
DC Power Supply	ZhaoXin	RXN-305D	SEM011-02	2016-10-09	2017-10-09
Spectrum Analyzer	Rohde & Schwarz	FSP	SEM004-06	2016-10-09	2017-10-09
Power Meter	Rohde & Schwarz	NRVS	SEM014-02	2016-10-09	2017-10-09

Power Spectrum Density					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
DC Power Supply	ZhaoXin	RXN-305D	SEM011-02	2016-10-09	2017-10-09
Spectrum Analyzer	Rohde & Schwarz	FSP	SEM004-06	2016-10-09	2017-10-09
Power Meter	Rohde & Schwarz	NRVS	SEM014-02	2016-10-09	2017-10-09

Conducted Spurious Emissions					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
DC Power Supply	ZhaoXin	RXN-305D	SEM011-02	2016-10-09	2017-10-09
Spectrum Analyzer	Rohde & Schwarz	FSP	SEM004-06	2016-10-09	2017-10-09
Power Meter	Rohde & Schwarz	NRVS	SEM014-02	2016-10-09	2017-10-09

Conducted Band Edges Measurement					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
DC Power Supply	ZhaoXin	RXN-305D	SEM011-02	2016-10-09	2017-10-09
Spectrum Analyzer	Rohde & Schwarz	FSP	SEM004-06	2016-10-09	2017-10-09
Power Meter	Rohde & Schwarz	NRVS	SEM014-02	2016-10-09	2017-10-09



**SGS-CSTC Standards Technical Services Co., Ltd.**  
**Shenzhen Branch**

Report No.: SZEM170400292602

Page: 11 of 53

General used equipment					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Humidity/ Temperature Indicator	Shanghai Meteorological Industry Factory	ZJ1-2B	SEM002-03	2016-10-12	2017-10-12
Humidity/ Temperature Indicator	Shanghai Meteorological Industry Factory	ZJ1-2B	SEM002-04	2016-10-12	2017-10-12
Humidity/ Temperature Indicator	Mingle	N/A	SEM002-08	2016-10-12	2017-10-12
Barometer	Changchun Meteorological Industry Factory	DYM3	SEM002-01	2016-05-18	2017-05-18

## 6 Radio Spectrum Technical Requirement

### 6.1 Antenna Requirement

#### 6.1.1 Test Requirement:


47 CFR Part 15, Subpart C 15.203

#### 6.1.2 Conclusion

Standard Requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

EUT Antenna:



The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is 2dBi.



## 7 Radio Spectrum Matter Test Results

### 7.1 Conducted Peak Output Power

Test Requirement 47 CFR Part 15, Subpart C 15.247(b)(3)

Test Method: ANSI C63.10 (2013) Section 11.9.1.1

Limit:

Frequency range(MHz)	Output power of the intentional radiator(watt)
902-928	1 for $\geq 50$ hopping channels
	0.25 for $25 \leq$ hopping channels $< 50$
	1 for digital modulation
2400-2483.5	1 for $\geq 75$ non-overlapping hopping channels
	0.125 for all other frequency hopping systems
	1 for digital modulation
5725-5850	1 for frequency hopping systems and digital modulation


### 7.1.1 E.U.T. Operation

Operating Environment:

Temperature: 23.0 °C      Humidity: 56 % RH      Atmospheric Pressure: 1020 mbar

Test mode: d: TX mode

### 7.1.2 Test Setup Diagram



### 7.1.3 Measurement Data

The detailed test data see: Appendix 15.247


## 7.2 Minimum 6dB Bandwidth

Test Requirement: 47 CFR Part 15, Subpart C 15.247a(2)  
Test Method: ANSI C63.10 (2013) Section 11.8.1  
Limit:  $\geq 500$  kHz

### 7.2.1 E.U.T. Operation

Operating Environment:  
Temperature: 23.0 °C      Humidity: 56 % RH      Atmospheric Pressure: 1020 mbar  
Test mode: d: TX mode

### 7.2.2 Test Setup Diagram



### 7.2.3 Measurement Data

The detailed test data see: Appendix 15.247


### 7.3 Power Spectrum Density

Test Requirement: 47 CFR Part 15, Subpart C 15.247(e)  
Test Method: ANSI C63.10 (2013) Section 11.10.2  
Limit:  $\leq 8\text{dBm}$  in any 3 kHz band during any time interval of continuous transmission

#### 7.3.1 E.U.T. Operation

Operating Environment:  
Temperature: 23.0 °C      Humidity: 56 % RH      Atmospheric Pressure: 1020 mbar  
Test mode: d: TX mode

#### 7.3.2 Test Setup Diagram



#### 7.3.3 Measurement Data

The detailed test data see: Appendix 15.247




## 7.4 Conducted Spurious Emissions

Test Requirement	47 CFR Part 15, Subpart C 15.247(d)
Test Method:	ANSI C63.10 (2013) Section 11.11
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

### 7.4.1 E.U.T. Operation

Operating Environment:			
Temperature:	23.0 °C	Humidity:	56 % RH
Test mode:	d: TX mode	Atmospheric Pressure:	1020 mbar

### 7.4.2 Test Setup Diagram



### 7.4.3 Measurement Data

The detailed test data see: Appendix 15.247



## 7.5 Radiated Spurious Emissions

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2013) Section 6.4,6.5,6.6

Measurement Distance: 3m

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

### 7.5.1 E.U.T. Operation

Operating Environment:

Temperature: 23.0 °C

Humidity: 53 % RH


Atmospheric Pressure: 1020 mbar

Test mode: d: TX mode

For below 1GHz part, through pre-scan, the worst case is the lowest channel.

Only the worst case is recorded in the report.

### 7.5.2 Test Setup Diagram





### **7.5.3 Measurement Data**

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.



# SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

Report No.: SZEM170400292602

Page: 21 of 53

Mode:d; Polarization:Horizontal; Modulation Type:GFSK; Channel:Low

Freq (MHz)	Antenna_ Factor (dB/m)	Cable_ Loss (dB)	Preamp_ Gain (dB)	Read_ Level (dBuV)	Level (dBuV/m)	Limit_ Line (dBuV/m)	Over_ Limit (dB)
1538.281	25.98	4.52	38.05	43.93	36.87	74	-37.13
3196.094	31.67	6.08	37.92	44.34	44.81	74	-29.19
4804.000	34.16	7.73	38.40	44.91	48.79	74	-25.21
7206.000	36.42	9.65	37.12	42.40	51.61	74	-22.39
9608.000	37.52	11.06	35.09	38.32	52.26	74	-21.74
15398.830	41.38	15.17	38.46	34.78	53.46	74	-20.54

Mode:d; Polarization:Vertical; Modulation Type:GFSK; Channel:Low

Freq (MHz)	Antenna_ Factor (dB/m)	Cable_ Loss (dB)	Preamp_ Gain (dB)	Read_ Level (dBuV)	Level (dBuV/m)	Limit_ Line (dBuV/m)	Over_ Limit (dB)
1872.381	27.34	4.89	38.01	43.66	38.76	74	-35.24
3505.809	32.22	6.30	37.95	44.92	46.02	74	-27.98
4804.000	34.16	7.73	38.40	44.45	48.33	74	-25.67
7206.000	36.42	9.65	37.12	42.99	52.20	74	-21.80
9608.000	37.52	11.06	35.09	38.53	52.47	74	-21.53
13837.020	39.01	14.44	38.84	38.30	53.41	74	-20.59

Mode:d; Polarization:Horizontal; Modulation Type:GFSK; Channel:middle

Freq (MHz)	Antenna_ Factor (dB/m)	Cable_ Loss (dB)	Preamp_ Gain (dB)	Read_ Level (dBuV)	Level (dBuV/m)	Limit_ Line (dBuV/m)	Over_ Limit (dB)
1611.091	26.30	4.60	38.04	42.30	35.65	74	-38.35
3746.792	32.91	6.50	37.97	43.69	45.64	74	-28.36
4880.000	34.28	7.83	38.44	44.74	48.82	74	-25.18
7320.000	36.37	9.73	37.01	41.51	50.83	74	-23.17
9760.000	37.55	11.20	35.02	37.87	52.06	74	-21.94
15577.900	41.37	15.31	38.26	34.32	53.34	74	-20.66

Mode:d; Polarization:Vertical; Modulation Type:GFSK; Channel:middle

Freq (MHz)	Antenna_ Factor (dB/m)	Cable_ Loss (dB)	Preamp_ Gain (dB)	Read_ Level (dBuV)	Level (dBuV/m)	Limit_ Line (dBuV/m)	Over_ Limit (dB)
1556.169	26.06	4.54	38.04	43.84	36.89	74	-37.11
3790.361	33.04	6.54	37.98	44.61	46.71	74	-27.29
4880.000	34.28	7.83	38.44	44.34	48.42	74	-25.58
7320.000	36.37	9.73	37.01	41.88	51.20	74	-22.80
9760.000	37.55	11.20	35.02	37.87	52.06	74	-21.94
15532.940	41.39	15.28	38.31	34.77	53.73	74	-20.27



**SGS-CSTC Standards Technical Services Co., Ltd.**  
**Shenzhen Branch**

Report No.: SZEM170400292602

Page: 22 of 53

Mode:d; Polarization:Horizontal; Modulation Type:GFSK; Channel:High

Freq (MHz)	Antenna_Factor (dB/m)	Cable_Loss (dB)	Preamp_Gain (dB)	Read_Level (dBUV)	Level (dBUV/m)	Limit_Line (dBUV/m)	Over_Limit (dB)
1498.781	25.80	4.47	38.05	43.62	36.32	74	-37.68
3845.537	33.19	6.58	37.98	44.79	47.07	74	-26.93
4960.000	34.43	7.94	38.48	45.27	49.59	74	-24.41
7440.000	36.33	9.81	36.91	41.77	51.22	74	-22.78
9920.000	37.59	11.37	34.94	36.87	51.35	74	-22.65
15398.830	41.38	15.17	38.46	34.59	53.27	74	-20.73

Mode:d; Polarization:Vertical; Modulation Type:GFSK; Channel:High

Freq (MHz)	Antenna_Factor (dB/m)	Cable_Loss (dB)	Preamp_Gain (dB)	Read_Level (dBUV)	Level (dBUV/m)	Limit_Line (dBUV/m)	Over_Limit (dB)
1426.916	25.50	4.38	38.06	47.07	39.38	74	-34.62
3577.463	32.43	6.37	37.96	43.94	45.31	74	-28.69
4960.000	34.28	7.83	38.44	42.72	46.80	74	-27.20
7440.000	36.37	9.73	37.01	42.76	52.08	74	-21.92
9920.000	37.55	11.20	35.02	38.03	52.22	74	-21.78
14618.170	40.62	14.75	38.94	36.91	53.91	74	-20.09

**Remark:**

- 1) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:  
Final Test Level = Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor
- 2) Scan from 9kHz to 25GHz, the disturbance above 13GHz and below 30MHz was very low, and the above harmonics were the highest point could be found when testing, so only the above harmonics had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
- 3) As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. So, only the peak measurements were shown in the report.

## 7.6 Radiated Emissions which fall in the restricted bands

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209  
 Test Method: ANSI C63.10 (2013) Section 6.10.5  
 Measurement Distance: 3m


### 7.6.1 E.U.T. Operation

Operating Environment:

Temperature: 23.0 °C Humidity: 53 % RH Atmospheric Pressure: 1020 mbar

Test mode: d: TX mode

### 7.6.2 Test Setup Diagram






### **7.6.3 Measurement Data**

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.





Mode:d; Polarization:Horizontal; Modulation Type:GFSK; Channel:Low



Condition: 3m HORIZONTAL

Job No: : 02926CR


Mode: : 2402 Band edge

: BLE

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2390.000	5.34	29.08	37.96	48.47	44.93	74.00	-29.07	Peak
2 pp	2402.250	5.35	29.11	37.96	91.89	88.39	74.00	14.39	Peak




Mode:d; Polarization:Vertical; Modulation Type:GFSK; Channel:Low



Condition: 3m VERTICAL  
Job No: : 02926CR  
Mode: : 2402 Band edge  
: BLE

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2387.635	5.34	29.07	37.96	49.08	45.53	74.00	-28.47	Peak
2	2390.000	5.34	29.08	37.96	48.36	44.82	74.00	-29.18	Peak
3 pp	2402.250	5.35	29.11	37.96	92.01	88.51	74.00	14.51	Peak

Mode:d; Polarization:Horizontal; Modulation Type:GFSK; Channel:High



Condition: 3m HORIZONTAL


Job No: : 02926CR

Mode: : 2480 Band edge

: BLE

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	pp 2480.229	5.41	29.34	37.95	92.48	89.28	74.00	15.28	Peak
2	2483.500	5.41	29.35	37.95	44.87	41.68	54.00	-12.32	Average
3	2483.500	5.41	29.35	37.95	61.19	58.00	74.00	-16.00	Peak
4	av 2483.896	5.41	29.35	37.95	48.13	44.94	54.00	-9.06	Average
5	2483.896	5.41	29.35	37.95	64.15	60.96	74.00	-13.04	Peak

Mode:d; Polarization:Vertical; Modulation Type:GFSK; Channel:High



Condition: 3m VERTICAL

Job No: : 02926CR

Mode: : 2480 Band edge

: BLE

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	pp 2480.204	5.41	29.34	37.95	92.35	89.15	74.00	15.15	Peak
2	av 2483.500	5.41	29.35	37.95	47.89	44.70	54.00	-9.30	Average
3	2483.500	5.41	29.35	37.95	64.92	61.73	74.00	-12.27	Peak


## 7.7 Conducted Band Edges Measurement

Test Requirement 47 CFR Part 15, Subpart C 15.247(d)  
Test Method: ANSI C63.10 (2013) Section 11.12.2.4

### 7.7.1 E.U.T. Operation

Operating Environment:  
Temperature: 23.0 °C Humidity: 56 % RH Atmospheric Pressure: 1020 mbar  
Test mode: d: TX mode

### 7.7.2 Test Setup Diagram





### 7.7.3 Measurement Data

The detailed test data see: Appendix 15.247

## 8 Photographs

### 8.1 Radiated Spurious Emissions Test Setup





## **8.2 EUT Constructional Details**

Refer to Appendix A - Photographs of EUT Constructional Details for SZEM1704002926CR.




## 9 Appendix


### 9.1 Appendix 15.247


#### 1.6dB Bandwidth

Test Mode	Test Channel	EBW[MHz]	Limit	Verdict
BLE	2402	0.690	$\geq 0.5$	PASS
BLE	2440	0.699	$\geq 0.5$	PASS
BLE	2480	0.705	$\geq 0.5$	PASS













**2.Maximum peak conducted output power**

Test Mode	Test Channel	Power[dBm]	Limit[dBm]	Verdict
BLE	2402	-0.62	<30	PASS
BLE	2440	0.35	<30	PASS
BLE	2480	1.25	<30	PASS






Maximum peak conducted output power\_BLE\_2440





Maximum peak conducted output power\_BLE\_2480








### 3.Maximum Peak power spectral density

Test Mode	Test Channel	PSD[dBm/3kHz]	Limit[dBm/3kHz]	Verdict
BLE	2402	-16.74	<8.00	PASS
BLE	2440	-15.75	<8.00	PASS
BLE	2480	-14.91	<8.00	PASS













#### 4. Band-edge for RF Conducted Emissions

Test Mode	Test Channel	Carrier Power[dBm]	Max. Spurious Level [dBm]	Limit [dBm]	Verdict
BLE	2402	-2.040	-57.522	<-22.04	PASS
BLE	2480	-0.080	-44.010	<-20.08	PASS






Band-edge for RF Conducted Emissions\_BLE\_2480\_Hopping Off






## 5.RF Conducted Spurious Emissions

Test Mode	Test Channel	StartFre [MHz]	StopFre [MHz]	RBW [kHz]	VBW [kHz]	Pref[dBm]	Max. Level [dBm]	Limit [dBm]	Verdict
BLE	2402	30	10000	1000	3000	-1.86	-54.020	<-21.86	PASS
BLE	2402	10000	25000	1000	3000	-1.86	-56.550	<-21.86	PASS
BLE	2440	30	10000	1000	3000	-1.1	-54.540	<-21.1	PASS
BLE	2440	10000	25000	1000	3000	-1.1	-57.310	<-21.1	PASS
BLE	2480	30	10000	1000	3000	-0.21	-54.230	<-20.21	PASS
BLE	2480	10000	25000	1000	3000	-0.21	-58.640	<-20.21	PASS











RF Conducted Spurious Emissions\_BLE\_2440

Pref







RF Conducted Spurious Emissions\_BLE\_2480

Pref

