

RF

TEST REPORT


ISSUED BY
Shenzhen BALUN Technology Co., Ltd.



FOR
**CENTAURI 200 Enterprise/Industrial IoT
Gateway**

ISSUED TO
Volansys Technologies Pvt Ltd

Block A-7th Floor, Safal Profitaire, Corporate Road, Prahladnagar,
Ahmedabad-380015, Gujarat, India



Tested by:
Ye Hongji
Date:
Jul. 07, 2021

Approved by:
Wei Yanquan
(Chief Engineer)
Date:
Jul. 07, 2021

Report No.: BL-SZ2120305-602

EUT Name: CENTAURI 200 Enterprise/Industrial
IoT Gateway

Model Name: CT200-20

Brand Name: Volansys

Test Standard: 47 CFR Part 15 Subpart C

RSS-Gen Issue 5

RSS-247 Issue 2

FCC ID: 2AKNO-CT20020

ISED Number: 22256-CT20020

Test Conclusion: Pass

Test Date: Feb. 24, 2021 ~ Jun. 01, 2021

Date of Issue: Jul. 07, 2021

NOTE: This test report of test results only related to testing samples, which can be duplicated completely for the legal use with the approval of the applicant; it shall not be reproduced except in full, without the written approval of Shenzhen BALUN Technology Co., Ltd. Any objections should be raised within thirty days from the date of issue. To validate the report, please contact us.

Revision History

Version	Issue Date	Revisions Content
<u>Rev. 01</u>	<u>Jun. 17, 2021</u>	<u>Initial Issue</u>
<u>Rev. 02</u>	<u>Jul. 07, 2021</u>	<u>Updated A.1 Output Power Test Data</u>

TABLE OF CONTENTS

1	ADMINISTRATIVE DATA (GENERAL INFORMATION)	5
1.1	Identification of the Testing Laboratory	5
1.2	Identification of the Responsible Testing Location	5
1.3	Laboratory Condition	5
1.4	Announce	5
2	PRODUCT INFORMATION	6
2.1	Applicant Information	6
2.2	Manufacturer Information	6
2.3	Factory Information	6
2.4	General Description for Equipment under Test (EUT)	6
2.5	Technical Information	7
2.6	Additional Instructions	8
3	SUMMARY OF TEST RESULTS	9
3.1	Test Standards	9
3.2	Verdict	9
4	GENERAL TEST CONFIGURATIONS	10
4.1	Test Environments	10
4.2	Test Equipment List	10
4.3	Measurement Uncertainty	11
4.4	Description of Test Setup	11
4.4.1	For Antenna Port Test	11
4.4.2	For AC Power Supply Port Test	12
4.4.3	For Radiated Test (Below 30 MHz)	12
4.4.4	For Radiated Test (30 MHz-1 GHz)	13
4.4.5	For Radiated Test (Above 1 GHz)	13
4.5	Measurement Results Explanation Example	14

4.5.1	For conducted test items:	14
4.5.2	For radiated band edges and spurious emission test:	14
5	TEST ITEMS	15
5.1	Antenna Requirements	15
5.1.1	Relevant Standards	15
5.1.2	Antenna Anti-Replacement Construction	15
5.1.3	Antenna Gain	15
5.2	Output Power	16
5.2.1	Test Limit.....	16
5.2.2	Test Setup	16
5.2.3	Test Procedure	16
5.2.4	Test Result	17
5.3	6dB Bandwidth	18
5.3.1	Limit.....	18
5.3.2	Test Setup	18
5.3.3	Test Procedure	18
5.3.4	Test Result	18
5.4	Conducted Spurious Emission.....	19
5.4.1	Limit.....	19
5.4.2	Test Setup	19
5.4.3	Test Procedure	19
5.4.4	Test Result	20
5.5	Band Edge (Authorized-band band-edge).....	21
5.5.1	Limit.....	21
5.5.2	Test Setup	21
5.5.3	Test Procedure	21
5.5.4	Test Result	22
5.6	Conducted Emission.....	23
5.6.1	Limit.....	23
5.6.2	Test Setup	23
5.6.3	Test Procedure	23
5.6.4	Test Result	23

5.7	Radiated Spurious Emission.....	24
5.7.1	Limit.....	24
5.7.2	Test Setup.....	24
5.7.3	Test Procedure.....	24
5.7.4	Test Result.....	27
5.8	Band Edge (Restricted-band band-edge).....	28
5.8.1	Limit.....	28
5.8.2	Test Setup.....	28
5.8.3	Test Procedure.....	28
5.8.4	Test Result.....	28
5.9	Power Spectral density (PSD).....	29
5.9.1	Limit.....	29
5.9.2	Test Setup.....	29
5.9.3	Test Procedure.....	29
5.9.4	Test Result.....	29
ANNEX A	TEST RESULT.....	30
A.1	Output Power.....	30
A.2	Occupied Bandwidth.....	32
A.3	Conducted Spurious Emissions.....	34
A.4	Band Edge (Authorized-band band-edge).....	37
A.5	Conducted Emissions.....	39
A.6	Radiated Spurious Emission.....	43
A.7	Band Edge (Restricted-band band-edge).....	55
A.8	Power Spectral Density (PSD).....	58
ANNEX B	TEST SETUP PHOTOS.....	59
ANNEX C	EUT EXTERNAL PHOTOS.....	59
ANNEX D	EUT INTERNAL PHOTOS.....	59

1 ADMINISTRATIVE DATA (GENERAL INFORMATION)

1.1 Identification of the Testing Laboratory

Company Name	Shenzhen BALUN Technology Co., Ltd.
Address	Block B, 1st FL, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Phone Number	+86 755 6685 0100

1.2 Identification of the Responsible Testing Location

Test Location	Shenzhen BALUN Technology Co., Ltd.
Address	Block B, 1st FL, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Description	All measurement facilities used to collect the measurement data are located at Block B, FL 1, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China 518055

1.3 Laboratory Condition

Ambient Temperature	20°C to 25°C
Ambient Relative Humidity	45% to 55%
Ambient Pressure	100 kPa to 102 kPa

1.4 Announce

- (1) The test report reference to the report template version v1.3.
- (2) The test report is invalid if not marked with the signatures of the persons responsible for preparing and approving the test report.
- (3) The test report is invalid if there is any evidence and/or falsification.
- (4) The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein.
- (5) This document may not be altered or revised in any way unless done so by BALUN and all revisions are duly noted in the revisions section.
- (6) Content of the test report, in part or in full, cannot be used for publicity and/or promotional purposes without prior written approval from the laboratory.
- (7) The laboratory is only responsible for the data released by the laboratory, except for the part provided by the applicant.

2 PRODUCT INFORMATION

2.1 Applicant Information

Applicant	Volansys Technologies Pvt Ltd
Address	Block A-7th Floor, Safal Profitaire, Corporate Road, Prahladnagar, Ahmedabad-380015, Gujarat, India

2.2 Manufacturer Information

Manufacturer	Volansys Technologies Pvt Ltd
Address	Ratana Business Hub,207, 2nd Floor, Opp Bharat Petrol PumpSanathal Chokdi, Changodar Highway, Ahmedabad 382210 Gujarat India

2.3 Factory Information

Factory	Volansys Technologies Pvt Ltd
Address	Ratana Business Hub,207, 2nd Floor, Opp Bharat Petrol PumpSanathal Chokdi, Changodar Highway, Ahmedabad 382210 Gujarat India

2.4 General Description for Equipment under Test (EUT)

EUT Name	CENTAURI 200 Enterprise/Industrial IoT Gateway
Model Name Under Test	CT200-20
Series Model Name	N/A
Description of Model name differentiation	N/A
Hardware Version	3.1
Software Version	RC6
Dimensions (Approx.)	N/A
Weight (Approx.)	N/A

2.5 Technical Information

Network and Wireless connectivity	2.4G WIFI 802.11b, 802.11g, 802.11n(HT20), Zigbee
-----------------------------------	---

The requirement for the following technical information of the EUT was tested in this report:

Modulation Technology	DSSS(IEEE802.15.4)
Modulation Type	O-QPSK
Product Type	<input checked="" type="checkbox"/> Mobile <input type="checkbox"/> Portable <input type="checkbox"/> Fix Location
Transfer Rate	250 KHz
Frequency Range	The frequency range used is 2400 MHz to 2483.5 MHz.
Number of channel	16 (at intervals of 5 MHz) $F_{CH} = 2350 + 5K$ [MHz], for K=11, 12, ..., 26
Tested Channel	11 (2405 MHz), 18 (2440 MHz), 25 (2475 MHz), 26 (2480 MHz)
Antenna Type	FPC Antenna & PCB Antenna
Antenna Gain	PCB Antenna 3.0 dBi (In test items related to antenna gain, the final results reflect this figure. This value is provided by the applicant.)
	FPC Antenna 3.2 dBi (In test items related to antenna gain, the final results reflect this figure. This value is provided by the applicant.)
Antenna System(MIMO Smart Antenna)	N/A

Note: Maximum PCB antenna gain must not exceed 3.0dBi and FPC not exceed 3.2dBi.

All channel list:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
11	2405	19	2445
12	2410	20	2450
13	2415	21	2455
14	2420	22	2460
15	2425	23	2465
16	2430	24	2470
17	2435	25	2475
18	2440	26	2480

2.6 Additional Instructions


EUT Software Settings:

Mode	<input checked="" type="checkbox"/> Special software is used. The software provided by client to enable the EUT under transmission condition continuously at specific channel frequencies individually.
------	--

During testing, Channel and Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

Power level setup in software			
Test Software Version	SecureCRTPortable		
Support Units (Software installation media)	Description	Manufacturer	Model
	Notebook	Lenovo	X220
Mode	Channel	Frequency (MHz)	Soft Set
O-QPSK	11	2405	4
	18	2440	4
	25	2475	4
	26	2480	2

Run software:



3 SUMMARY OF TEST RESULTS

3.1 Test Standards

No.	Identity	Document Title
1	47 CFR Part 15, Subpart C	Miscellaneous Wireless Communications Services
2	KDB Publication 558074 D01v05r02	GUIDANCE FOR COMPLIANCE MEASUREMENTS ON DIGITAL TRANSMISSION SYSTEM, FREQUENCY HOPPING SPREAD SPECTRUM SYSTEM, AND HYBRID SYSTEM DEVICES OPERATING UNDER SECTION 15.247 OF THE FCC RULES
3	ANSI C63.10-2013	American National Standard for Testing Unlicensed Wireless Devices
4	RSS-Gen Issue 5	General Requirements for Compliance of Radio Apparatus
5	RSS-247 Issue 2	Digital Transmission Systems (DTSs), Frequency Hopping Systems(FHSs) and Licence-Exempt Local Area Network (LE-LAN) Devices

3.2 Verdict

No.	Description	FCC PART No.	ISED Part No.	Test Result	Verdict
1	Antenna Requirement	15.203; 15.247(b)	RSS-247, 5.4 (6)	N/A	<i>Pass</i> ^{Note 1}
2	Output Power	15.247(b)	RSS-247, 5.4 (4)	ANNEX A.1	Pass
3	6dB Bandwidth	15.247(a)	RSS-GEN, 6.6; RSS-247, 5.2 (1)	ANNEX A.2	Pass
4	Conducted Spurious Emission	15.247(d)	RSS-247, 5.5	ANNEX A.3	Pass
5	Band Edge(Authorized-band band-edge)	15.209; 15.247(d)	RSS-GEN, 8.9; RSS-247, 5.5	ANNEX A.4	Pass
6	Conducted Emission	15.207	RSS-GEN, 8.8	ANNEX A.5	Pass
7	Radiated Spurious Emission	15.209; 15.247(d)	RSS-247, 5.5	ANNEX A.6	Pass
8	Band Edge(Restricted-band band-edge)	15.209; 15.247(d)	RSS-247, 5.5	ANNEX A.7	Pass
9	Power spectral density (PSD)	15.247(e)	RSS-247, 5.2 (2)	ANNEX A.8	Pass
10	Receiver Spurious Emissions	N/A	RSS-Gen, 7.1.2	N/A	N/A ^{Note 2}

Note 1: Please refer to section 5.1.

Note 2: Only radio communication receivers operating in stand-alone mode within the band 30-960 MHz, as well as scanner receivers, are subject to Industry Canada requirements, so this test is not applicable.

4 GENERAL TEST CONFIGURATIONS

4.1 Test Environments

During the measurement, the normal environmental conditions were within the listed ranges:

Relative Humidity	45% - 55%	
Atmospheric Pressure	100 kPa - 102 kPa	
Temperature	NT (Normal Temperature)	+22°C to +25°C
Working Voltage of the EUT	NV (Normal Voltage)	5.0 V

4.2 Test Equipment List

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
Spectrum Analyzer	ROHDE&SCHWARZ	FSV-40	101544	2021.04.01	2022.03.31
Bluetooth Signaling Unit	ROHDE&SCHWARZ	CMW500	142028	2020.06.08	2021.06.07
EMI Receiver	KEYSIGHT	N9038A	MY53220118	2020.06.09	2021.06.08
EMI Receiver	ROHDE&SCHWARZ	ESRP	101036	2020.06.09	2021.06.08
LISN	SCHWARZBECK	NSLK 8127	8127-687	2020.06.09	2021.06.08
Test Antenna-Loop(9 kHz-30 MHz)	SCHWARZBECK	FMZB 1519	1519-037	2019.10.29	2021.10.28
Test Antenna-Bi-Log(30 MHz-3 GHz)	SCHWARZBECK	VULB 9163	9163-624	2019.07.02	2021.07.01
Test Antenna-Horn(1-18 GHz)	SCHWARZBECK	BBHA 9120D	9120D-1917	2019.07.02	2021.07.01
Test Antenna-Horn (18-40 GHz)	A-INFO	LB-180400KF	J211060273	2021.01.05	2023.01.04
Anechoic Chamber	RAINFORD	9m*6m*6m	N/A	2017.02.21	2022.02.20
Anechoic Chamber	EMC Electronic Co., Ltd	20.10*11.60*7.35m	N/A	2018.08.08	2021.08.07
Shielded Enclosure	ChangNing	CN-130701	130703	--	--

4.3 Measurement Uncertainty

The following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2.

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Measurement	Value
Occupied Channel Bandwidth	±4%
RF output power, conducted	±1.21 dB
Power Spectral Density, conducted	±1.25 dB
Unwanted Emissions, conducted	±1.26 dB
All emissions, radiated	±3.86 dB
Temperature	±1°C
Humidity	±4%


4.4 Description of Test Setup

4.4.1 For Antenna Port Test

Conducted value (dBm) = Measurement value (dBm) + cable loss (dB)


For example: the measurement value is 10 dBm and the cable 0.5dBm used, then the final result of EUT:

Conducted value (dBm) = 10 dBm + 0.5 dB = 10.5 dBm




(Diagram 1)

4.4.2 For AC Power Supply Port Test




(Diagram 2)

4.4.3 For Radiated Test (Below 30 MHz)




(Diagram 3)

4.4.4 For Radiated Test (30 MHz-1 GHz)



(Diagram 4)

4.4.5 For Radiated Test (Above 1 GHz)



(Diagram 5)

4.5 Measurement Results Explanation Example

4.5.1 For conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

4.5.2 For radiated band edges and spurious emission test:

$$E = \text{EIRP} - 20\log D + 104.8$$

where:

E = electric field strength in dB μ V/m,

EIRP = equivalent isotropic radiated power in dBm

D = specified measurement distance in meters.

EIRP= Measure Conducted output power Value (dBm) + Maximum transmit antenna gain (dBi) + the appropriate maximum ground reflection factor (dB)

5 TEST ITEMS

5.1 Antenna Requirements

5.1.1 Relevant Standards

FCC §15.203 & 15.247(b); RSS-247, 5.4 (f)

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of § 15.211, § 15.213, § 15.217, § 15.219, or § 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

If directional gain of transmitting antennas is greater than 6 dBi, the power shall be reduced by the same level in dB comparing to gain minus 6 dBi. For the fixed point-to-point operation, the power shall be reduced by one dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

5.1.2 Antenna Anti-Replacement Construction

The Antenna Anti-Replacement as following method:

Protected Method	Description
The antenna is embedded in the product.	An embedded-in antenna design is used.

Reference Documents	Item
Photo	Please refer to the EUT Photo documents.

5.1.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

5.2 Output Power

5.2.1 Test Limit

FCC § 15.247(b); RSS-247, 5.4 (d)

For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements.

5.2.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.2.3 Test Procedure

Maximum peak conducted output power

This procedure shall be used when the measurement instrument has available a resolution bandwidth that is greater than the *DTS bandwidth*.

- a) Set the RBW \geq *DTS bandwidth*.
- b) Set VBW \geq 3 RBW.
- c) Set span \geq 3 RBW
- d) Sweep time = auto couple.
- e) Detector = peak.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use peak marker function to determine the peak amplitude level.

Maximum conducted (average) output power (Reporting Only)

a) As an alternative to spectrum analyzer or EMI receiver measurements, measurements may be performed using a wideband RF power meter with a thermocouple detector or equivalent if all of the conditions listed below are satisfied.

- 1) The EUT is configured to transmit continuously, or to transmit with a constant duty factor.
 - 2) At all times when the EUT is transmitting, it shall be transmitting at its maximum power control level.
 - 3) The integration period of the power meter exceeds the repetition period of the transmitted signal by at least a factor of five.
- b) If the transmitter does not transmit continuously, measure the duty cycle (x) of the transmitter output signal as described in Section 6.0.

- c) Measure the average power of the transmitter. This measurement is an average over both the on and off periods of the transmitter.
- d) Adjust the measurement in dBm by adding $10\log(1/x)$, where x is the duty cycle to the measurement result.

Measurements of duty cycle

The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the on and off times of the transmitted signal.

Set the center frequency of the instrument to the center frequency of the transmission.

Set $RBW \geq OBW$ if possible; otherwise, set RBW to the largest available value.

Set $VBW \geq RBW$. Set detector = peak or average.

The zero-span measurement method shall not be used unless both RBW and VBW are $> 50/T$ and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring duty cycle shall not be used if $T \leq 16.7$ microseconds.)

5.2.4 Test Result

Please refer to ANNEX A.1.

5.3 6dB Bandwidth

5.3.1 Limit

FCC §15.247(a); RSS-GEN, 6.7

Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. In order to make an accurate measurement, set the span greater than RBW. The 6 dB bandwidth must be greater than 500 kHz.

5.3.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.3.3 Test Procedure

Use the following spectrum analyzer settings:

Set RBW = 100 kHz.

Set the video bandwidth (VBW) ≥ 3 RBW.

Detector = Peak.

Trace mode = max hold.

Sweep = auto couple.

Allow the trace to stabilize.

Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

5.3.4 Test Result

Please refer to ANNEX A.2.

5.4 Conducted Spurious Emission

5.4.1 Limit

FCC §15.247(d); RSS-247, 5.5

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

5.4.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.4.3 Test Procedure

The DTS rules specify that in any 100 kHz bandwidth outside of the authorized frequency band, the power shall be attenuated according to the following conditions:

- a) If the maximum peak conducted output power procedure was used to demonstrate compliance as described in 9.1, then the peak output power measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz (i.e., 20 dBc).
- b) If maximum conducted (average) output power was used to demonstrate compliance as described in 9.2, then the peak power in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 30 dB relative to the maximum in-band peak PSD level in 100 kHz (i.e., 30 dBc).
- c) In either case, attenuation to levels below the 15.209 general radiated emissions limits is not required.

The following procedures shall be used to demonstrate compliance to these limits. Note that these procedures can be used in either an antenna-port conducted or radiated test set-up. Radiated tests must conform to the test site requirements and utilize maximization procedures defined herein.

Reference level measurement

Establish a reference level by using the following procedure:

Set instrument center frequency to DTS channel center frequency.

Set the span to ≥ 1.5 times the DTS bandwidth.

Set the RBW = 100 kHz.

Set the VBW $\geq 3 \times$ RBW.

Detector = peak.

Sweep time = auto couple.

Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum PSD level.

Emission level measurement

Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic. Typically, several plots are required to cover this entire span.

Set the RBW = 100 kHz.

Set the VBW $\geq 3 \times$ RBW.

Detector = peak.

Sweep time = auto couple.

Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum amplitude level.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements specified in 11.1 a) or 11.1 b). Report the three highest emissions relative to the limit.

5.4.4 Test Result

Please refer to ANNEX A.3.

5.5 Band Edge (Authorized-band band-edge)

5.5.1 Limit

FCC §15.247(d); RSS-GEN, 8.9, RSS-247, 5.5

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

5.5.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.5.3 Test Procedure

The following procedures may be used to determine the peak or average field strength or power of an unwanted emission that is within 2 MHz of the authorized band edge. If a peak detector is utilized, use the procedure described in 13.2.1. Use the procedure described in 13.2.2 when using an average detector and the EUT can be configured to transmit continuously (i.e., duty cycle $\geq 98\%$). Use the procedure described in 13.2.3 when using an average detector and the EUT cannot be configured to transmit continuously but the duty cycle is constant (i.e., duty cycle variations are less than ± 2 percent). Use the procedure described in 13.2.4 when using an average detector for those cases where the EUT cannot be configured to transmit continuously and the duty cycle is not constant (duty cycle variations equal or exceed 2 percent).

When using a peak detector to measure unwanted emissions at or near the band edge (within 2 MHz of the authorized band), the following integration procedure can be used.

Set instrument center frequency to the frequency of the emission to be measured (must be within 2 MHz of the authorized band edge).

Set span to 2 MHz

RBW = 100 kHz.

VBW $\geq 3 \times$ RBW.

Detector = peak.

Sweep time = auto.

Trace mode = max hold.

Allow sweep to continue until the trace stabilizes (required measurement time may increase for low duty cycle applications)

Compute the power by integrating the spectrum over 1 MHz using the analyzer's band power measurement function with band limits set equal to the emission frequency (femission) ± 0.5 MHz. If the instrument does not have a band power function, then sum the amplitude levels (in power units) at 100 kHz intervals extending across the 1 MHz spectrum defined by femission ± 0.5 MHz.

Standard method(The 99% OBW of the fundamental emission is without 2 MHz of the authorized band):

Span: Wide enough to capture the peak level of the emission operating on the channel closest to the band edge, as well as any modulation products that fall outside of the authorized band of operation.

Reference level: As required to keep the signal from exceeding the maximum instrument input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than $[10 \log (OBW/RBW)]$ below the reference level. Specific guidance is given in 4.1.5.2.

Attenuation: Auto (at least 10 dB preferred).

Sweep time: Coupled.

Resolution bandwidth: 100 kHz.

Video bandwidth: 300 kHz.

Detector: Peak.

Trace: Max hold.

5.5.4 Test Result

Please refer to ANNEX A.4.

5.6 Conducted Emission

5.6.1 Limit

FCC §15.207; RSS-GEN, 8.8

For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 Ω line impedance stabilization network (LISN).

Frequency range (MHz)	Conducted Limit (dB μ V)	
	Quai-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
0.50 - 30	60	50

5.6.2 Test Setup

See section 4.4.2 for test setup description for the AC power supply port. The photo of test setup please refer to ANNEX B.

5.6.3 Test Procedure

The maximum conducted interference is searched using Peak (PK), if the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. Refer to recorded points and plots below.

Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a nominal 120 VAC, 50/60 Hz and 240 VAC, 50/60 Hz) for which the device is capable of operation. A device rated for 50/60 Hz operation need not be tested at both frequencies provided the radiated and line conducted emissions are the same at both frequencies.

5.6.4 Test Result

Please refer to ANNEX A.5.

5.7 Radiated Spurious Emission

5.7.1 Limit

FCC §15.209&15.247(c); RSS-247, 5.5

Radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength ($\mu\text{V/m}$)	Measurement Distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

Note:

1. For Above 1000 MHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit.
2. For above 1000 MHz, limit field strength of harmonics: 54dBuV/m@3m (AV) and 74dBuV/m@3m (PK).

5.7.2 Test Setup

See section 4.4.3 to 4.4.5 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.7.3 Test Procedure

Since the emission limits are specified in terms of radiated field strength levels, measurements performed to demonstrate compliance have traditionally relied on a radiated test configuration. Radiated measurements remain the principal method for demonstrating compliance to the specified limits; however antenna-port conducted measurements are also now acceptable to demonstrate compliance (see below for details). When radiated measurements are utilized, test site requirements and procedures for maximizing and measuring radiated emissions that are described in ANSI C63.10 shall be followed.

Antenna-port conducted measurements may also be used as an alternative to radiated measurements for demonstrating compliance in the restricted frequency bands. If conducted measurements are performed, then proper impedance matching must be ensured and an additional radiated test for cabinet/case spurious emissions is required.

General Procedure for conducted measurements in restricted bands

- a) Measure the conducted output power (in dBm) using the detector specified (see guidance regarding measurement procedures for determining quasi-peak, peak, and average conducted output power, respectively).
- b) Add the maximum transmit antenna gain (in dBi) to the measured output power level to determine the EIRP level (see guidance on determining the applicable antenna gain)
- c) Add the appropriate maximum ground reflection factor to the EIRP level (6 dB for frequencies ≤ 30 MHz, 4.7 dB for frequencies between 30 MHz and 1000 MHz, inclusive and 0 dB for frequencies > 1000 MHz).
- d) For devices with multiple antenna-ports, measure the power of each individual chain and sum the EIRP of all

chains in linear terms (e.g., Watts, mW).

e) Convert the resultant EIRP level to an equivalent electric field strength using the following relationship:

$$E = \text{EIRP} - 20 \log D + 104.8$$

where:

E = electric field strength in dB μ V/m,

EIRP = equivalent isotropic radiated power in dBm

D = specified measurement distance in meters.

f) Compare the resultant electric field strength level to the applicable limit.

g) Perform radiated spurious emission test.

Quasi-Peak measurement procedure

The specifications for measurements using the CISPR quasi-peak detector can be found in Publication 16 of the International Special Committee on Radio Frequency Interference (CISPR) of the International Electrotechnical Commission.

As an alternative to CISPR quasi-peak measurement, compliance can be demonstrated to the applicable emission limits using a peak detector.

Peak power measurement procedure

Peak emission levels are measured by setting the instrument as follows:

a) RBW = as specified in Table 1.

b) VBW $\geq 3 \times$ RBW.

c) Detector = Peak.

d) Sweep time = auto.

e) Trace mode = max hold.

f) Allow sweeps to continue until the trace stabilizes. (Note that the required measurement time may be longer for low duty cycle applications).

Table 1—RBW as a function of frequency

Frequency	RBW
9-150 kHz	200-300 Hz
0.15-30 MHz	9-10 kHz
30-1000 MHz	100-120 kHz
> 1000 MHz	1 MHz

If the peak-detected amplitude can be shown to comply with the average limit, then it is not necessary to perform a separate average measurement.

Trace averaging across on and off times of the EUT transmissions followed by duty cycle correction

If continuous transmission of the EUT (i.e., duty cycle ≥ 98 percent) cannot be achieved and the duty cycle is constant (i.e., duty cycle variations are less than ± 2 percent), then the following procedure shall be used:

a) The EUT shall be configured to operate at the maximum achievable duty cycle.

b) Measure the duty cycle, x, of the transmitter output signal as described in section 6.0.

c) RBW = 1 MHz (unless otherwise specified).

d) VBW $\geq 3 \times$ RBW.

e) Detector = RMS, if $\text{span}/(\# \text{ of points in sweep}) \leq (\text{RBW}/2)$. Satisfying this condition may require increasing the number of points in the sweep or reducing the span. If this condition cannot be satisfied, then the detector mode shall be set to peak.

f) Averaging type = power (i.e., RMS).

1) As an alternative, the detector and averaging type may be set for linear voltage averaging.

2) Some instruments require linear display mode in order to use linear voltage averaging. Log or dB averaging shall not be used.

g) Sweep time = auto.

h) Perform a trace average of at least 100 traces.

i) A correction factor shall be added to the measurement results prior to comparing to the emission limit in order to compute the emission level that would have been measured had the test been performed at 100 percent duty cycle. The correction factor is computed as follows:

1) If power averaging (RMS) mode was used in step f), then the applicable correction factor is $10 \log(1/x)$, where x is the duty cycle.

2) If linear voltage averaging mode was used in step f), then the applicable correction factor is $20 \log(1/x)$, where x is the duty cycle.

3) If a specific emission is demonstrated to be continuous (≥ 98 percent duty cycle) rather than turning on and off with the transmit cycle, then no duty cycle correction is required for that emission.

NOTE: Reduction of the measured emission amplitude levels to account for operational duty factor is not permitted. Compliance is based on emission levels occurring during transmission - not on an average across on and off times of the transmitter.

Determining the applicable transmit antenna gain

A conducted power measurement will determine the maximum output power associated with a restricted band emission; however, in order to determine the associated EIRP level, the gain of the transmitting antenna (in dBi) must be added to the measured output power (in dBm).

Since the out-of-band characteristics of the EUT transmit antenna will often be unknown, the use of a conservative antenna gain value is necessary. Thus, when determining the EIRP based on the measured conducted power, the upper bound on antenna gain for a device with a single RF output shall be selected as the maximum in-band gain of the antenna across all operating bands, or 2 dBi, whichever is greater. However, for devices that operate in multiple frequency bands while using the same transmit antenna, the highest gain of the antenna within the operating band nearest in frequency to the restricted band emission being measured may be used in lieu of the overall highest gain when the emission is at a frequency that is within 20 percent of the nearest band edge frequency, but in no case shall a value less than 2 dBi be used.

See KDB 662911 for guidance on calculating the additional array gain term when determining the effective antenna gain for a EUT with multiple outputs occupying the same or overlapping frequency ranges in the same band.

Radiated spurious emission test

An additional consideration when performing conducted measurements of restricted band emissions is that unwanted emissions radiating from the EUT cabinet, control circuits, power leads, or intermediate circuit elements will likely go undetected in a conducted measurement configuration. To address this concern, a radiated test shall be performed to ensure that emissions emanating from the EUT cabinet (rather than the antenna port) also comply with the applicable limits.

For these cabinet radiated spurious emission measurements the EUT transmit antenna may be replaced with a termination matching the nominal impedance of the antenna. Procedures for performing radiated measurements are specified in ANSI C63.10. All detected emissions shall comply with the applicable limits.

The measurement frequency range is from 30 MHz to the 10th harmonic of the fundamental frequency. The Turn Table is actuated to turn from 0° to 360°, and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. Mid channels on all channel bandwidth verified. Only the worst RB size/offset presented.

The power of the EUT transmitting frequency should be ignored.

All Spurious Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \geq 1$ GHz, 100 kHz for $f < 1$ GHz

VBW \geq RBW

Sweep = auto

Detector function = peak

Trace = max hold

5.7.4 Test Result

Please refer to ANNEX A.6.

5.8 Band Edge (Restricted-band band-edge)

5.8.1 Limit

FCC §15.209&15.247(c); RSS-247, 5.5

Radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

5.8.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.8.3 Test Procedure

The measurement frequency range is from 9 kHz to the 10th harmonic of the fundamental frequency. The Turn Table is actuated to turn from 0° to 360°, and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. Mid channels on all channel bandwidth verified. Only the worst RB size/offset presented.

The power of the EUT transmitting frequency should be ignored.

All Spurious Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \geq 1$ GHz, 100 kHz for $f < 1$ GHz

VBW \geq RBW

Sweep = auto

Detector function = peak

Trace = max hold

For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported, Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.

For transmitters operating above 1 GHz repeat the measurement with an average detector.

5.8.4 Test Result

Please refer to ANNEX A.7.

5.9 Power Spectral density (PSD)

5.9.1 Limit

FCC §15.247(d); RSS-247, 5.2 (b)

The same method of determining the conducted output power shall be used to determine the power spectral density. If a peak output power is measured, then a peak power spectral density measurement is required. If an average output power is measured, then an average power spectral density measurement should be used.

5.9.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.9.3 Test Procedure

Set analyzer center frequency to DTS channel center frequency.

Set the span to 1.5 times the DTS bandwidth.

Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.

Set the VBW $\geq 3 \text{ RBW}$.

Detector = peak.

Sweep time = auto couple.

Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum amplitude level within the RBW.

If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

5.9.4 Test Result

Please refer to ANNEX A.8.

ANNEX A TEST RESULT

A.1 Output Power

Peak Power Test Data

Channel	Measured Output Peak Power		Limit		Verdict
	O-QPSK		dBm	mW	
	dBm	mW			
11	23.51	224.54	30	1000	Pass
18	23.80	239.72			Pass
25	23.51	224.44			Pass
26	-1.85	0.65			Pass

Average Power Test Data

Channel	Measured Output Average Power		Limit		Verdict
	O-QPSK		dBm	mW	
	dBm	mW			
11	22.41	174.18	30	1000	Pass
18	22.21	166.34			Pass
25	22.15	164.06			Pass
26	-2.13	0.61			Pass

E.I.R.P Test Data (For ISED)

Channel	E.I.R.P		Limit		Verdict
	O-QPSK		dBm	mW	
	dBm	mW			
11	26.71	468.81	36	4000	Pass
18	27.00	501.19			Pass
25	26.71	468.81			Pass
26	1.35	1.36			Pass

Test plots

CHANNEL 11



CHANNEL 18



CHANNEL 25



CHANNEL 26



A.2 Occupied Bandwidth

Test Data

Test Mode	O-QPSK		
Channel	6 dB Bandwidth (MHz)	99% Bandwidth (MHz)	6 dB Bandwidth Limits (kHz)
11	1.517000	2.285355	≥500
18	1.517000	2.323454	≥500
25	1.467000	2.251190	≥500
26	1.500000	2.295850	≥500

Test plots

6 dB Bandwidth

CHANNEL 11



CHANNEL 18



CHANNEL 25




CHANNEL 26




99% Bandwidth


CHANNEL 11




CHANNEL 18



CHANNEL 25



CHANNEL 26




A.3 Conducted Spurious Emissions

Test Data


O-QPSK				
Channel	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
11	-35.79	19.56	-0.45	Pass
18	-35.74	19.62	-0.38	Pass
25	-36.17	20.33	0.33	Pass
26	-36.31	-5.06	-25.06	Pass

Test Plots


CHANNEL 11 CARRIER LEVEL




CHANNEL 11, SPURIOUS 30 MHz ~ 3 GHz




CHANNEL 11, SPURIOUS 2 GHz ~ 25 GHz




CHANNEL 18 CARRIER LEVEL




CHANNEL 18, SPURIOUS 30 MHz ~ 3 GHz




CHANNEL 18, SPURIOUS 2 GHz ~ 25 GHz




CHANNEL 25 CARRIER LEVEL




CHANNEL 25, SPURIOUS 30 MHz ~ 3 GHz




CHANNEL 25, SPURIOUS 2 GHz ~ 25 GHz




CHANNEL 26 CARRIER LEVEL



CHANNEL 26, SPURIOUS 30 MHz ~ 3 GHz



CHANNEL 26, SPURIOUS 2 GHz ~ 25 GHz



A.4 Band Edge (Authorized-band band-edge)

Note: The lowest and highest channels are tested to verify the band edge emissions. Please refer to the following the plots for emissions values.


Channel	Measured Max. Band Edge Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
11	-26.21	19.56	-0.45	Pass
25	-38.40	20.33	0.33	Pass
26	-43.31	-5.06	-25.06	Pass

Test Plots


CHANNEL 11, Reference level




CHANNEL 11, Band Edge



CHANNEL 25, Reference level




CHANNEL 25, Band Edge



CHANNEL 26, Reference level



CHANNEL 26, Band Edge



A.5 Conducted Emissions

Note¹: The EUT is working in the Normal link mode. All modes have been tested and normal link mode is worst.


Note²: Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a nominal 120 VAC, 60 Hz and 240 VAC, 50 Hz) for which the device is capable of operation. So, The configuration 120 VAC, 60 Hz and 240 VAC, 50 Hz were tested respectively, but only the worst configuration (120 VAC, 60 Hz) shown here.

PCB Antenna

Test Data and Plots

PHASE L


CE Test case_FCC_CE_FCC PART 15B_Class B



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Over Limit (dB)	Detector	Line	Verdict
1	0.158	43.61	10.40	65.57	-21.96	Peak	L	Pass
1**	0.158	29.27	10.40	55.57	-26.30	AV	L	Pass
2	0.270	37.65	10.34	61.12	-23.47	Peak	L	Pass
2**	0.270	27.42	10.34	51.12	-23.70	AV	L	Pass
3	0.406	41.77	10.31	57.73	-15.96	Peak	L	Pass
3**	0.406	31.94	10.31	47.73	-15.79	AV	L	Pass
4	0.838	36.86	10.25	56.00	-19.14	Peak	L	Pass
4**	0.838	24.78	10.25	46.00	-21.22	AV	L	Pass
5	1.726	36.50	10.26	56.00	-19.50	Peak	L	Pass
5**	1.726	24.62	10.26	46.00	-21.38	AV	L	Pass
6	4.532	35.81	10.31	56.00	-20.19	Peak	L	Pass
6**	4.532	24.05	10.31	46.00	-21.95	AV	L	Pass

PHASE N

CE Test case_FCC_CE_FCC PART 15B_ Class B




No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Over Limit (dB)	Detector	Line	Verdict
1	0.218	40.88	10.37	62.89	-22.01	Peak	N	Pass
1**	0.218	28.56	10.37	52.89	-24.33	AV	N	Pass
2	0.418	45.15	10.31	57.49	-12.34	Peak	N	Pass
2**	0.418	35.26	10.31	47.49	-12.23	AV	N	Pass
3	0.660	37.77	10.28	56.00	-18.23	Peak	N	Pass
3**	0.660	26.26	10.28	46.00	-19.74	AV	N	Pass
4	1.116	38.12	10.24	56.00	-17.88	Peak	N	Pass
4**	1.116	26.50	10.24	46.00	-19.50	AV	N	Pass
5	2.238	35.89	10.27	56.00	-20.11	Peak	N	Pass
5**	2.238	24.60	10.27	46.00	-21.40	AV	N	Pass
6	4.392	36.40	10.31	56.00	-19.60	Peak	N	Pass
6**	4.392	24.46	10.31	46.00	-21.54	AV	N	Pass

FPC Antenna

Test Data and Plots

PHASE L


CE Test case_FCC_CE_FCC PART 15B_ Class B



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Over Limit (dB)	Detector	Line	Verdict
1	0.174	41.74	10.39	64.77	-23.03	Peak	L	Pass
1**	0.174	29.90	10.39	54.77	-24.87	AV	L	Pass
2	0.226	38.66	10.36	62.60	-23.94	Peak	L	Pass
2**	0.226	28.82	10.36	52.60	-23.78	AV	L	Pass
3	0.404	41.91	10.31	57.77	-15.86	Peak	L	Pass
3**	0.404	31.04	10.31	47.77	-16.73	AV	L	Pass
4	0.650	36.50	10.27	56.00	-19.50	Peak	L	Pass
4**	0.650	25.46	10.27	46.00	-20.54	AV	L	Pass
5	1.684	37.53	10.26	56.00	-18.47	Peak	L	Pass
5**	1.684	25.15	10.26	46.00	-20.85	AV	L	Pass
6	3.466	36.24	10.30	56.00	-19.76	Peak	L	Pass
6**	3.466	23.69	10.30	46.00	-22.31	AV	L	Pass

PHASE N

CE Test case_FCC_CE_FCC PART 15B_Class B



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Over Limit (dB)	Detector	Line	Verdict
1	0.180	41.97	10.39	64.49	-22.52	Peak	N	Pass
1**	0.180	27.88	10.39	54.49	-26.61	AV	N	Pass
2	0.212	39.85	10.38	63.13	-23.28	Peak	N	Pass
2**	0.212	27.35	10.38	53.13	-25.78	AV	N	Pass
3	0.418	44.25	10.31	57.49	-13.24	Peak	N	Pass
3**	0.418	34.70	10.31	47.49	-12.79	AV	N	Pass
4	0.658	37.72	10.28	56.00	-18.28	Peak	N	Pass
4**	0.658	26.57	10.28	46.00	-19.43	AV	N	Pass
5	1.134	38.58	10.24	56.00	-17.42	Peak	N	Pass
5**	1.134	26.48	10.24	46.00	-19.52	AV	N	Pass
6	4.644	36.84	10.31	56.00	-19.16	Peak	N	Pass
6**	4.644	25.13	10.31	46.00	-20.87	AV	N	Pass

A.6 Radiated Spurious Emission

Note 1: The symbol of "--" in the table which means not application.

Note 2: For the test data above 1 GHz, according the ANSI C63.4-2014, where limits are specified for both average and peak (or quasi-peak) detector functions, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement.


Note 3: The low frequency, which started from 9 kHz to 30 MHz, was pre-scanned and the result which was 20 dB lower than the limit line per 15.31(o) was not reported.

Note 4: The EUT is working in the Normal link mode below 1 GHz. All modes have been tested and normal link mode is worst.

PCB Antenna


Test Data and Plots

30 MHz to 1 GHz, ANT H



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	47.941	11.53	-27.17	30.0	-18.47	Peak	360.00	200	Horizontal	Pass
2	152.917	19.07	-25.92	33.5	-14.43	Peak	359.00	400	Horizontal	Pass
3	213.042	27.24	-28.91	33.5	-6.26	Peak	73.00	400	Horizontal	Pass
4	217.406	32.21	-28.66	36.0	-3.79	Peak	58.00	400	Horizontal	Pass
5	613.067	23.67	-17.88	36.0	-12.33	Peak	43.00	200	Horizontal	Pass
6	919.510	29.80	-12.01	36.0	-6.20	Peak	145.00	100	Horizontal	Pass

30 MHz to 1 GHz, ANT V




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	60.547	14.15	-27.92	30.0	-15.85	Peak	240.00	200	Vertical	Pass
2	102.247	16.30	-29.92	33.5	-17.20	Peak	332.00	100	Vertical	Pass
3	154.856	25.19	-25.71	33.5	-8.31	Peak	292.00	100	Vertical	Pass
4	215.361	34.09	-28.97	33.5	0.59	Peak	317.00	159	Vertical	N/A
4*	215.361	29.68	-28.97	33.5	-3.82	QP	317.00	159	Vertical	Pass
5	217.371	39.41	-28.66	36.0	3.41	Peak	0.00	106	Vertical	N/A
5*	217.371	33.81	-28.66	36.0	-2.19	QP	0.00	106	Vertical	Pass
6	225.406	26.24	-28.22	36.0	-9.76	Peak	347.00	100	Vertical	Pass

FPC Antenna


Test Data and Plots

30 MHz to 1 GHz, ANT H



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	49.395	10.18	-27.33	30.0	-19.82	Peak	0.00	300	Horizontal	Pass
2	154.856	19.91	-25.71	33.5	-13.59	Peak	300.00	400	Horizontal	Pass
3	165.281	19.20	-26.28	33.5	-14.30	Peak	225.00	400	Horizontal	Pass
4	215.224	28.51	-28.97	33.5	-4.99	Peak	78.00	200	Horizontal	Pass
5	217.163	32.97	-28.64	36.0	-3.03	Peak	58.00	200	Horizontal	Pass
6	919.753	28.02	-12.03	36.0	-7.98	Peak	261.00	100	Horizontal	Pass

30 MHz to 1 GHz, ANT V



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	63.699	14.06	-28.55	30.0	-15.94	Peak	194.00	100	Vertical	Pass
2	122.369	16.97	-27.85	33.5	-16.53	Peak	275.00	100	Vertical	Pass
3	152.917	23.92	-25.92	33.5	-9.58	Peak	255.00	100	Vertical	Pass
4	215.361	33.10	-28.97	33.5	-0.40	Peak	0.00	136	Vertical	N/A
4*	215.361	27.74	-28.97	33.5	-5.76	QP	0.00	136	Vertical	Pass
5	217.340	40.23	-28.64	36.0	4.23	Peak	1.00	108	Vertical	N/A
5*	217.340	33.56	-28.64	36.0	-2.44	QP	1.00	108	Vertical	Pass
6	219.345	30.95	-28.80	36.0	-5.05	Peak	315.00	100	Vertical	Pass

Note 1: The marked spikes near 2400 MHz with circle should be ignored because they are Fundamental signal.

Note 2: The spurious above 18G is noise only, do not show on the report.

PCB Antenna

1 GHz to 18 GHz, ANT H CHANNEL 11

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1114.600	40.09	-15.33	74.0	-33.91	Peak	333.00	150	Horizontal	Pass
1**	1114.600	29.81	-15.33	54.0	-24.19	AV	333.00	150	Horizontal	Pass
2	2405.500	71.23	-10.79	74.0	-2.77	Peak	225.00	150	Horizontal	N/A
2**	2405.500	68.46	-10.79	54.0	14.46	AV	225.00	150	Horizontal	N/A
3	4745.800	48.23	-1.89	74.0	-25.77	Peak	8.00	150	Horizontal	Pass
3**	4745.800	38.41	-1.89	54.0	-15.59	AV	8.00	150	Horizontal	Pass
4	6985.400	52.83	4.62	74.0	-21.17	Peak	16.00	150	Horizontal	Pass
4**	6985.400	42.73	4.62	54.0	-11.27	AV	16.00	150	Horizontal	Pass
5	11604.025	50.52	20.15	74.0	-23.48	Peak	192.00	150	Horizontal	Pass
5**	11604.025	38.12	20.15	54.0	-15.88	AV	192.00	150	Horizontal	Pass
6	17166.824	55.85	23.45	74.0	-18.15	Peak	29.00	150	Horizontal	Pass
6**	17166.824	44.12	23.45	54.0	-9.88	AV	29.00	150	Horizontal	Pass

1 GHz to 18 GHz, ANT V CHANNEL 11

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1115.000	39.27	-15.34	74.0	-34.73	Peak	286.00	150	Vertical	Pass
1**	1115.000	28.19	-15.34	54.0	-25.81	AV	286.00	150	Vertical	Pass
2	2404.500	65.20	-10.73	74.0	-8.80	Peak	260.00	150	Vertical	N/A
2**	2404.500	62.12	-10.73	54.0	8.12	AV	260.00	150	Vertical	N/A
3	4773.000	48.28	-2.20	74.0	-25.72	Peak	122.00	150	Vertical	Pass
3**	4773.000	38.55	-2.20	54.0	-15.45	AV	122.00	150	Vertical	Pass
4	6979.000	52.53	4.96	74.0	-21.47	Peak	295.00	150	Vertical	Pass
4**	6979.000	42.96	4.96	54.0	-11.04	AV	295.00	150	Vertical	Pass
5	12458.762	50.38	18.62	74.0	-23.62	Peak	179.00	150	Vertical	Pass
5**	12458.762	37.70	18.62	54.0	-16.30	AV	179.00	150	Vertical	Pass
6	17981.100	57.48	24.73	74.0	-16.52	Peak	94.00	150	Vertical	Pass
6**	17981.100	46.02	24.73	54.0	-7.98	AV	94.00	150	Vertical	Pass

1 GHz to 18 GHz, ANT H CHANNEL 18

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1115.500	39.56	-15.35	74.0	-34.44	Peak	301.00	150	Horizontal	Pass
1**	1115.500	27.73	-15.35	54.0	-26.27	AV	301.00	150	Horizontal	Pass
2	2439.600	68.89	-10.52	74.0	-5.11	Peak	225.00	150	Horizontal	N/A
2**	2439.600	67.02	-10.52	54.0	13.02	AV	225.00	150	Horizontal	N/A
3	5081.800	48.88	-0.08	74.0	-25.12	Peak	207.00	150	Horizontal	Pass
3**	5081.800	38.89	-0.08	54.0	-15.11	AV	207.00	150	Horizontal	Pass
4	6647.800	51.91	4.53	74.0	-22.09	Peak	102.00	150	Horizontal	Pass
4**	6647.800	42.21	4.53	54.0	-11.79	AV	102.00	150	Horizontal	Pass
5	12428.862	50.51	18.86	74.0	-23.49	Peak	66.00	150	Horizontal	Pass
5**	12428.862	37.95	18.86	54.0	-16.05	AV	66.00	150	Horizontal	Pass
6	17750.624	55.63	23.80	74.0	-18.37	Peak	35.00	150	Horizontal	Pass
6**	17750.624	45.34	23.80	54.0	-8.66	AV	35.00	150	Horizontal	Pass

1 GHz to 18 GHz, ANT V CHANNEL 18

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1131.800	39.76	-15.21	74.0	-34.24	Peak	139.00	150	Vertical	Pass
1**	1131.800	30.20	-15.21	54.0	-23.80	AV	139.00	150	Vertical	Pass
2	2440.500	65.86	-10.52	74.0	-8.14	Peak	266.00	150	Vertical	N/A
2**	2440.500	64.03	-10.52	54.0	10.03	AV	266.00	150	Vertical	N/A
3	4941.200	48.41	-1.39	74.0	-25.59	Peak	75.00	150	Vertical	Pass
3**	4941.200	39.06	-1.39	54.0	-14.94	AV	75.00	150	Vertical	Pass
4	6908.200	52.30	4.76	74.0	-21.70	Peak	260.00	150	Vertical	Pass
4**	6908.200	41.94	4.76	54.0	-12.06	AV	260.00	150	Vertical	Pass
5	11894.400	49.78	18.04	74.0	-24.22	Peak	198.00	150	Vertical	Pass
5**	11894.400	37.78	18.04	54.0	-16.22	AV	198.00	150	Vertical	Pass
6	17914.950	56.46	24.49	74.0	-17.54	Peak	360.00	150	Vertical	Pass
6**	17914.950	45.04	24.49	54.0	-8.96	AV	360.00	150	Vertical	Pass

1 GHz to 18 GHz, ANT H CHANNEL 25

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1104.100	37.69	-15.16	74.0	-36.31	Peak	102.00	150	Horizontal	Pass
1**	1104.100	25.34	-15.16	54.0	-28.66	AV	102.00	150	Horizontal	Pass
2	2474.500	71.45	-10.56	74.0	-2.55	Peak	358.00	150	Horizontal	N/A
2**	2474.500	70.33	-10.56	54.0	16.33	AV	358.00	150	Horizontal	N/A
3	3960.600	45.07	-4.50	74.0	-28.93	Peak	255.00	150	Horizontal	Pass
3**	3960.600	35.89	-4.50	54.0	-18.11	AV	255.00	150	Horizontal	Pass
4	6448.600	52.00	2.92	74.0	-22.00	Peak	53.00	150	Horizontal	Pass
4**	6448.600	41.55	2.92	54.0	-12.45	AV	53.00	150	Horizontal	Pass
5	9939.687	49.90	17.85	74.0	-24.10	Peak	318.00	150	Horizontal	Pass
5**	9939.687	37.54	17.85	54.0	-16.46	AV	318.00	150	Horizontal	Pass
6	17299.386	56.24	24.59	74.0	-17.76	Peak	329.00	150	Horizontal	Pass
6**	17299.386	46.33	24.59	54.0	-7.67	AV	329.00	150	Horizontal	Pass

1 GHz to 18 GHz, ANT V CHANNEL 25

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1378.400	37.93	-15.05	74.0	-36.07	Peak	13.00	150	Vertical	Pass
1**	1378.400	25.41	-15.05	54.0	-28.59	AV	13.00	150	Vertical	Pass
2	2474.500	64.01	-10.56	74.0	-9.99	Peak	231.00	150	Vertical	N/A
2**	2474.500	61.86	-10.56	54.0	7.86	AV	231.00	150	Vertical	N/A
3	4116.000	46.13	-4.03	74.0	-27.87	Peak	9.00	150	Vertical	Pass
3**	4116.000	37.70	-4.03	54.0	-16.30	AV	9.00	150	Vertical	Pass
4	6150.800	51.68	3.01	74.0	-22.32	Peak	309.00	150	Vertical	Pass
4**	6150.800	41.66	3.01	54.0	-12.34	AV	309.00	150	Vertical	Pass
5	8066.913	49.01	18.34	74.0	-24.99	Peak	32.00	150	Vertical	Pass
5**	8066.913	37.93	18.34	54.0	-16.07	AV	32.00	150	Vertical	Pass
6	15710.474	54.63	23.51	74.0	-19.37	Peak	360.00	150	Vertical	Pass
6**	15710.474	43.58	23.51	54.0	-10.42	AV	360.00	150	Vertical	Pass

1 GHz to 18 GHz, ANT H CHANNEL 26

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1137.900	39.54	-15.22	74.0	-34.46	Peak	329.00	150	Horizontal	Pass
1**	1137.900	27.32	-15.22	54.0	-26.68	AV	329.00	150	Horizontal	Pass
2	2479.500	51.03	-10.38	74.0	-22.97	Peak	226.00	150	Horizontal	N/A
2**	2479.500	47.83	-10.38	54.0	-6.17	AV	226.00	150	Horizontal	N/A
3	4802.800	48.53	-1.26	74.0	-25.47	Peak	78.00	150	Horizontal	Pass
3**	4802.800	39.09	-1.26	54.0	-14.91	AV	78.00	150	Horizontal	Pass
4	6996.600	51.57	4.06	74.0	-22.43	Peak	273.00	150	Horizontal	Pass
4**	6996.600	41.77	4.06	54.0	-12.23	AV	273.00	150	Horizontal	Pass
5	12160.338	49.42	20.05	74.0	-24.58	Peak	360.00	150	Horizontal	Pass
5**	12160.338	36.94	20.05	54.0	-17.06	AV	360.00	150	Horizontal	Pass
6	17989.239	56.38	24.81	74.0	-17.62	Peak	32.00	150	Horizontal	Pass
6**	17989.239	45.04	24.81	54.0	-8.96	AV	32.00	150	Horizontal	Pass

1 GHz to 18 GHz, ANT V CHANNEL 26

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1128.900	38.23	-15.29	74.0	-35.77	Peak	143.00	150	Vertical	Pass
1**	1128.900	31.21	-15.29	54.0	-22.79	AV	143.00	150	Vertical	Pass
2	2479.500	48.05	-10.38	74.0	-25.95	Peak	260.00	150	Vertical	N/A
2**	2479.500	46.31	-10.38	54.0	-7.69	AV	260.00	150	Vertical	N/A
3	4791.600	47.83	-1.75	74.0	-26.17	Peak	251.00	150	Vertical	Pass
3**	4791.600	38.80	-1.75	54.0	-15.20	AV	251.00	150	Vertical	Pass
4	6951.600	51.85	4.32	74.0	-22.15	Peak	98.00	150	Vertical	Pass
4**	6951.600	41.96	4.32	54.0	-12.04	AV	98.00	150	Vertical	Pass
5	11632.201	49.58	20.31	74.0	-24.42	Peak	242.00	150	Vertical	Pass
5**	11632.201	38.32	20.31	54.0	-15.68	AV	242.00	150	Vertical	Pass
6	17671.612	56.40	24.36	74.0	-17.60	Peak	232.00	150	Vertical	Pass
6**	17671.612	44.78	24.36	54.0	-9.22	AV	232.00	150	Vertical	Pass

FPC Antenna

1 GHz to 18 GHz, ANT H CHANNEL 11

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1300.000	37.55	-14.74	74.0	-36.45	Peak	287.00	150	Horizontal	Pass
1**	1300.000	31.69	-14.74	54.0	-22.31	AV	287.00	150	Horizontal	Pass
2	2405.500	61.29	-10.79	74.0	-12.71	Peak	56.00	150	Horizontal	N/A
2**	2405.500	58.55	-10.79	54.0	4.55	AV	56.00	150	Horizontal	N/A
3	4999.400	48.04	-0.90	74.0	-25.96	Peak	294.00	150	Horizontal	Pass
3**	4999.400	38.88	-0.90	54.0	-15.12	AV	294.00	150	Horizontal	Pass
4	6425.800	50.81	3.57	74.0	-23.19	Peak	116.00	150	Horizontal	Pass
4**	6425.800	40.91	3.57	54.0	-13.09	AV	116.00	150	Horizontal	Pass
5	11757.263	48.56	18.87	74.0	-25.44	Peak	226.00	150	Horizontal	Pass
5**	11757.263	38.11	18.87	54.0	-15.89	AV	226.00	150	Horizontal	Pass
6	17695.238	55.92	24.44	74.0	-18.08	Peak	314.00	150	Horizontal	Pass
6**	17695.238	44.43	24.44	54.0	-9.57	AV	314.00	150	Horizontal	Pass

1 GHz to 18 GHz, ANT V CHANNEL 11

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1113.300	41.64	-15.32	74.0	-32.36	Peak	206.00	150	Vertical	Pass
1**	1113.300	33.45	-15.32	54.0	-20.55	AV	206.00	150	Vertical	Pass
2	2404.600	59.11	-10.74	74.0	-14.89	Peak	59.00	150	Vertical	N/A
2**	2404.600	55.13	-10.74	54.0	1.13	AV	59.00	150	Vertical	N/A
3	2624.900	42.29	-8.98	74.0	-31.71	Peak	103.00	150	Vertical	Pass
3**	2624.900	37.76	-8.98	54.0	-16.24	AV	103.00	150	Vertical	Pass
4	6063.200	51.02	2.79	74.0	-22.98	Peak	140.00	150	Vertical	Pass
4**	6063.200	41.42	2.79	54.0	-12.58	AV	140.00	150	Vertical	Pass
5	11772.213	48.84	18.76	74.0	-25.16	Peak	213.00	150	Vertical	Pass
5**	11772.213	37.90	18.76	54.0	-16.10	AV	213.00	150	Vertical	Pass
6	17877.150	54.92	24.40	74.0	-19.08	Peak	302.00	150	Vertical	Pass
6**	17877.150	44.57	24.40	54.0	-9.43	AV	302.00	150	Vertical	Pass

1 GHz to 18 GHz, ANT H CHANNEL 18

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1300.500	37.44	-14.72	74.0	-36.56	Peak	62.00	150	Horizontal	Pass
1**	1300.500	30.49	-14.72	54.0	-23.51	AV	62.00	150	Horizontal	Pass
2	2440.600	64.70	-10.52	74.0	-9.30	Peak	49.00	150	Horizontal	N/A
2**	2440.600	59.36	-10.52	54.0	5.36	AV	49.00	150	Horizontal	N/A
3	3962.800	45.30	-4.47	74.0	-28.70	Peak	216.00	150	Horizontal	Pass
3**	3962.800	35.26	-4.47	54.0	-18.74	AV	216.00	150	Horizontal	Pass
4	6646.200	51.45	4.38	74.0	-22.55	Peak	101.00	150	Horizontal	Pass
4**	6646.200	42.48	4.38	54.0	-11.52	AV	101.00	150	Horizontal	Pass
5	12282.812	49.60	20.19	74.0	-24.40	Peak	114.00	150	Horizontal	Pass
5**	12282.812	36.95	20.19	54.0	-17.05	AV	114.00	150	Horizontal	Pass
6	17298.600	55.09	24.59	74.0	-18.91	Peak	351.00	150	Horizontal	Pass
6**	17298.600	44.19	24.59	54.0	-9.81	AV	351.00	150	Horizontal	Pass

1 GHz to 18 GHz, ANT V CHANNEL 18

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1110.300	38.67	-15.25	74.0	-35.33	Peak	201.00	150	Vertical	Pass
1**	1110.300	29.63	-15.25	54.0	-24.37	AV	201.00	150	Vertical	Pass
2	2439.500	61.63	-10.53	74.0	-12.37	Peak	181.00	150	Vertical	N/A
2**	2439.500	57.27	-10.53	54.0	3.27	AV	181.00	150	Vertical	N/A
3	4004.400	45.20	-4.69	74.0	-28.80	Peak	121.00	150	Vertical	Pass
3**	4004.400	35.90	-4.69	54.0	-18.10	AV	121.00	150	Vertical	Pass
4	6717.800	50.86	3.64	74.0	-23.14	Peak	112.00	150	Vertical	Pass
4**	6717.800	41.13	3.64	54.0	-12.87	AV	112.00	150	Vertical	Pass
5	12453.300	49.08	18.63	74.0	-24.92	Peak	19.00	150	Vertical	Pass
5**	12453.300	37.16	18.63	54.0	-16.84	AV	19.00	150	Vertical	Pass
6	17906.551	55.44	24.53	74.0	-18.56	Peak	290.00	150	Vertical	Pass
6**	17906.551	44.10	24.53	54.0	-9.90	AV	290.00	150	Vertical	Pass

1 GHz to 18 GHz, ANT H CHANNEL 25

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1027.700	39.62	-14.49	74.0	-34.38	Peak	30.00	150	Horizontal	Pass
1**	1027.700	27.93	-14.49	54.0	-26.07	AV	30.00	150	Horizontal	Pass
2	2475.400	65.73	-10.51	74.0	-8.27	Peak	116.00	150	Horizontal	N/A
2**	2475.400	62.77	-10.51	54.0	8.77	AV	116.00	150	Horizontal	N/A
3	4445.800	47.12	-2.14	74.0	-26.88	Peak	8.00	150	Horizontal	Pass
3**	4445.800	37.59	-2.14	54.0	-16.41	AV	8.00	150	Horizontal	Pass
4	6652.800	52.48	4.65	74.0	-21.52	Peak	76.00	150	Horizontal	Pass
4**	6652.800	42.49	4.65	54.0	-11.51	AV	76.00	150	Horizontal	Pass
5	9948.599	49.02	17.84	74.0	-24.98	Peak	241.00	150	Horizontal	Pass
5**	9948.599	37.56	17.84	54.0	-16.44	AV	241.00	150	Horizontal	Pass
6	15749.588	55.20	23.36	74.0	-18.80	Peak	286.00	150	Horizontal	Pass
6**	15749.588	43.14	23.36	54.0	-10.86	AV	286.00	150	Horizontal	Pass

1 GHz to 18 GHz, ANT V CHANNEL 25

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1229.800	37.22	-14.83	74.0	-36.78	Peak	115.00	150	Vertical	Pass
1**	1229.800	25.62	-14.83	54.0	-28.38	AV	115.00	150	Vertical	Pass
2	2474.500	61.84	-10.56	74.0	-12.16	Peak	192.00	150	Vertical	N/A
2**	2474.500	60.79	-10.56	54.0	6.79	AV	192.00	150	Vertical	N/A
3	4250.200	46.34	-3.18	74.0	-27.66	Peak	21.00	150	Vertical	Pass
3**	4250.200	37.62	-3.18	54.0	-16.38	AV	21.00	150	Vertical	Pass
4	6913.400	53.78	4.77	74.0	-20.22	Peak	295.00	150	Vertical	Pass
4**	6913.400	43.50	4.77	54.0	-10.50	AV	295.00	150	Vertical	Pass
5	9652.187	48.58	18.92	74.0	-25.42	Peak	222.00	150	Vertical	Pass
5**	9652.187	38.00	18.92	54.0	-16.00	AV	222.00	150	Vertical	Pass
6	16004.475	55.96	24.01	74.0	-18.04	Peak	361.00	150	Vertical	Pass
6**	16004.475	44.12	24.01	54.0	-9.88	AV	361.00	150	Vertical	Pass

1 GHz to 18 GHz, ANT H CHANNEL 26

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1299.500	39.62	-14.76	74.0	-34.38	Peak	319.00	150	Horizontal	Pass
1**	1299.500	27.86	-14.76	54.0	-26.14	AV	319.00	150	Horizontal	Pass
2	2480.600	45.01	-10.27	74.0	-28.99	Peak	43.00	150	Horizontal	N/A
2**	2480.600	39.66	-10.27	54.0	-14.34	AV	43.00	150	Horizontal	N/A
3	4247.400	46.51	-3.20	74.0	-27.49	Peak	14.00	150	Horizontal	Pass
3**	4247.400	37.05	-3.20	54.0	-16.95	AV	14.00	150	Horizontal	Pass
4	6917.200	51.30	4.67	74.0	-22.70	Peak	76.00	150	Horizontal	Pass
4**	6917.200	41.90	4.67	54.0	-12.10	AV	76.00	150	Horizontal	Pass
5	10946.224	49.55	18.61	74.0	-24.45	Peak	0.00	150	Horizontal	Pass
5**	10946.224	36.58	18.61	54.0	-17.42	AV	0.00	150	Horizontal	Pass
6	17839.874	55.57	24.07	74.0	-18.43	Peak	360.00	150	Horizontal	Pass
6**	17839.874	44.28	24.07	54.0	-9.72	AV	360.00	150	Horizontal	Pass

1 GHz to 18 GHz, ANT V CHANNEL 26

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1113.000	39.70	-15.33	74.0	-34.30	Peak	210.00	150	Vertical	Pass
1**	1113.000	30.28	-15.33	54.0	-23.72	AV	210.00	150	Vertical	Pass
2	2480.600	47.68	-10.27	74.0	-26.32	Peak	268.00	150	Vertical	N/A
2**	2480.600	42.72	-10.27	54.0	-11.28	AV	268.00	150	Vertical	N/A
3	3972.400	45.70	-4.20	74.0	-28.30	Peak	1.00	150	Vertical	Pass
3**	3972.400	36.99	-4.20	54.0	-17.01	AV	1.00	150	Vertical	Pass
4	6655.400	51.47	4.59	74.0	-22.53	Peak	282.00	150	Vertical	Pass
4**	6655.400	43.52	4.59	54.0	-10.48	AV	282.00	150	Vertical	Pass
5	9627.750	48.31	18.85	74.0	-25.69	Peak	175.00	150	Vertical	Pass
5**	9627.750	36.00	18.85	54.0	-18.00	AV	175.00	150	Vertical	Pass
6	17287.313	54.94	24.53	74.0	-19.06	Peak	33.00	150	Vertical	Pass
6**	17287.313	45.80	24.53	54.0	-8.20	AV	33.00	150	Vertical	Pass

A.7 Band Edge (Restricted-band band-edge)

Test Data

Note ¹: The lowest and highest channels are tested to verify the band edge emissions. Please refer to the following the plots for emissions values.

Note ²: The test data all are tested in the vertical and horizontal antenna which the trace is max hold. So these plots have shown the worst case.

Note ³: According the ANSI C63.10-2013, where limits are specified for both average and peak (or quasi-peak) detector functions, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement.

FPC Antenna

Test Mode	Test Channel	Frequency (MHz)	Level (dBuV/m)	Factor (dB)	Limit Line (dBuV/m)	Margin (dB)	Remark	Verdict
O-QPSK	11	2390	53.519	31.47	74	20.481	PEAK	Pass
		2390	N/A	N/A	54	N/A	AVERAGE	Pass
	25	2483.5	53.017	31.40	74	20.983	PEAK	Pass
		2483.5	N/A	N/A	54	N/A	AVERAGE	Pass
	26	2483.5	53.473	31.40	74	20.527	PEAK	Pass
		2483.5	N/A	N/A	54	N/A	AVERAGE	Pass


PCB Antenna

Test Mode	Test Channel	Frequency (MHz)	Level (dBuV/m)	Factor (dB)	Limit Line (dBuV/m)	Margin (dB)	Remark	Verdict
O-QPSK	11	2390	53.224	31.47	74	20.776	PEAK	Pass
		2390	N/A	N/A	54	N/A	AVERAGE	Pass
	25	2483.5	52.873	31.40	74	21.127	PEAK	Pass
		2483.5	N/A	N/A	54	N/A	AVERAGE	Pass
	26	2483.5	52.580	31.40	74	21.42	PEAK	Pass
		2483.5	N/A	N/A	54	N/A	AVERAGE	Pass

Test plots

PCB Antenna


CHANNEL 11, PEAK



CHANNEL 25, PEAK




CHANNEL 26, PEAK




FPC Antenna

CHANNEL 11, PEAK



CHANNEL 26, PEAK



A.8 Power Spectral Density (PSD)

Test Data

Channel	Spectral power density (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
11	1.317	8	Pass
18	3.069	8	Pass
25	1.677	8	Pass
26	-21.536	8	Pass

Test plots

CHANNEL 11



CHANNEL 18



CHANNEL 25



CHANNEL 26



ANNEX B TEST SETUP PHOTOS

Please refer the document "BL-SZ2120305-AR.pdf".

ANNEX C EUT EXTERNAL PHOTOS

Please refer the document "BL-SZ2120305-AW.pdf".

ANNEX D EUT INTERNAL PHOTOS

Please refer the document "BL-SZ2120305-AI.pdf".

--END OF REPORT--