

RF EXPOSURE REPORT

Applicant	Swann Communications Ltd
Address	RM1601, 249-255 DES VOEUX ROAD CENTRAL, HONG KONG

Manufacturer or Supplier	SHENZHEN AONI ELECTRONIC CO., LTD
Address	building 5, Honghui Industrial Park, Baoan District, Shenzhen, China
Product	IP Camera
Brand Name	Swann
Model	SWWHD-INDCAM
Additional Model & Model Difference	E963, E964, E965, E966, E967, E968, E96A, E96B, E937, E939, E938, Q1, S1
Date of tests	Apr. 13, 2018 ~ Jun. 25, 2018

- FCC Part 2 (Section 2.1091)
- **KDB 447498 D01**
- **⊠** IEEE C95.1

CONCLUSION: The submitted sample was found to COMPLY with the test requirement

Tested by Breeze Jiang	Approved by Glyn He
Project Engineer / EMC Department	Supervisor / EMC Department
Breeze	A

Date: Jul. 25, 2018

This report is governed by, and incorporates by reference, CPS Conditions of Service as posted at the date of issuance of this report at http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute you unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.



TABLE OF CONTENTS

RELE	ASE CONTROL RECORD	. 3
1.	CERTIFICATION	. 4
2.	RF EXPOSURE LIMIT	5
3.	MPE CALCULATION FORMULA	5
4.	CLASSIFICATION	5
5.	ANTENNA GAIN	6
	CALCULATION RESULT OF MAXIMUM CONDUCTED POWER	

Tel: +86 769 8593 5656 Fax: +86 769 8593 1080

Email: customerservice.dg@cn.bureauveritas.com



RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
FM180413N067	Original release	Jul. 25, 2018

Tel: +86 769 8593 5656 Fax: +86 769 8593 1080

Email: customerservice.dg@cn.bureauveritas.com



1. CERTIFICATION

FCC ID:	2AKPISWWHDINDCAM		
PRODUCT:	IP Camera		
BRAND NAME:	Swann		
MODEL NO.:	SWWHD-INDCAM		
ADDITIONAL NO.:	E963, E964, E965, E966, E967, E968, E96A, E96B, E937, E939, E938, Q1, S1		
TEST SAMPLE:	Engineering Sample		
APPLICANT:	CANT: Swann Communications Ltd		
STANDARDS:	FCC Part 2 (Section 2.1091)		
	KDB 447498 D01		
	IEEE C95.1		

Note: Additional models (see above table) are identical with the test model SWWHD-INDCAM except the model number for trading purpose.

Tel: +86 769 8593 5656 Fax: +86 769 8593 1080

Email: customerservice.dg@cn.bureauveritas.com



2. RF EXPOSURE LIMIT

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

FREQUENCY RANGE (MHz)			POWER DENSITY (mW/cm²)	AVERAGE TIME (minutes)		
LIMITS FOR GENERAL POPULATION / UNCONTROLLED EXPOSURE						
300-1500 F/1500 30						
1500-100,000			1.0	30		

F = Frequency in MHz

3. MPE CALCULATION FORMULA

 $Pd = (Pout*G) / (4*pi*r^2)$

where

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

4. CLASSIFICATION

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.

Tel: +86 769 8593 5656 Fax: +86 769 8593 1080

Email: customerservice.dg@cn.bureauveritas.com



5. ANTENNA GAIN

The antennas provided to the EUT, please refer to the following table:

Transmitter Circuit	Peak Gain (dBi)	Antenna Type	
Chain 0	3	Ceramic Antenna	

6. CALCULATION RESULT OF MAXIMUM CONDUCTED POWER

The tuned conducted Average Power (declared by client)

Mode	Frequency (MHz)	Target Power (dBm)	Tolerance (dBm)	Lower Tolerance (dBm)	Upper Tolerance (dBm)
802.11b	2412-2462	13	+-2	11	15
802.11g	2412-2462	12	+-2	10	14
802.11n(HT20)	2412-2462	11	+-2	9	13
802.11n(HT40)	2422-2452	10	+-2	8	12

The measured conducted Average Power

Mode	Frequency (MHz)	Averaged Power (dBm)
802.11b	2437	13.51
802.11g	2437	12.09
802.11n(HT20)	2437	11.22
802.11n(HT40)	2422	10.78

FREQUENCY BAND (MHz)	MAX AVERAGE POWER (dBm)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/cm²)	LIMIT (mW/cm²)
2412-2462	15	3	20	0.01255	1.0

--- END ---

Fax: +86 769 8593 1080 Guangdong 523942, China

Email: customerservice.dg@cn.bureauveritas.com

Tel: +86 769 8593 5656

Page 6 of 6