

**Statement of compliance to SAR****No. 170902254SHA-002**

Applicant : Omnicharge.Inc  
STE 180 Woodland Hills CA US

Manufacturing site : Same as applicant

Product Name : OMNI20C

Type/Model : P2C

TEST RESULT : PASS

According to KDB 447498D01(v06), the following exclusion for portable devices:

The 1g and 10g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq$  50mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})]^{1/2} f(\text{GHz})$

$\leq$  3.0 for 1-g SAR and  $\leq$  7.5 for 10-g extremity SAR,

Where:

- $f$  (GHz) is the RF channel transmit frequency in GHz;
- Power and distance are rounded to the nearest mW and mm before calculation;
- The result is rounded to one decimal place for comparison;

The test exclusions are applicable only when the minimum test separation distance is  $\leq$  50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $<$  5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

According the Test Report 170902254SHA-001:

Maximum transmitter power: -3.397dBm (0.46mW) at 2480MHz;

Distance = 5 mm (minimum separation distance: 5 mm was used in the calculation)

Result:

$(0.46/5)*\sqrt{2.480} = 0.145 < 3.0$

Conclusion:

The SAR requirement is deemed to be satisfied without test.

Date of issue: December 28, 2017

Prepared by:



Eric Li (Project engineer)

Reviewed by:



Daniel Zhao (Reviewer)