

No. 1 Workshop, M-10, Middle section, Science & Technology Park,
Shenzhen, Guangdong, China 518057
Telephone: +86 (0) 755 2601 2053
Fax: +86 (0) 755 2671 0594
Email: ee.shenzhen@sgs.com

Report No.: HR/2018/9000303
Page: 1 of 6


RF Exposure Evaluation Report

Application No.: HR/2018/90003
Applicant: Anima AB
Address of Applicant: Vastra Varvsgatan 19
ATT: Mikael Henning
Malm, S21177
Sweden
Manufacturer: Anima AB
Address of Manufacturer: Vastra Varvsgatan 19
ATT: Mikael Henning
Malm, S21177
Sweden
Factory: GoerTek Inc.
Address of Factory: No.8877 Yingqian Street,High-Tech Industrial Development
District,Weifang,Shandong,261031, P.R.China
Product Name: Wireless connected hybrid smart watch movement
Model No.: BT003NFC
Trade Mark: Kronaby
FCC ID: 2AKPL-BT003NFC
Standards: 47 CFR Part 1
47 CFR Part 15 subpart C
KDB447498 D01 General RF Exposure Guidance v06
Date of Receipt: 2018-09-01
Date of Test: 2018-09-02 to 2018-09-12
Date of Issue: 2018-09-13

Test Result:	PASS*
---------------------	--------------

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Derek Yang
Wireless Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.



1 Version

Revision Record				
Version	Chapter	Date	Modifier	Remark
01		2018-09-13		Original

Authorized for issue by:				
				2018-09-13
		<hr/> Mike Hu /Project Engineer		
				2018-09-13
		<hr/> David Chen /Reviewer		



Contents

RF EXPOSURE EVALUATION REPORT	1
1 VERSION	2
CONTENTS.....	3
2 GENERAL INFORMATION.....	4
2.1 CLIENT INFORMATION	4
2.2 GENERAL DESCRIPTION OF EUT	4
2.3 TEST LOCATION	5
2.4 TEST FACILITY	5
2.5 DEVIATION FROM STANDARDS	5
2.6 ABNORMALITIES FROM STANDARD CONDITIONS	5
2.7 OTHER INFORMATION REQUESTED BY THE CUSTOMER.....	5
3 RF EXPOSURE EVALUATION	6
3.1 RF EXPOSURE COMPLIANCE REQUIREMENT	6
3.1.1 <i>Limits</i>	6
3.1.2 <i>Limits</i>	6
3.1.3 <i>EUT RF Exposure</i>	6



2 General Information

2.1 Client Information

Applicant:	Anima AB
Address of Applicant:	Vastra Varvsgatan 19 ATT: Mikael Henning Malm, S21177 Sweden
Manufacturer:	Anima AB
Address of Manufacturer:	Vastra Varvsgatan 19 ATT: Mikael Henning Malm, S21177 Sweden
Factory:	GoerTek Inc.
Address of Factory:	No.8877 Yingqian Street,High-Tech Industrial Development District,Weifang,Shandong,261031, P.R.China

2.2 General Description of EUT

Product Name:	Wireless connected hybrid smart watch movement
Model No.:	BT003NFC
Trade Mark:	Kronaby
Antenna Gain:	Bluetooth: -4.5dBi
Hardware Version:	A1000-3005_C
Software Version:	20180731.01.03



2.3 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

No. 1 Workshop, M-10, Middle section, Science & Technology Park, Shenzhen, Guangdong, China
518057

Telephone: +86 (0) 755 2601 2053 Fax: +86 (0) 755 2671 0594

No tests were sub-contracted.

2.4 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **CNAS (No. CNAS L2929)**

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

- **A2LA (Certificate No. 3816.01)**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

- **VCCI**

The 3m Fully-anechoic chamber for above 1GHz, 10m Semi-anechoic chamber for below 1GHz, Shielded Room for Mains Port Conducted Interference Measurement and Telecommunication Port Conducted Interference Measurement of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-20026, R-14188, C-12383 and T-11153 respectively.

- **FCC –Designation Number: CN1178**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized as an accredited testing laboratory.

Designation Number: CN1178. Test Firm Registration Number: 406779.

- **Industry Canada (IC)**

Two 3m Semi-anechoic chambers and the 10m Semi-anechoic chamber of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab have been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-1, 4620C-2, 4620C-3.

2.5 Deviation from Standards

None.

2.6 Abnormalities from Standard Conditions

None.

2.7 Other Information Requested by the Customer

None.



3 RF Exposure Evaluation

3.1 RF Exposure Compliance Requirement

3.1.1 Limits

According to KDB447498D01 General RF Exposure Guidance v06

4.3.1. Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

3.1.2 Limits

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$$\left[\frac{\text{(max. power of channel, including tune-up tolerance, mW)}}{\text{(min. test separation distance, mm)}} \right] \cdot \sqrt{f(\text{GHz})} \leq 3.0$$
 for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

$f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation¹⁷

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion

3.1.3 EUT RF Exposure

$$\text{General RF Exposure} = \frac{\text{Max. Power of channel, including tune-up tolerance, mW}}{(\text{min. test separation distance, mm}) \cdot \sqrt{f(\text{GHz})}}$$

$$\text{General RF Exposure} = (3.16 \text{ mW} / 5 \text{ mm}) \times \sqrt{2.402 \text{ GHz}} = 0.98 \quad (1)$$

SAR requirement:

$$S = 3.0 \quad (2)$$

$$(1) < (2)$$

So the SAR report is not required.

(*) Max. power refer to Report No.:HR/2018/9000301