

JianYan Testing Group Shenzhen Co., Ltd.

Report No.: JYTSZ-R12-2400901

RF Exposure Evaluation Report

Report No.: JYTSZ-R12-2400901

Applicant: Shenzhen RodinBell Technology Co., Ltd.

Address of Applicant: 905#, Block B, Xinghe WORLD, Wuhe Avenue, Longgang

District, Shenzhen City, PRC

Equipment Under Test (EUT)

Product Name: 4-port UHF RFID Module

Model No.: M-702

FCC ID: 2AKQD-M-702

Applicable standards: FCC CFR Title 47 Part 2 (§2.1091)

Date of sample receipt: 30 Jul., 2024

Date of Test: 31 Aug., to 23 Aug., 2024

Date of report issue: 23 Sep., 2024

Test Result: PASS

Project by: _____ Date: ____ 23 Sep., 2024

Reviewed by: 23 Sep., 2024

Approved by: Date: 23 Sep., 2024

Manager

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in above the application standard version. Test results reported herein relate only to the item(s) tested.

This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.





1 Version

Version No.	Date	Description		
00	23 Aug., 2024	Original		
01	23 Sep., 2024	Update page 7		





2 Contents

		Page
Cover	r Page	1
1 V	Version	2
2 C	Contents	3
3 G	General Information	4
3.1	Client Information	4
3.2	General Description of E.U.T.	4
3.3		
3.4	Additions to, deviations, or exclusions from the method	4
3.5	Laboratory Facility	5
3.6		
4 T	Technical Requirements Specification	6
4.1	Limits	6
4.2	Test Procedure	6
4.3	Result	7
4 4	Conclusion	7



3 General Information

3.1 Client Information

Analianata	Chamban Badin Ball Tachada an Call Idd		
Applicant:	Shenzhen RodinBell Technology Co., Ltd.		
Address:	905#, Block B, Xinghe WORLD, Wuhe Avenue, Longgang District, Shenzhen City, PRC		
Manufacturer:	Shenzhen RodinBell Technology Co., Ltd.		
Address:	905#, Block B, Xinghe WORLD, Wuhe Avenue, Longgang District, Shenzhen City, PRC		

3.2 General Description of E.U.T.

Product Name:	4-port UHF RFID Module
Model No.:	M-702
Operation Frequency:	902 MHz - 928 MHz
Modulation technology:	ASK
Antenna Type:	External Antenna
Antenna gain:	1.5 dBi
Test Sample Condition:	The test samples were provided in good working order with no visible defects.

3.3 Operating Modes

Operating mode	Detail description
Transmitting mode	Keep the EUT in continuously transmitting in transmitting mode

3.4 Additions to, deviations, or exclusions from the method

No



Report No.: JYTSZ-R12-2400901

3.5 Laboratory Facility

The test facility is recognized, certified, or accredited by the following organizations:

• FCC - Designation No.: CN1211

JianYan Testing Group Shenzhen Co., Ltd. has been accredited as a testing laboratory by FCC(Federal Communications Commission). The test firm Registration No. is 727551.

■ ISED – CAB identifier.: CN0021

The 3m Semi-anechoic chamber and 10m Semi-anechoic chamber of JianYan Testing Group Shenzhen Co., Ltd. has been Registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 10106A-1.

• CNAS - Registration No.: CNAS L15527

JianYan Testing Group Shenzhen Co., Ltd. is accredited to ISO/IEC 17025:2017 General Requirements for the Competence of Testing and Calibration laboratories for the competence of testing. The Registration No. is CNAS L15527.

A2LA - Registration No.: 4346.01

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2017 General requirements for the competence of testing and calibration laboratories. The test scope can be found as below link: https://portal.a2la.org/scopepdf/4346-01.pdf

Laboratory Location

JianYan Testing Group Shenzhen Co., Ltd.

Address: No.101, Building 8, Innovation Wisdom Port, No.155 Hongtian Road, Huangpu Community, Xingiao Street, Bao'an District, Shenzhen, Guangdong, People's Republic of China.

Tel: +86-755-23118282, Fax: +86-755-23116366

Email: info-JYTee@lets.com, Website: http://jyt.lets.com

JianYan Testing Group Shenzhen Co., Ltd. Report Template No.: JYTSZ4b-177-C No.101, Building 8, Innovation Wisdom Port, No.155 Hongtian Road, Huangpu Community, Xinqiao Street, Bao'an District, Shenzhen, Guangdong, People's Republic of China. Tel: +86-755-23118282, Fax: +86-755-23116366



4 Technical Requirements Specification

4.1 Limits

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)			
(A) Limits for Occupational/Controlled Exposures							
0.3–3.0 614 1.63 *(100) 6							
3.0–30	1842/f	4.89/f *(900/f ²)		6			
30–300	61.4	61.4 0.163		6			
300–1500			f/300	6			
1500–100,000			5	6			
(B) Limits for General Population/Uncontrolled Exposure							
0.3–1.34	614	1.63	*(100)	30			
1.34–30	824/f	2.19/f	*(180/f ²)	30			
30–300	27.5	0.073	0.2	30			
300–1500			f/1500	30			
1500–100,000			1.0	30			

4.2 Test Procedure

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = \frac{P \times G}{4 \times \pi \times R^2}$$

Where:

S = power density

P = power input to the antenna

G = numeric gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the centre of radiation of the antenna





4.3 Result

Frequency (MHz)	Maximum Output power (dBm)	Maximum Output power (mW)	Antenna Gain (dBi)	Antenna Gain (numeric)	Distance (cm)	Result (mW/cm²)	Limits for General Population/ Uncontrolled Exposure (mW/cm²)
927.5	29.79	952.796	1.5	1.41	20.00	0.268	0.62

Note: Just the worst case mode was shown in report.

4.4 Conclusion

The device is exempt from the SAR test and satisfies RF exposure evaluation.

-----End of report-----