

Assessment report No:

NIE: 51934RAN.001

Assessment report RF EXPOSURE REPORT ACCORDING TO FCC 47 CFR Part 2.1091 ISED RSS -102 Issue 5:2015

Identification of item tested.....:	Smart Sensor
Trademark	Imr / AIUT
Model and /or type reference	ALEVEL 0275
Other identification of the product	FCC ID: 2AKQSALE0275 ISED ID:22378-ALEVEL0275
Final HW version	v.3
Final SW version	v.1
Features	Not provided data
Manufacturer	AIUT SP. Z O.O. ul. Wyczółkowskiego 113, 44-109 Gliwice, Poland.
Test method requested, standard.....:	FCC 47 CFR Part 2.1091 Radiofrequency radiation exposure evaluation: mobile devices. ISED RSS-102 Issue 5 (2015-03) – Radio Frequency Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands)
Summary	IN COMPLIANCE
Approved by (name / position & signature)	Miguel Lacave Antennas Lab Manager
Date of issue	2017-02-14
Report template No.....:	FAN24_01

Index

Competences and guarantees.....	3
General conditions.....	3
Identification of the client	3
General description of the device under evaluation	4
Assessment summary	5
Appendix A – FCC RF Exposure	6
FCC RF Exposure evaluation for mobile devices.....	7
FCC MPE Evaluation Results.....	8
Appendix B – ISED RF Exposure.....	10
ISED RF Exposure evaluation for mobile devices	11
ISED MPE Evaluation Results	12

Competences and guarantees

In order to assure the traceability to other national and international laboratories, AT4 wireless has a calibration and maintenance program for its measurement equipment.

AT4 wireless guarantees the reliability of the data presented in this report, which is the result of the measurements and the tests performed to the item under test on the date and under the conditions stated on the report and, it is based on the knowledge and technical facilities available at AT4 wireless at the time of performance of the test.

AT4 wireless is liable to the client for the maintenance of the confidentiality of all information related to the item under test and the results of the test.

The results presented in this Test Report apply only to the particular item under test established in this document.

IMPORTANT: No parts of this report may be reproduced or quoted out of context, in any form or by any means, except in full, without the previous written permission of AT4 wireless.

General conditions

1. This report is only referred to the item that has undergone the test.
2. This report does not constitute or imply on its own an approval of the product by the Certification Bodies or competent Authorities.
3. This document is only valid if complete; no partial reproduction can be made without previous written permission of AT4 wireless.
4. This test report cannot be used partially or in full for publicity and/or promotional purposes without previous written permission of AT4 wireless and the Accreditation Bodies.

Identification of the client

AIUT SP. Z O.O.

ul. Wyczółkowskiego 113, 44-109 Gliwice, Poland.

General description of the device under evaluation

The test sample consists of a Smart Sensor designed to remote wireless indicate the liquid gas level in tank equipped with float level gauge. Additionally, it is possible to visually read the gas level on its built-in mechanical level indicator. The device ALEVEL 0275 comprises one printed circuit board with electronic circuitry, an integrated antenna and primary battery, all housed in a polycarbonate enclosure.

The equipment specifications declared by the manufacturer for the supported technology are:

Band (MHz)	Frequency Range (MHz)	Modulation	Max. output power (dBm)	Max. Antenna gain (dBi)	Maximum E.I.R.P. (dBm)
900	902-928	2-GFSK	-1.23	0	-1.23

Table 1: Equipment specifications

Assessment summary

Radiofrequency radiation exposure limits		
FCC 47 CFR § 2.1091		
Band (MHz)	Technology	VERDICT (Pass/Fail)
900	RF Transmission	Pass
ISED RSS-102 Issue 5 (2015-03)		
Band (MHz)	Technology	VERDICT (Pass/Fail)
900	RF Transmission	Pass

Table 2: Assessment summary.

Appendix A – FCC RF Exposure

FCC RF Exposure evaluation for mobile devices

Devices operating in standalone mobile device exposure conditions may contain a single transmitter or multiple transmitters that do not transmit simultaneously. A minimum test separation distance ≥ 20 cm is required between the antenna and radiating structures of the device and nearby persons to apply mobile device exposure limits. The distance must be at least 20 cm and fully supported by the operating and installation configurations of the transmitter and its antenna(s), according to the source-based time-averaged maximum power requirements of § 2.1091(d)(2). In cases where cable losses or other attenuations are applied to determine compliance, the most conservative operating configurations and exposure conditions must be evaluated. The minimum test separation distance required for a device to comply with mobile device exposure conditions must be clearly identified in the installation and operating instructions, for all installation and exposure conditions, to enable users and installers to comply with RF exposure requirements. For mobile devices that have the potential to operate in portable device exposure conditions, similar to the configurations described in § 2.1091(d)(4), a KDB inquiry is required to determine the SAR test requirements for demonstrating compliance.

When a device qualifies for the categorical exclusion provision of § 2.1091(c), the minimum test separation distance may be estimated, when applicable, by simple calculations according to plane-wave equivalent conditions, to ensure the transmitter and its antenna(s) can operate in manners that meet or exceed the estimated distance. The source-based time-averaged maximum radiated power, according to the maximum antenna gain, must be applied to calculate the field strength and power density required to establish the minimum test separation distance. When the estimated test separation distance becomes overly conservative and does not support compliance, MPE measurement or computational modeling may be used to determine the required minimum separation distance.

According to §1.1310 Radiofrequency radiation exposure limits, paragraph (e), the limits for Maximum Permissible Exposure (MPE) to radiofrequency electromagnetic fields are:

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3–3.0	614	1.63	* 100	6
3.0–30	1842/f	4.89/f	* 900/f ²	6
30–300	61.4	0.163	1.0	6
300–1,500	f/300	6
1,500–100,000	5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	* 100	30
1.34–30	824/f	2.19/f	* 180/f ²	30
30–300	27.5	0.073	0.2	30
300–1,500	f/1500	30
1,500–100,000	1.0	30

f = frequency in MHz * = Plane-wave equivalent power density

FCC MPE Evaluation Results

In order to perform the assessment, the following equations have been used for the calculations:

$$\text{Power density: } S[mW/cm^2] = \frac{P_{E.I.R.P.}[mW]}{4\pi R[cm]^2}$$

$$\text{Minimum compliance distance: } R_{\min}[m] = \sqrt{\frac{P_{E.I.R.P.}[mW]}{4\pi S[mW/cm^2]}}$$

Where:

S = power density

$P_{E.I.R.P.}$ = Equivalent isotropically radiated power

R = distance to the center of radiation of the antenna (evaluation distance)

R_{\min} = distance to the center of radiation of the antenna

Assessment for 900 MHz band

Antenna Gain (dBi):	0
Minimum use distance (cm):	20
Worst Case Frequency (MHz):	902
Maximum EIRP (dBm):	-1.23
Maximum EIRP (mW):	0.75
General public - Power density limit (mW/cm ²):	0.6013

Power density at minimum use distance:

Power density (mW/cm ²):	0.00015
Verdict for general public:	PASS

The power density level for this transmission mode is below general public and controlled exposure power density limits.

Minimum compliance distance for this technology:

Minimum distance for general public (cm):	0.32
Verdict for general public:	PASS

The minimum use distance is larger than general public and controlled exposure minimum compliance distances.

Appendix B – ISED RF Exposure

ISED RF Exposure evaluation for mobile devices

According to RSS-102 Issue 5, Paragraph “4. Exposure Limits”, Industry of Canada has adopted the RF field strength limits established in Healths Canada’s RF exposure guideline, Safety code 6:

**Table 4: RF Field Strength Limits for Devices Used by the General Public
(Uncontrolled Environment)**

Frequency Range (MHz)	Electric Field (V/m rms)	Magnetic Field (A/m rms)	Power Density (W/m ²)	Reference Period (minutes)
0.003-10 ²¹	83	90	-	Instantaneous*
0.1-10	-	0.73/ <i>f</i>	-	6**
1.1-10	87/ <i>f</i> ^{0.5}	-	-	6**
10-20	27.46	0.0728	2	6
20-48	58.07/ <i>f</i> ^{0.25}	0.1540/ <i>f</i> ^{0.25}	8.944/ <i>f</i> ^{0.5}	6
48-300	22.06	0.05852	1.291	6
300-6000	3.142 <i>f</i> ^{0.3417}	0.008335 <i>f</i> ^{0.3417}	0.02619 <i>f</i> ^{0.6834}	6
6000-15000	61.4	0.163	10	6
15000-150000	61.4	0.163	10	616000/ <i>f</i> ^{1.2}
150000-300000	0.158 <i>f</i> ^{0.5}	4.21 x 10 ⁻⁴ <i>f</i> ^{0.5}	6.67 x 10 ⁻⁵ <i>f</i>	616000/ <i>f</i> ^{1.2}
Note: <i>f</i> is frequency in MHz. *Based on nerve stimulation (NS). ** Based on specific absorption rate (SAR).				

ISED MPE Evaluation Results

In order to perform the assessment, the following equations have been used for the calculations:

$$\text{Power density: } S[W/m^2] = \frac{P_{E.I.R.P.}[W]}{4\pi R[m]^2}$$

$$\text{Minimum compliance distance: } R_{\min}[m] = \sqrt{\frac{P_{E.I.R.P.}[W]}{4\pi S[W/m^2]}}$$

Where:

S = power density

$P_{E.I.R.P.}$ = Equivalent isotropically radiated power

R = distance to the center of radiation of the antenna (evaluation distance)

R_{\min} = distance to the center of radiation of the antenna

Assessment for 900 MHz band

Antenna Gain (dBi):	0
Minimum use distance (cm):	20
Worst Case Frequency (MHz):	902
Maximum EIRP (dBm):	-1.23
Maximum EIRP (mW):	0.75
General public - Power density limit (W/m2):	2.735

Power density at minimum use distance:

Power density (W/m2):	0.00015
Verdict for general public:	PASS

The power density level for this transmission mode is below general public and controlled exposure power density limits.

Minimum compliance distance for this technology:

Minimum distance for general public (cm):	0.47
Verdict for general public:	PASS

The minimum use distance is larger than general public and controlled exposure minimum compliance distances.