

Assessment report No:

NIE: 51934RAN.002

Assessment report RF EXPOSURE REPORT ACCORDING TO FCC 47 CFR Part 2.1091 ISED RSS -102 Issue 5:2015

| | |
|---|--|
| Identification of item tested.....: | Mobile Data Gateway |
| Trademark | Imr / AIUT |
| Model and /or type reference | OKO 5875 |
| Other identification of the product | FCC ID: 2AKQSOKO5875 IC ID: 22378-OKO5875 |
| Final HW version | 3 |
| Final SW version | C1 |
| IMEI TAC | 35696107 |
| Features | Mobile Data Gateway supporting FDD 2, 4, 5, 12, 13 LTE bands and FDD II, V UMTS bands |
| Manufacturer | AIUT SP. Z O.O. ul. Wyczółkowskiego 113, 44-109 Gliwice, Poland. |
| Test method requested, standard.....: | FCC 47 CFR Part 2.1091 Radiofrequency radiation exposure evaluation: mobile devices. ISED RSS-102 Issue 5 (2015-03) – Radio Frequency Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands) |
| Summary | IN COMPLIANCE |
| Approved by (name / position & signature) | Miguel Lacave Antennas Lab Manager |
| Date of issue | 2017-03-03 |
| Report template No.....: | FAN24_01 |

Index

| | |
|--|----|
| Competences and guarantees..... | 3 |
| General conditions..... | 3 |
| Identification of the client | 3 |
| General description of the device under evaluation | 4 |
| Assessment summary | 5 |
| Appendix A – FCC RF Exposure | 6 |
| FCC RF Exposure evaluation for mobile devices..... | 7 |
| FCC MPE Evaluation Results..... | 8 |
| Appendix B – ISED RF Exposure..... | 18 |
| ISED RF Exposure evaluation for mobile devices | 19 |
| ISED MPE Evaluation Results | 20 |

Competences and guarantees

In order to assure the traceability to other national and international laboratories, AT4 wireless has a calibration and maintenance program for its measurement equipment.

AT4 wireless guarantees the reliability of the data presented in this report, which is the result of the measurements and the tests performed to the item under test on the date and under the conditions stated on the report and, it is based on the knowledge and technical facilities available at AT4 wireless at the time of performance of the test.

AT4 wireless is liable to the client for the maintenance of the confidentiality of all information related to the item under test and the results of the test.

The results presented in this Test Report apply only to the particular item under test established in this document.

IMPORTANT: No parts of this report may be reproduced or quoted out of context, in any form or by any means, except in full, without the previous written permission of AT4 wireless.

General conditions

1. This report is only referred to the item that has undergone the test.
2. This report does not constitute or imply on its own an approval of the product by the Certification Bodies or competent Authorities.
3. This document is only valid if complete; no partial reproduction can be made without previous written permission of AT4 wireless.
4. This test report cannot be used partially or in full for publicity and/or promotional purposes without previous written permission of AT4 wireless and the Accreditation Bodies.

Identification of the client

AIUT SP. Z O.O.

ul. Wyczółkowskiego 113, 44-109 Gliwice, Poland.

General description of the device under evaluation

The device under evaluation consists of a compact, battery-powered mobile data gateway, which receives via radio measurements from assigned smart level sensors installed on tanks, to collect the tank level/volume data and retransmit the current stock information, archive measurement and status of the device via cellular networks to acquisition server.

The equipment specifications declared by the manufacturer for each supported feature are:

| Assessment | Technology | Band | Band (MHz) | Maximum RF output power (dBm) | Maximum antenna gain (dBi) | Average radiated power (E.I.R.P.) (dBm) |
|------------|------------|------|------------|-------------------------------|----------------------------|---|
| 1 | 25K0F1D | 900 | 900 | -1.23 | +0.0 | 1.23 |
| 2 | WCDMA | II | 1900 | 24.0 | +6.0 | 30.0 |
| 3 | WCDMA | V | 950 | 24.0 | +6.0 | 30.0 |
| 4 | LTE | 2 | 1900 | 23.0 | +6.0 | 29.0 |
| 5 | LTE | 4 | 1700 | 23.0 | +6.0 | 29.0 |
| 6 | LTE | 5 | 850 | 23.0 | +6.0 | 29.0 |
| 7 | LTE | 12 | 700 | 23.0 | +6.0 | 29.0 |
| 8 | LTE | 13 | 750 | 23.0 | +6.0 | 29.0 |

Table 1: Equipment specifications

Assessment summary

| Radiofrequency radiation exposure limits | | | | |
|--|------------|------|------------|---------------------|
| FCC 47 CFR § 2.1091 & ISED RSS-102 Issue 5 (2015-03) | | | | |
| Assessment | Technology | Band | Band (MHz) | VERDICT (Pass/Fail) |
| 1 | 25K0F1D | 900 | 900 | Pass |
| 2 | WCDMA | II | 1900 | Pass |
| 3 | WCDMA | V | 950 | Pass |
| 4 | LTE | 2 | 1900 | Pass |
| 5 | LTE | 4 | 1700 | Pass |
| 6 | LTE | 5 | 850 | Pass |
| 7 | LTE | 12 | 700 | Pass |
| 8 | LTE | 13 | 750 | Pass |

Table 2: Assessment summary.

Appendix A – FCC RF Exposure

FCC RF Exposure evaluation for mobile devices

Devices operating in standalone mobile device exposure conditions may contain a single transmitter or multiple transmitters that do not transmit simultaneously. A minimum test separation distance ≥ 20 cm is required between the antenna and radiating structures of the device and nearby persons to apply mobile device exposure limits. The distance must be at least 20 cm and fully supported by the operating and installation configurations of the transmitter and its antenna(s), according to the source-based time-averaged maximum power requirements of § 2.1091(d)(2). In cases where cable losses or other attenuations are applied to determine compliance, the most conservative operating configurations and exposure conditions must be evaluated. The minimum test separation distance required for a device to comply with mobile device exposure conditions must be clearly identified in the installation and operating instructions, for all installation and exposure conditions, to enable users and installers to comply with RF exposure requirements. For mobile devices that have the potential to operate in portable device exposure conditions, similar to the configurations described in § 2.1091(d)(4), a KDB inquiry is required to determine the SAR test requirements for demonstrating compliance.

When a device qualifies for the categorical exclusion provision of § 2.1091(c), the minimum test separation distance may be estimated, when applicable, by simple calculations according to plane-wave equivalent conditions, to ensure the transmitter and its antenna(s) can operate in manners that meet or exceed the estimated distance. The source-based time-averaged maximum radiated power, according to the maximum antenna gain, must be applied to calculate the field strength and power density required to establish the minimum test separation distance. When the estimated test separation distance becomes overly conservative and does not support compliance, MPE measurement or computational modeling may be used to determine the required minimum separation distance.

According to §1.1310 Radiofrequency radiation exposure limits, paragraph (e), the limits for Maximum Permissible Exposure (MPE) to radiofrequency electromagnetic fields are:

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

| Frequency range (MHz) | Electric field strength (V/m) | Magnetic field strength (A/m) | Power density (mW/cm ²) | Averaging time (minutes) |
|--|-------------------------------|-------------------------------|-------------------------------------|--------------------------|
| (A) Limits for Occupational/Controlled Exposure | | | | |
| 0.3–3.0 | 614 | 1.63 | * 100 | 6 |
| 3.0–30 | 1842/f | 4.89/f | * 900/f ² | 6 |
| 30–300 | 61.4 | 0.163 | 1.0 | 6 |
| 300–1,500 | | | f/300 | 6 |
| 1,500–100,000 | | | 5 | 6 |
| (B) Limits for General Population/Uncontrolled Exposure | | | | |
| 0.3–1.34 | 614 | 1.63 | * 100 | 30 |
| 1.34–30 | 824/f | 2.19/f | * 180/f ² | 30 |
| 30–300 | 27.5 | 0.073 | 0.2 | 30 |
| 300–1,500 | | | f/1500 | 30 |
| 1,500–100,000 | | | 1.0 | 30 |

f = frequency in MHz * = Plane-wave equivalent power density

FCC MPE Evaluation Results

In order to perform the assessment, the following equations have been used for the calculations:

$$\text{Power density: } S[mW/cm^2] = \frac{P_{E.I.R.P.}[mW]}{4\pi R[cm]^2}$$

$$\text{Minimum compliance distance: } R_{\min}[m] = \sqrt{\frac{P_{E.I.R.P.}[mW]}{4\pi S[mW/cm^2]}}$$

Where:

S = power density

$P_{E.I.R.P.}$ = Equivalent isotropically radiated power

R = distance to the center of radiation of the antenna (evaluation distance)

R_{\min} = distance to the center of radiation of the antenna

Assessment 1 – RF 900 MHz

| | |
|--|-------|
| Maximum output power (dBm): | -1.23 |
| Antenna Gain (dBi): | 0.02 |
| Minimum use distance (cm): | 20.0 |
| Worst Case Frequency (MHz): | 902.0 |
| Maximum EIRP (dBm): | -1.23 |
| Maximum EIRP (mW): | 0.75 |
| General public - Power density limit (mW/cm2): | 0.601 |

Power density at minimum use distance:

| | |
|-----------------------------|---------|
| Power density (mW/cm2): | 0.00015 |
| Verdict for general public: | PASS |

The power density level for this transmission mode is below general public and controlled exposure power density limits.

Minimum compliance distance for this technology:

| | |
|---|------|
| Minimum distance for general public (cm): | 0.32 |
| Verdict for general public: | PASS |

The minimum use distance is larger than general public and controlled exposure minimum compliance distances.

Assessment 2 - WCDMA Band II

| | |
|--|---------|
| Maximum output power (dBm): | 24.0 |
| Antenna Gain (dBi): | 6.0 |
| Minimum use distance (cm): | 20.0 |
| Worst Case Frequency (MHz): | 1850.0 |
| Maximum EIRP (dBm): | 30.0 |
| Maximum EIRP (mW): | 1000.00 |
| General public - Power density limit (mW/cm2): | 1 |

Power density at minimum use distance:

| | |
|-----------------------------|-------|
| Power density (mW/cm2): | 0.199 |
| Verdict for general public: | PASS |

The power density level for this transmission mode is below general public and controlled exposure power density limits.

Minimum compliance distance for this technology:

| | |
|---|------|
| Minimum distance for general public (cm): | 8.92 |
| Verdict for general public: | PASS |

The minimum use distance is larger than general public and controlled exposure minimum compliance distances.

Assessment 3 - WCDMA Band V

| | |
|--|---------|
| Maximum output power (dBm): | 24.0 |
| Antenna Gain (dBi): | 6.0 |
| Minimum use distance (cm): | 20.0 |
| Worst Case Frequency (MHz): | 824.0 |
| Maximum EIRP (dBm): | 30.0 |
| Maximum EIRP (mW): | 1000.00 |
| General public - Power density limit (mW/cm2): | 0.549 |

Power density at minimum use distance:

| | |
|-----------------------------|-------|
| Power density (mW/cm2): | 0.199 |
| Verdict for general public: | PASS |

The power density level for this transmission mode is below general public and controlled exposure power density limits.

Minimum compliance distance for this technology:

| | |
|---|-------|
| Minimum distance for general public (cm): | 12.04 |
| Verdict for general public: | PASS |

The minimum use distance is larger than general public and controlled exposure minimum compliance distances.

Assessment 4 - LTE Band 2

| | |
|--|--------|
| Maximum output power (dBm): | 23.0 |
| Antenna Gain (dBi): | 6.0 |
| Minimum use distance (cm): | 20.0 |
| Worst Case Frequency (MHz): | 1850.0 |
| Maximum EIRP (dBm): | 29.0 |
| Maximum EIRP (mW): | 794.33 |
| General public - Power density limit (mW/cm2): | 1 |

Power density at minimum use distance:

| | |
|-----------------------------|------|
| Power density (mW/cm2): | 0.16 |
| Verdict for general public: | PASS |

The power density level for this transmission mode is below general public and controlled exposure power density limits.

Minimum compliance distance for this technology:

| | |
|---|------|
| Minimum distance for general public (cm): | 7.95 |
| Verdict for general public: | PASS |

The minimum use distance is larger than general public and controlled exposure minimum compliance distances.

Assessment 5 - LTE Band 4

| | |
|---|--------|
| Maximum output power (dBm): | 23.0 |
| Antenna Gain (dBi): | 6.0 |
| Minimum use distance (cm): | 20 |
| Worst Case Frequency (MHz): | 1710.0 |
| Maximum EIRP (dBm): | 29.0 |
| Maximum EIRP (mW): | 794.33 |
| General public - Power density limit (mW/cm ²): | 1 |

Power density at minimum use distance:

| | |
|--------------------------------------|------|
| Power density (mW/cm ²): | 0.16 |
| Verdict for general public: | PASS |

The power density level for this transmission mode is below general public and controlled exposure power density limits.

Minimum compliance distance for this technology:

| | |
|---|------|
| Minimum distance for general public (cm): | 7.95 |
| Verdict for general public: | PASS |

The minimum use distance is larger than general public and controlled exposure minimum compliance distances.

Assessment 6 - LTE Band 5

| | |
|---|--------|
| Maximum output power (dBm): | 23.0 |
| Antenna Gain (dBi): | 6.0 |
| Minimum use distance (cm): | 20 |
| Worst Case Frequency (MHz): | 824.0 |
| Maximum EIRP (dBm): | 29.0 |
| Maximum EIRP (mW): | 794.33 |
| General public - Power density limit (mW/cm ²): | 0.5491 |

Power density at minimum use distance:

| | |
|--------------------------------------|------|
| Power density (mW/cm ²): | 0.16 |
| Verdict for general public: | PASS |

The power density level for this transmission mode is below general public and controlled exposure power density limits.

Minimum compliance distance for this technology:

| | |
|---|-------|
| Minimum distance for general public (cm): | 10.73 |
| Verdict for general public: | PASS |

The minimum use distance is larger than general public and controlled exposure minimum compliance distances.

Assessment 7 - LTE Band 12

| | |
|---|--------|
| Maximum output power (dBm): | 23.0 |
| Antenna Gain (dBi): | 6.0 |
| Minimum use distance (cm): | 20 |
| Worst Case Frequency (MHz): | 699.0 |
| Maximum EIRP (dBm): | 29.0 |
| Maximum EIRP (mW): | 794.33 |
| General public - Power density limit (mW/cm ²): | 0.466 |

Power density at minimum use distance:

| | |
|--------------------------------------|------|
| Power density (mW/cm ²): | 0.16 |
| Verdict for general public: | PASS |

The power density level for this transmission mode is below general public and controlled exposure power density limits.

Minimum compliance distance for this technology:

| | |
|---|-------|
| Minimum distance for general public (cm): | 11.65 |
| Verdict for general public: | PASS |

The minimum use distance is larger than general public and controlled exposure minimum compliance distances.

Assessment 8 - LTE Band 13

| | |
|---|--------|
| Maximum output power (dBm): | 23.0 |
| Antenna Gain (dBi): | 6.0 |
| Minimum use distance (cm): | 20 |
| Worst Case Frequency (MHz): | 777.0 |
| Maximum EIRP (dBm): | 29.0 |
| Maximum EIRP (mW): | 794.33 |
| General public - Power density limit (mW/cm ²): | 2.59 |

Power density at minimum use distance:

| | |
|--------------------------------------|------|
| Power density (mW/cm ²): | 0.16 |
| Verdict for general public: | PASS |

The power density level for this transmission mode is below general public and controlled exposure power density limits.

Minimum compliance distance for this technology:

| | |
|---|-------|
| Minimum distance for general public (cm): | 11.05 |
| Verdict for general public: | PASS |

The minimum use distance is larger than general public and controlled exposure minimum compliance distances.

Multiple frequencies assessment

When multiple sources are introduced into an environment, it becomes necessary to address the sources interdependently, since each source will contribute some percentage of the maximum exposure toward the total exposure at a fixed location. The sum of the ratios of the exposure from each source to the corresponding maximum exposure for the frequency of each source must be evaluated.

The exposure complies with the maximum permissible exposure if the sum of the ratios is less than unity:

$$\sum_{i=1}^n \frac{S_i}{MPE_i} < 1$$

Where

S_i is the power density of each source;

MPE_i is the power density basic restriction of each source.

The device can transmit using 25K0F1D and cellular technologies at the same time, so the worst case for simultaneous transmission will be:

$$\frac{0.00015}{0.601} + \frac{0.199}{0.549} = 0.00025 + 0.363 = 0.3633 < 1 \text{ Limit}$$

Appendix B – ISED RF Exposure

ISED RF Exposure evaluation for mobile devices

According to RSS-102 Issue 5, Paragraph “4. Exposure Limits”, Industry of Canada has adopted the RF field strength limits established in Health Canada’s RF exposure guideline, Safety code 6:

**Table 4: RF Field Strength Limits for Devices Used by the General Public
 (Uncontrolled Environment)**

| Frequency Range (MHz) | Electric Field (V/m rms) | Magnetic Field (A/m rms) | Power Density (W/m ²) | Reference Period (minutes) |
|--|-----------------------------|-----------------------------------|--------------------------------------|-------------------------------|
| 0.003-10 ²¹ | 83 | 90 | - | Instantaneous* |
| 0.1-10 | - | 0.73/ f | - | 6** |
| 1.1-10 | 87/ $f^{0.5}$ | - | - | 6** |
| 10-20 | 27.46 | 0.0728 | 2 | 6 |
| 20-48 | 58.07/ $f^{0.25}$ | 0.1540/ $f^{0.25}$ | 8.944/ $f^{0.5}$ | 6 |
| 48-300 | 22.06 | 0.05852 | 1.291 | 6 |
| 300-6000 | 3.142 $f^{0.3417}$ | 0.008335 $f^{0.3417}$ | 0.02619 $f^{0.6834}$ | 6 |
| 6000-15000 | 61.4 | 0.163 | 10 | 6 |
| 15000-150000 | 61.4 | 0.163 | 10 | 616000/ $f^{1.2}$ |
| 150000-300000 | 0.158 $f^{0.5}$ | 4.21 x 10 ⁻⁴ $f^{0.5}$ | 6.67 x 10 ⁻⁵ f | 616000/ $f^{1.2}$ |
| Note: f is frequency in MHz. *Based on nerve stimulation (NS). ** Based on specific absorption rate (SAR). | | | | |

ISED MPE Evaluation Results

In order to perform the assessment, the following equations have been used for the calculations:

$$\text{Power density: } S[W/m^2] = \frac{P_{E.I.R.P.}[W]}{4\pi R[m]^2}$$

$$\text{Minimum compliance distance: } R_{\min}[m] = \sqrt{\frac{P_{E.I.R.P.}[W]}{4\pi S[W/m^2]}}$$

Where:

S = power density

$P_{E.I.R.P.}$ = Equivalent isotropically radiated power

R = distance to the center of radiation of the antenna (evaluation distance)

R_{\min} = distance to the center of radiation of the antenna

Assessment 1 – RF 900 MHz

| | |
|---|-------|
| Maximum output power (dBm): | -1.23 |
| Antenna Gain (dBi): | 0 |
| Minimum use distance (cm): | 20 |
| Worst Case Frequency (MHz): | 902.0 |
| Maximum EIRP (dBm): | -1.23 |
| Maximum EIRP (mW): | 0.75 |
| General public - Power density limit (W/m ²): | 2.74 |

Power density at minimum use distance:

| | |
|------------------------------------|--------|
| Power density (W/m ²): | 0.0015 |
| Verdict for general public: | PASS |

The power density level for this transmission mode is below general public and controlled exposure power density limits.

Minimum compliance distance for this technology:

| | |
|---|------|
| Minimum distance for general public (cm): | 0.47 |
| Verdict for general public: | PASS |

The minimum use distance is larger than general public and controlled exposure minimum compliance distances.

Assessment 2 - WCDMA Band II

| | |
|---|---------|
| Maximum output power (dBm): | 24.0 |
| Antenna Gain (dBi): | 6.0 |
| Minimum use distance (cm): | 20 |
| Worst Case Frequency (MHz): | 1850.0 |
| Maximum EIRP (dBm): | 30.0 |
| Maximum EIRP (mW): | 1000.00 |
| General public - Power density limit (W/m ²): | 4.476 |

Power density at minimum use distance:

| | |
|------------------------------------|------|
| Power density (W/m ²): | 1.99 |
| Verdict for general public: | PASS |

The power density level for this transmission mode is below general public and controlled exposure power density limits.

Minimum compliance distance for this technology:

| | |
|---|-------|
| Minimum distance for general public (cm): | 13.33 |
| Verdict for general public: | PASS |

The minimum use distance is larger than general public and controlled exposure minimum compliance distances.

Assessment 3 - WCDMA Band V

| | |
|---|---------|
| Maximum output power (dBm): | 24.0 |
| Antenna Gain (dBi): | 6.0 |
| Minimum use distance (cm): | 20 |
| Worst Case Frequency (MHz): | 824.0 |
| Maximum EIRP (dBm): | 30.00 |
| Maximum EIRP (mW): | 1000.00 |
| General public - Power density limit (W/m ²): | 2.58 |

Power density at minimum use distance:

| | |
|------------------------------------|------|
| Power density (W/m ²): | 1.99 |
| Verdict for general public: | PASS |

The power density level for this transmission mode is below general public and controlled exposure power density limits.

Minimum compliance distance for this technology:

| | |
|---|-------|
| Minimum distance for general public (cm): | 17.58 |
| Verdict for general public: | PASS |

The minimum use distance is larger than general public and controlled exposure minimum compliance distances.

Assessment 4 - LTE Band 2

| | |
|---|--------|
| Maximum output power (dBm): | 23.0 |
| Antenna Gain (dBi): | 6.0 |
| Minimum use distance (cm): | 20 |
| Worst Case Frequency (MHz): | 1850.0 |
| Maximum EIRP (dBm): | 29.0 |
| Maximum EIRP (mW): | 794.33 |
| General public - Power density limit (W/m ²): | 4.476 |

Power density at minimum use distance:

| | |
|------------------------------------|------|
| Power density (W/m ²): | 1.58 |
| Verdict for general public: | PASS |

The power density level for this transmission mode is below general public and controlled exposure power density limits.

Minimum compliance distance for this technology:

| | |
|---|-------|
| Minimum distance for general public (cm): | 11.88 |
| Verdict for general public: | PASS |

The minimum use distance is larger than general public and controlled exposure minimum compliance distances.

Assessment 5 - LTE Band 4

| | |
|---|--------|
| Maximum output power (dBm): | 23.0 |
| Antenna Gain (dBi): | 6.0 |
| Minimum use distance (cm): | 20 |
| Worst Case Frequency (MHz): | 1710.0 |
| Maximum EIRP (dBm): | 29.0 |
| Maximum EIRP (mW): | 794.33 |
| General public - Power density limit (W/m ²): | 4.242 |

Power density at minimum use distance:

| | |
|------------------------------------|------|
| Power density (W/m ²): | 1.58 |
| Verdict for general public: | PASS |

The power density level for this transmission mode is below general public and controlled exposure power density limits.

Minimum compliance distance for this technology:

| | |
|---|-------|
| Minimum distance for general public (cm): | 12.21 |
| Verdict for general public: | PASS |

The minimum use distance is larger than general public and controlled exposure minimum compliance distances.

Assessment 6 - LTE Band 5

| | |
|---|--------|
| Maximum output power (dBm): | 23.0 |
| Antenna Gain (dBi): | 6.0 |
| Minimum use distance (cm): | 20 |
| Worst Case Frequency (MHz): | 824.0 |
| Maximum EIRP (dBm): | 29.0 |
| Maximum EIRP (mW): | 794.33 |
| General public - Power density limit (W/m ²): | 2.576 |

Power density at minimum use distance:

| | |
|------------------------------------|------|
| Power density (W/m ²): | 1.58 |
| Verdict for general public: | PASS |

The power density level for this transmission mode is below general public and controlled exposure power density limits.

Minimum compliance distance for this technology:

| | |
|---|-------|
| Minimum distance for general public (cm): | 15.67 |
| Verdict for general public: | PASS |

The minimum use distance is larger than general public and controlled exposure minimum compliance distances.

Assessment 7 - LTE Band 12

| | |
|---|--------|
| Maximum output power (dBm): | 23.0 |
| Antenna Gain (dBi): | 6.0 |
| Minimum use distance (cm): | 20 |
| Worst Case Frequency (MHz): | 699.0 |
| Maximum EIRP (dBm): | 29.0 |
| Maximum EIRP (mW): | 794.33 |
| General public - Power density limit (W/m ²): | 2.302 |

Power density at minimum use distance:

| | |
|------------------------------------|------|
| Power density (W/m ²): | 1.58 |
| Verdict for general public: | PASS |

The power density level for this transmission mode is below general public and controlled exposure power density limits.

Minimum compliance distance for this technology:

| | |
|---|-------|
| Minimum distance for general public (cm): | 16.57 |
| Verdict for general public: | PASS |

The minimum use distance is larger than general public and controlled exposure minimum compliance distances.

Assessment 8 - LTE Band 13

| | |
|---|--------|
| Maximum output power (dBm): | 23.0 |
| Antenna Gain (dBi): | 6.0 |
| Minimum use distance (cm): | 20 |
| Worst Case Frequency (MHz): | 777.0 |
| Maximum EIRP (dBm): | 29.0 |
| Maximum EIRP (mW): | 794.33 |
| General public - Power density limit (W/m ²): | 2.474 |

Power density at minimum use distance:

| | |
|------------------------------------|------|
| Power density (W/m ²): | 1.58 |
| Verdict for general public: | PASS |

The power density level for this transmission mode is below general public and controlled exposure power density limits.

Minimum compliance distance for this technology:

| | |
|---|-------|
| Minimum distance for general public (cm): | 15.98 |
| Verdict for general public: | PASS |

The minimum use distance is larger than general public and controlled exposure minimum compliance distances.

Multiple frequencies assessment

When multiple sources are introduced into an environment, it becomes necessary to address the sources interdependently, since each source will contribute some percentage of the maximum exposure toward the total exposure at a fixed location. The sum of the ratios of the exposure from each source to the corresponding maximum exposure for the frequency of each source must be evaluated.

The exposure complies with the maximum permissible exposure if the sum of the ratios is less than unity:

$$\sum_{i=1}^n \frac{S_i}{MPE_i} < 1$$

Where

S_i is the power density of each source;

MPE_i is the power density basic restriction of each source.

The device can transmit using 25K0F1D and cellular technologies at the same time, so the worst case for simultaneous transmission will be:

$$\frac{0.0015}{2.74} + \frac{1.99}{2.58} = 0.00055 + 0.771 = 0.772 < 1 \text{ Limit}$$