



# RF EXPOSURE EVALUATION

## 1. PRODUCT INFORMATION

<b>FCC ID</b>	2AKSOX02
<b>Product Description</b>	W+ Link Transmitter
<b>Model Name</b>	X02
<b>Frequency Band (Operating)</b>	<input type="checkbox"/> WLAN: 2.412GHz ~ 2.462GHz <input type="checkbox"/> WLAN: 5.18GHz ~ 5.32GHz / 5.50GHz ~ 5.70GHz <input type="checkbox"/> WLAN: 5.745GHz ~ 5825GHz <input checked="" type="checkbox"/> Others (2.4G: 2403.35-2479.35MHz)
<b>Device Category</b>	<input checked="" type="checkbox"/> Portable (<20cm separation) <input type="checkbox"/> Mobile (>20cm separation) <input type="checkbox"/> Others:
<b>Antenna Diversity</b>	<input checked="" type="checkbox"/> Single antenna <input type="checkbox"/> Multiple antennas <input type="checkbox"/> Tx diversity <input type="checkbox"/> Rx diversity <input type="checkbox"/> Tx/Rx diversity
<b>Max. Output Power</b>	<b>Antenna A0:</b> 89.90dBuV/m(Average)@3m <b>Antenna A1:</b> 89.24dBuV/m(Average)@3m <b>Antenna B0:</b> 88.96dBuV/m(Average)@3m <b>Antenna B1:</b> 90.22dBuV/m(Average)@3m
<b>Antenna Gain</b>	1.9dBi
<b>Minimum Assessment Distance</b>	5mm
<b>Evaluation Applied</b>	<input type="checkbox"/> MPE Evaluation <input checked="" type="checkbox"/> SAR Evaluation
<b>Evaluation Result</b>	Pass

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.



## 2. PORTABLE DEVICE EVALUATION METHOD AND LIMIT

Following FCC KDB 447498 D01 “General SAR test exclusion guidance” The corresponding SAR Exclusion Threshold condition, listed below:

- 1) The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:  
[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] [f(GHz)] s  
3.0 for 1-g SAR and  $\approx 7.5$  for 10-g extremity SAR, where
  - f(GHz) is the RF channel transmit frequency in GHz.
  - Power and distance are rounded to the nearest mW and mm before calculation.
  - The result is rounded to one decimal place for comparison The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion.
  
- 2) At 100 MHz to 6 GHz and for test separation distances  $> 50$  mm, the SAR test exclusion threshold is determined according to the following:
  - a) [Threshold at 50 mm in step 1) + (test separation distance - 50mm) ( f(MHz)/150)] mW, at 100MHz to 1500 MHz;
  - b) [Threshold at 50 mm in step 1) + (test separation distance - 50 mm)-10] mW at  $> 1500$  MHz and  $\leq 6$  GHz;
  
- 3) At frequencies below 100 MHz, the following may be considered for SAR test exclusion.
  - a) The threshold at the corresponding test separation distance at 100 MHz in step 2) is multiplied by  $[1 + \log(100/f(\text{MHz}))]$  for test separation distances  $> 50$  mm and  $< 200$  mm.
  - b) The threshold determined by the equation in a) for 50 mm and 100 MHz is multiplied by 1/2 for test separation distances  $\approx 50$  mm.
  - c) SAR measurement procedures are not established below 100 MHz. When SAR test exclusion cannot be applied, a KDB inquiry is required to determine SAR evaluation requirements for any test results to be acceptable.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the “Dedicated Testing/Inspection Stamp” is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by [agc01@agccert.com](mailto:agc01@agccert.com).



### 3. MOBILE DEVICE EVALUATION METHOD AND LIMIT

Human exposure to RF emissions from mobile devices (47 CFR §2.1091) may be evaluated based on the MPE limits adopted by the FCC for electric and magnetic field strength and/or power density, as appropriate, since exposures are assumed to occur at distances of 20 cm or more from persons.

#### LIMITS FOR GENERAL POPULATION / UNCONTROLLED EXPOSURE

Frequency Range (MHz)	E-field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> ,  H  <sup>2</sup> or S (Minutes)
0.3 -- 1.34	614	1.63	(100)*	30
1.34 -- 30	824/f	2.19/f	(180/f <sup>2</sup> )*	30
30 -- 300	27.5	0.073	0.2	30
300 -- 1500	--	--	f/1500	30
1500 -- 100,000	--	--	1.0	30

\*Note:

1. f= Frequency in MHz \* Plane-wave Equivalent Power Density
2. The averaging time for General Population/Uncontrolled exposure to fixed transmitters is not applicable for mobile and portable transmitters. See 47 CFR §§2.1091 and 2.1093 on source-based time-averaging requirement for mobile and portable transmitters.

$$S=PG/4\pi R^2$$

Where:

S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator R=distance to the center of radiation of the antenna

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

#### 4. MEASUREMENT RESULT

Test Mode	Channel Frequency (MHz)	Field Strength (dBuV/m@3m)	Max Output power (mW)	Calculation Value (Note 1)	Threshold Value
GFSK					
2.4G Antenna A0	2403.35	89.90	0.29	0.090	3.0
2.4G Antenna A1	2403.35	89.24	0.25	0.078	3.0
2.4G Antenna B0	2403.35	88.96	0.24	0.074	3.0
2.4G Antenna B1	2403.35	90.22	0.32	0.099	3.0

Note 1: Calculation Value = [(max. power of channel, mW)/(min. test separation distance, mm)] · [√f(GHz)].

2.4G Antenna A0: Fox example:  $0.29/5 \cdot \sqrt{2.40335} = 0.090 \leq 3.0$

2.4G Antenna A1: Fox example:  $0.25/5 \cdot \sqrt{2.40335} = 0.078 \leq 3.0$

2.4G Antenna B0: Fox example:  $0.24/5 \cdot \sqrt{2.40335} = 0.074 \leq 3.0$

2.4G Antenna B1: Fox example:  $0.32/5 \cdot \sqrt{2.40335} = 0.099 \leq 3.0$

Note 2: Max Power (dBm) = Field Strength of Fundamental (dBuV/m@3m) - 95.23

Note 3: Max Power (mW) =  $10^{(\text{Max power (dBm)}/10)}$

The 2.4G Antenna A0 and 2.4G Antenna B0 can transmit simultaneously:  $0.090/3 + 0.074/3 = 0.0547 < 1.000$

The 2.4G Antenna A0 and 2.4G Antenna B1 can transmit simultaneously:  $0.090/3 + 0.099/3 = 0.0630 < 1.000$

The 2.4G Antenna A1 and 2.4G Antenna B0 can transmit simultaneously:  $0.078/3 + 0.074/3 = 0.0507 < 1.000$

The 2.4G Antenna A1 and 2.4G Antenna B1 can transmit simultaneously:  $0.078/3 + 0.099/3 = 0.0590 < 1.000$

**According to KDB447498 D01 V06, threshold at which no SAR required is  $\leq 3.0$  for 1-g SAR, separation distance is 5mm, and no simultaneous SAR measurement is required.**

#### 5. CONCLUSION

Since Source-base time average power is below SAR test exclusion power thresholds, the SAR evaluation is not required.