

FCC ID: 2AKU5ZG18

Portable device

According to §15.247(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V06

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})]^* [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

f(GHz) is the RF channel transmit frequency in GHz;

Power and distance are rounded to the nearest mW and mm before calculation;

The result is rounded to one decimal place for comparison;

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

We use 5mm as separation distance to calculate.

Maximum measured transmitter power:

WIFI 2.4G:

Transmit Frequency (GHz)	Mode	peak conducted output power (dBm)	tune up maximum power	Result calculation	1-g SAR
2412	802.11b	8.28	9.8	2.9663	3
2437	802.11b	7.78	9	2.4800	3
2462	802.11b	8.69	9.8	2.9969	3
2412	802.11g	8.97	9.8	2.9663	3
2437	802.11g	7.76	9	2.4800	3
2462	802.11g	8.90	9.8	2.9969	3
2412	802.11n(HT20)	8.22	9.8	2.9663	3
2437	802.11n(HT20)	7.20	9	2.4800	3
2462	802.11n(HT20)	8.25	9.8	2.9969	3

Conclusion:

For the max result : $2.9969 \leq 3.0$ for 1-g SAR extremity SAR, No SAR is required.

Signature:



Date: 2023.05.04

NAME AND TITLE (Please print or type): Lisa Wang/Manager

COMPANY (Please print or type): Shenzhen EMTEK Co.,Ltd./Building 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, China