



RF EXPOSURE Test Report

Report No.: MTi211008024-11E2

Date of issue: Nov. 24, 2021

Applicant: Woan Technology (Shenzhen) Co., Ltd.

Product name: SwitchBot Pan/Tilt Cam

Model(s): W1801200, W1801201, W1801202,
W1801203, W1801204, W1801205

FCC ID: 2AKXB-W1801200

Shenzhen Microtest Co., Ltd.


<http://www.mtitest.com>

Instructions

1. The report shall not be partially reproduced without the written consent of the laboratory;
2. The test results of this report are only responsible for the samples submitted;
3. This report is invalid without the seal and signature of the laboratory;
4. This report is invalid if transferred, altered or tampered with in any form without authorization;
5. Any objection to this report shall be submitted to the laboratory within 15 days from the date of receipt of the report.




TEST RESULT CERTIFICATION	
Applicant's name	Woan Technology (Shenzhen) Co., Ltd.
Address	Room 1101, Qiancheng Commercial Center, No. 5 Haicheng Road, Mabu Community, Xixiang Sub-district, Bao'an District, Shenzhen, Guangdong, P.R.China, 518100
Manufacturer's Name	Woan Technology (Shenzhen) Co., Ltd.
Address	Room 1101, Qiancheng Commercial Center, No. 5 Haicheng Road, Mabu Community, Xixiang Sub-district, Bao'an District, Shenzhen, Guangdong, P.R.China, 518100
Factory's Name	Woan Technology (Shenzhen) Co., Ltd.
Address	Building A2, Zhengfeng Industrial Area, No.610 Fengtang Boulevard, Fuhai Sub-district, Bao'an District, Shenzhen
Product description	
Product name	SwitchBot Pan/Tilt Cam
Trademark	SwitchBot
Model Name	W1801200
Serial Model	W1801201, W1801202, W1801203, W1801204, W1801205
Standards.....	N/A
Test procedure	KDB 447498 D01 v06
Date of Test	
Date (s) of performance of tests	Oct. 30, 2021 ~ Nov. 24, 2021
Test Result.....	Pass
This device described above has been tested by Shenzhen Microtest Co., Ltd. and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.	

Testing Engineer : 

 (Danny Xu)

Technical Manager : 

 (Leon Chen)

Authorized Signatory : 

 (Tom Xue)

RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*300/f ²	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f ²	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

f = frequency in MHz * = Plane-wave equivalent power density

MPE Calculation Method

Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

P_d = Power density in mW/cm²

P_{out} = output power to antenna in mW

G = Numeric gain of the antenna relative to isotropic antenna

π = 3.1415926

R = distance between observation point and center of the radiator in cm (20cm)

P_d the limit of MPE, 1mW/cm². If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

Measurement Result

2.4GWiFi:

Operation Frequency: WIFI 802.11b/g/n HT20: 2412-2462MHz,

802.11n HT40: 2422-2452MHz,

Power density limited: 1mW/ cm²

Antenna Type: Ceramic Antenna;

WIFI antenna gain: 3.14dBi

R=20cm

$mW=10^{(dBm/10)}$

antenna gain Numeric= $10^{(dBi/10)}=10^{(3.14/10)}=2.06$

2.4GWiFi:

Channel Freq. (MHz)	modulation	conducted power	Tune-up power	Max		Antenna	Evaluation result at 20cm	Power density Limits
		(dBm)	(dBm)	tune-up power		Gain	Power density(mW/cm ²)	(mW/cm ²)
		Ant A	Ant A	(dBm)	(mW)	Numeric		
2412	802.11b	13.53	13±1	14	25.118864	2.06	0.01029	1
2437		13.52	13±1	14	25.118864	2.06	0.01029	1
2462		13.71	13±1	14	25.118864	2.06	0.01029	1
2412	802.11g	12.97	12±1	13	19.952623	2.06	0.00818	1
2437		14.60	14±1	15	31.622777	2.06	0.01296	1
2462		14.59	14±1	15	31.622777	2.06	0.01296	1
2412	802.11n H20	12.85	12±1	13	19.952623	2.06	0.00818	1
2437		14.48	14±1	15	31.622777	2.06	0.01296	1
2462		14.22	14±1	15	31.622777	2.06	0.01296	1
2422	802.11n H40	11.01	12±1	13	19.952623	2.06	0.00818	1
2437		12.14	12±1	13	19.952623	2.06	0.00818	1
2452		12.79	12±1	13	19.952623	2.06	0.00818	1

Conclusion:

For the max result: $0.01296 \leq 3.0$ for 1g SAR, No SAR is required.

----END OF REPORT----