

FCC ID: 2AKXB-W2802000

Maximum Permissible Exposure (MPE)

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f ²	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f ²	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

f = frequency in MHz * = Plane-wave equivalent power density

MPE Calculation Method

$$E \text{ (V/m)} = \frac{\sqrt{30 * P * G}}{d} \qquad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric field (V/m)

P = Average RF output power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 * P * G}{377 * D^2}$$

From the EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained.

Operation Frequency: 802.11b/g/n HT20: 2412-2462MHz

Power density limited: 1mW/ cm²

Antenna Type: FPC Antenna

Antenna gain: 2.7dBi

R=20cm

mW=10^{^(dBi/10)}

antenna gain Numeric=10^{^(dBi/10)}= 10^{^(2.7/10)}=1.86

2.4g WIFI

Antenna	Channel Freq. (MHz)	modulation	conducted power (dBm)	Tune-up power (dBm)	Max		Antenna		Evaluation result (mW/cm ²)	Power density Limits (mW/cm ²)
					tune-up power		Gain			
					(dBm)	(mW)	(dBi)	Numeric		
Ant 1	2412	802.11b	16	16±1	17	50.119	2.70	1.86	0.01857	1
Ant 1	2437		16.54	16±1	17	50.119	2.70	1.86	0.01857	1
Ant 1	2462		15.35	16±1	17	50.119	2.70	1.86	0.01857	1
Ant 1	2412	802.11g	16.59	16±1	17	50.119	2.70	1.86	0.01857	1
Ant 1	2437		16.97	16±1	17	50.119	2.70	1.86	0.01857	1
Ant 1	2456		15.17	16±1	17	50.119	2.70	1.86	0.01857	1
Ant 1	2412	802.11n H20	15.56	16±1	17	50.119	2.70	1.86	0.01857	1
Ant 1	2437		16.18	16±1	17	50.119	2.70	1.86	0.01857	1
Ant 1	2462		15.18	16±1	17	50.119	2.70	1.86	0.01857	1

Operation Frequency: 2402-2480MHz

Power density limited: 1mW/ cm²

Antenna Type: FIPA Antenna

Antenna gain: 0.36 dBi

R=20cm

mW=10^{^(dBi/10)}

antenna gain Numeric=10^{^(dBi/10)}= 10^{^(0.36/10)}=1.09

BLE

Channel Freq. (MHz)	modulation	conducted power (dBm)	Tune-up power (dBm)	Max		Antenna		Evaluation result (mW/cm ²)	Power density Limits (mW/cm ²)
				tune-up power		Gain			
				(dBm)	(mW)	(dBi)	Numeric		
2402	BLE(1M)	2.422	2±1	3	1.995	0.36	1.09	0.00043	1
2440		2.882	2±1	3	1.995	0.36	1.09	0.00043	1
2480		1.423	2±1	3	1.995	0.36	1.09	0.00043	1
2402	BLE(2M)	2.429	2±1	3	1.995	0.36	1.09	0.00043	1
2440		2.872	2±1	3	1.995	0.36	1.09	0.00043	1
2480		1.392	2±1	3	1.995	0.36	1.09	0.00043	1

Note: This product does not support simultaneous transmission.

The conclusion should be 0.01857 < 1 for Max Power Density, Compliance the RF Exposure requirement.

Signature:

Date: 2022-08-12



NAME AND TITLE (Please print or type): alex li/Manager

COMPANY (Please print or type): Shenzhen NTEK Testing Technology Co., Ltd./ 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street Bao'an District, Shenzhen P.R. China.