



CTC Laboratories, Inc.

2/F., Building 1 and 1-2/F., Building 2, Jiaquan Building, Guanlan High-Tech Park, Longhua District, Shenzhen, Guangdong, China

Tel: +86-755-27521059 Fax: +86-755-27521011 <http://www.sz-ctc.org.cn>

Maximum Permissible Exposure Evaluation

FCC ID: 2AKXB-W3902310

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) Radiation as specified in §1.1307(b).

EUT Specification

Product Name:	SwitchBot Evaporative Humidifier (Auto-refill)
Trade Mark:	SwitchBot
Model/Type Reference:	W3902310
Listed Model(s):	W3902311, W3902312, W3902313, W3902314, W3902310-RT
Model Differences:	All these models are identical in the same PCB, layout, electrical circuit and enclosure. The difference is model name.
Frequency Band (Operating)	BLE: 2402MHz ~ 2480MHz 2.4G WiFi: 2412MHz ~ 2462MHz
Device Category	<input type="checkbox"/> Portable (<5mm separation) <input type="checkbox"/> Mobile (>20cm separation) <input checked="" type="checkbox"/> Fixed (>20cm separation) <input type="checkbox"/> Others ____
Exposure Classification	<input type="checkbox"/> Occupational/Controlled exposure (S=5mW/cm ²) <input checked="" type="checkbox"/> General Population/Uncontrolled exposure (S=1mW/cm ²)
Antenna Diversity	<input checked="" type="checkbox"/> Single antenna <input type="checkbox"/> Multiple antennas <input type="checkbox"/> Tx diversity <input type="checkbox"/> Rx diversity <input type="checkbox"/> Tx/Rx diversity
Antenna Gain (Max)	4.28dBi
Evaluation Applied	<input checked="" type="checkbox"/> MPE Evaluation <input type="checkbox"/> SAR Evaluation

CTC Laboratories, Inc.

1-2/F., Building 2, Jiaquan Building, Guanlan High-Tech Park, Shenzhen, Guangdong, China
Tel.: (86)755-27521059 Fax: (86)755-27521011 [Http://www.sz-ctc.org.cn](http://www.sz-ctc.org.cn)



For anti-fake verification, please visit the official website of Certification and Accreditation Administration of the People's Republic of China : yz.cnca.cn

**Limits for Maximum Permissible Exposure (MPE)**

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)
(A) Limits for Occupational/Controlled Exposure				
300-1500	--	--	F/300	<6
1500-100000	--	--	5	<6
(B) Limits for General Population/Uncontrolled Exposure				
300-1500	--	--	F/1500	<30
1500-100000	--	--	1	<30

Calculation Method

Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where:

P_d = Power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d limit of MPE is 1mW/cm². If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

Measurement Result

Mode	Frequency (MHz)	Antenna Gain (dBi)	Maximum Power (dBm)	Tune Up Tolerance (dB)	Max. Tune Up Power (dBm)	Power Density at 20cm (mW/cm ²)	Limit (mW/cm ²)
BLE	2480	4.28	6.570	±1	7.50	0.0030	1
IEEE 802.11n(HT20)	2462	4.28	16.05	±1	17.00	0.0267	1

The WLAN and BT can transmit simultaneously.

BLE Power density at 20cm (mW/cm ²)	WLAN Power density at 20cm (mW/cm ²)	Total Power density at 20cm (mW/cm ²)	Power density Limit (mW/cm ²)
0.0030	0.0267	0.0297	1

Note:

1. Calculate in the worst-case mode.
2. Max. Tune Up Power is declared by manufacturer, and used to calculate.
3. For a more detailed features description, please refer to the RF Test Report.

*****THE END*****