

# RADIO TEST REPORT – APFWL

Type of assessment:

**MPE Calculation report**

Manufacturer:

**Alert Labs Inc.**

Hardware Version Identification Number (HVIN):

**ALRM001**

Product Marketing Name (PMN):

**Alert Labs ALRM001 Sub-1GHz Radio Module**

FCC ID:

**2AKXF-ALB080**

IC certification number:

**22365-ALB080**

Specification:

- ◆ FCC 47 CFR Part 1 Subpart I, §§1.1307, 1.1310
- ◆ FCC 47 CFR Part 2 Subpart J, §2.1091
- ◆ FCC KDB 447498 D01 General RF Exposure Guidance v06
- ◆ ISED Canada RSS-102 Issue 5 Amendment 1, (February 2021)

## **RSS-102 Annex B - Declaration of RF Exposure Compliance**

ATTESTATION: I attest that the information provided in Annex A is correct; that the Technical Brief was prepared and the information contained therein is correct; that the device evaluation was performed or supervised by me; that applicable measurement methods and evaluation methodologies have been followed; and that the device meets the SAR and/or RF field strength limits of RSS-102.

Date of issue: January 24, 2022

**Andrey Adelberg, Senior EMC/RF Specialist**

Prepared by

Signature

Nemko Canada Inc., a testing laboratory, is accredited by the Standards Council of Canada.  
The tests included in this report are within the scope of this accreditation.  
The SCC Accreditation Symbol is an official symbol of the Standards Council of Canada, used under licence.

SCC File Number: 15064 (Ottawa/Almonte); 151100 (Montreal); 151097 (Cambridge)

FCC and RSS-102 Annex C – MPE Calculation; Date: May 2021



Lab locations

---

Company name	Nemko Canada Inc.			
Facilities	<i>Ottawa site:</i> 303 River Road Ottawa, Ontario Canada K1V 1H2  Tel: +1 613 737 9680 Fax: +1 613 737 9691	<i>Montréal site:</i> 292 Labrosse Avenue Pointe-Claire, Québec Canada H9R 5L8  Tel: +1 514 694 2684 Fax: +1 514 694 3528	<i>Cambridge site:</i> 1-130 Saltsman Drive Cambridge, Ontario Canada N3E 0B2  Tel: +1 519 650 4811	<i>Almonte site:</i> 1500 Peter Robinson Road West Carleton, Ontario Canada K0A 1L0  Tel: +1 613 256-9117
	Test site identifier	<b>Organization</b>	<b>Ottawa/Almonte</b>	<b>Montreal</b>
	FCC:	CA2040	CA2041	CA0101
	ISED:	2040A-4	2040G-5	24676
Website	<a href="http://www.nemko.com">www.nemko.com</a>			

Limits of responsibility

---

Note that the results contained in this report relate only to the items tested and were obtained in the period between the date of initial receipt of samples and the date of issue of the report.

This test report has been completed in accordance with the requirements of ISO/IEC 17025. All results contained in this report are within Nemko Canada's ISO/IEC 17025 accreditation.

Copyright notification

---

Nemko Canada Inc. authorizes the applicant to reproduce this report provided it is reproduced in its entirety and for use by the company's employees only. Any use which a third party makes of this report, or any reliance on or decisions to be made based on it, are the responsibility of such third parties.

Nemko Canada Inc. accepts no responsibility for damages, if any, suffered by any third party as a result of decisions made or actions based on this report.

© Nemko Canada Inc.



## Table of Contents

<b>Table of Contents</b> .....	<b>3</b>
<b>Section 1 Evaluation summary</b> .....	<b>4</b>
1.1 MPE calculation for standalone transmission .....	4

## Section 1 Evaluation summary

### 1.1 MPE calculation for standalone transmission

#### 1.1.1 References, definitions and limits

##### FCC §2.1091(d)

- (2) (2) For operations within the frequency range of 300 kHz and 6 GHz (inclusive), the limits for maximum permissible exposure (MPE), derived from whole-body SAR limits and listed in Table 1 in paragraph (e)(1) of this section, may be used instead of whole-body SAR limits as set forth in paragraphs (a) through (c) of this section to evaluate the environmental impact of human exposure to RF radiation as specified in §1.1307(b) of this part, except for portable devices as defined in §2.1093 of this chapter as these evaluations shall be performed according to the SAR provisions in §2.1093.

**Table 1.1-1: Table 1 to §1.1310(e)(1)—Limits for Maximum Permissible Exposure (MPE)**

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
<b>(i) Limits for Occupational/Controlled Exposure</b>				
0.3–3.0	614	1.63	*(100)	≤6
3.0–30	1842 / f	4.89 / f	*(900 / f <sup>2</sup> )	<6
30–300	61.4	0.163	1.0	<6
300–1500			f / 300	<6
1500–100000			5	<6
<b>(ii) Limits for General Population/Uncontrolled Exposure</b>				
0.3–1.34	614	1.63	*(100)	<30
1.34–30	824 / f	2.19 / f	*(180 / f <sup>2</sup> )	<30
30–300	27.5	0.073	0.2	<30
300–1500			f / 1500	<30
1500–100000			1.0	<30

Notes: f = frequency in MHz. \* = Plane-wave equivalent power density.

##### RSS-102, Section 2.5.2

RF exposure evaluation is required if the separation distance between the user and/or bystander and the device's radiating element is greater than 20 cm, except when the device operates as follows:

- below 20 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 1 W (adjusted for tune-up tolerance);
- at or above 20 MHz and below 48 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than  $4.49/f^{0.5}$  W (adjusted for tune-up tolerance), where f is in MHz;
- at or above 48 MHz and below 300 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 0.6 W (adjusted for tune-up tolerance);
- at or above 300 MHz and below 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than  $0.0131 f^{0.6834}$  W (adjusted for tune-up tolerance), where f is in MHz;
- at or above 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 5 W (adjusted for tune-up tolerance).

In these cases, the information contained in the RF exposure technical brief may be limited to information that demonstrates how the e.i.r.p. was derived.

References, definitions and limits, continued

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = \frac{PG}{4\pi R^2}$$

where: S = power density (mW/cm<sup>2</sup> or W/m<sup>2</sup>)  
P = power input to the antenna (mW or W)  
G = power gain of the antenna in the direction of interest relative to an isotropic radiator  
R = distance to the center of radiation of the antenna (cm or m)

1.1.2 EUT technical information

Prediction frequency	903 MHz
Antenna gain	0.01 dBi
Number of antennas	1
Maximum transmitter conducted power	17.7 dBm
Prediction distance	20 cm

1.1.3 MPE calculation

Fundamental transmit (prediction) frequency:	<u>903</u> MHz	
Maximum measured conducted peak output power:	<u>17.7</u> dBm	
Cable and/or jumper loss:	<u>0</u> dB	
Maximum peak power at antenna input terminal:	<u>17.7</u> dBm	
Tx On time:	<u>1.000</u> ms	
Tx period time:	<u>1.000</u> ms	
Average factor:	<u>100</u> %	
Maximum calculated average power at antenna input terminal:	<u>58.88436554</u> mW	
Single Antenna gain (typical):	<u>0.01</u> dBi	
Number of antennae:	<u>1</u>	
Total system gain:	<u>0.01</u> dBi	
	<b>FCC limit:</b>	<b>ISED limit:</b>
<b>MPE limit for uncontrolled exposure at prediction frequency:</b>	<u>0.602000</u> mW/cm <sup>2</sup>	<u>0.274191</u> mW/cm <sup>2</sup>
	<u>6.020000</u> W/m <sup>2</sup>	<u>2.741906</u> W/m <sup>2</sup>
Minimum calculated prediction distance for compliance:	<u>20</u> cm	<u>20</u> cm
Typical (declared) distance:	<u>20</u> cm	<u>20</u> cm
<b>Average power density at prediction frequency:</b>	<u>0.011742</u> mW/cm <sup>2</sup>	<u>0.011742</u> mW/cm <sup>2</sup>
	<u>0.117417</u> W/m <sup>2</sup>	<u>0.117417</u> W/m <sup>2</sup>
<b>Margin of Compliance:</b>	<u>17.10</u> dB	<u>13.68</u> dB
Maximum allowable antenna gain:	<u>17.11</u> dBi	<u>13.69</u> dBi

1.1.4 Verdict

The calculation is below the limit; therefore, the product is passing the RF Exposure requirements for the declared distance.

1.1.5 RSS-102, Annex A - RF technical brief cover sheet

IC Certification Number	22365-ALB080
Product marketing name (PMN)	Alert Labs ALRM001 Sub-1GHz Radio Module
Hardware version identification number (HVIN)	ALRM001
Firmware version identification number (FVIN)	N/A
Host marketing name (HMN)	N/A
Applicant company number	22365
Applicant name	Alert Labs Inc.
SAR/RF exposure test laboratory	2040A-4 (3 m semi anechoic chamber)
Type of evaluation	<input type="checkbox"/> SAR Evaluation: Device Used in the Vicinity of the Human Head <input type="checkbox"/> SAR Evaluation: Body-Worn Device and Body-Supported Device <input type="checkbox"/> SAR Evaluation: Limb-Worn Device <input type="checkbox"/> RF Exposure Evaluation <input type="checkbox"/> Nerve Stimulation Exposure Evaluation (SPR-002)
SAR evaluation	Multiple transmitters: <input type="checkbox"/> Yes <input type="checkbox"/> No
	Evaluated against exposure limits: <input type="checkbox"/> General Public Use <input type="checkbox"/> Controlled Use
	Duty cycle used in evaluation: N/A %
	Separation distance: N/A mm
	Standard used for evaluation: N/A
	SAR value: N/A W/kg <input type="checkbox"/> Measured <input type="checkbox"/> Computed <input type="checkbox"/> Calculated
Nerve Stimulation Evaluation (SPR-002)	Evaluated against exposure limits: <input type="checkbox"/> General Public Use <input type="checkbox"/> Controlled Use
	Measurement distance: N/A m
	Field Strength: N/A <input type="checkbox"/> V/m (electric) <input type="checkbox"/> A/m (magnetic) <input type="checkbox"/> Measured <input type="checkbox"/> Computed <input type="checkbox"/> Calculated
	Exposure condition: <input type="checkbox"/> Whole body/Torso/Head <input type="checkbox"/> Leg <input type="checkbox"/> Arm <input type="checkbox"/> Hand/Foot
RF exposure evaluation	Evaluated against exposure limits: <input type="checkbox"/> General Public Use <input type="checkbox"/> Controlled Use
	Duty cycle used in evaluation: <b>100</b> %
	Operational frequency: <b>903</b> MHz
	Standard used for evaluation: <b>Safety Code 6</b>
	Measurement distance: <b>0.2</b> m
	RF value: <b>0.12</b> <input checked="" type="checkbox"/> W/m <sup>2</sup> <input type="checkbox"/> V/m <input type="checkbox"/> A/m <input type="checkbox"/> Measured <input type="checkbox"/> Computed <input type="checkbox"/> Calculated

**End of the test report**