







No.: BCTC/RF-EMC-007 Page: 62 of 80 / / Edition: A.5










No.: BCTC/RF-EMC-007 Page: 64 of 80 / / / Edition: A.5




Report No.:BCTC2212037380E





Report No.:BCTC2212037380E







13. Number Of Hopping Frequency

13.1 Block Diagram Of Test Setup



13.2 Limit

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.

13.3 Test procedure


- 1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
- 2. Set the spectrum analyzer: RBW = 100kHz. VBW = 300kHz. Sweep = auto; Detector Function = Peak. Trace = Max hold.
- 3. Allow the trace to stabilize. It may prove necessary to break the span up to sections. in order to clearly show all of the hopping frequencies. The limit is specified in one of the subparagraphs of this Section.
- 4. Set the spectrum analyzer: Start Frequency = 2.4GHz, Stop Frequency = 2.4835GHz. Sweep=auto;


13.4 Test Result

Condition	Mode	Hopping Number	Limit	Verdict
NVNT	1-DH1	79	15	Pass
NVNT	2-DH1	79	15	Pass
NVNT	3-DH1	79	15	Pass

No.: BCTC/RF-EMC-007 Page: 67 of 80 / / / Edition: A.5











Report No.:BCTC2212037380E





No.: BCTC/RF-EMC-007 Page: 69 of 80 / / / / Edition: A.5



14. Dwell Time

14.1 Block Diagram Of Test Setup

EUT	SPECTRUM		
	ANALYZER		

14.2 Limit

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

14.3 Test procedure

- 1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
- 2. Set spectrum analyzer span = 0. Centred on a hopping channel;
- 3. Set RBW = 1MHz and VBW = 3MHz.Sweep = as necessary to capture the entire dwell time per hopping channel. Set the EUT for DH5, DH3 and DH1 packet transmitting.
- 4. Use the marker-delta function to determine the dwell time. If this value varies with different modes of operation (e.g., data rate, modulation format, etc.), repeat this test for each variation. The limit is specified in one of the subparagraphs of this Section. Submit this plot(s).

14.4 Test Result

DH5 Packet permit maximum 1600 / 79 / 6 hops per second in each channel (5 time slots RX, 1 time slot TX).

DH3 Packet permit maximum 1600 / 79 / 4 hops per second in each channel (3 time slots RX, 1 time slot TX).

DH1 Packet permit maximum 1600 / 79 /2 hops per second in each channel (1 time slot RX, 1 time slot TX). So, the Dwell Time can be calculated as follows:

DH5:1600/79/6*0.4*79*(MkrDelta)/1000 DH3:1600/79/4*0.4*79*(MkrDelta)/1000 DH1:1600/79/2*0.4*79*(MkrDelta)/1000 Remark: Mkr Delta is once pulse time.

No.: BCTC/RF-EMC-007

Page: 70 of 80 / / Edition: A.5


,TC

OPF







Condition	Mode	Frequency (MHz)	Pulse Time (ms)	Total Dwell Time (ms)	Limit (ms)	Verdict
NVNT	1-DH1	2441	0.409	129.244	400	Pass
NVNT	1-DH3	2441	1.661	269.082	400	Pass
NVNT	1-DH5	2441	2.909	331.626	400	Pass
NVNT	2-DH1	2441	0.414	131.238	400	Pass
NVNT	2-DH3	2441	1.666	261.562	400	Pass
NVNT	2-DH5	2441	2.917	320.870	400	Pass
NVNT	3-DH1	2441	0.419	133.661	400	Pass
NVNT	3-DH3	2441	1.670	273.880	400	Pass
NVNT	3-DH5	2441	2.920	318.280	400	Pass



No.: BCTC/RF-EMC-007 Page: 71 of 80 / / Edition: A.5









No.: BCTC/RF-EMC-007 Page: 72 of 80 / / Edition: A.5









No.: BCTC/RF-EMC-007 Page: 73 of 80 / / Edition: A.5









No.: BCTC/RF-EMC-007 Page: 74 of 80 / / / Edition: A.5







No.: BCTC/RF-EMC-007 Page: 75 of 80 / / / Edition: A.5




15. Antenna Requirement

15.1 Limit

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

15.2 Test Result

The EUT antenna is PCB antenna, fulfill the requirement of this section.



No.: BCTC/RF-EMC-007




16. EUT Photographs

EUT Photo



NOTE: Appendix-Photographs Of EUT Constructional Details



No.: BCTC/RF-EMC-007 Page: 77 of 80 / / / Edition: A.




17. EUT Test Setup Photographs

Conducted emissions



Radiated Measurement Photos



No.: BCTC/RF-EMC-007 Page: 78 of 80 / / / Edițion: A.5


ES

)VE









No.: BCTC/RF-EMC-007

Page: 79 of 80

Edition: A.5





STATEMENT

1. The equipment lists are traceable to the national reference standards.

2. The test report can not be partially copied unless prior written approval is issued from our

lab.

3. The test report is invalid without the "special seal for inspection and testing".

4. The test report is invalid without the signature of the approver.

5. The test process and test result is only related to the Unit Under Test.

6. Sample information is provided by the client and the laboratory is not responsible for its

authenticity.

7. The test report without CMA mark is only used for scientific research, teaching, enterprise

product development and internal quality control purposes.

8. The quality system of our laboratory is in accordance with ISO/IEC17025.

9. If there is any objection to this test report, the client should inform issuing laboratory

within 15 days from the date of receiving test report.

Address:

1-2/F., Building B, Pengzhou Industrial Park, No.158, Fuyuan 1st Road, Zhancheng, Fuhai

Subdistrict, Bao'an District, Shenzhen, Guangdong, China

TEL: 400-788-9558

P.C.: 518103

FAX: 0755-33229357

Website: http://www.chnbctc.com

E-Mail: bctc@bctc-lab.com.cn

**** END ****

No.: BCTC/RF-EMC-007 Page: 80 of 80 / / / Edition: A.5