



MEASUREMENT REPORT LTE Band 8

Applicant Name:
Council Rock Enterprises LLC
11 Centre Park
Rochester, NY 14614
United States


Date of Testing:
04/2 – 08/10/2021
Test Site/Location:
PCTEST Lab. Columbia, MD, USA
Test Report Serial No.:
1M2108110092-03.2AL52

FCC ID:	2AL52E15008B
Applicant:	Council Rock Enterprises LLC

Application Type: Class II Permissive Change
Model: TELiG E1500-L8W
Additional Model(s): TELiG E1500-LW
EUT Type: Cellular Module
FCC Classification: PCS Licensed Transmitter (PCB)
FCC Rule Part(s): Part 27 Subpart P
Test Procedure(s): ANSI C63.26-2015, KDB 971168 D01 v03r01, ANSI C63.10-2013
Class II Permissive Change: Integrating and co-locating module into host TELiG E1500 product
Original Grant Date: 04/27/2021

This equipment has been evaluated against the requirements in the technical service rules presented in Part 27 Subpart P. Test results reported herein relate only to the item(s) tested.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.



Randy Ortanez
President



FCC ID: 2AL52E15008B	 <small>Proud to be part of  element</small>	MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)	Approved by: Technical Manager
Test Report S/N: 1M2108110092-03.2AL52	Test Dates: 04/2 – 08/10/2021	EUT Type: Cellular Module Integrated Into TELiG Device	Page 1 of 21

TABLE OF CONTENTS

1.0	INTRODUCTION	3
1.1	Scope	3
1.2	PCTEST Test Location.....	3
1.3	Test Facility / Accreditations.....	3
2.0	PRODUCT INFORMATION.....	4
2.1	Equipment Description	4
2.2	Device Capabilities.....	4
2.3	Test Configuration	4
2.4	EMI Suppression Device(s)/Modifications	4
2.5	Software and Firmware	4
3.0	DESCRIPTION OF TESTS	5
3.1	Evaluation Procedure	5
3.2	Radiated Spurious Emissions	5
4.0	MEASUREMENT UNCERTAINTY	6
5.0	TEST EQUIPMENT CALIBRATION DATA	7
6.0	SAMPLE CALCULATIONS	8
7.0	TEST RESULTS	9
7.1	Summary	9
7.2	Transmitter Conducted Output Power	10
7.3	Radiated Spurious Emissions Measurements.....	12
8.0	CONCLUSION.....	21

FCC ID: 2AL52E15008B	 <small>Proud to be part of  element</small>	MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)	Approved by: Technical Manager
Test Report S/N: 1M2108110092-03.2AL52	Test Dates: 04/2 – 08/10/2021	EUT Type: Cellular Module Integrated Into TELiG Device	Page 2 of 21

1.0 INTRODUCTION

1.1 Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Innovation, Science and Economic Development Canada.

1.2 PCTEST Test Location

These measurement tests were conducted at the PCTEST Engineering Laboratory, facility located at 7185 Oakland Mills Road, Columbia, MD 21046. The measurement facility is compliant with the test site requirements specified in ANSI C63.4-2014.

1.3 Test Facility / Accreditations

Measurements were performed at PCTEST Engineering Lab located in Columbia, MD 21046, U.S.A.

- PCTEST is an ISO 17025-2017 accredited test facility under the American Association for Laboratory Accreditation (A2LA) with Certificate number 2041.01 for Specific Absorption Rate (SAR), Hearing Aid Compatibility (HAC) testing, where applicable, and Electromagnetic Compatibility (EMC) testing for FCC and Innovation, Science, and Economic Development Canada rules.
- PCTEST TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC 17065-2012 by A2LA (Certificate number 2041.03) in all scopes of FCC Rules and ISED Standards (RSS).
- PCTEST facility is a registered (2451B) test laboratory with the site description on file with ISED.

FCC ID: 2AL52E15008B	 <small>Proud to be part of element</small>	MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)	Approved by: Technical Manager
Test Report S/N: 1M2108110092-03.2AL52	Test Dates: 04/2 – 08/10/2021	EUT Type: Cellular Module Integrated Into TELiG Device	Page 3 of 21

2.0 PRODUCT INFORMATION

2.1 Equipment Description

The Equipment Under Test (EUT) is the **Council Rock Enterprises LLC LTE Cellular Module FCC ID: 2AL52E15008B**. This host device includes modules integrated and co-located as shown below in the table. The device operates under the provisions of Part 27, WLAN (DTS), and UNII transmitter.

Model	Module 1	Module 2	Module 3
TELiG E1500-L8W	TK4WLE900VX	2AL52E15008B	N7NEM75S
TELiG E1500-LW		TK4WLE900VX	N7NEM75S

Table 2-1. EUT and supported modules

Test Device Serial No.: 812012

2.2 Device Capabilities

This device contains the following capabilities:

Multi-band LTE Band 2/25, 4, 5, 8, 12, 13, 802.11b WLAN, 802.11a UNII(5GHz)

The EUT was tested with 2 modules being radiated transmitting and 1 module conducted transmitting. Module 1 (WLE900VX) is always radiated transmitting either at 2.4GHz or 5GHz. Band 8 on module 2 (MC7455) is always radiated transmitting and module 3 (EM7511) is always conducted transmitting. The combinations of test cases were tested with Band 8 (MC7455) with low, mid, and high bands (EM7511), and WIFI transmissions (2.4GHz or 5GHz) were tested for compliance.

2.3 Test Configuration

The EUT was tested per the guidance of ANSI C63.26-2015 and KDB 971168 D01 v03r01. See Section 3.0 of this test report for a description of the radiated and antenna port conducted emissions tests.

2.4 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and no modifications were made during testing.

2.5 Software and Firmware

The test was conducted with software/firmware version L0.0.00.00.05.08 installed on the EUT.

FCC ID: 2AL52E15008B	 PCTEST [®] Proud to be part of element	MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)	Approved by: Technical Manager
Test Report S/N: 1M2108110092-03.2AL52	Test Dates: 04/2 – 08/10/2021	EUT Type: Cellular Module Integrated Into TELiG Device	Page 4 of 21

3.0 DESCRIPTION OF TESTS

3.1 Evaluation Procedure

This device was evaluated for compliance to the radiated spurious emissions requirements in the various FCC rule parts governing operation of the supported transmitters and in KDB 996369 for module integrations.

3.2 Radiated Spurious Emissions

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. The test site inside the chamber is a 6m x 5.2m elliptical, obstruction-free area in accordance with Figure 5.7 of Clause 5 in ANSI C63.4-2014. Absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections for measurements above 1GHz. For measurements below 1GHz, the absorbers are removed. A raised turntable is used for radiated measurement. The turn table is a continuously rotatable, remote-controlled, metallic turntable and 2 meters (6.56 ft.) in diameter. The turn table is flush with the raised floor of the chamber in order to maintain its function as a ground plane. An 80cm tall test table made of Styrodur is placed on top of the turn table. A Styrodur pedestal is placed on top of the test table to bring the total table height to 1.5m.

The equipment under test was transmitting while connected to an external DC power adapter and is placed on a turntable 3 meters from the receive antenna. The receive antenna height is adjusted between 1 and 4 meter height, the turntable is rotated through 360 degrees, and the EUT is manipulated through all orthogonal planes representative of its typical use to achieve the highest reading on the receive spectrum analyzer.

For radiated spurious emissions measurements, field strength method is used per the guidance of ANSI C63.26-2015. Radiated emissions were measured from the EUT and the field strength was calculated to the ERP or EIRP value with their corresponding limits. At least six of the highest data points were measured and reported.

For radiated spurious emissions measurements and calculations, conversion method is used per the formulas in KDB 971168 Section 5.8.4. Field Strength (EIRP) is calculated using the following formulas:

$$E_{[dB\mu V/m]} = \text{Measured amplitude level}_{[dBm]} + 107 + \text{Cable Loss}_{[dB]} + \text{Antenna Factor}_{[dB/m]}$$

And

$$\text{EIRP}_{[dBm]} = E_{[dB\mu V/m]} + 20\log D - 104.8; \text{ where } D \text{ is the measurement distance in meters.}$$

All radiated measurements are performed in a chamber that meets the site requirements per ANSI C63.4-2014. Additionally, radiated emissions below 30MHz are also validated on an Open Area Test Site to assert correlation with the chamber measurements per the requirements of KDB 414788 D01.

Radiated spurious emission levels are investigated with the receive antenna horizontally and vertically polarized per ANSI C63.26-2015.

FCC ID: 2AL52E15008B		MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)	Approved by: Technical Manager
Test Report S/N: 1M2108110092-03.2AL52	Test Dates: 04/2 – 08/10/2021	EUT Type: Cellular Module Integrated Into TELiG Device	Page 5 of 21

4.0 MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.4-2014. All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95% level of confidence. The measurement uncertainty shown below meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Contribution	Expanded Uncertainty (\pm dB)
Conducted Bench Top Measurements	1.13
Radiated Disturbance (<1GHz)	4.98
Radiated Disturbance (>1GHz)	5.07
Radiated Disturbance (>18GHz)	5.09

FCC ID: 2AL52E15008B	 <small>Proud to be part of element</small>	MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)	Approved by: Technical Manager
Test Report S/N: 1M2108110092-03.2AL52	Test Dates: 04/2 – 08/10/2021	EUT Type: Cellular Module Integrated Into TELiG Device	Page 6 of 21

5.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST). Measurements antennas used during testing were calibrated in accordance to the requirements of ANSI C63.5-2017.

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
-	AP2	EMC Cable and Switch System	3/4/2021	Annual	3/4/2022	AP2
-	ETS	EMC Cable and Switch System	3/4/2021	Annual	3/4/2022	ETS
-	LTx2	Licensed Transmitter Cable Set	3/12/2021	Annual	3/12/2022	LTx2
Agilent	N9030A	50GHz PXA Signal Analyzer	1/20/2021	Annual	1/20/2022	US51350301
Anritsu	MT8821C	Radio Communication Analyzer	4/30/2021	Annual	4/30/2022	6201524620
Emco	3115	Horn Antenna (1-18GHz)	6/18/2020	Biennial	6/18/2022	9704-5182
Rohde & Schwarz	CMW500	Radio Communication Tester	11/5/2020	Annual	11/5/2021	112347
Rohde & Schwarz	ESU40	EMI Test Receiver (40GHz)	9/9/2020	Annual	9/9/2021	100348
Rohde & Schwarz	ESW44	EMI Test Receiver 2Hz to 44 GHz	1/21/2021	Annual	1/21/2022	101716

Table 5-1. Summary of Test Results

Notes:

1. For equipment listed above that has a calibration date or calibration due date that falls within the test date range, care was taken to ensure that this equipment was used after the calibration date and before the calibration due date.
2. Equipment with a calibration date of "N/A" shown in this list was not used to make direct calibrated measurements.

FCC ID: 2AL52E15008B		MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)	Approved by: Technical Manager
Test Report S/N: 1M2108110092-03.2AL52	Test Dates: 04/2 – 08/10/2021	EUT Type: Cellular Module Integrated Into TELiG Device	Page 7 of 21

6.0 SAMPLE CALCULATIONS

Emission Designator

QPSK Modulation

Emission Designator = 8M62G7D

- LTE BW = 8.62 MHz
- G = Phase Modulation
- 7 = Quantized/Digital Info
- D = Data transmission, telemetry, telecommand

QAM Modulation

Emission Designator = 8M45W7D

- LTE BW = 8.45 MHz
- W = Amplitude/Angle Modulated
- 7 = Quantized/Digital Info
- D = Data transmission, telemetry, telecommand

Spurious Radiated Emission – LTE Band

Example: Middle Channel LTE Mode 2nd Harmonic (1564 MHz)

The average spectrum analyzer reading at 3 meters with the EUT on the turntable was -81.0 dBm. The gain of the substituted antenna is 8.1 dBi. The signal generator connected to the substituted antenna terminals is adjusted to produce a reading of -81.0 dBm on the spectrum analyzer. The loss of the cable between the signal generator and the terminals of the substituted antenna is 2.0 dB at 1564 MHz. So 6.1 dB is added to the signal generator reading of -30.9 dBm yielding -24.80 dBm. The fundamental EIRP was 25.501 dBm so this harmonic was 25.501 dBm $- (-24.80)$.

FCC ID: 2AL52E15008B	 <small>Proud to be part of element</small>	MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)	Approved by: Technical Manager
Test Report S/N: 1M2108110092-03.2AL52	Test Dates: 04/2 – 08/10/2021	EUT Type: Cellular Module Integrated Into TELiG Device	Page 8 of 21

7.0 TEST RESULTS

7.1 Summary

Company Name: Council Rock Enterprises LLC
 FCC ID: 2AL52E15008B
 Mode(s): Multi-band LTE, 2.4/5GHz WiFi

Test Condition	Test Description	FCC Part Section(s)	Test Limit	Test Result	Report Reference
CONDUCTED (Licensed)	Transmitter Conducted Output Power	2.1046	N/A	PASS	Section 7.2
CONDUCTED (DTS)	Transmitter Output Power	15.247(B)(3)	< 1 Watt	PASS	Section 7.2
CONDUCTED (UNII)	Maximum Conducted Output Power	15.407 (a.1.iv), (a.2), (a.3)	Maximum conducted powers must meet the limits detailed in 15.407 (a)	PASS	Section 7.2
Radiated	Radiated Spurious Emissions	2.1051, 27.1509(a)	Attenuation > 43 + 10 log ₁₀ (P[Watts]) for all out-of-band emissions	PASS	Section 7.3

Table 7-1. Summary of Test Results

Notes:

- 1) All modes of operation and data rates were investigated. The test results shown in the following sections represent the worst case emissions.
- 2) The analyzer plots shown in Section 7.0 were taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables, directional couplers, and attenuators used as part of the system to maintain a link between the call box and the EUT at all frequencies of interest.
- 3) All antenna port conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the spectrum analyzer through calibrated cables, attenuators, and couplers.
- 4) All conducted emissions measurements are performed with automated test software to capture the corresponding plots necessary to show compliance. The measurement software utilized is LTE Automation Version 5.3
- 5) All harmonics are evaluated to the limits that govern their operation while intermod products are assessed to the least stringent limit per FCC guidance

FCC ID: 2AL52E15008B	 PCTEST <small>Proud to be part of element</small>	MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)	Approved by: Technical Manager
Test Report S/N: 1M2108110092-03.2AL52	Test Dates: 04/2 – 08/10/2021	EUT Type: Cellular Module Integrated Into TELiG Device	Page 9 of 21

7.2 Transmitter Conducted Output Power

Test Overview

The transmitter conducted output power is a measure of the total average power contained within 1.4MHz and 3MHz channels as defined in §27.1506. All modes of operation were investigated and the worst-case configuration results are reported in this section.

Test Procedure Used

ANSI C63.26-2015 – Section 5.2.4.2

Test Settings

All conducted powers were measured using the R&S CMW500's Channel Measurement function.

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



Figure 7-1. Test Instrument & Measurement Setup

Test Notes

None

FCC ID: 2AL52E15008B		MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)	Approved by: Technical Manager
Test Report S/N: 1M2108110092-03.2AL52	Test Dates: 04/2 – 08/10/2021	EUT Type: Cellular Module Integrated Into TELiG Device	Page 10 of 21

LTE Band 8 3MHz Bandwidth			
Modulation	Number of RB	RB Offset	Mid Channel
			21640 (899.0 MHz)
			Conducted Power [dBm]
QPSK	2	0	23.08
	2	7	23.18
	2	13	22.90
	15	0	22.01
16 QAM	2	0	22.28
	5	0	19.56
	5	1	20.04

Table 7-2. Transmitter Conducted Output Power Measurements of 2AL52E15008B - (3 MHz)

2.4GHZ	2.4GHz Conducted Power [dBm]				
	Freq [MHz]	Channel	IEEE Transmission Mode		
			802.11b		
			Average	Target	
		2437	6	21.53	22.1

Table 7-3. Transmitter Conducted Output Power Measurements of TK4WLE900VX (DTS) – CH0

5GHz (20MHz Bandwidth)	5GHz (20MHz) Conducted Power [dBm]				
	Freq [MHz]	Channel	IEEE Transmission Mode		
			802.11a		
			Average	Target	
		5240	48	19.30	20.4

Table 7-4. Transmitter Conducted Output Power Measurements of TK4WLE900VX (UNII) – CH0

FCC ID: 2AL52E15008B	 PCTEST Proud to be part of  element	MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)	Approved by: Technical Manager
Test Report S/N: 1M2108110092-03.2AL52	Test Dates: 04/2 – 08/10/2021	EUT Type: Cellular Module Integrated Into TELiG Device	Page 11 of 21

7.3 Radiated Spurious Emissions Measurements

Test Overview

Radiated spurious emissions measurements are performed using the direct field strength conversion method described in ANSI C63.26-2015 with the EUT connected to their corresponding antenna ports. Module 1 was connected with Linx antenna for radiated transmission. Modules 2 was connected with shark fin antenna for radiated transmission and module 3 was connected with SMA cable for conducted transmissions. The combinations of test cases were tested with Band 8 (module 2) with low, mid, and high bands (from module 3 where applicable), and WIFI transmissions (2.4GHz or 5GHz) were tested for compliance. Measurements on signals operating below 1GHz are performed using horizontally and vertically polarized tuned dipole antennas. Measurements on signals operating above 1GHz are performed using vertically and horizontally polarized broadband horn antennas. All measurements are performed as peak measurements while the EUT is operating at maximum power, and at the appropriate frequencies.

Test Procedures Used

KDB 971168 D01 v03r01 – Section 7

ANSI C63.26-2015 – Section 5.5.4

Test Settings

1. RBW = 100kHz for emissions below 1GHz and 1MHz for emissions above 1GHz
2. VBW $\geq 3 \times$ RBW
3. Span = 1.5 times the OBW
4. No. of sweep points $\geq 2 \times$ span / RBW
5. Detector = RMS
6. Trace mode = Average (Max Hold for pulsed emissions)
7. The trace was allowed to stabilize

FCC ID: 2AL52E15008B	 <small>Proud to be part of element</small>	MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)	Approved by: Technical Manager
Test Report S/N: 1M2108110092-03.2AL52	Test Dates: 04/2 – 08/10/2021	EUT Type: Cellular Module Integrated Into TELiG Device	Page 12 of 21

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.





Figure 7-2. Test Instrument & Measurement Setup

Test Notes

- 1) Field strengths are calculated using the Measurement quantity conversions in KDB 971168 Section 5.8.4.
 - b) $E(\text{dB}\mu\text{V}/\text{m}) = \text{Measured amplitude level (dBm)} + 107 + \text{Cable Loss (dB)} + \text{Antenna Factor (dB/m)}$
 - d) $\text{EIRP (dBm)} = E(\text{dB}\mu\text{V}/\text{m}) + 20\log D - 104.8$; where D is the measurement distance in meters.
- 2) The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case emissions are reported with the EUT positioning, modulations, RB sizes and offsets, and channel bandwidth configurations shown in the tables below.
- 3) The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case setup is reported in the tables below.
- 4) The spectrum is measured from 9kHz to the 10th harmonic of the fundamental frequency of the transmitter. The worst-case emissions are reported.
- 5) Emissions below 18GHz were measured at a 3 meter test distance while emissions above 18GHz were measured at a 1 meter test distance with the application of a distance correction factor.
- 6) The "-" shown in the following RSE tables are used to denote a noise floor measurement.

FCC ID: 2AL52E15008B	 PCTEST [®] Proud to be part of element	MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)	Approved by: Technical Manager
Test Report S/N: 1M2108110092-03.2AL52	Test Dates: 04/2 – 08/10/2021	EUT Type: Cellular Module Integrated Into TELiG Device	Page 13 of 21




Plot 7-1. Radiated Spurious Plot (LTE Band 8 / LTE Band 5 / 2.4GHz)

Case:	B8 (Rad)_B5 (Cond) _2.4GHz
Bandwidth (MHz):	3/10/20
Frequency (MHz):	899/836.5/2437
RB / Offset:	2/7 & 1/25
Mode:	Multi-Band LTE and WIFI RSE
Detector / Trace Mode:	RMS / Max Hold
RBW / VBW:	1MHz / 3MHz

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
1538.00	H	165.00	310.00	-47.40	0.21	59.81	-35.45	-13.00	-22.45
1798.10	H	320.00	265.00	-51.75	-6.76	48.49	-46.77	-13.00	-33.77
1475.50	H	353.00	58.00	-69.62	0.50	37.88	-57.38	-13.00	-44.38
2572.00	V	147.00	137.00	-80.24	4.60	31.36	-63.90	-13.00	-50.90
3975.00	V	293.00	116.00	-72.28	8.09	42.81	-52.45	-13.00	-39.45
4110.00	H	230.00	264.00	-73.41	8.35	41.94	-53.32	-13.00	-40.32

Table 7-5. Radiated Spurious Data (LTE Band 8 / LTE Band 5 / 2.4GHz)

FCC ID: 2AL52E15008B		MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)	Approved by: Technical Manager
Test Report S/N: 1M2108110092-03.2AL52	Test Dates: 04/2 – 08/10/2021	EUT Type: Cellular Module Integrated Into TELiG Device	Page 14 of 21




Plot 7-2. Radiated Spurious Plot (LTE Band 8 / LTE Band 2 / 2.4GHz)

Case:	B8 (Rad)_B2 (Cond) _2.4GHz
Bandwidth (MHz):	3/10/20
Frequency (MHz):	899/1880/2437
RB / Offset:	2/7 & 1/25
Mode:	Multi-Band LTE and WIFI RSE
Detector / Trace Mode:	RMS / Max Hold
RBW / VBW:	1MHz / 3MHz

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turtable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
1538.00	V	127.00	61.00	-43.94	0.21	63.27	-31.99	-13.00	-18.99
1962.00	V	114.00	2.00	-66.41	4.46	45.05	-50.21	-13.00	-37.21
4741.00	H	114.00	320.00	-66.43	9.16	49.73	-45.53	-13.00	-32.53
5431.00	V	133.00	28.00	-68.17	10.90	49.73	-45.53	-13.00	-32.53
5855.00	H	133.00	314.00	-68.03	11.66	50.63	-44.63	-13.00	-31.63
6539.00	V	281.00	8.00	-64.14	13.41	56.27	-38.98	-13.00	-25.98

Table 7-6. Radiated Spurious Data (LTE Band 8 / LTE Band 2 / 2.4GHz)

FCC ID: 2AL52E15008B		MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)	Approved by: Technical Manager
Test Report S/N: 1M2108110092-03.2AL52	Test Dates: 04/2 – 08/10/2021	EUT Type: Cellular Module Integrated Into TELiG Device	Page 15 of 21




Plot 7-3. Radiated Spurious Plot (LTE Band 8 / LTE Band 7 / 2.4GHz)

Case:	B8 (Rad)_B7(Cond)_2.4GHz
Bandwidth (MHz):	3/10/20
Frequency (MHz):	899/2535/2437
RB / Offset:	2/7 & 1/25
Mode:	Multi-Band LTE and WIFI RSE
Detector / Trace Mode:	RMS / Max Hold
RBW / VBW:	1MHz / 3MHz


Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
1440.00	H	144.00	3.00	-65.72	-0.72	40.56	-54.70	-13.00	-41.70
3336.00	H	153.00	203.00	-66.75	4.38	44.63	-50.63	-13.00	-37.63
4776.00	V	142.00	219.00	-59.03	7.45	55.42	-39.84	-13.00	-26.84
4972.00	V	121.00	42.00	-64.42	6.98	49.56	-45.70	-13.00	-32.70
5394.00	V	351.00	197.00	-72.02	7.96	42.94	-52.32	-13.00	-39.32
5969.00	V	154.00	38.00	-62.09	9.98	54.89	-40.37	-13.00	-27.37

Table 7-7. Radiated Spurious Data (LTE Band 8 / LTE Band 7 / 2.4GHz)

FCC ID: 2AL52E15008B	 PCTEST Proud to be part of 	MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)	Approved by: Technical Manager
Test Report S/N: 1M2108110092-03.2AL52	Test Dates: 04/2 – 08/10/2021	EUT Type: Cellular Module Integrated Into TELiG Device	Page 16 of 21



Plot 7-4. Radiated Spurious Plot (LTE Band 8 / LTE Band 12 / 5GHz)




Plot 7-5. Radiated Spurious Plot (LTE Band 8 / LTE Band 12 / 5GHz)

Case:	B8 (Rad)_B12 (Cond)_5GHz
Bandwidth (MHz):	3/10/20
Frequency (MHz):	899/707.5/5240
RB / Offset:	2/7 & 2/24
Mode:	Multi-Band LTE and WIFI RSE
Detector / Trace Mode:	RMS / Max Hold
RBW / VBW:	1MHz / 3MHz


Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
1798.00	V	111.00	243.00	-64.62	0.75	43.13	-52.13	-13.00	-39.13
2001.16	V	294.00	293.00	-65.91	2.51	43.60	-51.65	-13.00	-38.65
2268.10	V	207.00	129.00	-67.46	2.20	41.74	-53.52	-13.00	-40.52
2414.60	V	101.00	307.00	-65.90	3.43	44.53	-50.73	-13.00	-37.73
3500.00	V	294.00	268.00	-60.74	4.81	51.07	-44.18	-13.00	-31.18
4341.00	H	157.00	293.00	-39.81	5.04	72.23	-23.02	-13.00	-10.02
6131.80	H	103.00	287.00	-59.47	17.76	65.29	-29.97	-13.00	-16.97

Table 7-8. Radiated Spurious Data (LTE Band 8 / LTE Band 12 / 5GHz)

FCC ID: 2AL52E15008B		MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)	Approved by: Technical Manager
Test Report S/N: 1M2108110092-03.2AL52	Test Dates: 04/2 – 08/10/2021	EUT Type: Cellular Module Integrated Into TELiG Device	Page 17 of 21



Plot 7-6. Radiated Spurious Plot (LTE Band 8 / LTE Band 4 / 5GHz)




Plot 7-7. Radiated Spurious Plot (LTE Band 8 / LTE Band 4 / 5GHz)

Case:	B8 (Rad)_B4 (Cond)_5GHz
Bandwidth (MHz):	3/20/20
Frequency (MHz):	899/1732.5/5240
RB / Offset:	2/7 & 2/24
Mode:	Multi-Band LTE and WIFI RSE
Detector / Trace Mode:	RMS / Max Hold
RBW / VBW:	1MHz / 3MHz


Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
2500.00	V	147.00	299.00	-61.82	5.97	51.15	-44.11	-13.00	-31.11
3500.00	V	192.00	293.00	-60.58	7.22	53.64	-41.61	-13.00	-28.61
3541.50	V	165.00	351.00	-67.41	7.17	46.76	-48.50	-13.00	-35.50
4341.00	H	210.00	343.00	-44.77	9.18	71.41	-23.85	-13.00	-10.85
6131.80	V	165.00	150.00	-67.33	21.68	61.35	-33.91	-13.00	-20.91
10000.00	V	101.00	334.00	-67.23	20.59	60.36	-34.89	-13.00	-21.89

Table 7-9. Radiated Spurious Data (LTE Band 8 / LTE Band 4 / 5GHz)


FCC ID: 2AL52E15008B		MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)	Approved by: Technical Manager
Test Report S/N: 1M2108110092-03.2AL52	Test Dates: 04/2 – 08/10/2021	EUT Type: Cellular Module Integrated Into TELiG Device	Page 18 of 21



Plot 7-8. Radiated Spurious Plot (LTE Band 8 / LTE Band 41 / 5GHz)




Plot 7-9. Radiated Spurious Plot (LTE Band 8 / LTE Band 41 / 5GHz)



Plot 7-10. Radiated Spurious Plot (LTE Band 8 / LTE Band 41 / 5GHz)

FCC ID: 2AL52E15008B		MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)	Approved by: Technical Manager
Test Report S/N: 1M2108110092-03.2AL52	Test Dates: 04/2 – 08/10/2021	EUT Type: Cellular Module Integrated Into TELiG Device	Page 19 of 21



Plot 7-11. Radiated Spurious Plot (LTE Band 8 / LTE Band 41 / 5GHz)

Case:	B8 (Rad)_B41(Cond)_5GHz
Bandwidth (MHz):	3/20/20
Frequency (MHz):	899/2593/5240
RB / Offset:	2/7 & 2/49
Mode:	Multi-Band LTE and WIFI RSE
Detector / Trace Mode:	RMS / Max Hold
RBW / VBW:	1MHz / 3MHz

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
1798.00	H	135.00	83.00	-59.55	2.85	50.30	-44.96	-13.00	-31.96
3500.00	H	194.00	291.00	-60.73	7.22	53.49	-41.76	-13.00	-28.76
3596.00	H	225.00	96.00	-64.76	7.60	49.84	-45.42	-13.00	-32.42
4341.00	H	171.00	72.00	-36.31	9.18	79.87	-15.39	-13.00	-2.39
4495.00	H	210.00	60.00	-61.53	9.27	54.74	-40.52	-13.00	-27.52
6131.80	H	163.00	107.00	-55.68	21.68	73.00	-22.26	-13.00	-9.26
6293.80	H	136.00	95.00	-68.57	13.39	51.82	-43.44	-13.00	-30.44
7000.24	V	304.00	288.00	-65.27	15.77	57.50	-37.76	-13.00	-24.76
10000.00	V	102.00	336.00	-67.48	20.59	60.11	-35.14	-13.00	-22.14

Table 7-10. Radiated Spurious Data (LTE Band 8 / LTE Band 41 / 5GHz)

FCC ID: 2AL52E15008B		MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)	Approved by: Technical Manager
Test Report S/N: 1M2108110092-03.2AL52	Test Dates: 04/2 – 08/10/2021	EUT Type: Cellular Module Integrated Into TELiG Device	Page 20 of 21

8.0 CONCLUSION

The data collected relate only to the item(s) tested and show that the **Council Rock Enterprises LLC LTE Cellular Module FCC ID: 2AL52E15008B** complies with all requirements specified in FCC Part 27 of the FCC Rules for LTE Operation.

FCC ID: 2AL52E15008B	 <small>Proud to be part of element</small>	MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)	Approved by: Technical Manager
Test Report S/N: 1M2108110092-03.2AL52	Test Dates: 04/2 – 08/10/2021	EUT Type: Cellular Module Integrated Into TELiG Device	Page 21 of 21