



MPE Report

Applicant : Emplus Technologies, Inc
Product Type : 4x4 AX Dual-band AP
Trade Name : emplus
Model Number : WAP380-C
Applicable Standard : IEEE Std.C95.1
47 CFR § 2.1091 / 47 CFR § 1.1310
Received Date : Feb. 08, 2021
Test Period : Feb. 20, 2021
Issue Date : Mar. 12, 2021

Issued by

Approved By : Kris Pan
(Kris Pan)

A Test Lab Techno Corp.
No. 140-1, Changan Street, Bade District,
Taoyuan City 33465, Taiwan (R.O.C.)
Tel : +886-3-2710188 / Fax : +886-3-2710190



Taiwan Accreditation Foundation accreditation number: 1330
Test Firm MRA designation number: TW0010

Note:

- 1.The test results are valid only for samples provided by customers and under the test conditions described in this report.
- 2.This report shall not be reproduced except in full, without the written approval of A Test Lab Technology Corporation.
- 3.The relevant information is provided by customers in this test report. According to the correctness, appropriateness or completeness of the information provided by the customer, if there is any doubt or error in the information which affects the validity of the test results, the laboratory does not take the responsibility.



Revision History

Rev.	Issued Date	Revisions	Revised By
00	Mar. 12, 2021	Initial Issue	Nicole Chu



Contents

- 1. Reference Applicable Standard 4
- 2. Description of Equipment under Test (EUT) 5
- 3. Human Exposure Assessment..... 7
- 4. Power Density Limit – RF Exposure Evaluation 8
- 4.1 Conducted Power 9
- 5. Test Result 14



1. Reference Applicable Standard

Standard	Description	Version
ANSI/IEEE C95.1	American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 300 KHz to 100 GHz, New York.	1992
47 CFR Part §2.1091	Radiofrequency radiation exposure evaluation: mobile devices.	-
47 CFR Part §1.1310	Radiofrequency radiation exposure limits.	-

2. Description of Equipment under Test (EUT)

Applicant	Emplus Technologies, Inc Bld B, 10F, No.209 Nangang Rd., Taipei City, Taiwan		
Manufacturer	Emplus Technologies., Inc. 10F., Building B, No.209, Sec. 1, Nangang Rd., Nangang Dist., Taipei City 115, Taiwan (R.O.C.)		
Product Type	4x4 AX Dual-band AP		
Trade Name	emplus		
Model Number	WAP380-C		
FCC ID	2AL6XWAP380-C1		
Frequency Range	Operate Band	Frequency Range (MHz)	
	IEEE 802.11b / 802.11g	2412 - 2462	
	IEEE 802.11n 2.4 GHz 20 MHz(256-QAM) IEEE 802.11ax 2.4 GHz 20 MHz	2412 - 2462	
	IEEE 802.11n 2.4 GHz 40 MHz (256-QAM) IEEE 802.11ax 2.4 GHz 40 MHz	2422 - 2452	
	IEEE 802.11a U-NII Band I	5180 - 5240	
	IEEE 802.11a U-NII Band III	5745 - 5825	
	IEEE 802.11ac 5 GHz 20 MHz U-NII Band I IEEE 802.11ax 20 MHz U-NII Band I	5180 - 5240	
	IEEE 802.11ac 5 GHz 20 MHz U-NII Band III IEEE 802.11ax 20 MHz U-NII Band III	5745 - 5825	
	IEEE 802.11ac 5 GHz 40 MHz U-NII Band I IEEE 802.11ax 40 MHz U-NII Band I	5190 - 5230	
	IEEE 802.11ac 5 GHz 40 MHz U-NII Band III IEEE 802.11ax 40 MHz U-NII Band III	5755 - 5795	
	IEEE 802.11ac 80 MHz IEEE 802.11ax 80 MHz	5210	
		5775	
Antenna Information	Model	Type	Max. Gain (dBi)
	5718A0514300	PIFA Antenna	2412 - 2472 3.70
	5718A0515300	PIFA Antenna	2412 - 2472 4.08
	5718A0516300	PIFA Antenna	2412 - 2472 4.12
	5718A0517300	PIFA Antenna	2412 - 2472 5.01
	GANT		4.25
	Directional		10.26



Antenna Information	Model	Type	Max. Gain (dBi)	
	5718A0518300	PIFA Antenna	5150~5250	5.13
			5725~5850	5.19
	5718A0522300	PIFA Antenna	5150~5250	4.26
			5725~5850	3.81
	5718A0520300	PIFA Antenna	5150~5250	4.03
			5725~5850	4.56
	5718A0521300	PIFA Antenna	5150~5250	5.04
			5725~5850	5.04
	G _{ANT}		5150~5250	4.64
			5725~5850	4.68
	Directional		5150~5250	10.65
			5725~5850	10.69
Antenna Delivery	IEEE 802.11b: 4TX / 4RX (CDD)			
	IEEE 802.11g : 4TX / 4RX (CDD)			
	IEEE 802.11n 2.4 GHz 20 MHz / 40 MHz: 4TX / 4RX (STBC / Beamforming on)			
	IEEE 802.11ax 2.4 GHz 20 MHz / 40 MHz: 4TX / 4RX (STBC / Beamforming on)			
	IEEE 802.11a: 4TX / 4RX(CDD)			
	IEEE 802.11ac 20 MHz / 40 MHz / 80 MHz: 4TX / 4RX (STBC / Beamforming on)			
	IEEE 802.11ax 20 MHz / 40 MHz / 80 MHz: 4TX / 4RX (STBC / Beamforming on)			
RF Evaluation	0.419 mW/cm ²			
Operate Temp. Range	0 ~ +40°C			

The above equipment was tested by A Test Lab Techno Corp. For compliance with the requirements set forth in 47 CFR § 2.1091 / 47 CFR § 1.1310. The results of testing in this report apply only to the product/system, which was tested. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

Data re-use Description :

In accordance with KDB 484596 D01 c) Spot-check test data shall be based on Max. Output Power and Transmitter Radiated Emissions in the original FCC ID filing, should remain within the tune-up tolerance range specified for the product, and should be compliant with applicable rule part(s), After evaluation above, data re-use is applicable.

Original FCC ID: 2AL6XWAP380-C



3. *Human Exposure Assessment*

Due to the design and installation of this product, it is not possible to conduct SAR evaluation. This is because client either manufactures or supplies the antenna(s) that will be used in the installation of this product. Therefore, this product will be evaluated as a mobile device per 47 CFR § 1.1310 titled "Radiofrequency radiation exposure limits", generally referred to as MPE limits.

In 47 CFR § 2.1091, paragraph (b) defines a mobile device as "a transmitting device designed to be used in other than fixed locations and to generally be used in such a way that a separation distance of at least 20 cm is normally maintained between the transmitter's radiating structure(s) and the body of the user or nearby persons. " This product is intended to be installed into a vehicle such that the unit is physically secured at one location. In the installation guide supplied with the product,

Client has made the following statement: "IMPORTANT: To meet the FCC's RF Exposure Guidelines, the antenna should be installed so there is at least 20 cm of separation between the body of the user and nearby persons and the antenna". Based on the installation of the transceiver and the antenna, the transmitters radiating structure is more than 20 cm from the user. Thus, this product is a "mobile device" as defined in section § 2.1091 paragraph (b).

Exposure evaluation

$$S_{eirp} = \frac{EIRP}{4\pi d^2} = \frac{PG}{4\pi d^2} (W / m^2)$$

Where

S: is the input power (W);

G: is the antenna gain;

d : is the distance between antennas and evaluation point (m).



4. Power Density Limit – RF Exposure Evaluation

Thv In 47 CFR § 1.1310, use of the device as based upon the user's awareness and ability to exercise control over human exposure. The two categories defined are Occupational / Controlled Exposure and General Population / Uncontrolled. These two categories are defined as follow:

Limits for General Population / Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824 / f	2.19 / f	(180 / f ²)*	30
30-300	27.5	0.073	0.2	30
300-1500	-	-	F / 1,500	30
1,500-100,000	-	-	1.0	30
Limits for Occupational / Controlled Exposure				
Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1,842 / f	4.89 / f	(900 / f ²)*	6
30-300	61.4	0.163	1.0	6
300-1,500	-	-	F / 300	6
1,500-100,000	-	-	5	6

4.1 Conducted Power

Beamforming on										
Band	Date Rate or Sub-test	CH	Frequency (MHz)			ANT-0	ANT-1	ANT-2	ANT-3	All ANT
						Average Conducted power				
						dBm	dBm	dBm	dBm	dBm
802.11n_HT20 (256-QAM)	26M	1	2412			10.18	10.26	10.19	10.15	16.22
		6	2437			12.69	12.30	12.24	12.37	18.42
		11	2462			9.85	9.76	9.67	9.65	15.75
802.11n_HT40 (256-QAM)	54M	3	2422			10.05	9.87	9.83	9.95	15.95
		6	2437			10.69	10.62	10.50	10.55	16.61
		9	2452			8.69	8.56	8.75	8.62	14.68
Band	Date Rate or Sub-test	CH	Frequency (MHz)	RU	RU Number	ANT-0	ANT-1	ANT-2	ANT-3	All ANT
						Average Conducted power				
						dBm	dBm	dBm	dBm	dBm
802.11ax_HE20	MCS0	1	2412	242	1	9.87	9.83	9.70	9.75	15.81
		6	2437	242	1	12.72	12.39	12.32	12.61	18.53
		11	2462	242	1	7.76	7.79	7.77	7.81	13.80
802.11ax_HE40	MCS0	3	2422	484	1	9.01	8.93	8.81	8.98	14.95
		6	2437	484	1	9.76	9.61	9.73	9.70	15.72
		9	2452	484	1	7.68	7.63	7.71	7.77	13.72



Beamforming off

Band	Date Rate or Sub-test	CH	Frequency (MHz)			ANT-0	ANT-1	ANT-2	ANT-3	All ANT
						Average Conducted power				
						dBm	dBm	dBm	dBm	dBm
802.11b	1M	1	2412			19.22	19.61	19.26	19.32	25.38
		6	2437			19.52	19.11	19.19	19.22	25.28
		11	2462			19.61	19.65	19.42	19.51	25.57
802.11g	6M	1	2412			15.82	16.01	15.87	15.84	21.91
		6	2437			18.82	18.52	18.69	18.62	24.68
		11	2462			16.22	16.21	15.92	16.13	22.14
802.11n_HT20	26M	1	2412			16.29	16.57	16.33	16.16	22.36
		6	2437			18.67	18.26	18.38	18.43	24.46
		11	2462			16.09	15.92	15.89	15.88	21.97
802.11n_HT40	54M	3	2422			15.94	15.79	15.89	15.93	21.91
		6	2437			17.00	16.61	16.78	16.78	22.82
		9	2452			15.14	14.83	14.97	14.86	20.97
802.11n_HT20 (256-QAM)	26M	1	2412			16.58	16.78	16.56	16.45	22.61
		6	2437			18.81	18.69	18.61	18.55	24.69
		11	2462			16.22	16.14	16.05	16.00	22.12
802.11n_HT40 (256-QAM)	54M	3	2422			16.25	16.47	16.32	16.30	22.36
		6	2437			17.14	16.92	17.11	17.08	23.08
		9	2452			15.23	14.84	15.01	14.98	21.04
Band	Date Rate or Sub-test	CH	Frequency (MHz)	RU	RU Number	ANT-0	ANT-1	ANT-2	ANT-3	All ANT
						Average Conducted power				
						dBm	dBm	dBm	dBm	dBm
802.11ax_HE20	MCS0	1	2412	242	1	16.09	16.32	16.05	16.25	22.20
		6	2437	242	1	18.85	18.59	18.67	18.71	24.73
		11	2462	242	1	14.32	14.21	14.12	14.23	20.24
802.11ax_HE40	MCS0	3	2422	484	1	15.58	15.35	15.23	15.47	21.43
		6	2437	484	1	16.26	16.18	16.12	16.15	22.20
		9	2452	484	1	14.37	14.21	14.14	14.22	20.26

Beamforming on

Band	Date Rate or Sub-test	CH	Frequency (MHz)			ANT-0	ANT-1	ANT-2	ANT-3	All ANT
						Average Conducted power				
						dBm	dBm	dBm	dBm	dBm
802.11n_5G_HT20	26M	36	5180			11.71	11.83	11.95	11.78	17.84
		40	5200			12.75	12.51	12.37	12.64	18.59
		44	5220			12.74	12.34	12.37	12.67	18.55
		48	5240			12.81	12.33	12.37	12.48	18.52
		149	5745			12.26	11.85	12.47	12.57	18.32
		153	5765			12.09	12.01	12.43	12.31	18.23
		157	5785			12.13	12.13	12.67	12.47	18.38
		161	5805			12.19	12.08	12.59	12.24	18.30
		165	5825			12.60	12.41	12.92	12.50	18.63
802.11n_5G_HT40	54M	38	5190			9.97	9.80	10.11	10.15	16.03
		46	5230			12.92	12.57	12.56	12.62	18.69
		151	5755			12.46	12.08	12.95	12.79	18.60
		159	5795			12.69	12.55	13.07	13.05	18.87
802.11ac_VHT20	26M	36	5180			11.73	11.97	12.06	11.83	17.92
		40	5200			12.87	12.57	12.50	12.76	18.70
		44	5220			12.83	12.36	12.46	12.68	18.61
		48	5240			12.84	12.39	12.44	12.53	18.57
		149	5745			12.29	11.98	12.60	12.64	18.41
		153	5765			12.22	12.11	12.56	12.40	18.35
		157	5785			12.22	12.22	12.71	12.54	18.45
		161	5805			12.30	12.15	12.60	12.38	18.38
802.11ac_VHT40	54M	38	5190			10.10	9.92	10.20	10.18	16.12
		46	5230			13.02	12.66	12.66	12.75	18.80
		151	5755			12.52	12.21	12.96	12.91	18.68
		159	5795			12.76	12.65	13.18	13.12	18.95
802.11ac_VHT80	117.2M	42	5210			10.04	9.42	9.74	9.72	15.76
		155	5775			12.53	12.36	12.98	12.98	18.74
Band	Date Rate or Sub-test	CH	Frequency (MHz)	RU	RU Number	ANT-0	ANT-1	ANT-2	ANT-3	All ANT
						Average Conducted power				
						dBm	dBm	dBm	dBm	dBm
802.11ax_HE20	MCS 0	36	5180	242	1	11.63	11.63	11.59	11.80	17.68
		40	5200	242	1	13.09	12.72	12.70	12.93	18.88
		44	5220	242	1	12.95	12.61	12.60	12.66	18.73
		48	5240	242	1	12.97	12.75	12.52	12.69	18.76
		149	5745	242	1	12.26	12.08	12.78	12.65	18.47
		153	5765	242	1	12.35	12.34	12.75	12.62	18.54
		157	5785	242	1	12.43	12.41	13.04	12.90	18.72
		161	5805	242	1	12.33	12.42	12.87	12.82	18.64
		165	5825	242	1	12.82	12.63	12.77	12.85	18.79
802.11ax_HE40	MCS 0	38	5190	484	1	10.26	10.18	10.22	10.35	16.27
		46	5230	484	1	13.22	12.94	12.98	12.78	19.00
		151	5755	484	1	12.72	12.32	12.98	13.08	18.81
		159	5795	484	1	12.90	12.66	13.08	13.22	18.99
802.11ax_HE80	MCS 0	42	5210	968	1	9.61	9.47	9.39	9.69	15.56
		155	5775	968	1	12.68	12.65	13.07	12.98	18.87



Beamforming off

Band	Data Rate or Sub-test	CH	Frequency (MHz)	ANT-0	ANT-1	ANT-2	ANT-3	All ANT
				Average Conducted power				
				dBm	dBm	dBm	dBm	dBm
802.11a	6M	36	5180	16.44	16.51	16.45	16.61	22.52
		40	5200	16.42	16.32	16.37	16.56	22.44
		44	5220	16.32	16.28	16.32	16.52	22.38
		48	5240	16.31	16.22	16.41	16.48	22.38
		149	5745	18.93	18.51	18.68	18.94	24.79
		153	5765	18.71	18.61	18.64	19.01	24.77
		157	5785	18.92	18.87	19.07	19.35	25.08
		161	5805	18.88	18.65	19.01	19.31	24.99
		165	5825	18.93	18.81	19.11	19.07	25.00
802.11n_5G_HT20	26M	36	5180	17.98	18.24	18.26	18.30	24.22
		40	5200	19.21	18.81	18.77	18.87	24.94
		44	5220	19.00	18.50	18.77	18.90	24.82
		48	5240	19.06	18.38	18.69	18.85	24.77
		149	5745	18.49	18.27	18.72	18.75	24.58
		153	5765	18.53	18.45	18.75	18.76	24.65
		157	5785	18.57	18.49	18.87	18.79	24.70
		161	5805	18.66	18.56	18.88	18.83	24.76
		165	5825	19.05	18.64	19.19	18.82	24.95
802.11n_5G_HT40	54M	38	5190	16.45	16.22	16.59	16.61	22.49
		46	5230	19.33	18.57	19.07	19.02	25.03
		151	5755	18.67	18.44	19.05	19.24	24.88
		159	5795	19.03	18.85	19.37	19.41	25.19
802.11ac_VHT20	26M	36	5180	18.12	18.29	18.28	18.32	24.27
		40	5200	19.25	18.85	18.86	19.01	25.02
		44	5220	19.11	18.58	18.78	18.94	24.88
		48	5240	19.07	18.63	18.81	18.91	24.88
		149	5745	18.51	18.31	18.83	18.88	24.66
		153	5765	18.64	18.51	18.84	18.84	24.73
		157	5785	18.71	18.62	18.94	18.91	24.82
		161	5805	18.69	18.59	18.91	18.88	24.79
		165	5825	19.07	18.77	19.27	18.94	25.04
802.11ac_VHT40	54M	38	5190	16.58	16.33	16.61	16.67	22.57
		46	5230	19.44	18.71	19.11	19.02	25.10
		151	5755	18.81	18.51	19.18	19.29	24.98
		159	5795	19.12	18.92	19.41	19.44	25.25
802.11ac_VHT80	117.2M	42	5210	16.41	15.82	16.15	16.14	22.16
		155	5775	18.92	18.79	19.21	19.28	25.08



Beamforming off

Band	Data Rate or Sub-test	CH	Frequency (MHz)	RU	RU Number	ANT-0	ANT-1	ANT-2	ANT-3	All ANT
						Average Conducted power				
802.11ax_HE20	MCS 0	36	5180	242	1	18.05	17.97	17.92	18.14	24.04
		40	5200	242	1	19.52	18.96	19.01	19.21	25.20
		44	5220	242	1	19.42	18.67	18.94	19.15	25.07
		48	5240	242	1	19.37	18.81	18.96	19.14	25.10
		149	5745	242	1	18.73	18.52	18.86	18.97	24.79
		153	5765	242	1	18.75	18.69	19.11	19.11	24.94
		157	5785	242	1	18.84	18.74	19.31	19.29	25.07
		161	5805	242	1	18.82	18.71	19.24	19.21	25.02
802.11ax_HE40	MCS 0	165	5825	242	1	19.12	18.92	19.22	19.31	25.17
		38	5190	484	1	16.78	16.43	16.85	16.64	22.70
		46	5230	484	1	19.61	19.22	19.45	19.22	25.40
		151	5755	484	1	18.94	18.71	19.41	19.32	25.12
802.11ax_HE80	MCS 0	159	5795	484	1	19.22	18.96	19.52	19.49	25.32
		42	5210	968	1	16.09	15.73	15.88	15.97	21.94
		155	5775	968	1	19.01	18.92	19.35	19.37	25.19



5. Test Result

Antenna	Band	Frequency (MHz)	Limit (mw)/cm ²	Distance	Tune-up Power	ANT Gain	Numeric Gain	Duty Cycle	Power with Duty cycle	Power Density
				(cm)	(dBm)				(mW)	(mw)/cm ²
				[R]	[P]				[P]x[G]	[S]
Wi-Fi Antenna	2.4GHz	2412-2462	1.0	20	26.00	4.25	2.66	1	1058.97	0.211
	5GHz	5150-5250	1.0	20	25.50	4.64	2.91	1	1032.51	0.205
		5725-5850	1.0	20	25.50	4.68	2.94	1	1043.15	0.208
Wi-Fi Antenna (Beamforming)	2.4GHz	2412-2462	1.0	20	19.00	10.26	10.62	1	843.58	0.168
	5GHz	5150-5250	1.0	20	19.00	10.65	11.61	1	922.22	0.183
		5725-5850	1.0	20	19.00	10.69	11.72	1	930.95	0.185

Note:

1. Mobile or fixed location transmitters, minimum separation distance is 20 cm, even if calculations indicate MPE distance is less.
2. We used the maximum power and gain to provide MPE results.
3. The Numeric Gain calculated by $10^{(\text{ant. Gain(dBi)} / 10)}$.
4. The MPE results are evaluated by lowest data rate for WLAN.

Simultaneous Transmitting :

$$\text{Total MPE} = 2.4\text{GHz MPE} + 5\text{GHz MPE} = 0.211 + 0.208 = 0.419 \text{ (mw)/cm}^2 < 1 \text{ (mw)/cm}^2$$

---END---