


MPE Report

Applicant : Emplus Technologies, Inc
Product Type : 4x4 AX Dual-band AP
Trade Name : emplus
Model Number : WAP380
Applicable Standard : IEEE Std.C95.1
47 CFR § 2.1091 / 47 CFR § 1.1310
Received Date : May 13, 2020
Test Period : Jun. 20 ~ Jul. 10, 2020
Issue Date : Aug. 19, 2020

Issued by

Approved By : 
(Kris Pan)

A Test Lab Techno Corp.
No. 140-1, Changan Street, Bade District,
Taoyuan City 33465, Taiwan (R.O.C.)
Tel : +886-3-2710188 / Fax : +886-3-2710190



Taiwan Accreditation Foundation accreditation number: 1330
Test Firm MRA designation number: TW0010

Note:

- 1.The test results are valid only for samples provided by customers and under the test conditions described in this report.
- 2.This report shall not be reproduced except in full, without the written approval of A Test Lab Technology Corporation.
- 3.The relevant information is provided by customers in this test report. According to the correctness, appropriateness or completeness of the information provided by the customer, if there is any doubt or error in the information which affects the validity of the test results, the laboratory does not take the responsibility.



Revision History

Rev.	Issued Date	Revisions	Revised By
00	Jul. 27, 2020	Initial Issue	Nicole Chu
01	Aug. 19, 2020	P01&05 Revised Model number	Nicole Chu



Contents

1.	Reference Applicable Standard	4
2.	Description of Equipment under Test (EUT)	5
3.	Human Exposure Assessment.....	7
4.	Power Density Limit – RF Exposure Evaluation	8
4.1	Conducted Power	9
5.	Test Result	14



1. *Reference Applicable Standard*

Standard	Description	Version
ANSI/IEEE C95.1	American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 300 KHz to 100 GHz, New York.	1992
47 CFR Part §2.1091	Radiofrequency radiation exposure evaluation: mobile devices.	-
47 CFR Part §1.1310	Radiofrequency radiation exposure limits.	-

2. Description of Equipment under Test (EUT)

Applicant	Emplus Technologies, Inc Bld B, 10F, No.209 Nangang Rd., Taipei City, Taiwan	
Manufacturer	Emplus Technologies., Inc. 10F., Building B, No.209, Sec. 1, Nangang Rd., Nangang Dist., Taipei City 115, Taiwan (R.O.C.)	
Product Type	4x4 AX Dual-band AP	
Trade Name	emplus	
Model Number	WAP380	
FCC ID	2AL6XWAP380	
Frequency Range	Operate Band	Frequency Range (MHz)
	IEEE 802.11b / 802.11g	2412 - 2462
	IEEE 802.11n 2.4 GHz 20 MHz(256-QAM) IEEE 802.11ax 2.4 GHz 20 MHz	2412 - 2462
	IEEE 802.11n 2.4 GHz 40 MHz (256-QAM) IEEE 802.11ax 2.4 GHz 40 MHz	2422 - 2452
	IEEE 802.11a U-NII Band I	5180 - 5240
	IEEE 802.11a U-NII Band III	5745 - 5825
	IEEE 802.11ac 5 GHz 20 MHz U-NII Band I IEEE 802.11ax 20 MHz U-NII Band I	5180 - 5240
	IEEE 802.11ac 5 GHz 20 MHz U-NII Band III IEEE 802.11ax 20 MHz U-NII Band III	5745 - 5825
	IEEE 802.11ac 5 GHz 40 MHz U-NII Band I IEEE 802.11ax 40 MHz U-NII Band I	5190 - 5230
	IEEE 802.11ac 5 GHz 40 MHz U-NII Band III IEEE 802.11ax 40 MHz U-NII Band III	5755 - 5795
	IEEE 802.11ac 80 MHz IEEE 802.11ax 80 MHz	5210 5775
	Bluetooth LE	2402 - 2480



	Model	Type	Max. Gain (dBi)		
	Antenna Information	5718A0524300	PIFA Antenna	2402 - 2480	5.90
5718A0514300		PIFA Antenna	2412 - 2472	3.70	
5718A0515300		PIFA Antenna	2412 - 2472	4.08	
5718A0516300		PIFA Antenna	2412 - 2472	4.12	
5718A0517300		PIFA Antenna	2412 - 2472	5.01	
G _{ANT}				4.25	
Directional				10.26	
5718A0518300		PIFA Antenna	5150~5250	5.13	
			5725~5850	5.19	
5718A0522300		PIFA Antenna	5150~5250	4.26	
			5725~5850	3.81	
5718A0520300		PIFA Antenna	5150~5250	4.03	
			5725~5850	4.56	
5718A0521300		PIFA Antenna	5150~5250	5.04	
			5725~5850	5.04	
G _{ANT}		5150~5250	4.64		
		5725~5850	4.68		
Directional		5150~5250	10.65		
		5725~5850	10.69		
Antenna Delivery		IEEE 802.11b: 1TX / 1RX (Diversity) IEEE 802.11g : 4TX / 4RX (CDD) IEEE 802.11n 2.4 GHz 20 MHz / 40 MHz: 4TX / 4RX (STBC / Beamforming on) IEEE 802.11ax 2.4 GHz 20 MHz / 40 MHz: 4TX / 4RX (STBC / Beamforming on) IEEE 802.11a: 4TX / 4RX(CDD) IEEE 802.11ac 20 MHz / 40 MHz / 80 MHz: 4TX / 4RX (STBC / Beamforming on) IEEE 802.11ax 20 MHz / 40 MHz / 80 MHz: 4TX / 4RX (STBC / Beamforming on)			
RF Evaluation	0.443 mW/cm ²				
Operate Temp. Range	0 ~ +40°C				

The above equipment was tested by A Test Lab Techno Corp. For compliance with the requirements set forth in 47 CFR § 2.1091 / 47 CFR § 1.1310. The results of testing in this report apply only to the product/system, which was tested. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

3. Human Exposure Assessment

Due to the design and installation of this product, it is not possible to conduct SAR evaluation. This is because client either manufactures or supplies the antenna(s) that will be used in the installation of this product. Therefore, this product will be evaluated as a mobile device per 47 CFR § 1.1310 titled "Radiofrequency radiation exposure limits", generally referred to as MPE limits.

In 47 CFR § 2.1091, paragraph (b) defines a mobile device as "a transmitting device designed to be used in other than fixed locations and to generally be used in such a way that a separation distance of at least 20 cm is normally maintained between the transmitter's radiating structure(s) and the body of the user or nearby persons." This product is intended to be installed into a vehicle such that the unit is physically secured at one location. In the installation guide supplied with the product,

Client has made the following statement: "IMPORTANT: To meet the FCC's RF Exposure Guidelines, the antenna should be installed so there is at least 20 cm of separation between the body of the user and nearby persons and the antenna". Based on the installation of the transceiver and the antenna, the transmitters radiating structure is more than 20 cm from the user. Thus, this product is a "mobile device" as defined in section § 2.1091 paragraph (b).

Exposure evaluation

$$S_{eirp} = \frac{EIRP}{4\pi d^2} = \frac{PG}{4\pi d^2} (W / m^2)$$

Where

S: is the input power (W);

G: is the antenna gain;

d : is the distance between antennas and evaluation point (m).



4. Power Density Limit – RF Exposure Evaluation

Thv In 47 CFR § 1.1310, use of the device as based upon the user's awareness and ability to exercise control over human exposure. The two categories defined are Occupational / Controlled Exposure and General Population / Uncontrolled. These two categories are defined as follow:

Limits for General Population / Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824 / f	2.19 / f	(180 / f ²)*	30
30-300	27.5	0.073	0.2	30
300-1500	-	-	F / 1,500	30
1,500-100,000	-	-	1.0	30
Limits for Occupational / Controlled Exposure				
Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1,842 / f	4.89 / f	(900 / f ²)*	6
30-300	61.4	0.163	1.0	6
300-1,500	-	-	F / 300	6
1,500-100,000	-	-	5	6



4.1 Conducted Power

Beamforming on

Band	Data Rate or Sub-test	CH	Frequency (MHz)			Average Conducted power (dBm)		
						ANT-0	ANT-1	All ANT
802.11n_HT20 (256-QAM)	26M	1	2412			10.76	10.84	16.68
		6	2437			13.01	13.04	18.90
		11	2462			10.58	10.39	16.22
802.11n_HT40 (256-QAM)	54M	3	2422			10.42	10.45	16.43
		6	2437			11.14	11.19	17.07
		9	2452			9.06	8.99	14.98
Band	Data Rate or Sub-test	CH	Frequency (MHz)	RU	RU Number	Average Conducted power (dBm)		
						ANT-0	ANT-1	All ANT
802.11ax_HE20	MCS0	1	2412	242	1	10.34	10.32	16.30
		6	2437	242	1	13.04	13.04	19.00
		11	2462	242	1	8.23	8.46	14.27
802.11ax_HE40	MCS0	3	2422	484	1	9.46	9.42	15.42
		6	2437	484	1	10.21	10.28	16.19
		9	2452	484	1	8.06	8.11	14.07



Beamforming off

Band	Date Rate or Sub-test	CH	Frequency (MHz)			Average Conducted power (dBm)		
						ANT-0	ANT-1	All ANT
802.11b	1M	1	2412			19.28	19.42	---
		6	2437			19.21	19.24	---
		11	2462			19.32	19.49	---
802.11g	6M	1	2412			16.66	16.82	22.70
		6	2437			19.24	19.35	25.24
		11	2462			16.74	16.83	22.76
802.11n_HT20 (256-QAM)	26M	1	2412			17.34	17.28	23.09
		6	2437			19.31	19.34	25.18
		11	2462			16.77	16.62	22.61
802.11n_HT40 (256-QAM)	54M	3	2422			16.81	16.84	22.82
		6	2437			17.54	17.57	23.55
		9	2452			15.44	15.52	21.48
Band	Date Rate or Sub-test	CH	Frequency (MHz)	RU	RU Number	Average Conducted power (dBm)		
						ANT-0	ANT-1	All ANT
802.11ax_HE20	MCS0	1	2412	242	1	16.72	16.81	22.68
		6	2437	242	1	19.21	19.32	25.21
		11	2462	242	1	14.74	14.82	20.72
802.11ax_HE40	MCS0	3	2422	484	1	15.82	15.96	21.89
		6	2437	484	1	16.54	16.71	22.68
		9	2452	484	1	14.41	14.58	20.53



Beamforming on

Band	Date Rate or Sub-test	CH	Frequency (MHz)			Average Conducted power (dBm)		
						ANT-0	ANT-1	All ANT
802.11ac_5G_VHT20	26M	36	5180			11.91	12.14	18.11
		40	5200			12.95	13.11	19.06
		44	5220			12.93	13.08	19.03
		48	5240			13.14	13.33	19.24
		149	5745			12.76	12.74	18.98
		153	5765			12.75	12.64	18.91
		157	5785			12.81	12.68	18.96
		161	5805			12.77	12.65	18.92
802.11ac_5G_VHT40	54M	38	5190			10.26	10.42	16.33
		46	5230			13.21	13.41	19.34
		151	5755			12.84	12.85	19.16
		159	5795			13.22	12.78	19.29
802.11ac_5G_VHT80	117.2M	42	5210			10.06	10.09	16.07
		155	5775			12.86	12.67	19.08
Band	Date Rate or Sub-test	CH	Frequency (MHz)	RU	RU Number	Average Conducted power (dBm)		
						ANT-0	ANT-1	All ANT
802.11ax_5G_HE20	MCS 0	36	5180	242	1	11.81	12.04	17.96
		40	5200	242	1	13.25	13.41	19.32
		44	5220	242	1	13.21	13.44	19.29
		48	5240	242	1	13.51	13.57	19.49
		149	5745	242	1	13.02	12.78	19.19
		153	5765	242	1	13.01	12.73	19.16
		157	5785	242	1	13.09	12.82	19.23
		161	5805	242	1	13.06	12.77	19.18
802.11ax_5G_HE40	MCS 0	38	5190	484	1	10.36	10.46	16.40
		46	5230	484	1	13.24	13.56	19.40
		151	5755	484	1	12.94	13.02	19.32
		159	5795	484	1	13.26	12.97	19.41
802.11ax_5G_HE80	MCS 0	42	5210	968	1	9.68	9.76	15.74
		155	5775	968	1	13.08	12.97	19.35



Beamforming off

Band	Data Rate or Sub-test	CH	Frequency (MHz)			Average Conducted power (dBm)		
						ANT-0	ANT-1	All ANT
802.11a	6M	36	5180			16.51	16.71	22.65
		40	5200			16.48	16.69	22.65
		44	5220			16.46	16.65	22.61
		48	5240			16.61	16.91	22.75
		149	5745			19.24	18.94	25.28
		153	5765			19.28	18.78	25.26
		157	5785			19.31	18.82	25.30
		161	5805			19.25	18.80	25.26
		165	5825			19.52	19.15	25.46
802.11ac_5G_VHT20	26M	36	5180			18.22	18.34	24.34
		40	5200			19.32	19.24	25.28
		44	5220			19.29	19.20	25.24
		48	5240			19.41	19.34	25.35
		149	5745			19.14	18.80	25.13
		153	5765			19.20	18.79	25.18
		157	5785			19.22	18.85	25.24
		161	5805			19.19	18.82	25.21
802.11ac_5G_VHT40	54M	38	5190			16.64	16.74	22.76
		46	5230			19.51	19.68	25.59
		151	5755			19.21	19.18	25.44
		159	5795			19.48	19.12	25.55
802.11ac_5G_VHT80	117.2M	42	5210			16.44	16.48	22.46
		155	5775			19.22	18.94	25.36
Band	Data Rate or Sub-test	CH	Frequency (MHz)	RU	RU Number	Average Conducted power (dBm)		
						ANT-0	ANT-1	All ANT
802.11ax_5G_HE20	MCS 0	36	5180	242	1	18.12	18.21	24.20
		40	5200	242	1	19.61	19.51	25.50
		44	5220	242	1	19.55	19.48	25.45
		48	5240	242	1	19.72	19.61	25.58
		149	5745	242	1	19.14	18.82	25.27
		153	5765	242	1	19.22	19.00	25.32
		157	5785	242	1	19.31	19.02	25.38
		161	5805	242	1	19.29	18.97	25.32
		165	5825	242	1	19.64	19.21	25.55
802.11ax_5G_HE40	MCS 0	38	5190	484	1	16.82	16.88	22.93
		46	5230	484	1	19.64	19.91	25.76
		151	5755	484	1	19.32	19.14	25.54
		159	5795	484	1	19.54	19.24	25.67
802.11ax_5G_HE80	MCS 0	42	5210	968	1	16.14	16.19	22.14
		155	5775	968	1	19.32	19.14	25.51



Band	Date Rate	Frequency (MHz)	Average Conducted power (dBm)
Bluetooth LE	1 Mbps	2402	5.04
		2440	4.93
		2480	4.75
	500 Kbps (C2)	2402	5.03
		2440	4.91
		2480	4.73
	125 Kbps (C8)	2402	5.02
		2440	4.89
		2480	4.71
Bluetooth BLR C8	---	2402	5.03
		2440	4.87
		2480	4.70

5. Test Result

Test Result										
Antenna	Band	Frequency (MHz)	Limit (mw)/cm ²	Distance	Tune-up Power	ANT Gain	Numeric Gain	Duty Cycle	Power with Duty cycle	Power Density
				(cm)	(dBm)	(dBi)	[G]		(mW)	(mw)/cm ²
				[R]	[P]	[G]	[P]x[G]		[S]	
Bluetooth Antenna	LE	2402-2480	10	20	5.54	5.09	3.23	1	11.57	0.002
Wi-Fi Antenna	2.4GHz	2412-2462	10	20	25.74	4.25	2.66	1	997.76	0.198
	5GHz	5150-5250	10	20	26.26	4.64	2.91	1	1230.01	0.245
		5725-5850	10	20	26.17	4.68	2.94	1	1216.97	0.242
Wi-Fi Antenna (Beamforming)	2.4GHz	2412-2462	10	20	19.50	10.26	10.62	1	947.27	0.188
	5GHz	5150-5250	10	20	19.99	10.65	11.61	1	1158.20	0.230
		5725-5850	10	20	19.96	10.69	11.72	1	1160.98	0.231

Note:

1. Mobile or fixed location transmitters, minimum separation distance is 20 cm, even if calculations indicate MPE distance is less.
2. We used the maximum power and gain to provide MPE results.
3. The Numeric Gain calculated by $10^{(\text{ant. Gain(dBi)} / 10)}$.
4. The MPE results are evaluated by lowest data rate for WLAN.

Simultaneous Transmitting :

$$\text{Total MPE} = 2.4\text{GHz MPE} + 5\text{GHz MPE} = 0.198 + 0.245 = 0.443 \text{ (mw)/cm}^2 < 1 \text{ (mw)/cm}^2$$

---END---