



中认信通
CHINA CERTIFICATION ICT CO., LTD (DONGGUAN)



TEST REPORT

Applicant: Flyability SA

Address: EPFL INNOVATION PARK BLDG C, Lausanne Switzerland

FCC ID: 2AL7M-MAGICKAYAKRC2

Product Name: GCS GOV

**Standard(s): 47 CFR Part 15, Subpart C(15.247)
ANSI C63.10-2013
KDB 558074 D01 15.247 Meas Guidance v05r02**

The above equipment has been tested and found compliance with the requirement of the relative standards by China Certification ICT Co., Ltd (Dongguan)

Report Number: CR21100120-00

Date Of Issue: 2021-11-26

Reviewed By: Sun Zhong *Sun Zhong*

Title: Manager

Test Laboratory: China Certification ICT Co., Ltd (Dongguan)
No. 113, Pingkang Road, Dalang Town, Dongguan,
Guangdong, China
Tel: +86-769-82016888

Test Facility

The Test site used by China Certification ICT Co., Ltd (Dongguan) to collect test data is located on the No. 113, Pingkang Road, Dalang Town, Dongguan, Guangdong, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 442868, the FCC Designation No. : CN1314.

The lab has been recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements, the CAB identifier: CN0123.

Declarations

China Certification ICT Co., Ltd (Dongguan) is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with a triangle symbol “▲”. Customer model name, addresses, names, trademarks etc. are not considered data.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.

This report cannot be reproduced except in full, without prior written approval of the Company.

This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

This report may contain data that are not covered by the accreditation scope and shall be marked with an asterisk “★”.

CONTENTS

TEST FACILITY	2
DECLARATIONS.....	2
1. GENERAL INFORMATION	5
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	5
1.2 DESCRIPTION OF TEST CONFIGURATION.....	7
1.2.2 Support Equipment List and Details	7
1.2.3 Support Cable List and Details	7
1.2.4 Block Diagram of Test Setup.....	7
1.3 MEASUREMENT UNCERTAINTY	9
2. SUMMARY OF TEST RESULTS	10
3. REQUIREMENTS AND TEST PROCEDURES	11
3.1 AC LINE CONDUCTED EMISSIONS.....	11
3.1.1 Applicable Standard.....	11
3.1.2 EUT Setup.....	12
3.1.3 EMI Test Receiver Setup	12
3.1.4 Test Procedure	13
3.1.5 Corrected Amplitude & Margin Calculation.....	13
3.2 RADIATION SPURIOUS EMISSIONS	14
3.2.1 Applicable Standard.....	14
3.2.2 EUT Setup.....	14
3.2.3 EMI Test Receiver & Spectrum Analyzer Setup	15
3.2.4 Test Procedure	15
3.2.5 Corrected Amplitude & Margin Calculation.....	15
3.3 6 dB EMISSION BANDWIDTH:.....	16
3.3.1 Applicable Standard.....	16
3.3.2 EUT Setup.....	16
3.3.3 Test Procedure	16
3.4 MAXIMUM PEAK CONDUCTED OUTPUT POWER:.....	17
3.4.1 Applicable Standard.....	17
3.4.2 EUT Setup.....	17
3.4.3 Test Procedure	17
3.5 MAXIMUM POWER SPECTRAL DENSITY:	18
3.5.1 Applicable Standard.....	18
3.5.2 EUT Setup.....	18
3.5.3 Test Procedure	18
3.6 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE:	19
3.6.1 Applicable Standard.....	19
3.6.2 EUT Setup.....	19
3.6.3 Test Procedure	19
3.7 DUTY CYCLE:.....	20
3.7.1 EUT Setup.....	20

3.7.2 Test Procedure20

3.8 ANTENNA REQUIREMENT.....21

3.8.1 Applicable Standard.....21

3.8.2 Judgment.....21

4. Test DATA AND RESULTS 22

4.1 AC LINE CONDUCTED EMISSIONS.....22

4.2 RADIATION SPURIOUS EMISSIONS25

4.3 6 dB EMISSION BANDWIDTH:34

4.4 MAXIMUM CONDUCTED OUTPUT POWER:37

4.5 MAXIMUM POWER SPECTRAL DENSITY:39

4.6 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE:44

4.7 DUTY CYCLE:.....49

5. RF EXPOSURE EVALUATION 51

5.1 APPLICABLE STANDARD.....51

1. GENERAL INFORMATION

1.1 Product Description for Equipment under Test (EUT)

EUT Name:	GCS GOV
EUT Model:	108060
Operation Frequency:	4MHz Mode:2405-2479 MHz 8MHz Mode:2407-2477 MHz
Maximum Average Output Power (Conducted):	24.71 dBm
Modulation Type:	OFDM
Rated Input Voltage:	DC 7.2V from battery or DC 12V from adapter
Serial Number:	CR21100120-RF-S1
EUT Received Date:	2021.10.27
EUT Received Status:	Good

Operation Frequency Detail:

For 4MHz Mode:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2405	39	2443
2	2406
...
...	...	74	2478
37	2441	75	2479
38	2442	/	/

Per section 15.31(m), the lowest frequency, middle frequency, and highest frequency were performed the test as below:

Test Channel	Frequency (MHz)
Lowest	2405
Middle	2442
Highest	2479

Per the power test, the additional test should be performed with conducted output power test and radiation bandedge test.

For 8MHz Mode:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2407	37	2443
2	2408
...
...	...	70	2476
35	2441	71	2477
36	2442	/	/

Per section 15.31(m), the lowest frequency, middle frequency, and highest frequency were performed the test as below:

Test Channel	Frequency (MHz)
Lowest	2407
Middle	2442
Highest	2477

Per the power test, the additional test should be performed with conducted output power test and radiation bandedge test.

Antenna Information Detail▲:

Antenna Chain	Manufacturer	Antenna Type	input impedance (Ohm)	Antenna Gain /Frequency Range	§15.203 Requirement
0	Flyability SA	Dipole	50	3.2 dBi/ 2.4~2.5GHz	Compliance
1	Flyability SA	Dipole	50	3.2 dBi/ 2.4~2.5GHz	Compliance

The Method of §15.203 Compliance:

- Antenna must be permanently attached to the unit.
 Antenna must use a unique type of connector to attach to the EUT.
 Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

Accessory Information:

Accessory Description	Manufacturer	Model	Parameters
Adapter	Sunny COMPUTER TECHNOLOGY EUROPE s.r.o.	SYS1541-2412	Input: 100~240V, 50/60Hz 1A MAX Output: DC 12V 2A

1.2 Description of Test Configuration

1.2.1 EUT Operation Condition:

EUT Operation Mode:	The system was configured for testing in Engineering Mode, which was provided by the manufacturer.
Equipment Modifications:	No
EUT Exercise Software:	IP Control
The software " IP Control "was provided by manufacturer. The power was configured to the maximum power per test purpose, the setting was provided by the manufacturer▲, please refer to the power test section.	
The device supports SISO and MIMO in all modes, per pretest, MIMO was the worst mode and reported in this report.	

1.2.2 Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
SAMSUNG	Galaxy Tab Active2	SM-T390	R52K8040QTJ
ZIONCOM	Router	MB-R210-00	107324

1.2.3 Support Cable List and Details


Cable Description	Shielding Type	Ferrite Core	Length (m)	From Port	To
RJ45 Cable	Yes	No	10	Router	EUT
USB Cable	Yes	No	0.5	EUT	Galaxy Tab Active2

1.2.4 Block Diagram of Test Setup


AC line conducted emissions:



Spurious Emissions Below 1GHz:



Spurious Emissions Above 1GHz:



1.3 Measurement Uncertainty

Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval.

Parameter	Measurement Uncertainty
Occupied Channel Bandwidth	±5 %
RF output power, conducted	±0.61 dB
Power Spectral Density, conducted	±0.61 dB
Unwanted Emissions, radiated	30M~200MHz: 4.15 dB, 200M~1GHz: 5.61 dB, 1G~6GHz: 5.14 dB, 6G~18GHz: 5.93 dB, 18G~26.5G: 5.47 dB, 26.5G~40G: 5.63 dB
Unwanted Emissions, conducted	±1.26 dB
Temperature	±1 °C
Humidity	±5%
DC and low frequency voltages	±0.4%
Duty Cycle	1%
AC Power Lines Conducted Emission	2.8 dB (150 kHz to 30 MHz)

2. SUMMARY OF TEST RESULTS

Standard(s) Section	Test Items	Result
§15.207(a)	AC line conducted emissions	Compliance
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliance
§15.247 (a)(2)	6 dB Bandwidth	Compliance
§15.247(b)(3)	Maximum Conducted Output Power	Compliance
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliance
§15.247(e)	Power Spectral Density	Compliance
§15.203	Antenna Requirement	Compliance
§15.247 (i) & §1.1310 & §2.1093	RF Exposure	Compliance

3. REQUIREMENTS AND TEST PROCEDURES

3.1 AC Line Conducted Emissions

3.1.1 Applicable Standard

FCC§15.207(a).

(a) Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

(b) The limit shown in paragraph (a) of this section shall not apply to carrier current systems operating as intentional radiators on frequencies below 30 MHz. In lieu thereof, these carrier current systems shall be subject to the following standards:

(1) For carrier current system containing their fundamental emission within the frequency band 535-1705 kHz and intended to be received using a standard AM broadcast receiver: no limit on conducted emissions.

(2) For all other carrier current systems: 1000 μ V within the frequency band 535-1705 kHz, as measured using a 50 μ H/50 ohms LISN.

(3) Carrier current systems operating below 30 MHz are also subject to the radiated emission limits in §15.205, §15.209, §15.221, §15.223, or §15.227, as appropriate.

(c) Measurements to demonstrate compliance with the conducted limits are not required for devices which only employ battery power for operation and which do not operate from the AC power lines or contain provisions for operation while connected to the AC power lines. Devices that include, or make provisions for, the use of battery chargers which permit operating while charging, AC adapters or battery eliminators or that connect to the AC power lines indirectly, obtaining their power through another device which is connected to the AC power lines, shall be tested to demonstrate compliance with the conducted limits.

3.1.2 EUT Setup



- Note: 1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

The adapter or EUT was connected to the main LISN with a 120 V/60 Hz AC power source.

3.1.3 EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

3.1.4 Test Procedure

The frequency and amplitude of the six highest ac power-line conducted emissions relative to the limit, measured over all the current-carrying conductors of the EUT power cords, and the operating frequency or frequency to which the EUT is tuned (if appropriate), should be reported, unless such emissions are more than 20 dB below the limit. AC power-line conducted emissions measurements are to be separately carried out only on each of the phase (“hot”) line(s) and (if used) on the neutral line(s), but not on the ground [protective earth] line(s). If less than six emission frequencies are within 20 dB of the limit, then the noise level of the measuring instrument at representative frequencies should be reported. The specific conductor of the power-line cord for each of the reported emissions should be identified. Measure the six highest emissions with respect to the limit on each current-carrying conductor of each power cord associated with the EUT (but not the power cords of associated or peripheral equipment that are part of the test configuration). Then, report the six highest emissions with respect to the limit from among all the measurements identifying the frequency and specific current-carrying conductor identified with the emission. The six highest emissions should be reported for each of the current-carrying conductors, or the six highest emissions may be reported over all the current-carrying conductors.

3.1.5 Corrected Amplitude & Margin Calculation

The basic equation is as follows:

Result = Reading + Factor

Factor = attenuation caused by cable loss + voltage division factor of AMN

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. The equation for margin calculation is as follows:

Margin = Limit – Result

3.2 Radiation Spurious Emissions


3.2.1 Applicable Standard

FCC §15.247 (d);


In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

3.2.2 EUT Setup

Below 1GHz:



Above 1GHz:



The radiated emissions were performed in the 3 meters distance, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

3.2.3 EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

30MHz-1000MHz:

Measurement	RBW	Video B/W	IF B/W
QP	120 kHz	300 kHz	120kHz

1GHz- 25GHz:

Measurement	Duty cycle	RBW	Video B/W
PK	Any	1MHz	3 MHz
AV	>98%	1MHz	10 Hz
	<98%	1MHz	1/T

Note: T is minimum transmission duration

If the maximized peak measured value complies with under the QP/Average limit more than 6dB, then it is unnecessary to perform an QP/Average measurement.

3.2.4 Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection modes for frequencies above 1 GHz.

3.2.5 Corrected Amplitude & Margin Calculation

The basic equation is as follows:

Result = Reading + Factor

Factor = Antenna Factor + Cable Loss- Amplifier Gain

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. The equation for margin calculation is as follows:

Margin = Limit – Result


3.3 6 dB Emission Bandwidth:

3.3.1 Applicable Standard

FCC §15.247 (a)(2)

Systems using digital modulation techniques may operate in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

3.3.2 EUT Setup



3.3.3 Test Procedure

According to ANSI C63.10-2013 Section 11.8

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.


3.4 Maximum conducted output power:

3.4.1 Applicable Standard

FCC §15.247 (b)(3)

For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

3.4.2 EUT Setup



3.4.3 Test Procedure

According to ANSI C63.10-2013 Section 11.9.1.3, and(or) ANSI C63.10-2013 Section 11.9.2.3.1

PKPM1 Peak power meter method

The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall use a fast-responding diode detector.

- a) Set the EUT in transmitting mode.
- b) Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to test equipment.
- c) Add a correction factor to the display.
- d) Set the power meter to test peak output power, record the result.

Method AVGPM

Method AVGPM is a measurement using an RF average power meter, as follows:

- a) As an alternative to spectrum analyzer or EMI receiver measurements, measurements may be performed using a wideband RF power meter with a thermocouple detector or equivalent if all of the conditions listed below are satisfied:
 - 1) The EUT is configured to transmit continuously, or to transmit with a constant duty cycle.
 - 2) At all times when the EUT is transmitting, it shall be transmitting at its maximum power control level.
 - 3) The integration period of the power meter exceeds the repetition period of the transmitted signal by at least a factor of five.
- b) If the transmitter does not transmit continuously, measure the duty cycle, D, of the transmitter output signal as described in 11.6.
- c) Measure the average power of the transmitter. This measurement is an average over both the ON and OFF periods of the transmitter.
- d) Adjust the measurement in dBm by adding $[10 \log (1 / D)]$, where D is the duty cycle.

3.5 Maximum power spectral density:

3.5.1 Applicable Standard

FCC §15.247 (e)

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

3.5.2 EUT Setup



3.5.3 Test Procedure

According to ANSI C63.10-2013 Section 11.10.2

- a) Set analyzer center frequency to DTS channel center frequency.
- b) Set the span to 1.5 times the DTS bandwidth.
- c) Set the RBW to $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- d) Set the VBW $\geq [3 \cdot \text{RBW}]$.
- e) Detector = Peak.
- f) Sweep time = auto couple.
- g) Trace mode = max hold.
- h) Allow trace to fully stabilize.
- i) Use the peak marker function to determine the maximum amplitude level within the RBW.
- j) If measured value exceeds requirement, then reduce RBW (but no less than 3 kHz) and repeat.


3.6 100 kHz Bandwidth of Frequency Band Edge:

3.6.1 Applicable Standard

FCC §15.247 (d);

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

3.6.2 EUT Setup



3.6.3 Test Procedure


According to ANSI C63.10-2013 Section 11.11

- a) Set the center frequency and span to encompass frequency range to be measured.
- b) Set the RBW = 100 kHz.
- c) Set the VBW $\geq [3 \times \text{RBW}]$.
- d) Detector =RMS.
- e) Sweep time = auto couple.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use the peak marker function to determine the maximum amplitude level.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) is attenuated by at least the minimum requirements specified in 11.11. Report the three highest emissions relative to the limit.

3.7 Duty Cycle:

3.7.1 EUT Setup



3.7.2 Test Procedure

According to ANSI C63.10-2013 Section 11.6

The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the ON and OFF times of the transmitted signal:

- 1) Set the center frequency of the instrument to the center frequency of the transmission.
- 2) Set $RBW \geq OBW$ if possible; otherwise, set RBW to the largest available value.
- 3) Set $VBW \geq RBW$. Set detector = peak or average.
- 4) The zero-span measurement method shall not be used unless both RBW and VBW are $> 50/T$ and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring the duty cycle shall not be used if $T \leq 16.7 \mu s$.)

3.8 Antenna Requirement

3.8.1 Applicable Standard

FCC §15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §§15.211, 15.213, 15.217, 15.219, 15.221, or §15.236. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

3.8.2 Judgment

Please refer to the Antenna Information detail in Section 1.

4. Test DATA AND RESULTS

4.1 AC Line Conducted Emissions

Serial Number: CR21100120-RF-S1
 Test Site: CE
 Tester: Nick Tang

Test Date: 2021-11-25
 Test Mode: Transmitting
 Test Result: Pass

Environmental Conditions:


Temperature: 19.8 (°C) Relative Humidity: 57 (%) ATM Pressure: 101.4 (kPa)

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	LISN	ENV216	101132	2021-04-25	2022-04-24
R&S	EMI Test Receiver	ESR3	102726	2021-07-22	2022-07-21
MICRO-COAX	Coaxial Cable	UTIFLEX	C-0200-01	2021-08-08	2022-08-07
Audix	Test Software	E3	190306 (V9)	N/A	N/A


* *Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).*

Line



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.191	28.61	9.61	38.22	53.98	15.76	Average
2	0.191	47.38	9.61	56.99	63.98	6.99	QP
3	0.249	17.61	9.61	27.22	51.78	24.56	Average
4	0.249	38.09	9.61	47.70	61.78	14.08	QP
5	0.313	17.55	9.61	27.16	49.88	22.72	Average
6	0.313	33.42	9.61	43.03	59.88	16.85	QP
7	0.588	11.64	9.62	21.26	46.00	24.74	Average
8	0.588	21.77	9.62	31.39	56.00	24.61	QP
9	1.205	16.22	9.62	25.85	46.00	20.15	Average
10	1.205	24.84	9.62	34.46	56.00	21.54	QP
11	6.437	13.18	9.66	22.84	50.00	27.16	Average
12	6.437	26.70	9.66	36.36	60.00	23.64	QP

Neutral



No.	Frequency (MHz)	Reading (dB μ V)	Factor (dB)	Result (dB μ V)	Limit (dB μ V)	Margin (dB)	Detector
1	0.187	24.87	9.61	34.48	54.17	19.70	Average
2	0.187	46.63	9.61	56.24	64.17	7.93	QP
3	0.253	21.42	9.61	31.03	51.66	20.63	Average
4	0.253	38.33	9.61	47.94	61.66	13.72	QP
5	0.321	19.36	9.61	28.97	49.67	20.69	Average
6	0.321	32.61	9.61	42.22	59.67	17.45	QP
7	0.564	11.47	9.62	21.08	46.00	24.92	Average
8	0.564	23.15	9.62	32.76	56.00	23.24	QP
9	1.157	15.91	9.62	25.53	46.00	20.47	Average
10	1.157	25.41	9.62	35.03	56.00	20.97	QP
11	6.361	6.03	9.66	15.69	50.00	34.31	Average
12	6.361	18.43	9.66	28.09	60.00	31.91	QP

4.2 Radiation Spurious Emissions

Serial Number:	CR21100120-RF-S1	Test Date:	2021-11-25
Test Site:	966-1,966-2	Test Mode:	Transmitting
Tester:	Great Qiao, Carl Liang	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	18.6	Relative Humidity: (%)	44	ATM Pressure: (kPa)	101.4
----------------------	------	------------------------------	----	------------------------	-------


Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Sunol Sciences	Antenna	JB6	A082520-5	2020-10-19	2023-10-18
R&S	EMI Test Receiver	ESR3	102724	2021-07-22	2022-07-21
TIMES MICROWAVE	Coaxial Cable	LMR-600-UltraFlex	C-0470-02	2021-07-18	2022-07-17
TIMES MICROWAVE	Coaxial Cable	LMR-600-UltraFlex	C-0780-01	2021-07-18	2022-07-17
Sonoma	Amplifier	310N	186165	2021-07-18	2022-07-17
Audix	Test Software	E3	201021 (V9)	N/A	N/A
ETS-Lindgren	Horn Antenna	3115	9912-5985	2020-10-13	2023-10-12
PASTERNAK	Horn Antenna	PE9852/2F-20	112002	2021-02-05	2023-02-04
R&S	Spectrum Analyzer	FSV40	101591	2021-07-22	2022-07-21
MICRO-COAX	Coaxial Cable	UFA210A-1-1200-70U300	217423-008	2021-08-08	2022-08-07
MICRO-COAX	Coaxial Cable	UFA210A-1-2362-300300	235780-001	2021-08-08	2022-08-07
MICRO-COAX	Coaxial Cable	UFB142A-1-2362-200200	235772-001	2021-08-08	2022-08-07
Mini	Pre-amplifier	ZVA-183-S+	5969001149	2021-11-10	2022-11-09
AH	Preamplifier	PAM-1840VH	190	2021-11-19	2022-11-18
E-Microwave	Band Rejection Filter	2400-2483.5MHz	OE01902424	2021-08-08	2022-08-07
Mini Circuits	High Pass Filter	VHF-6010+	31119	2021-08-08	2022-08-07

* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).


1) 30MHz-1GHz(4M Low channel was the worst)

Horizontal:



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	31.399	31.23	-4.86	26.37	40.00	13.63	Peak
2	87.418	48.68	-17.31	31.37	40.00	8.63	Peak
3	143.326	42.55	-12.18	30.37	43.50	13.13	Peak
4	250.301	50.47	-13.25	37.22	46.00	8.78	Peak
5	375.939	42.58	-9.48	33.10	46.00	12.90	Peak
6	750.108	43.88	-3.24	40.64	46.00	5.36	QP

Vertical:



No.	Frequency (MHz)	Reading (dB μ V)	Factor (dB/m)	Result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Detector
1	30.638	39.90	-4.28	35.62	40.00	4.38	QP
2	31.399	41.61	-4.86	36.75	40.00	3.25	QP
3	38.888	46.11	-10.63	35.48	40.00	4.52	QP
4	47.659	47.72	-16.04	31.68	40.00	8.32	QP
5	62.651	49.58	-17.39	32.18	40.00	7.82	QP
6	85.898	50.22	-17.39	32.82	40.00	7.18	Peak

2) 1-25GHz:
4M

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dBµV/m)	Limit (dBµV/m)	Margin (dB)
	Reading (dBµV)	Detector					
Low Channel: 2405 MHz							
2405.00	82.95	PK	H	31.51	114.46	N/A	N/A
2405.00	71.69	AV	H	31.51	103.20	N/A	N/A
2405.00	93.75	PK	V	31.51	125.26	N/A	N/A
2405.00	82.15	AV	V	31.51	113.66	N/A	N/A
2390.00	31.95	PK	V	31.46	63.41	74.00	10.59
2390.00	19.16	AV	V	31.46	50.62	54.00	3.38
4810.00	35.65	PK	V	10.92	46.57	74.00	27.43
4810.00	24.81	AV	V	10.92	35.73	54.00	18.27
7215.00	34.59	PK	V	14.28	48.87	74.00	25.13
7215.00	22.91	AV	V	14.28	37.19	54.00	16.81
2639.00	90.35	PK	V	4.40	94.75	95.26	0.51
2168.00	88.67	PK	V	2.85	91.52	95.26	3.74
2497.00	56.94	PK	V	3.62	60.56	74.00	13.44
2497.00	44.62	AV	V	3.62	48.24	54.00	5.76
1930.00	43.90	PK	V	2.00	45.90	74.00	28.10
1930.00	31.94	AV	V	2.00	33.94	54.00	20.06
2891.00	40.74	PK	V	5.56	46.30	74.00	27.70
2891.00	28.16	AV	V	5.56	33.72	54.00	20.28
2407 MHz							
2407.00	93.02	PK	V	31.52	124.54	N/A	N/A
2407.00	81.28	AV	V	31.52	112.80	N/A	N/A
2390.00	32.05	PK	V	31.46	63.51	74.00	10.49
2390.00	19.25	AV	V	31.46	50.71	54.00	3.29
Middle Channel: 2442 MHz							
2442.00	82.36	PK	H	31.61	113.97	N/A	N/A
2442.00	71.75	AV	H	31.61	103.36	N/A	N/A
2442.00	93.84	PK	V	31.61	125.45	N/A	N/A
2442.00	81.73	AV	V	31.61	113.34	N/A	N/A
4884.00	37.35	PK	V	11.08	48.43	74.00	25.57
4884.00	23.14	AV	V	11.08	34.22	54.00	19.78
7326.00	34.73	PK	V	14.79	49.52	74.00	24.48
7326.00	22.64	AV	V	14.79	37.43	54.00	16.57
2682.00	67.56	PK	V	4.62	72.18	95.45	23.27
2197.00	62.38	PK	V	2.92	65.30	95.45	30.15
2495.00	54.76	PK	V	3.62	58.38	74.00	15.62
2495.00	42.58	AV	V	3.62	46.20	54.00	7.80
2474 MHz							
2474.00	92.45	PK	V	31.64	124.09	N/A	N/A
2474.00	81.14	AV	V	31.64	112.78	N/A	N/A
2483.50	32.01	PK	V	31.64	63.65	74.00	10.35
2483.50	19.87	AV	V	31.64	51.51	54.00	2.49
2475 MHz							
2475.00	86.41	PK	V	31.64	118.05	N/A	N/A
2475.00	75.38	AV	V	31.64	107.02	N/A	N/A
2483.50	33.14	PK	V	31.64	64.78	74.00	9.22
2483.50	20.12	AV	V	31.64	51.76	54.00	2.24

2476 MHz							
2476.00	82.34	PK	V	31.64	113.98	N/A	N/A
2476.00	71.35	AV	V	31.64	102.99	N/A	N/A
2483.50	34.41	PK	V	31.64	66.05	74.00	7.95
2483.50	20.36	AV	V	31.64	52.00	54.00	2.00
2477 MHz							
2477.00	77.23	PK	V	31.64	108.87	N/A	N/A
2477.00	66.39	AV	V	31.64	98.03	N/A	N/A
2483.50	35.17	PK	V	31.64	66.81	74.00	7.19
2483.50	21.39	AV	V	31.64	53.03	54.00	0.97
2478 MHz							
2478.00	72.18	PK	V	31.64	103.82	N/A	N/A
2478.00	61.34	AV	V	31.64	92.98	N/A	N/A
2483.50	32.19	PK	V	31.64	63.83	74.00	10.17
2483.50	21.35	AV	V	31.64	52.99	54.00	1.01
High Channel: 2479 MHz							
2479.00	63.98	PK	H	31.64	95.62	N/A	N/A
2479.00	52.81	AV	H	31.64	84.45	N/A	N/A
2479.00	74.73	PK	V	31.64	106.37	N/A	N/A
2479.00	62.85	AV	V	31.64	94.49	N/A	N/A
2483.50	36.88	PK	V	31.64	68.52	74.00	5.48
2483.50	22.01	AV	V	31.64	53.65	54.00	0.35
4958.00	35.42	PK	V	11.23	46.65	74.00	27.35
4958.00	23.47	AV	V	11.23	34.70	54.00	19.30
7437.00	34.68	PK	V	15.23	49.91	74.00	24.09
7437.00	22.14	AV	V	15.23	37.37	54.00	16.63




8M

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
	Reading (dB μ V)	Detector					
Low Channel: 2407 MHz							
2407.00	77.75	PK	H	31.52	109.27	N/A	N/A
2407.00	66.32	AV	H	31.52	97.84	N/A	N/A
2407.00	88.68	PK	V	31.52	120.20	N/A	N/A
2407.00	77.39	AV	V	31.52	108.91	N/A	N/A
2390.00	37.74	PK	V	31.46	69.20	74.00	4.80
2390.00	19.98	AV	V	31.46	51.44	54.00	2.56
4814.00	35.49	PK	V	10.93	46.42	74.00	27.58
4814.00	23.67	AV	V	10.93	34.60	54.00	19.40
7221.00	35.49	PK	V	14.33	49.82	74.00	24.18
7221.00	22.74	AV	V	14.33	37.07	54.00	16.93
2409 MHz							
2409.00	89.26	PK	V	31.52	120.78	N/A	N/A
2409.00	77.87	AV	V	31.52	109.39	N/A	N/A
2390.00	36.45	PK	V	31.46	67.91	74.00	6.09
2390.00	19.72	AV	V	31.46	51.18	54.00	2.82
Middle Channel: 2442 MHz							
2442.00	79.84	PK	H	31.61	111.45	N/A	N/A
2442.00	68.21	AV	H	31.61	99.82	N/A	N/A
2442.00	89.34	PK	V	31.61	120.95	N/A	N/A
2442.00	77.97	AV	V	31.61	109.58	N/A	N/A
4884.00	35.47	PK	V	11.08	46.55	74.00	27.45
4884.00	23.55	AV	V	11.08	34.63	54.00	19.37
7326.00	35.74	PK	V	14.79	50.53	74.00	23.47
7326.00	22.18	AV	V	14.79	36.97	54.00	17.03
2682.00	55.34	PK	V	4.62	59.96	90.95	30.99
2471 MHz							
2471.00	88.98	PK	V	31.64	120.62	N/A	N/A
2471.00	77.69	AV	V	31.64	109.33	N/A	N/A
2483.50	40.26	PK	V	31.64	71.90	74.00	2.10
2483.50	20.29	AV	V	31.64	51.93	54.00	2.07
2472 MHz							
2472.00	84.38	PK	V	31.64	116.02	N/A	N/A
2472.00	73.24	AV	V	31.64	104.88	N/A	N/A
2483.50	39.88	PK	V	31.64	71.52	74.00	2.48
2483.50	21.16	AV	V	31.64	52.80	54.00	1.20
2473 MHz							
2473.00	82.41	PK	V	31.64	114.05	N/A	N/A
2473.00	71.25	AV	V	31.64	102.89	N/A	N/A
2483.50	40.85	PK	V	31.64	72.49	74.00	1.51
2483.50	21.98	AV	V	31.64	53.62	54.00	0.38
2474 MHz							
2474.00	80.36	PK	V	31.64	112.00	N/A	N/A
2474.00	69.12	AV	V	31.64	100.76	N/A	N/A
2483.50	39.56	PK	V	31.64	71.20	74.00	2.80
2483.50	20.61	AV	V	31.64	52.25	54.00	1.75

2475 MHz							
2475.00	71.34	PK	V	31.64	102.98	N/A	N/A
2475.00	60.16	AV	V	31.64	91.80	N/A	N/A
2483.50	40.68	PK	V	31.64	72.32	74.00	1.68
2483.50	19.62	AV	V	31.64	51.26	54.00	2.74
2477 MHz							
2477.00	60.41	PK	H	31.64	92.05	N/A	N/A
2477.00	58.66	AV	H	31.64	90.30	N/A	N/A
2477.00	71.47	PK	V	31.64	103.11	N/A	N/A
2477.00	60.12	AV	V	31.64	91.76	N/A	N/A
2483.50	40.75	PK	V	31.64	72.39	74.00	1.61
2483.50	22.02	AV	V	31.64	53.66	54.00	0.34
4954.00	36.21	PK	V	11.24	47.45	74.00	26.55
4954.00	24.51	AV	V	11.24	35.75	54.00	18.25
7431.00	35.46	PK	V	15.18	50.64	74.00	23.36
7431.00	22.99	AV	V	15.18	38.17	54.00	15.83




Worst Test plots(4M Low channel was the worst)
Horizontal:

Fundamental Test with Band Rejection Filter



Vertical:

Fundamental Test with Band Rejection Filter



4.3 6 dB Emission Bandwidth:

Serial Number:	CR21100120-RF-S1	Test Date:	2021/11/25
Test Site:	RF	Test Mode:	Transmitting
Tester:	Le Qiao	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	22	Relative Humidity: (%)	40	ATM Pressure: (kPa)	101.3
----------------------	----	------------------------------	----	------------------------	-------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSV40	101474	2021-07-22	2022-07-21
Unknown	Coaxial Cable	C-SJ00-0010	C0010/01	Each time	N/A

* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:

Test Modes	Test Frequency (MHz)	6 dB Bandwidth (MHz)	Limit (MHz)
4M	2405	4.530	0.5
	2442	4.540	0.5
	2479	4.530	0.5
8M	2407	9.070	0.5
	2442	9.070	0.5
	2477	9.030	0.5

Note: Test only was performed at Chain 0.

6dB Emission Bandwidth	
4M Lowest Channel	<p> Spectrum 2 Spectrum 3 Spectrum 4 Ref Level 30.00 dBm Offset 1.00 dB RBW 100 kHz ATT 40 dB SWT 1 ms VBW 300 kHz Mode Sweep 1Pk Max D1[1] -0.94 dB M1[1] 4.5300 MHz 4.35 dBm 2.4027569 GHz D1 9.460 dBm D2 3.460 dBm CF 2.405 GHz 691 pts Span 10.0 MHz Date: 25.NOV.2021 22:32:53 </p>
4M Middle Channel	<p> Spectrum 2 Spectrum 3 Spectrum 4 Ref Level 30.00 dBm Offset 1.00 dB RBW 100 kHz ATT 40 dB SWT 1 ms VBW 300 kHz Mode Sweep 1Pk Max D1[1] 0.71 dB M1[1] 4.5440 MHz 3.64 dBm 2.4397424 GHz D1 10.200 dBm D2 4.200 dBm CF 2.442 GHz 691 pts Span 10.0 MHz Date: 25.NOV.2021 22:38:38 </p>
4M Highest Channel	<p> Spectrum 2 Spectrum 3 Spectrum 4 Ref Level 21.00 dBm Offset 1.00 dB RBW 100 kHz ATT 30 dB SWT 1 ms VBW 300 kHz Mode Sweep 1Pk Max D1[1] 0.93 dB M1[1] 4.5300 MHz -15.11 dBm 2.4767280 GHz D1 -9.580 dBm D2 -15.580 dBm CF 2.479 GHz 691 pts Span 10.0 MHz Date: 25.NOV.2021 22:42:37 </p>

6dB Emission Bandwidth	
8M Lowest Channel	<p>Spectrum Spectrum 2 Spectrum 3 Spectrum 4</p> <p>Ref Level 21.00 dBm Offset 1.00 dB RBW 100 kHz ATT 30 dB SWT 1 ms VBW 300 kHz Mode Sweep</p> <p>1Pk Max</p> <p>10 dBm 01[1] 4.14 dB 9.0740 MHz -2.83 dBm</p> <p>0 dBm 01 5.000 dBm 02 -1.000 dBm</p> <p>CF 2.407 GHz 691 pts Span 30.0 MHz</p> <p>Date: 25.NOV.2021 22:48:57</p>
8M Middle Channel	<p>Spectrum Spectrum 2 Spectrum 3 Spectrum 4</p> <p>Ref Level 21.00 dBm Offset 1.00 dB RBW 100 kHz ATT 30 dB SWT 1 ms VBW 300 kHz Mode Sweep</p> <p>1Pk Max</p> <p>10 dBm 01[1] 0.26 dB 9.0740 MHz -0.27 dBm</p> <p>0 dBm 01 6.880 dBm 02 0.880 dBm</p> <p>CF 2.442 GHz 691 pts Span 30.0 MHz</p> <p>Date: 25.NOV.2021 22:54:43</p>
8M Highest Channel	<p>Spectrum Spectrum 2 Spectrum 3 Spectrum 4</p> <p>Ref Level 21.00 dBm Offset 1.00 dB RBW 100 kHz ATT 30 dB SWT 1 ms VBW 300 kHz Mode Sweep</p> <p>1Pk Max</p> <p>10 dBm 01[1] 2.01 dB 9.0300 MHz -18.65 dBm</p> <p>0 dBm 01 -12.500 dBm 02 -18.500 dBm</p> <p>CF 2.477 GHz 691 pts Span 30.0 MHz</p> <p>Date: 25.NOV.2021 22:56:21</p>

4.4 Maximum conducted output power:

Serial Number:	CR21100120-RF-S1	Test Date:	2021/11/25
Test Site:	RF	Test Mode:	Transmitting
Tester:	Le Qiao	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	22	Relative Humidity: (%)	40	ATM Pressure: (kPa)	101.3
----------------------	----	------------------------------	----	------------------------	-------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Agilent	USB Wideband Power Sensor	U2021XA	MY54080015	2021-07-22	2022-07-21
eastsheep	Coaxial Attenuator	2W-SMA-JK-18G	21060301	Each time	N/A
Unknown	Coaxial Cable	C-SJ00-0010	C0010/01	Each time	N/A

* *Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).*

Test Data:

Test Modes	Test Frequency (MHz)	Maximum Conducted Average Output Power (dBm)			Limit (dBm)	Power Level Setting
		Chain 0	Chain 1	Total		
4M	2405	10.34	11.44	13.94	30	23
	2406	10.61	10.86	13.75	30	23
	2407	13.31	14.03	16.7	30	25
	2442	13.16	13.24	16.21	30	25
	2474	12.51	13.23	15.9	30	25
	2475	5.73	6.83	9.33	30	20
	2476	1.07	3.09	5.21	30	16
	2477	-3.73	-2.61	-0.12	30	11
	2478	-7.46	-6.87	-4.14	30	7
2479	-6.82	-7.09	-3.94	30	7	
8M	2407	17.81	18.03	20.93	30	23
	2408	17.67	18.06	20.88	30	23
	2409	21.45	21.93	24.71	30	25
	2442	19.91	20.32	23.13	30	25
	2471	20.38	21.33	23.89	30	25
	2472	12.58	13.7	16.19	30	20
	2473	10.16	11.52	13.9	30	18
	2474	8.05	9.82	12.03	30	16
	2475	-0.91	0.02	2.59	30	7
	2476	-0.8	0.07	2.67	30	7
2477	-0.85	0.4	2.83	30	7	

Note: The device employed Cyclic Delay Diversity (CDD) for 802.11 MIMO transmitting, per KDB 662911 D01 Multiple Transmitter Output v02r01, for power measurements on IEEE 802.11 devices:
 Array Gain = 0 dB (i.e., no array gain) for $N_{ANT} \leq 4$

Antenna Gain:	3.20	dB	Directional gain:	3.20	dB
---------------	------	----	-------------------	------	----

4.5 Maximum power spectral density:

Serial Number:	CR21100120-RF-S1	Test Date:	2021/11/25
Test Site:	RF	Test Mode:	Transmitting
Tester:	Le Qiao	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	22	Relative Humidity: (%)	40	ATM Pressure: (kPa)	101.3
----------------------	----	------------------------------	----	------------------------	-------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSV40	101474	2021/7/22	2022/7/21
Unknown	Coaxial Cable	C-SJ00-0010	C0010/01	Each time	N/A
YINSAIGE	Coaxial Cable	SS402	SJ0100002	Each time	N/A

* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:




Test Modes	Test Frequency (MHz)	Maximum Power Spectral Density (dBm/3kHz)			Limit (dBm/3kHz)
		Chain 0	Chain 1	Total	
4M	2405	-3.78	-2.01	0.20	7.8
	2442	-2.57	0.60	2.31	7.8
	2479	-21.83	-20.71	-19.29	7.8
8M	2407	-7.34	-4.45	-2.65	7.8
	2442	-5.96	-3.75	-1.71	7.8
	2477	-25.70	-23.94	-21.72	7.8

Note: The device employed Cyclic Delay Diversity (CDD) for 802.11 MIMO transmitting, per KDB 662911 D01 Multiple Transmitter Output v02r01, for power spectral density (PSD) measurements on the devices:
Array Gain = $10 \log(N_{\text{ANT}}/N_{\text{SS}})$ dB

Antenna Gain:	3.20	dBi	Directional gain:	6.20	dBi
---------------	------	-----	-------------------	------	-----

Chain 0

Maximum power spectral density

<p>4M Lowest Channel</p>	 <p>The spectrum plot shows a signal centered at 2.405 GHz. The y-axis represents power spectral density in dBm, ranging from -70 to 10. The x-axis represents frequency in MHz, with a span of 6.75 MHz. A peak is observed at 2.40362260 GHz with a value of -3.78 dBm. The plot includes a 1Pk Max marker and a measurement point M1[1].</p>
<p>4M Middle Channel</p>	 <p>The spectrum plot shows a signal centered at 2.442 GHz. The y-axis represents power spectral density in dBm, ranging from -70 to 10. The x-axis represents frequency in MHz, with a span of 6.75 MHz. A peak is observed at 2.44073010 GHz with a value of -2.57 dBm. The plot includes a 1Pk Max marker and a measurement point M1[1].</p>
<p>4M Highest Channel</p>	 <p>The spectrum plot shows a signal centered at 2.479 GHz. The y-axis represents power spectral density in dBm, ranging from -70 to 10. The x-axis represents frequency in MHz, with a span of 6.75 MHz. A peak is observed at 2.47917580 GHz with a value of -21.83 dBm. The plot includes a 1Pk Max marker and a measurement point M1[1].</p>

Maximum power spectral density

<p>8M Lowest Channel</p>	<p>1Pk Max -7.34 dBm 2.4049315 GHz</p> <p>CF 2.407 GHz 691 pts Span 13.611 MHz</p> <p>Date: 25.NOV.2021 23:18:18</p>
<p>8M Middle Channel</p>	<p>1Pk Max -5.96 dBm 2.4416655 GHz</p> <p>CF 2.442 GHz 691 pts Span 13.611 MHz</p> <p>Date: 25.NOV.2021 23:20:19</p>
<p>8M Highest Channel</p>	<p>1Pk Max -25.70 dBm 2.4785685 GHz</p> <p>CF 2.477 GHz 691 pts Span 13.545 MHz</p> <p>Date: 25.NOV.2021 23:22:31</p>

Chain 1

Maximum power spectral density	
<p>4M Lowest Channel</p>	<p>CF 2.405 GHz 691 pts Span 6.75 MHz</p> <p>Date: 25.NOV.2021 23:33:35</p>
<p>4M Middle Channel</p>	<p>CF 2.442 GHz 691 pts Span 6.75 MHz</p> <p>Date: 25.NOV.2021 23:35:02</p>
<p>4M Highest Channel</p>	<p>CF 2.479 GHz 691 pts Span 6.75 MHz</p> <p>Date: 25.NOV.2021 23:36:40</p>

Maximum power spectral density

<p>8M Lowest Channel</p>	<p>Spectrum 2 Spectrum 3 Spectrum 4</p> <p>Ref Level 21.00 dBm Offset 1.00 dB RBW 3 kHz ATT 30 dB SWT 152 ms VBW 10 kHz Mode Sweep</p> <p>1Pk Max M1[1] -4.45 dBm 2.403525 GHz</p> <p>CF 2.407 GHz 691 pts Span 13.611 MHz</p> <p>Date: 25.NOV.2021 23:31:50</p>
<p>8M Middle Channel</p>	<p>Spectrum 2 Spectrum 3 Spectrum 4</p> <p>Ref Level 21.00 dBm Offset 1.00 dB RBW 3 kHz ATT 30 dB SWT 152 ms VBW 10 kHz Mode Sweep</p> <p>1Pk Max M1[1] -3.75 dBm 2.4461165 GHz</p> <p>CF 2.442 GHz 691 pts Span 13.611 MHz</p> <p>Date: 25.NOV.2021 23:29:12</p>
<p>8M Highest Channel</p>	<p>Spectrum 2 Spectrum 3 Spectrum 4</p> <p>Ref Level 21.00 dBm Offset 1.00 dB RBW 3 kHz ATT 30 dB SWT 151 ms VBW 10 kHz Mode Sweep</p> <p>1Pk Max M1[1] -23.94 dBm 2.4749615 GHz</p> <p>CF 2.477 GHz 691 pts Span 13.545 MHz</p> <p>Date: 25.NOV.2021 23:24:41</p>

4.6 100 kHz Bandwidth of Frequency Band Edge:

Serial Number:	CR21100120-RF-S1	Test Date:	2021/11/25~2021/11/26
Test Site:	RF	Test Mode:	Transmitting
Tester:	Le Qiao	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	22~23.4	Relative Humidity: (%)	40~47	ATM Pressure: (kPa)	101.3~101.4
----------------------	---------	------------------------------	-------	------------------------	-------------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSV40	101474	2021/7/22	2022/7/21
Unknown	Coaxial Cable	C-SJ00-0010	C0010/01	Each time	N/A


* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:


Chain 0

100 kHz Bandwidth of Frequency Band Edge

4M
Lowest Band edge




4M
Highest Band edge




100 kHz Bandwidth of Frequency Band Edge

8M
Lowest Band edge




8M
Highest Band edge




Chain 1

100 kHz Bandwidth of Frequency Band Edge

4M
Lowest Band edge




4M
Highest Band edge



100 kHz Bandwidth of Frequency Band Edge

8M
Lowest Band edge



8M
Highest Band edge



4.7 Duty Cycle:

Serial Number:	CR21100120-RF-S1	Test Date:	2021/11/26
Test Site:	RF	Test Mode:	Transmitting
Tester:	Le Qiao	Test Result:	N/A

Environmental Conditions:

Temperature: (°C)	23.4	Relative Humidity: (%)	47	ATM Pressure: (kPa)	101.4
----------------------	------	---------------------------	----	------------------------	-------


Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSV40	101474	2021/7/22	2022/7/21
Unknown	Coaxial Cable	C-SJ00-0010	C0010/01	Each time	N/A

* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).


Test Data:

Test Modes	Ton (ms)	Ton+off (ms)	Duty cycle (%)
4M	1.739	101.449	1.71
8M	2.319	102.029	2.27



Duty Cycle

8M



5. RF EXPOSURE EVALUATION

5.1 Applicable Standard

FCC§1.1310 and §2.1093.

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See §1.1307(b)(1) of this chapter.

RSS-102 Clause 4 Table 3, SAR limits for device used by the general public.

Body Region	Average SAR (W/Kg)	Averaging Time (minutes)	Mass Average (g)
Whole Body	0.08	6	Whole Body
Localized Head, Neck and Trunk	1.6	6	1
Localized Limbs	4	6	10

5.2 Measurement Result

Please refer to the SAR report: CR21100120-SA.

Result: Compliance.

******* END OF REPORT *******