



# FCC Part 22H Measurement and Test Report

For

**Shenzhen Reo-link Digital Technology Co., Ltd**

**11th floor, Building C, Unisplendour Information Harbour, North High-Tech**

**Zone, Nanshan District, Shenzhen, China, 518057**

**FCC ID: 2AL7V-2002A**

**FCC Rules:** FCC Part 22,

**Product Description:** IP Camera

**Tested Model:** Reolink Go PT

**Report No.:** WTX20X05026072W-1

**Sample Receipt Date:** May.11, 2020

**Tested Date:** May.11, 2020 to May.25, 2020

**Issued Date:** May.25, 2020

**Tested By:** Jason Su / Engineer

**Reviewed By:** Lion Cai / RF Manager

**Approved & Authorized By:** Silin Chen / Manager

**Prepared By:**

*Jason Su*  
*Lion Cai*  
*Silin Chen*



**Waltek Testing Group (Shenzhen) Co., Ltd.**

1/F., Room 101, Building 1, Hongwei Industrial Park, Liuxian 2nd Road,  
Block 70 Bao'an District, Shenzhen, Guangdong, China

Tel.: +86-755-33663308 Fax.: +86-755-33663309 Website: www.semtest.com.cn

Note: This test report is limited to the above client company and the product model only. It may not be duplicated without prior permitted by Waltek Testing Group (Shenzhen) Co., Ltd.



**TABLE OF CONTENTS**

**1. GENERAL INFORMATION.....4**  
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....4  
1.2 TEST STANDARDS.....6  
1.3 TEST METHODOLOGY.....6  
1.4 TEST FACILITY.....6  
1.5 EUT SETUP AND TEST MODE.....7  
1.6 MEASUREMENT UNCERTAINTY.....8  
1.7 TEST EQUIPMENT LIST AND DETAILS.....9

**2. SUMMARY OF TEST RESULTS .....11**

**3. RF EXPOSURE .....12**  
3.1 STANDARD APPLICABLE.....12  
3.2 TEST RESULT.....12

**4. RF OUTPUT POWER .....13**  
4.1 STANDARD APPLICABLE.....13  
4.2 TEST PROCEDURE.....13  
4.3 SUMMARY OF TEST RESULTS/PLOTS.....13

**5. PEAK-TO-AVERAGE RATIO (PAR) OF TRANSMITTER.....15**  
5.1 STANDARD APPLICABLE.....15  
5.2 TEST PROCEDURE.....15  
5.3 SUMMARY OF TEST RESULTS.....15

**6. EMISSION BANDWIDTH.....16**  
6.1 STANDARD APPLICABLE.....16  
6.2 TEST PROCEDURE.....16  
6.3 SUMMARY OF TEST RESULTS/PLOTS.....16

**7. OUT OF BAND EMISSIONS AT ANTENNA TERMINAL.....17**  
7.1 STANDARD APPLICABLE.....17  
7.2 TEST PROCEDURE.....17  
7.3 SUMMARY OF TEST RESULTS/PLOTS.....17

**8. SPURIOUS RADIATED EMISSIONS.....18**  
8.1 STANDARD APPLICABLE.....18  
8.2 TEST PROCEDURE.....18  
8.3 SUMMARY OF TEST RESULTS/PLOTS.....18

**9. FREQUENCY STABILITY .....22**  
9.1 STANDARD APPLICABLE.....22  
9.2 TEST PROCEDURE.....22  
9.3 SUMMARY OF TEST RESULTS/PLOTS.....22



## Report version

Version No.	Date of issue	Description
Rev.00	May.25, 2020	Original
/	/	/



## 1. GENERAL INFORMATION

### 1.1 Product Description for Equipment Under Test (EUT)

#### Client Information

Applicant: Shenzhen Reo-link Digital Technology Co., Ltd  
Address of applicant: 11th floor, Building C, Unisplendour Information Harbour,  
North High-Tech Zone, Nanshan District, Shenzhen, China,  
518057

Manufacturer: SHENZHEN BAICHUAN SECURITY TECHNOLOGY CO.,  
LTD.  
Address of manufacturer: 2-4th Floor, Building 2, YuanLing Industrial Park, ShangWu,  
Shiyan Street, Bao'an District, Shenzhen, China

General Description of EUT:	
Product Name:	IP Camera
Brand Name:	reolink
Model No.:	Reolink Go PT
Adding Model(s):	/
Rated Voltage:	DC3.6V
Battery:	6500mAh
Adapter Model:	/
Software Version:	/
Hardware Version:	/
<i>Note: The test data is gathered from a production sample provided by the manufacturer.</i>	



<b>Technical Characteristics of EUT: Main board</b>	
<b>4G</b>	
Support Networks:	FDD-LTE
Support Band:	FDD-LTE Band 5,
Uplink Frequency:	FDD-LTE Band 5: Tx: 824-849MHz,
Downlink Frequency:	FDD-LTE Band 5: Rx: 869-894MHz,
RF Output Power:	FDD-LTE Band 5: 22.87dBm,
Type of Emission:	FDD-LTE Band 5: 8M92G7D
Type of Modulation:	QPSK
Antenna Type:	External Antenna
Antenna Gain:	FDD-LTE Band 5: 2.45dBi,

## 1.2 Test Standards

The tests were performed according to following standards:

**FCC Rules Part 2:** FREQUENCY ALLOCATIONS AND RADIO TREATY MATTERS; GENERAL RULES AND REGULATIONS.

**FCC Rules Part 22:** PRIVATE LAND MOBILE RADIO SERVICES.

**TIA/EIA 603 E March 2016:** Land Mobile FM or PM Communications Equipment Measurement and Performance Standards.

**ANSI C63.26-2015:** American National Standard for Compliance Testing of Transmitters Used in Licensed Radio Services

**KDB 971168 D01 Power Meas License Digital Systems v03r01:** MEASUREMENT GUIDANCE FOR CERTIFICATION OF LICENSED DIGITAL TRANSMITTERS.

**Maintenance of compliance** is the responsibility of the manufacturer. Any modification of the product, which result in lowering the emission, should be checked to ensure compliance has been maintained.

## 1.3 Test Methodology

All measurements contained in this report were conducted with TIA/EIA 603 E/ KDB 971168/ ANSI C63.26. The equipment under test (EUT) was configured to measure its highest possible emission level. The test modes were adapted accordingly in reference to the Operating Instructions.

## 1.4 Test Facility

### **Address of the test laboratory**

Laboratory: Waltek Testing Group (Shenzhen) Co., Ltd.

Address: 1/F., Room 101, Building 1, Hongwei Industrial Park, Liuxian 2nd Road, Block 70 Bao'an District, Shenzhen, Guangdong, China

### **FCC – Registration No.: 125990**

Waltek Testing Group (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. The Designation Number is CN5010, and Test Firm Registration Number is 125990.

### **Industry Canada (IC) Registration No.: 11464A**

The 3m Semi-anechoic chamber of Waltek Testing Group (Shenzhen) Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 11464A.



### 1.5 EUT Setup and Test Mode

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. All testing shall be performed under maximum output power condition, and to measure its highest possible emissions level, more detailed description as follows:

Test Mode List		
Test Mode	Description	Remark
TM1	FDD-LTE Band 5	Low, Middle, High Channels

Test Conditions	
Temperature:	22~25 °C
Relative Humidity:	50~55 %.
ATM Pressure:	1019 mbar

EUT Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
/	/	/	/

Special Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
/	/	/	/

Auxiliary Equipment List and Details			
Description	Manufacturer	Model	Serial Number
/	/	/	/



### 1.6 Measurement Uncertainty

Measurement uncertainty		
Parameter	Conditions	Uncertainty
RF Output Power	Conducted	$\pm 0.42\text{dB}$
Occupied Bandwidth	Conducted	$\pm 1.5\%$
Frequency Stability	Conducted	2.3%
Transmitter Spurious Emissions	Conducted	$\pm 0.42\text{dB}$
Transmitter Spurious Emissions	Radiated	30-200MHz $\pm 4.52\text{dB}$
		0.2-1GHz $\pm 5.56\text{dB}$
		1-6GHz $\pm 3.84\text{dB}$
		6-18GHz $\pm 3.92\text{dB}$



**1.7 Test Equipment List and Details**

No.	Description	Manufacturer	Model	Serial No.	Cal Date	Due. Date
SEMT-1075	Communication Tester	Rohde & Schwarz	CMW500	148650	2020-04-28	2021-04-27
SEMT-1063	GSM Tester	Rohde & Schwarz	CMU200	114403	2020-04-28	2021-04-27
SEMT-1072	Spectrum Analyzer	Agilent	E4407B	MY41440400	2020-04-28	2021-04-27
SEMT-1079	Spectrum Analyzer	Agilent	N9020A	US47140102	2020-04-28	2021-04-27
SEMT-1080	Signal Generator	Agilent	83752A	3610A01453	2020-04-28	2021-04-27
SEMT-1081	Vector Signal Generator	Agilent	N5182A	MY47070202	2020-04-28	2021-04-27
SEMT-1028	Power Divider	Weinschel	1506A	PM204	2020-04-28	2021-04-27
SEMT-1082	Power Divider	RF-Lambda	RFLT4W5M18G	14110400027	2020-04-28	2021-04-27
SEMT-1031	Spectrum Analyzer	Rohde & Schwarz	FSP30	836079/035	2020-04-28	2021-04-27
SEMT-1007	EMI Test Receiver	Rohde & Schwarz	ESVB	825471/005	2020-04-28	2021-04-27
SEMT-1008	Amplifier	Agilent	8447F	3113A06717	2020-04-28	2021-04-27
SEMT-1043	Amplifier	C&D	PAP-1G18	2002	2020-04-28	2021-04-27
SEMT-1069	Loop Antenna	Schwarz beck	FMZB 1516	9773	2019-05-05	2021-05-04
SEMT-1068	Broadband Antenna	Schwarz beck	VULB9163	9163-333	2019-05-05	2021-05-04
SEMT-1042	Horn Antenna	ETS	3117	00086197	2019-05-05	2021-05-04
SEMT-1121	Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170582	2019-05-05	2021-05-04
SEMT-1168	Pre-amplifier	Direction Systems Inc.	PAP-0126	14141-12838	2020-04-28	2021-04-27
SEMT-1169	Pre-amplifier	Direction Systems Inc.	PAP-2640	14145-14153	2020-04-28	2021-04-27
SEMT-1163	Spectrum Analyzer	Rohde & Schwarz	FSP40	100612	2020-04-28	2021-04-27
SEMT-1170	DRG Horn Antenna	A.H. SYSTEMS	SAS-574	571	2019-05-05	2021-05-04
SEMT-1166	Power Limiter	Agilent	N9356B	MY45450376	2020-04-28	2021-04-27
SEMT-1048	RF Limiter	ATTEN	AT-BSF-2400~2500	/	2020-04-28	2021-04-27
SEMT-1055	RF Limiter	ATTEN	AT-BSF-0820~0920	/	2020-04-28	2021-04-27
SEMT-1056	RF Limiter	ATTEN	AT-BSF-1710~1910	/	2020-04-28	2021-04-27
SEMT-1076	RF Switcher	Top Precision	RCS03-A2	/	2020-04-28	2021-04-27
SEMT-C001	Cable	Zheng DI	LL142-07-07-10M(A)	/	2020-03-17	2021-03-16
SEMT-C002	Cable	Zheng DI	ZT40-2.92J-2.92J-6M	/	2020-03-17	2021-03-16



SEMT-C003	Cable	Zheng DI	ZT40-2.92J-2.92J-2.5M	/	2020-03-17	2021-03-16
SEMT-C004	Cable	Zheng DI	2M0RFC	/	2020-03-17	2021-03-16
SEMT-C005	Cable	Zheng DI	1M0RFC	/	2020-03-17	2021-03-16
SEMT-C006	Cable	Zheng DI	1M0RFC	/	2020-03-17	2021-03-16

Software List			
Description	Manufacturer	Model	Version
EMI Test Software (Radiated Emission)*	Farad	EZ-EMC	RA-03A1
LTE Test System*	Tonscend	JS1120-1	V2.5

\*Remark: indicates software version used in the compliance certification testing



## 2. SUMMARY OF TEST RESULTS

FCC Rules	Description of Test Item	Result
§1.1307, §2.1091	RF Exposure	Compliant
§22.913(a)	RF Output Power	Compliant
/	Peak-to-average Ratio (PAR) of Transmitter	Compliant
§22.917(b)	Emission Bandwidth	Compliant
§22.917(a)	Spurious Emissions at Antenna Terminal	Compliant
§22.917(a)	Spurious Radiation Emissions	Compliant
§2.917(a)	Out of Band Emissions	Compliant
§22.355	Frequency Stability	Compliant



### **3. RF Exposure**

---

#### **3.1 Standard Applicable**

According to §1.1307 and §2.1091, the mobile transmitter must comply the RF exposure requirements.

#### **3.2 Test Result**

This product complied with the requirement of the RF exposure, please see the RF exposure report.

## 4. RF Output Power


---

### 4.1 Standard Applicable

According to §22.913(a)(2), the ERP of mobile and portable stations transmitters and auxiliary test transmitters must not exceed 7 Watts.

### 4.2 Test Procedure

- Conducted output power test method:



- Radiated power test method:

1. The setup of EUT is according with per ANSI/TIA Standard 603E and ANSI C63.26 measurement procedure.
2. The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.
3. The frequency range up to tenth harmonic of the fundamental frequency was investigated.
4. Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution.

### 4.3 Summary of Test Results/Plots



**Max. Radiated Power:**

FDD-LTE Band 5

Channel Bandwidth: 1.4 MHz					
Modulation	Channel	Antenna Polar	E.i.r.p [dBm]	Limit (dBm)	Verdict
QPSK	LCH	V	20.15	<38.45	PASS
		H	14.78		
	MCH	V	20.39		PASS
		H	13.97		
	HCH	V	20.53		PASS
		H	13.32		
Channel Bandwidth: 3 MHz					
Modulation	Channel	Antenna Polar	E.i.r.p [dBm]	Limit (dBm)	Verdict
QPSK	LCH	V	19.97	<38.45	PASS
		H	13.02		
	MCH	V	19.56		PASS
		H	13.11		
	HCH	V	19.37		PASS
		H	13.02		
Channel Bandwidth: 5 MHz					
Modulation	Channel	Antenna Polar	E.i.r.p [dBm]	Limit (dBm)	Verdict
QPSK	LCH	V	19.84	<38.45	PASS
		H	13.05		
	MCH	V	19.64		PASS
		H	13.16		
	HCH	V	19.47		PASS
		H	13.43		
Channel Bandwidth: 10 MHz					
Modulation	Channel	Antenna Polar	E.i.r.p [dBm]	Limit (dBm)	Verdict
QPSK	LCH	V	19.67	<38.45	PASS
		H	13.01		
	MCH	V	19.34		PASS
		H	13.55		
	HCH	V	19.14		PASS
		H	13.23		

**Max. Conducted Output Power**

Please refer to Appendix A: Average Power Output Data

Test result: Pass

## 5. Peak-to-average Ratio (PAR) of Transmitter

### 5.1 Standard Applicable


The peak-to-average power ratio (PAPR) of the transmitter output power must not exceed 13 dB. The PAPR measurements should be made using either an instrument with complementary cumulative distribution function (CCDF) capabilities to determine that PAPR will not exceed 13 dB for more than 0.1 percent of the time or other Commission approved procedure. The measurement must be performed using a signal corresponding to the highest PAPR expected during periods of continuous transmission.

### 5.2 Test Procedure

According with KDB 971168

1. The signal analyzer's CCDF measurement profile is enabled
2. Frequency = carrier center frequency
3. Measurement BW > Emission bandwidth of signal
4. The signal analyzer was set to collect one million samples to generate the CCDF curve
5. The measurement interval was set depending on the type of signal analyzed. For continuous signals (>98% duty cycle), the measurement interval was set to 1ms. For burst transmissions, the spectrum analyzer is set to use an internal "RF Burst" trigger that is synced with an incoming pulse and the measurement interval is set to less than the duration of the "on time" of one burst to ensure that energy is only captured during a time in which the transmitter is operating at maximum power

Test Configuration for the emission bandwidth testing:



### 5.3 Summary of Test Results

Please refer to Appendix B: Peak-to-Average Ratio

Test result: Pass

## 6. Emission Bandwidth

---


### 6.1 Standard Applicable

According to §22.917(b), the emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

### 6.2 Test Procedure

According to §22.917(b), the emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

Test Configuration for the emission bandwidth testing:



### 6.3 Summary of Test Results/Plots

Please refer to Appendix C: 26dB Bandwidth and Occupied Bandwidth

Test result: Pass



## 7. Out of Band Emissions at Antenna Terminal

---


### 7.1 Standard Applicable

According to §22.917(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log(P)$  dB.

### 7.2 Test Procedure

The RF output terminal of the transmitter was connected to the input of the spectrum analyzer via a suitable attenuation. The RBW of the spectrum analyzer was set to 100kHz and 1MHz for the scan frequency from 30MHz to 1GHz and the scan frequency from 1GHz to up to 10<sup>th</sup> harmonic.

Test Configuration for the out of band emissions testing:



### 7.3 Summary of Test Results/Plots

Please refer to Appendix D & E: Band Edge & Conducted Spurious Emission

Test result: Pass

## 8. Spurious Radiated Emissions

---

### 8.1 Standard Applicable

According to §22.917(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log(P)$  dB.

### 8.2 Test Procedure

1. The setup of EUT is according with per ANSI/TIA-603-E and ANSI C63.4-2014 measurement procedure.
2. The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.
3. The frequency range up to tenth harmonic of the fundamental frequency was investigated.
4. Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution.

Spurious attenuation limit in dB =  $43 + 10 \log_{10}(\text{power out in Watts})$

### 8.3 Summary of Test Results/Plots


*Note: 1. this EUT was tested in 3 orthogonal positions and the worst case position data was reported.*

*2. All test modes (different bandwidth and different modulation) are performed, but only the worst case is recorded in this report.*



➤ Spurious Emissions Below 1GHz


Test Mode	FDD_LTE Band 5	Polarity:	Horizontal
-----------	----------------	-----------	------------



No.	Frequency (MHz)	Reading (dBm)	Correct (dB)	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	49.1866	-77.65	0.75	-76.90	-13.00	-63.90	ERP
2	118.6014	-77.57	-2.18	-79.75	-13.00	-66.75	ERP
3	382.5879	-75.38	4.23	-71.15	-13.00	-58.15	ERP



Test Mode	FDD_LTE Band 5	Polarity:	Vertical
-----------	----------------	-----------	----------



No.	Frequency (MHz)	Reading (dBm)	Correct (dB)	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	59.6493	-73.65	-1.45	-75.10	-13.00	-62.10	ERP
2	118.6014	-76.28	-2.18	-78.46	-13.00	-65.46	ERP
3	454.3100	-76.59	5.34	-71.25	-13.00	-58.25	ERP



➤ Spurious Emissions Above 1GHz

For FDD\_LTE Band 5 Mode

Frequency	Reading	Correct	Result	Limit	Margin	Polar
(MHz)	(dBm)	dB	(dBm)	(dBm)	(dB)	H/V
Low Channel (824.7MHz)						
1649.40	-36.14	4.94	-31.2	-13	-18.2	H
2474.10	-42.57	8.46	-34.11	-13	-21.11	H
1649.40	-34.73	4.94	-29.79	-13	-16.79	V
2474.10	-41.95	8.46	-33.49	-13	-20.49	V
Middle Channel (836.5MHz)						
1673.00	-37.35	5.11	-32.24	-13	-19.24	H
2509.50	-44.58	8.54	-36.04	-13	-23.04	H
1673.00	-37.37	5.11	-32.26	-13	-19.26	V
2509.50	-43.19	8.54	-34.65	-13	-21.65	V
High Channel (848.3MHz)						
1696.60	-37.71	5.25	-32.46	-13	-19.46	H
2544.90	-42.9	8.57	-34.33	-13	-21.33	H
1696.60	-36.93	5.25	-31.68	-13	-18.68	V
2544.90	-43.43	8.57	-34.86	-13	-21.86	V

Note: Result=Reading+ Correct, Margin= Result- Limit

Note: Testing is carried out with frequency rang 9kHz to the tenth harmonics, other than listed in the table above are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.



## 9. Frequency Stability

---

### 9.1 Standard Applicable

According to §22.355, the limit is 2.5ppm.

### 9.2 Test Procedure

According to §2.1055, the following test procedure was performed.

The Frequency Stability is measured directly with a Frequency Domain Analyzer. Frequency Deviation in ppm is calculated from the measured peak to peak value.

The Carrier Frequency Stability over Power Supply Voltage and over Temperature is measured with a Frequency Domain Analyzer in histogram mode

### 9.3 Summary of Test Results/Plots

Note: 1.Normal Voltage NV=DC3.6V; Low Voltage LV=DC3.2V;High Voltage HV=DC4.0V

Please refer to Appendix F: Frequency Stability

Test result: Pass

\*\*\*\*\* END OF REPORT \*\*\*\*\*