

# TEST REPORT

**Application No.:** KSEM2012001572CR  
**FCC ID:** 2AL8S-0235C4CF  
**IC:** 25987-0235C4CF  
**Applicant:** Zhejiang Uniview Technologies Co., Ltd.  
**Address of Applicant:** 88 Jiangling Road, Xixing Town, Binjiang District, Hangzhou City  
**Manufacturer:** Zhejiang Uniview Technologies Co., Ltd.  
**Address of Manufacturer:** 88 Jiangling Road, Xixing Town, Binjiang District, Hangzhou City  
**Equipment Under Test (EUT):**  
**EUT Name:** Face Recognition Access Control Terminal  
**Model No.:** OET-213H,OET-213H-NB,OET-213H-xxxxxxx-yyy-yyyy-zzzzzzzz  
 OET-213KH ,OET-213KH-NB,OET-213KH-xxxxxxx-yyy-yyyy-zzz  
 ("x" "y""z" can be 0-9,A-Z,a-z or blank denoting target regional; "-" may be blank)  
 ☐ Please refer to section 2 of this report which indicates which model was actually tested and which were electrically identical.  
**Standard(s):** 47 CFR Part 15, Subpart C 15.225  
 RSS-210 Issue 10 December 2019  
 RSS-Gen Issue 5, March 2019 Amendment 1  
**Date of Receipt:** 2020-04-01;2020-04-23;2020-12-04  
**Date of Test:** 2020-04-01 to 2020-04-02;2020-04-28;2020-12-08 to 2020-12-09  
**Date of Issue:** 2020-12-19

<b>Test Result:</b>	<b>Pass*</b>
---------------------	--------------

\* In the configuration tested, the EUT complied with the standards specified above.

Eric Lin  
EMC Lab Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.  
**Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN\_Doccheck@sgs.com**

No.10, Weiye Road, Innovation Park, Kunshan, Jiangsu, China 215300  
 中国·江苏·昆山市留学院创业园伟业路10号 邮编 215300

t(86-512)57355888 f(86-512)57370818 www.sgs.com.cn  
 t(86-512)57355888 f(86-512)57370818 sgs.china@sgs.com





**Compliance Certification Services  
(Kunshan) Inc.**

Report No.: KSEM201200157201  
Page: 2 of 20

For IC Model: OET-213KH ,OET-213KH-NB

Revision Record			
Version	Description	Date	Remark
00	Update report	2020-12-19	Base on KSEM2004000365CR (Original Report No.: KSEM2004000217CR)

<b>Authorized for issue by:</b>			
			
		<hr/>	
		<b>Terry Hou / Project Engineer</b>	
			
		<hr/>	
		<b>Eric Lin / Reviewer</b>	

## 2 Test Summary

Radio Spectrum Technical Requirement				
Item	FCC Requirement	IC Requirement	Method	Result
Antenna Requirement	47 CFR Part 15, Subpart C 15.225	N/A	RSS-210 Issue 10 December 2019	Customer Declaration

Radio Spectrum Matter Part				
Item	FCC Requirement	IC Requirement	Method	Result
Conducted Emissions at AC Power Line (150kHz-30MHz)	47 CFR Part 15, Subpart C 15.225	RSS-210 Issue 10 December 2019	ANSI C63.10 (2013) Section 6.2	Pass
20dB Bandwidth	47 CFR Part 15, Subpart C 15.225	RSS-210 Issue 10 December 2019	ANSI C63.10 (2013) Section 6.9	Pass
Emission Mask	47 CFR Part 15, Subpart C 15.225	RSS-210 Issue 10 December 2019	ANSI C63.10 (2013) Section 6.4	*Pass
Frequency tolerance	47 CFR Part 15, Subpart C 15.225	RSS-210 Issue 10 December 2019	ANSI C63.10 (2013) Section 6.8	Pass
Radiated Emissions(9kHz-30MHz)	47 CFR Part 15, Subpart C 15.225	RSS-210 Issue 10 December 2019	ANSI C63.10 (2013) Section 6.4&6.5	Pass
Radiated Emissions(30MHz-1GHz)	47 CFR Part 15, Subpart C 15.225	RSS-210 Issue 10 December 2019	ANSI C63.10 (2013) Section 6.4&6.5	Pass
99% Bandwidth	-	RSS-210 Issue 10 December 2019	RSS-Gen Section 6.7	Pass

**Remark \***: The test level of the fundamental signal is below the limit of general spurious emission, so the test item doesn't be performed.

### Declaration of EUT Family Grouping:

**Note 1:** This test report KSEM200400036501 only update EUT photo is valid with the original test report KSEM200400021701.

**Note 2:** This test report KSEM201200157201 only retest RE.

**Note 3:** There are series models mentioned in this report, and they are the similar in electrical and electronic characters. Only the model OET-213KH was tested since their differences were the model number and regional difference.

### 3 Contents

	Page
<b>1 COVER PAGE .....</b>	<b>1</b>
<b>2 TEST SUMMARY .....</b>	<b>4</b>
<b>3 CONTENTS .....</b>	<b>5</b>
<b>4 GENERAL INFORMATION .....</b>	<b>6</b>
4.1 DETAILS OF E.U.T. ....	6
4.2 DESCRIPTION OF SUPPORT UNITS.....	6
4.3 MEASUREMENT UNCERTAINTY .....	6
4.4 TEST LOCATION .....	7
4.5 TEST FACILITY .....	7
4.6 ABNORMALITIES FROM STANDARD CONDITIONS .....	7
<b>5 EQUIPMENT LIST .....</b>	<b>8</b>
<b>6 RADIO SPECTRUM TECHNICAL REQUIREMENT .....</b>	<b>9</b>
6.1 ANTENNA REQUIREMENT .....	9
<b>7 RADIO SPECTRUM MATTER TEST RESULTS .....</b>	<b>10</b>
7.1 RADIATED EMISSIONS(9KHZ-30MHZ) .....	10
7.2 RADIATED EMISSIONS(30MHZ-1GHZ) .....	14
<b>8 TEST SETUP PHOTOGRAPHS .....</b>	<b>20</b>
<b>9 EUT CONSTRUCTIONAL DETAILS .....</b>	<b>20</b>

## 4 General Information

### 4.1 Details of E.U.T.

Power supply:	DC 12V by adapter
Serial Number:	210235C4S4
Firmware Version:	B2209.3.19.CLA002LJ02
Test voltage:	AC 120V/60Hz
Operation Frequency	13.56MHz
Modulation Technique:	ASK
Antenna Type:	Loop antenna
Antenna Gain	-5dBi (Provided by the manufacturer)
Number of Channel:	1

### 4.2 Description of Support Units

Description	Manufacturer	Model No.	Serial No.
Adapter	CHANNEL WELL	KPL-040F-VI	/

Parameter of Adapter:

Adapter	Rated Input	AC100V-240V 50/60Hz 1700mA
	Rated Output	12V,3,33A

### 4.3 Measurement Uncertainty

No.	Item	Measurement Uncertainty
1	Radio Frequency	$\pm 8.4 \times 10^{-8}$
2	Timeout	$\pm 2s$
3	Duty cycle	$\pm 0.37\%$
4	Occupied Bandwidth	$\pm 3\%$
5	RF conducted power	$\pm 0.6dB$
6	RF power density	$\pm 2.84dB$
7	Conducted Spurious emissions	$\pm 0.75dB$
8	RF Radiated power	$\pm 4.6dB$ (Below 1GHz)
		$\pm 4.1dB$ (Above 1GHz)
9	Radiated Spurious emission test	$\pm 4.2dB$ (Below 30MHz)
		$\pm 4.4dB$ (30MHz-1GHz)
		$\pm 4.8dB$ (1GHz-18GHz)
		$\pm 5.2dB$ (Above 18GHz)
10	Temperature test	$\pm 1^{\circ}C$
11	Humidity test	$\pm 3\%$
12	Supply voltages	$\pm 1.5\%$
13	Time	$\pm 3\%$

Note: The measurement uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

#### 4.4 Test Location

All tests were performed at:

Compliance Certification Services (Kunshan) Inc.

All measurement facilities used to collect the measurement data are located at  
No.10 Weiye Rd, Innovation park, Eco&Tec, Development Zone, Kunshan City, Jiangsu, China.

No tests were sub-contracted.

#### 4.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **CNAS (No. CNAS L4354)**

CNAS has accredited Compliance Certification Services (Kunshan) Inc. to ISO/IEC 17025:2017 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

- **A2LA (Certificate No. 2541.01)**

Compliance Certification Services (Kunshan) Inc. is accredited by the American Association for Laboratory Accreditation (A2LA). Certificate No. 2541.01.

- **FCC (Designation Number: CN1172)**

Compliance Certification Services Inc. has been recognized as an accredited testing laboratory.  
Designation Number: CN1172.

- **ISED (CAB Identifier: CN0072)**

Compliance Certification Services (Kunshan) Inc. has been recognized by Innovation, Science and Economic Development (ISED) Canada as an accredited testing laboratory.

CAB Identifier: CN0072.

- **VCCI (Member No.: 1938)**

The 3m and 10m Semi-anechoic chamber and Shielded Room of Compliance Certification Services (Kunshan) Inc. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-1600, C-1707, T-1499, G-10216 respectively.

None

#### 4.6 Abnormalities from Standard Conditions

None

## 5 Equipment List

Item	Equipment	Manufacturer	Model	Serial Number	Cal Date	Cal. Due Date
<b>Conducted Emission at Mains Terminals (150kHz-30MHz)</b>						
1	EMI Test Receive	R&S	ESCI	100781	02/24/2020	02/23/2021
2	LISN	R&S	ENV216	101604	10/24/2019	10/23/2020
3	LISN	Schwarzbeck	NNLK 8129	8129-143	10/24/2019	10/23/2020
4	Pulse Limiter	R&S	ESH3-Z2	100609	02/24/2020	02/23/2021
5	CE test Cable	Thermax	/	14	12/24/2019	12/23/2020
<b>RF Radiated Test</b>						
1	Spectrum Analyzer	R&S	FSV40	101493	01/08/2020	01/07/2021
2	Signal Generator	Agilent	E8257C	MY43321570	10/24/2019	10/23/2020
3	Signal Generator	Agilent	E8257C	MY43321570	10/10/2020	10/18/2021
4	Loop Antenna	Schwarzbeck	HXYZ9170	9170-108	02/24/2020	02/23/2021
5	Bilog Antenna	TESEQ	CBL 6112D	35403	06/22/2019	06/21/2020
6	Bilog Antenna	TESEQ	CBL 6112D	35403	06/21/2020	06/20/2021
7	Bilog Antenna	SCHWARZBECK	VULB9160	9160-3342	04/29/2019	04/28/2021
8	Horn-antenna(1-18GHz)	Schwarzbeck	BBHA9120D	267	11/04/2018	11/03/2020
9	Horn-antenna(1-18GHz)	Schwarzbeck	BBHA9120D	267	10/26/2020	10/25/2022
10	Horn-antenna(1-18GHz)	ETS-LINDGREN	3117	00143290	02/25/2019	02/24/2021
11	Horn Antenna(18-40GHz)	Schwarzbeck	BBHA9170	BBHA9170171	02/27/2018	02/26/2021
12	Pre-Amplifier(30MHz~18GHz)	CCSRF	AMP1277	1	12/19/2019	12/18/2020
13	Pre-Amplifier(30MHz~18GHz)	CCSRF	AMP1277	1	10/19/2020	10/18/2021
14	Pre-Amplifier(0.1~26.5GHz)	EMCI	EMC012645	980060	07/03/2019	07/02/2020
15	Pre-Amplifier(0.1~26.5GHz)	EMCI	EMC012645	980060	04/21/2020	04/20/2021
16	Low Pass Filter	MICRO-TRONICS	VLFX-950	RV142900829	N.C.R	N.C.R
17	High Pass Filter	Mini-Circuits	VHF-1200	15542	N.C.R	N.C.R
18	Filter (5450MHz~5770 MHz)	MICRO-TRONICS	BRC50704-01	2	N.C.R	N.C.R
19	Filter (5690 MHz~5930 MHz)	MICRO-TRONICS	BRC50705-01	4	N.C.R	N.C.R
20	Filter (5150 MHz~5350 MHz)	MICRO-TRONICS	BRC50703-01	2	N.C.R	N.C.R
21	Filter (885 MHz~915 MHz)	MICRO-TRONICS	BRM14698	1	N.C.R	N.C.R
22	Filter (815 MHz~860 MHz)	MICRO-TRONICS	BRM14697	1	N.C.R	N.C.R
23	Filter (1745 MHz~1910 MHz)	MICRO-TRONICS	BRM14700	1	N.C.R	N.C.R
24	Filter (1922 MHz~1977 MHz)	MICRO-TRONICS	BRM50715	1	N.C.R	N.C.R
25	Filter (2550 MHz)	MICRO-TRONICS	HPM13362	5	N.C.R	N.C.R
26	Filter (1532 MHz~1845 MHz)	MICRO-TRONICS	BRM50713	1	N.C.R	N.C.R
27	Filter (2.4GHz)	MICRO-TRONICS	BRM50701	5	N.C.R	N.C.R
28	RE test cable	/	RE01-RE04	/	04/21/2020	04/22/2021
29	Software	Fard technology co.,ltd	EZ-EMC	1.1.1.2	N/A	N/A



## 6 Radio Spectrum Technical Requirement

### 6.1 Antenna Requirement

#### 6.1.1 Test Requirement:

47 CFR Part 15, Subpart C 15.203

#### 6.1.2 Conclusion

Standard Requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit permanently attached antenna or of an so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

EUT Antenna:

The antenna is loop antenna integrated on the main PCB and no consideration of replacement.

Antenna location: Refer to Appendix (Internal Photos)

## 7 Radio Spectrum Matter Test Results

### 7.1 Radiated Emissions(9kHz-30MHz)

Test Requirement 47 CFR Part 15, Subpart C 15.225(d) & 15.209

Test Method: ANSI C63.10 (2013) Section 6.4&6.5

Limit:

Frequency(MHz)	Field strength (microvolts/meter)	Limit (dBuV/m)	Detector	Measurement Distance (meters)
0.009-0.490	2400/F(kHz)	-	-	300
0.490-1.705	24000/F(kHz)	-	-	30
1.705-30	30	-	-	30
30-88	100	40.0	QP	3
88-216	150	43.5	QP	3
216-960	200	46.0	QP	3
960-1000	500	54.0	QP	3
Above 1000	500	54.0	AV	3

NOTE:

(1) For test distance other than what is specified, but fulfilling the requirements of section 15.31(f) (2) the field strength is calculated by adding additionally an extrapolation factor of 40dB/decade (inverse linear distance for field strength measurements).

So the Distance Extrapolation Factor in dB is  $40 \cdot \log(D_{TEST} / D_{SPEC})$  where  $D_{TEST}$  = Test Distance and  $D_{SPEC}$  = Specified Distance.

Field strength limit (dBuV/m)@test distance= Field strength limit (dBuV/m)@specified distance +Distance Extrapolation Factor

(2) The lower limit shall apply at the transition frequencies.

#### 7.1.1 E.U.T. Operation


Operating Environment:

Temperature: 22 °C Humidity: 50 % RH Atmospheric Pressure: 1002 mbar

Test mode: a : TX mode\_Keep the EUT in transmitting with modulation mode with Temperature module 1.

b: TX mode\_Keep the EUT in transmitting with modulation mode with Temperature module 2.

### 7.1.2 Test Setup Diagram




### 7.1.3 Measurement Procedure and Data

For testing performed with the loop antenna, the center of the loop was positioned 1 m above the ground and positioned with its plane vertical at the specified distance from the EUT. During testing the loop was rotated about its vertical axis for maximum response at each azimuth and also investigated with the loop positioned in the horizontal plane. Only the worst position of vertical was shown in the report.

Mode a:


150.0 dBuV/m



Item	Freq.	Read Level	Correct Factor	Result Level@3m	Result Level@SPEC	Limit Line@SPEC	Over Limit	Detector
(Mark)	(MHz)	(dB $\mu$ V)	(dB/m)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	0.1904	29.22	15.12	44.34	-35.66	22.01	-57.67	QP
2	0.442	28.62	15.25	43.87	-36.13	14.69	-50.82	QP
3	0.51	29.45	15.26	44.71	4.71	33.45	-28.74	QP
4	0.739	27.43	14.92	42.35	2.35	30.24	-27.89	QP
5	1.5766	25.99	15.55	41.54	1.54	23.68	-22.14	QP
6	3.4174	21.8	15.5	37.3	-2.7	29.5	-32.2	QP
7	13.6227	42.35	15.49	57.84	17.84	29.5	-11.66	PK

Note: 0.009-0.49MHz Distance factor is 80, 0.49MHz~30MHz Distance factor is 40.

Mode b:



Item	Freq.	Read Level	Correct Factor	Result Level@3m	Result Level@S PEC	Limit Line@SPE C	Over Limit	Detector
(Mark)	(MHz)	(dBμV)	(dB/m)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	0.018	26.75	15.13	41.88	-38.12	42.48	-80.6	QP
2	0.0354	23.26	15.11	38.37	-41.63	36.61	-78.24	QP
3	0.2316	26.76	15.16	41.92	-38.08	20.31	-58.39	QP
4	0.6401	26.69	15.26	41.95	1.95	31.49	-29.54	QP
5	0.9183	25.07	15.33	40.4	0.4	28.36	-27.96	QP
6	1.619	23.46	15.44	38.9	-1.1	23.45	-24.55	QP
7	13.6227	42.85	15.49	58.34	18.34	29.5	-11.16	PK

Note: 0.009-0.49MHz Distance factor is 80, 0.49MHz~30MHz Distance factor is 40.

## 7.2 Radiated Emissions(30MHz-1GHz)

Test Requirement 47 CFR Part 15, Subpart C 15.225(d) & 15.209  
 Test Method: ANSI C63.10 (2013) Section 6.4&6.5  
 Limit:

Frequency	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
30MHz-88MHz	100	40.0	Quasi-peak	3
88MHz-216MHz	150	43.5	Quasi-peak	3
216MHz-960MHz	200	46.0	Quasi-peak	3
960MHz-1GHz	500	54.0	Quasi-peak	3

### 7.2.1 E.U.T. Operation


Operating Environment:

Temperature: 22 °C Humidity: 50 % RH Atmospheric Pressure: 1002 mbar

Test mode: a : TX mode\_Keep the EUT in transmitting with modulation mode with Temperature module 1.

b: TX mode\_Keep the EUT in transmitting with modulation mode with Temperature module 2.

### 7.2.2 Test Setup Diagram




### 7.2.3 Measurement Procedure and Data

- a. The EUT was placed on the top of a rotating table 12mm above the ground for below 1GHz at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- g. The radiation measurements are performed in X, Y, Z axis positioning. And found the X axis positioning which it is worse case, only the test worst case mode is recorded in the report.

Remark: Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor

Mode:a; Polarization:Horizontal

100.0 dBuV/m




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	30.9700	2.02	25.50	27.52	40.00	-12.48	QP
2	450.0100	4.14	24.51	28.65	46.00	-17.35	QP
3	669.2300	0.19	27.36	27.55	46.00	-18.45	QP
4	750.7100	1.76	27.89	29.65	46.00	-16.35	QP
5	850.6200	1.20	28.48	29.68	46.00	-16.32	QP
6	900.0900	2.10	28.74	30.84	46.00	-15.16	QP



Mode:a; Polarization:Vertical


100.0 dBuV/m



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	149.3100	9.46	20.18	29.64	43.50	-13.86	QP
2	222.0600	14.01	17.72	31.73	46.00	-14.27	QP
3	350.1000	11.50	22.78	34.28	46.00	-11.72	QP
4	445.1600	9.68	24.44	34.12	46.00	-11.88	QP
5	706.0900	7.77	27.76	35.53	46.00	-10.47	QP
6	900.0900	8.37	28.74	37.11	46.00	-8.89	QP

Mode:b; Polarization:Horizontal


100.0 dBuV/m



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	140.5800	6.54	19.90	26.44	43.50	-17.06	QP
2	324.8800	9.44	21.71	31.15	46.00	-14.85	QP
3	375.3200	7.97	23.31	31.28	46.00	-14.72	QP
4	531.4900	6.59	25.65	32.24	46.00	-13.76	QP
5	763.3200	5.25	27.97	33.22	46.00	-12.78	QP
6	935.0100	7.40	28.99	36.39	46.00	-9.61	QP

Mode:b; Polarization:Vertical

100.0 dBuV/m



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	154.1600	7.65	19.88	27.53	43.50	-15.97	QP
2	308.3900	9.18	21.02	30.20	46.00	-15.80	QP
3	586.7800	5.60	26.41	32.01	46.00	-13.99	QP
4	721.6100	5.73	27.80	33.53	46.00	-12.47	QP
5	850.6200	6.96	28.48	35.44	46.00	-10.56	QP
6	891.3600	6.77	28.70	35.47	46.00	-10.53	QP

## 8 Test Setup Photographs

Refer to the < Test Setup photos-FCC>.

## 9 EUT Constructional Details

Refer to the < External Photos > & < Internal Photos >.

**- End of the Report -**