

承 认 书

APPROVAL SHEET

客户名称

CUSTOMER NAME:

产品名称

PRODUCT NAME: 2.4/5.8G PIFA Antenna

客户料号

CUSTOMER P/N:

优比电子料号

Youbi P/N: UB01C210F2D385aA REV: A

	MANUFACTURER SIGNATURE	CUSTOMER SIGNATURE
CHECKED BY:	Eddy 	
APPROVED BY:	工程专用章 Changxing. Liu	
DATE:	2023/6/17	

Modification History

Version	Content Revision	Issued by	Date
A	Original version	Eddy	2023-6-17

Content


<i>Item</i>	<i>Description</i>
1.-----	Electrical Specification
2.-----	Test Items and Equipment
3.-----	S Parameter
4.-----	Efficiency and Gain
5.-----	Radiation Pattern
6.-----	Active test data
7.-----	Antenna installation diagram
8.-----	Mechanical Specification
9.-----	Packaging

1. Electrical Specification

Characteristics	Specifications	Unit
Outline Dimensions	33.45x29.2,L210	mm
Frequency	2400-2500;5150-5850	MHz
Impedance	50	Ω
VSWR	< 2	
Polarization	Linear Polarization	
Gain	1 REF	dBi
Efficiency	>30	%
Connector Type	RF 1	
Operating temperature	-20°C~+85°C	
Storage Temp	-20°C~+50°C	

2. Test Items and Equipment


	Test items	Test equipment
S Parameter	1.Return Loss 2.VSWR	Network analyzer (Agilent E5071B)
The whole machine of Passive parameters	1.Frequency 2.Gain 3.Radiation Pattern	1.3D microwave darkroom (5m*5m*5m) 2.Network analyzer (Agilent E5071B)
The whole machine of Active parameters	1.TRP 2.TIS	1.3D microwave darkroom (5m*5m*5m) 2.Comprehensive test instrument (CMW500)



3. S Parameter



Frequency (MHz)	Return Loss (dB)	VSWR
2400	-13.94	1.50
2450	-17.34	1.31
2500	-15.21	1.42
5150	-15.09	1.42
5350	-17.55	1.30
5725	-18.86	1.26
5850	-11.94	1.67

* Voltage Standing Wave Ratio(VSWR)
Return Loss(RL)
 $RL = 20 * \log_{10}[(VSWR+1)/(VSWR-1)]$




4. Efficiency and Gain

Frequency (MHz)	2400	2450	2500	5150	5510	5850
Efficiency (%)	52.75	54.89	50.83	38.55	40.18	36.36
Gain (dBi)	1.69	1.87	2.11	0.97	0.48	0.34




5. Radiation Pattern


5-1 Antenna 3D Radiation Pattern




2400MHz




5150MHz




2450MHz



5510MHz




2500MHz




5850MHz


5-2 Antenna 2D Radiation Pattern




2400MHz




2450MHz




2500MHz



5150MHz



5510MHz





5850MHz

6. Active test data


Channel	Measurement	Channel	B(11M)	G(54M)	N(MCS7)	Channel	A(54M)
1	TRP	1	13.18	14.46	13.86	36	11.03
6	TRP	6	13.36	14.27	14.11	149	11.83
11	TRP	11	13.36	15.08	13.62	165	11.82
1	TIS(EIRP)	1	-81.55	-73.77	-68.42	36	-72.09
6	TIS(EIRP)	6	-86.93	-74.14	-67.95	149	-70.62
11	TIS(EIRP)	11	-82.94	-73.42	-68.86	165	-72.03

7. Antenna installation diagram



1:天线装贴时靠近左边螺丝柱, 天线装配位置如图。
 2:出线位置如图内红色走线。

9. Packaging



注: 此份包装规范适用于FPC, PCB天线类的线材总长 ≥ 90 mm带ipex和不带ipex产品, 属于通用类型。
 1. **中号纸箱**装10000pcs产品每箱。