

FCC RF Exposure Evaluation

1. Product Information

FCC ID	2AL9D-P10W
Product Name	IP Phone
Test Model	P10W, P11W
Power Supply	Adapter 1: Model: KA0601A-0500600USS Input: 100-240V~, 50/60Hz, 0.2A Max Output: 5V/600mA Adapter 2: Model: KA0601A-0500600USS Input: 100-240V~, 50/60Hz, 0.2A Max Output: 5V/600mA Input: 100-240V~, 50/60Hz, 0.2A Max Output: 5V/600mA
Modulation Type	2.4G WIFI: 802.11b: DSSS 802.11g/802.11n(H20)/802.11n(H40): OFDM 5G WIFI : IEEE 802.11a/ac/n: OFDM
Antenna Type	PIFA Antenna
Antenna Gain	2.4G WIFI: 2.11dBi 5G WIFI : 0.97dBi
Frequency Range	2412 – 2462MHz / 5180 – 5240MHz / 5745 – 5825MHz
Exposure Category	General population/uncontrolled environment
EUT Type	Production Unit
Device Type	Mobile Device

2. Evaluation Method and Limit

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

In accordance with KDB447498D01 for Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneous transmitting antennas incorporated in a host device, based on the calculated/estimated, numerically modelled or measured field strengths or power density, is ≤ 1.0 . The MPE ratio of each antenna is determined at the minimum test separation distance required by the operating configurations and exposure conditions of the host device, according to the ratio of field strengths or power density to MPE limit, at the test frequency. Either the maximum peak or spatially averaged results from measurements or numerical simulations may be used to determine the MPE ratios. Spatial averaging does not apply when MPE is estimated using simple calculations based on far-field plane-wave equivalent conditions. The antenna installation and operating requirements for the host device must meet the minimum test separation distances required by all antennas, in both standalone and simultaneous transmission operations, to satisfy compliance.

3. Limit

3.1 Refer Evaluation Method

[ANSI C95.1-1999](#): IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz.

[FCC KDB publication 447498 D01 General RF Exposure Guidance v06](#): Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies.

[FCC CFR 47 part1 1.1310](#): Radiofrequency radiation exposure limits.

[FCC CFR 47 part2 2.1091](#): Radiofrequency radiation exposure evaluation: mobile devices

3. 2 Limit

Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	6
3.0 – 30	1842/f	4.89/f	(900/f ²)*	6
30 – 300	61.4	0.163	1.0	6
300 – 1500	/	/	f/300	6
1500 – 100,000	/	/	5	6

Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	30
3.0 – 30	824/f	2.19/f	(180/f ²)*	30
30 – 300	27.5	0.073	0.2	30
300 – 1500	/	/	f/1500	30
1500 – 100,000	/	/	1.0	30

F=frequency in MHz

*=Plane-wave equivalent power density

4. MPE Calculation Method

Predication of MPE limit at a given distance
Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S=PG/4\pi R^2$$

Where: S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

5. Antenna Information

P10W can only use antennas certificated as follows provided by manufacturer;

Antenna type and antenna number	Operate frequency band	Maximum antenna gain	Note
PIFA Antenna	2412 MHz – 2462 MHz 5180MHz - 5240MHz 5745MHz - 5825MHz	2.4G WIFI: 2.11dBi 5G WIFI : 0.97dBi	WLAN Antenna

6. Conducted Power Results

[2.4GWIFI Max Conducted Power]

Mode	Channel	Frequency(MHz)	Max Conducted Power(dBm)
IEEE 802.11b	1	2412	15.77
	6	2437	15.84
	11	2462	15.65
IEEE 802.11g	1	2412	14.14
	6	2437	14.31
	11	2462	14.51
IEEE 802.11n HT20	1	2412	14.36
	6	2437	14.42
	11	2462	14.19
IEEE 802.11n HT40	3	2422	14.64
	6	2437	14.42
	9	2452	14.44

[5.2GWIFI Max Conducted Power]

Mode	Channel	Frequency (MHz)	Max Conducted Power(dBm)
11A	36	5180	12.46
	40	5200	12.79
	48	5240	12.94
11N20 SISO	36	5180	12.36
	40	5200	12.77
	48	5240	12.90
11N40 SISO	38	5190	12.82
	46	5230	12.97
11AC20 SISO	36	5180	12.48
	40	5200	12.84
	48	5240	12.96
11AC40 SISO	38	5190	12.88
	46	5230	13.04
11AC80 SISO	42	5210	12.75

[5.8GWIFI Max Conducted Power]

Mode	Channel	Frequency (MHz)	Max Conducted Power(dBm)
11A	149	5745	11.66
	157	5785	10.74
	165	5825	7.98
11N20 SISO	149	5745	11.49
	157	5785	10.41
	165	5825	8.43
11N40 SISO	151	5755	11.49
	159	5795	10.04
11AC20 SISO	149	5745	11.52
	157	5785	10.61
	165	5825	8.13
11AC40 SISO	151	5755	11.61
	159	5795	10.36
11AC80 SISO	155	5775	11.05

7.Manufacturing Tolerance

<2.4GWLAN >

IEEE 802.11b (Peak)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	15.0	15.0	15.0
Tolerance ±(dB)	1.0	1.0	1.0
IEEE 802.11g (Peak)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	14.0	14.0	14.0
Tolerance ±(dB)	1.0	1.0	1.0
IEEE 802.11n HT20 (Peak)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	14.0	14.0	14.0
Tolerance ±(dB)	1.0	1.0	1.0
IEEE 802.11n HT40 (Peak)			
Channel	Channel 3	Channel 6	Channel 9
Target (dBm)	14.0	14.0	14.0
Tolerance ±(dB)	1.0	1.0	1.0

<5.2GWLAN>

11A (Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	12.0	12.0	12.0
Tolerance ±(dB)	1.0	1.0	1.0
11N20 (Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	12.0	12.0	12.0
Tolerance ±(dB)	1.0	1.0	1.0
11N40 (Average)			
Channel	Channel 38	Channel 46	
Target (dBm)	12.0	12.0	
Tolerance ±(dB)	1.0	1.0	
11AC20 (Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	12.0	12.0	12.0
Tolerance ±(dB)	1.0	1.0	1.0
11AC40 (Average)			
Channel	Channel 38	Channel 46	
Target (dBm)	13.0	13.0	
Tolerance ±(dB)	1.0	1.0	
11AC80 (Average)			
Channel	Channel 42		
Target (dBm)	12.0		
Tolerance ±(dB)	1.0		

<5.8GWLAN>

11A (Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	11.0	10.0	8.0
Tolerance ±(dB)	1.0	1.0	1.0
11N20 (Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	11.0	10.0	8.0
Tolerance ±(dB)	1.0	1.0	1.0
11N40 (Average)			
Channel	Channel 151	Channel 159	
Target (dBm)	11.0	10.0	
Tolerance ±(dB)	1.0	1.0	
11AC20 (Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	11.0	10.0	8.0
Tolerance ±(dB)	1.0	1.0	1.0

11AC40 (Average)		
Channel	11.0	10.0
Target (dBm)	2.0	3.0
Tolerance ±(dB)	1.0	1.0
11AC80 (Average)		
Channel	Channel 155	
Target (dBm)	11.0	
Tolerance ±(dB)	1.0	

8. Evaluation Results

8.1 Standalone MPE

As declared by the Applicant, the EUT is a wireless device used in a fix application, at least 20 cm from any body part of the user or nearby persons; from the maximum EUT RF output power, the minimum separation distance, $r=20\text{cm}$, as well as the gain of the used antenna refer to antenna information, the RF power density can be obtained.

<2.4GWLAN>

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	Duty Cycle	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW					
IEEE 802.11b	16.0	39.8107	2.11	1.6255	100%	0.0129	1.0000
IEEE 802.11g	15.0	31.6228	2.11	1.6255	100%	0.0102	1.0000
IEEE 802.11n HT20	15.0	31.6228	2.11	1.6255	100%	0.0102	1.0000
IEEE 802.11 n HT40	15.0	31.6228	2.11	1.6255	100%	0.0102	1.0000

<5.2GWLAN>

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	Duty Cycle	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW					
IEEE 802.11a	13.0	19.9526	0.97	1.2503	100%	0.0050	1.0000
IEEE 802.11 n HT20	13.0	19.9526	0.97	1.2503	100%	0.0050	1.0000
IEEE 802.11 n HT40	13.0	19.9526	0.97	1.2503	100%	0.0050	1.0000
IEEE 802.11 ac20	13.0	19.9526	0.97	1.2503	100%	0.0050	1.0000
IEEE 802.11 Ac40	14.0	25.1189	0.97	1.2503	100%	0.0062	1.0000
IEEE 802.11 Ac80	13.0	19.9526	0.97	1.2503	100%	0.0050	1.0000

<5.8GWLAN>

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	Duty Cycle	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW					
IEEE 802.11a	12.0	15.8489	0.97	1.2503	100%	0.0039	1.0000
IEEE 802.11n HT20	12.0	15.8489	0.97	1.2503	100%	0.0039	1.0000
IEEE 802.11n HT40	12.0	15.8489	0.97	1.2503	100%	0.0039	1.0000
IEEE 802.11ac20	12.0	15.8489	0.97	1.2503	100%	0.0039	1.0000
IEEE 802.11Ac40	12.0	15.8489	0.97	1.2503	100%	0.0039	1.0000
IEEE 802.11Ac80	12.0	15.8489	0.97	1.2503	100%	0.0039	1.0000

Emark:

1. Output power including tune-up tolerance;
2. MPE evaluate distance is 20cm from user manual provide by manufacturer;

8.2 Simultaneous Transmission MPE

The sample supports a modular, 1 antennas. This means they don't transmit at the same time, and MIMO mode is not supported. No need to consider simultaneous transmission;

9.Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.

.....THE END OF REPORT.....