



FCC REPORT

Report Reference No. : **TRE1705013204** R/C.....:57093
FCC ID : **2AL9QADB-1729CW**
Applicant's name : **Shenzhen Jiuzhou Electric Co., Ltd.**
Address : 6F, Jiuzhou Electric Building, Southern No. 12 Rd., High-tech Industrial Park, Nanshan District, Shenzhen, China
Manufacturer..... : Shenzhen Jiuzhou Electric Co., Ltd.
Address..... : 6F, Jiuzhou Electric Building, Southern No. 12 Rd., High-tech Industrial Park, Nanshan District, Shenzhen, China
Test item description..... : **DVB-C Set- Back Box with Wi-Fi 11ac**
Trade Mark : ADB
Model/Type reference : ADB-1729CWF vuCaster
List Model : ADB-1729CWF
Standard..... : **47 CFR FCC Part 15 Subpart B - Unintentional Radiators**
Date of receipt of test sample..... : May 15, 2017
Date of testing..... : May 16, 2017 – June 03, 2017
Date of issue..... : June 03, 2017
Result : **Pass**

Compiled by
 (position+printedname+signature) .. : Project Engineer Denny Huang

Supervised by
 (position+printedname+signature) ... : Laboratory Leader Shawn Wen

Approved by
 (position+printedname+signature) ... : Laboratory Manager Stephen Guo

Testing Laboratory Name..... : **Shenzhen Huatongwei International Inspection Co., Ltd.**
Address : 1/F, Bldg 3, Hongfa Hi-tech Industrial Park, Genyu Road, Tianliao, Gongming, Shenzhen, China

UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch. is acknowledged as copyright owner and source of the material UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

*The test report merely corresponds to the test sample.
 It is not permitted to copy extracts of these test result without the written permission of the test laboratory.*

Contents

1.	<u>TEST STANDARDS AND REPORT VERSION</u>	<u>3</u>
1.1.	Test Standards	3
1.2.	Report version	3
2.	<u>TEST DESCRIPTION</u>	<u>4</u>
3.	<u>SUMMARY.....</u>	<u>5</u>
3.1.	Client Information	5
3.2.	Product Description	5
3.3.	EUT operation mode	6
3.4.	EUT configuration	6
3.5.	Configuration of Tested System	6
4.	<u>TEST ENVIRONMENT</u>	<u>7</u>
4.1.	Address of the test laboratory	7
4.2.	Test Facility	7
4.3.	Equipments Used during the Test	8
4.4.	Environmental conditions	8
4.5.	Statement of the measurement uncertainty	9
5.	<u>TEST CONDITIONS AND RESULTS</u>	<u>10</u>
5.1.	Conducted Emissions Test	10
5.2.	Radiated Emissions Test	13
6.	<u>TEST SETUP PHOTOS OF THE EUT</u>	<u>17</u>
7.	<u>EXTERNAL AND INTERNAL PHOTOS OF THE EUT</u>	<u>18</u>

1. Test standards and Report version

1.1. Test Standards

The tests were performed according to following standards:

[47 CFR FCC Part 15 Subpart B](#) - Unintentional Radiators

[ANSI C63.4: 2014](#) – American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40GHz

1.2. Report version

Version No.	Date of issue	Description
00	June 03, 2017	Original

2. Test Description

Test Item	Section in CFR 47	Result
Conducted Emissions	15.107(a)	Pass
Radiated Emissions	15.109(a)	Pass

Note: The measurement uncertainty is not included in the test result.

3. Summary

3.1. Client Information

Applicant:	Shenzhen Jiuzhou Electric Co., Ltd.
Address:	6F, Jiuzhou Electric Building, Southern No. 12 Rd., High-tech Industrial Park, Nanshan District, Shenzhen, China
Manufacturer:	Shenzhen Jiuzhou Electric Co., Ltd.
Address:	6F, Jiuzhou Electric Building, Southern No. 12 Rd., High-tech Industrial Park, Nanshan District, Shenzhen, China

3.2. Product Description

Name of EUT	DVB-C Set- Back Box with Wi-Fi 11ac
Trade Mark:	ADB
Model No.:	ADB-1729CWF-vuCaster
List Model:	ADB-1729CWF
Power supply:	AC 120V/60Hz
Adapter information 1:	MODEL:ZX301202500W2 INPUT:100-240~50/60Hz 1.0A max OUTPUT:12Vd.c.,2.5A
Adapter information 2:	MODEL:ZX301202500W3 INPUT:100-240~50/60Hz 1.0A max OUTPUT:12Vd.c.,2.5A

3.3. EUT operation mode

The EUT has been tested under HDMI-1080P,USB connect USB device, RJ45 ping to computer, with transport stream Colorbar(SD)

3.4. EUT configuration


The following peripheral devices and interface cables were connected during the measurement:

- - supplied by the manufacturer
- - supplied by the lab

<input type="radio"/>	PC	Manufacturer :	DELL
		Model No. :	OptiPlex 3020 MT
<input type="radio"/>	Monitor	Manufacturer :	DELL
		Model No. :	E1912Hf
<input type="radio"/>	Keyboard	Manufacturer :	DELL
		Model No. :	SK8115
<input type="radio"/>	Mouse	Manufacturer :	DELL
		Model No. :	MS111-T

Note:Peripheral devices comply with FCC DOC approval.

3.5. Configuration of Tested System



4. Test Environment

4.1. Address of the test laboratory

Laboratory: Shenzhen Huatongwei International Inspection Co., Ltd.

Address: 1/F, Bldg 3, Hongfa Hi-tech Industrial Park, Genyu Road, Tianliao, Gongming, Shenzhen, China

Phone: 86-755-26748019 Fax: 86-755-26748089

4.2. Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

CNAS-Lab Code: L1225

Shenzhen Huatongwei International Inspection Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC17025: 2005 General Requirements) for the Competence of Testing and Calibration Laboratories.

A2LA-Lab Cert. No. 3902.01

Shenzhen Huatongwei International Inspection Co., Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

FCC-Registration No.: 317478

Shenzhen Huatongwei International Inspection Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. Registration 317478.

IC-Registration No.: 5377B-1

Two 3m Alternate Test Site of Shenzhen Huatongwei International Inspection Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for the performance of radiated measurements with Registration No. 5377B-1.

ACA

Shenzhen Huatongwei International Inspection Co., Ltd. EMC Laboratory can also perform testing for the Australian C-Tick mark as a result of our A2LA accreditation.

4.3. Equipments Used during the Test

Conducted Emissions					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal
1	EMI Test Receiver	Rohde & Schwarz	ESCI	101247	2016/11/13
2	Artificial Mains	Rohde & Schwarz	NNLK 8121	573	2016/11/13
3	Pulse Limiter	Rohde & Schwarz	ESH3-Z2	101488	2016/11/13
4	Test cable	ENVIROFLEX	3651	1101902	2016/11/13
5	Test Software	Rohde & Schwarz	ES-K1	N/A	N/A

Radiated Emissions					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal
1	Ultra-Broadband Antenna	ShwarzBeck	VULB9163	538	2016/11/13
2	EMI Test Receiver	Rohde & Schwarz	ESCI	101247	2016/11/13
3	EMI Test Software	Audix	E3	N/A	N/A
4	Turntable	MATURO	TT2.0	----	N/A
5	Antenna Mast	MATURO	TAM-4.0-P-12	----	N/A
6	EMI Test Software	Rohde & Schwarz	ESK1	N/A	N/A
7	Ultra-Broadband Antenna	Rohde&Schwarz	HL562	100015	2016/11/13
8	Amplifier	ShwarzBeck	BBV 9743	9743-0022	2016/11/13
9	TURNTABLE	ETS	2088	2149	N/A
10	HORN ANTENNA	Rohde&Schwarz	HF906	100039	2016/11/13
11	Test cable	Siva Cables Italy	RG 58A/U	W14.02	2016/11/13

The calibration interval was one year.

4.4. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15~35°C
Relative Humidity:	30~60 %
Air Pressure:	950~1050mba

4.5. Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 „Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements“ and is documented in the Shenzhen Huatongwei International Inspection Co., Ltd quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Shenzhen Huatongwei laboratory is reported:

Test	Range	Measurement Uncertainty	Notes
Radiated Emissions	30~1000MHz	4.24 dB	(1)
Radiated Emissions	1~18GHz	5.16 dB	(1)
Radiated Emissions	18-40GHz	5.54 dB	(1)
Conducted Disturbance	0.15~30MHz	3.39 dB	(1)

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

5. Test Conditions and Results

5.1. Conducted Emissions Test


LIMIT

FCC CFR Title 47 Part 15 Subpart B Section 15.107:

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

TEST CONFIGURATION



TEST PROCEDURE

1. The EUT was setup according to ANSI C63.10:2013 for compliance to FCC 47CFR 15.247 requirements.
2. The EUT was placed on a plat form of nominal size, 1 m by 1.5 m, raised 10 cm above the conducting ground plane. The vertical conducting plane was located 40 cm to the rear of the EUT. All other surfaces of EUT were at least 10 cm from any other grounded conducting surface.
3. The EUT and simulators are connected to the main power through a line impedance stabilization network (LISN). The LISN provides a 50ohm / 50uH coupling impedance for the measuring equipment.
4. The peripheral devices are also connected to the main power through a LISN. (Please refer to the block diagram of the test setup and photographs)
5. Each current-carrying conductor of the EUT power cord, except the ground (safety) conductor, was individually connected through a LISN to the input power source.
6. The excess length of the power cord between the EUT and the LISN receptacle were folded back and forth at the center of the lead to form a bundle not exceeding 40 cm in length.
7. Conducted emissions were investigated over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9 kHz.
8. During the above scans, the emissions were maximized by cable manipulation.

TEST MODE:


Please refer to the clause 3.3

TEST RESULTS

Passed **Not Applicable**

Test Line:


L



Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.150000	49.50	10.4	66	16.5	QP	L1	GND
0.352500	40.20	10.2	59	18.7	QP	L1	GND
3.723000	35.70	10.3	56	20.3	QP	L1	GND
7.449000	36.20	10.4	60	23.8	QP	L1	GND
27.019500	26.20	10.7	60	33.8	QP	L1	GND
27.033000	27.80	10.7	60	32.2	QP	L1	GND
Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.172500	31.00	10.4	55	23.8	AV	L1	GND
0.343500	29.90	10.2	49	19.2	AV	L1	GND
0.352500	31.10	10.2	49	17.8	AV	L1	GND
0.357000	28.70	10.2	49	20.1	AV	L1	GND
4.749000	26.80	10.3	46	19.2	AV	L1	GND
14.149500	29.80	10.5	50	20.2	AV	L1	GND

Test Line:

N



x x x MES GM1705185007_fin

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.154500	48.40	10.4	66	17.4	QP	N	GND
2.260500	32.00	10.2	56	24.0	QP	N	GND
3.714000	31.90	10.3	56	24.1	QP	N	GND
4.713000	33.70	10.3	56	22.3	QP	N	GND
7.395000	36.90	10.4	60	23.1	QP	N	GND
12.673500	33.40	10.5	60	26.6	QP	N	GND
Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.154500	31.50	10.4	56	24.3	AV	N	GND
0.352500	25.50	10.2	49	23.4	AV	N	GND
0.357000	24.70	10.2	49	24.1	AV	N	GND
4.956000	26.00	10.3	46	20.0	AV	N	GND
7.395000	27.90	10.4	50	22.1	AV	N	GND
14.212500	30.10	10.5	50	19.9	AV	N	GND

5.2. Radiated Emissions Test


LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.209


Frequency	Limit (dBuV/m @3m)	Value
30MHz-88MHz	40.00	Quasi-peak
88MHz-216MHz	43.50	Quasi-peak
216MHz-960MHz	46.00	Quasi-peak
960MHz-1GHz	54.00	Quasi-peak
Above 1GHz	54.00	Average
	74.00	Peak

TEST CONFIGURATION

➤ 30MHz ~ 1GHz



➤ Above 1GHz



TEST PROCEDURE

1. The EUT was tested according to ANSI C63.4:2014.
2. The EUT is placed on a turn table which is 0.8 meter above ground. The turn table is rotated 360 degrees to determine the position of the maximum emission level.
3. The EUT was positioned such that the distance from antenna to the EUT was 3 meters.
4. The antenna is scanned from 1 meter to 4 meters to find out the maximum emission level. This is repeated for both horizontal and vertical polarization of the antenna.
5. The tested frequency range 30MHz to 25GHz.
6. Use the following spectrum analyzer settings
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Below 1GHz, RBW=120KHz, VBW=300KHz, Sweep=auto, Detector function=peak, Trace=max hold;
If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
 - (3) Above 1GHz, RBW=1MHz, VBW=3MHz

TEST MODE:


Please refer to the clause 3.3

TEST RESULTS


Passed **Not Applicable**

Note: *Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor*

Polarization: Horizontal



Frequency MHz	Level dBuV/m	Transd dB	Limit dBuV/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
282.200000	36.70	-7.7	46.0	9.3	QP	100.0	160.00	HORIZONTAL
289.960000	41.90	-7.4	46.0	4.1	QP	100.0	187.00	HORIZONTAL
305.480000	34.10	-7.2	46.0	11.9	QP	100.0	172.00	HORIZONTAL
445.160000	33.10	-3.3	46.0	12.9	QP	100.0	119.00	HORIZONTAL
472.320000	39.70	-2.8	46.0	6.3	QP	100.0	28.00	HORIZONTAL
916.580000	39.30	6.9	46.0	6.7	QP	100.0	3.00	HORIZONTAL




Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	1798.13	42.91	25.58	5.96	37.14	37.31	74.00	-36.69	Peak
2	3141.15	36.70	28.56	7.65	38.21	34.70	74.00	-39.30	Peak
3	4039.21	35.59	29.60	8.81	38.02	35.98	74.00	-38.02	Peak
4	4748.89	38.81	31.05	9.52	37.03	42.35	74.00	-31.65	Peak
5	7739.86	32.63	36.45	13.10	35.04	47.14	74.00	-26.86	Peak
6	8917.46	33.68	37.80	13.22	34.36	50.34	74.00	-23.66	Peak


Note: The frequency range 18GHz to 40GHz no emission found, only show worse case for report.

Polarization:

Vertical



Frequency MHz	Level dBuV/m	Transd dB	Limit dBuV/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
37.760000	35.30	-10.8	40.0	4.7	QP	100.0	267.00	VERTICAL
59.100000	23.60	-9.8	40.0	16.4	QP	100.0	346.00	VERTICAL
288.020000	33.10	-7.5	46.0	12.9	QP	100.0	267.00	VERTICAL
472.320000	42.60	-2.8	46.0	3.4	QP	100.0	131.00	VERTICAL
499.480000	32.70	-1.8	46.0	13.3	QP	100.0	147.00	VERTICAL
924.340000	38.70	7.0	46.0	7.3	QP	100.0	199.00	VERTICAL



Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	1658.34	36.13	25.19	5.68	36.84	30.16	74.00	-43.84	Peak
2	1798.13	43.49	25.58	5.96	37.14	37.89	74.00	-36.11	Peak
3	3703.72	36.00	29.04	8.39	38.25	35.18	74.00	-38.82	Peak
4	4762.63	38.22	31.06	9.53	37.01	41.80	74.00	-32.20	Peak
5	6776.27	29.27	35.49	11.57	35.03	41.30	74.00	-32.70	Peak
6	9725.22	31.39	38.23	13.68	35.49	47.81	74.00	-26.19	Peak


Note: The frequency range 18GHz to 40GHz no emission found, only show worse case for report.

6. Test Setup Photos of the EUT


Conducted Emissions (AC Mains)



Radiated Emissions (30MHz-1GHz)



Radiated Emissions (Above 1GHz)



7. External and Internal Photos of the EUT

Reference to Test Report No.: TRE1705013201.

-----End of Report-----