



Test report No: 4392250.56

TEST REPORT

Radio Spectrum Matters (RF)

Identification of item tested	Bluetooth controllable dimmer
Trademark	Casambi
Model and /or type reference	CBU-TED-LR, CBU-TDP-LR
FCC/IC ID	FCC ID: 2ALA3-CBUTEDLR IC ID: 22496-CBUTEDLR
Features	85-240 Vac, 50-60 Hz
Applicant's name / address	Casambi Technologies Oy Alberga Business Park Bertel Jungin Aukio 1 C Espoo, Finland
Test method requested, standard	KDB 447498 D01V06 FCC Part 1.1310
Verdict Summary	COMPLIANCE
Tested by (name & signature)	Harry Deng 
Approved by (name & signature)	Tim Yan 
Date of issue	2022-11-14
Report template No	TRF_EMCC 2017-06- FCC_Exposure

INDEX

	page
General conditions	3
Uncertainty	3
Environmental conditions	3
Possible test case verdicts	3
Definition of symbols used in this test report.....	4
Abbreviations	4
Document History	4
Remarks and Comments	4
1 General Information	5
1.1 General Description of the Item(s)	5
1.2 Test data.....	6
1.3 The environment(s) in which the EUT is intended to be used	6
2 Description of Test Setup	7
2.1 Operating mode(s) used for tests	7
2.2 Support / Auxiliary equipment / unit / software for the EUT	7
3 RF Exposure Evaluation.....	8
3.1 Limits	8
3.2 Test Procedure	9
3.3 Test Result.....	9

GENERAL CONDITIONS

1. This report is only referred to the item that has undergone the test.
2. This report does not constitute or imply on its own an approval of the product by the Certification Bodies or Competent Authorities.
3. This document is only valid if complete; no partial reproduction can be made without previous written permission of DEKRA.
4. This test report cannot be used partially or in full for publicity and/or promotional purposes without previous written permission of DEKRA.
5. This report will not be used for social proof function in China market.

UNCERTAINTY

For all measurements where guidance for the calculation of the instrumentation uncertainty of a measurement is specified in EN 55016-4-2 (CISPR 16-4-2), EN/IEC 61000-4 series or a product standard, the measurement instrumentation uncertainty has been calculated and applied in accordance with these standards.

Uncertainties have been calculated according to the DEKRA internal document. The reported expanded uncertainties are based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95%.

ENVIRONMENTAL CONDITIONS

The climatic conditions during the tests are within the limits specified by the manufacturer for the operation of the EUT and the test equipment. The climatic conditions during the tests were within the following limits:

Ambient temperature	15 °C – 35 °C
Relative Humidity air	30% - 60%
Atmospheric pressure	86 kPa – 106 kPa

If explicitly required in the basic standard or applied product / product family standard the climatic values are recorded and documented separately in this test report.

POSSIBLE TEST CASE VERDICTS

Test case does not apply to test object	N/A
Test object does meet requirement	P (Pass) / PASS
Test object does not meet requirement	F (Fail) / FAIL
Not measured	N/M

DEFINITION OF SYMBOLS USED IN THIS TEST REPORT

<input checked="" type="checkbox"/> Indicates that the listed condition, standard or equipment is applicable for this report/test/EUT.			
<input type="checkbox"/> Indicates that the listed condition, standard or equipment is not applicable for this report/test/EUT.			
Decimal separator used in this report	<input checked="" type="checkbox"/>	Comma (,)	<input type="checkbox"/> Point (.)

ABBREVIATIONS

For the purposes of the present document, the following abbreviations apply:

EUT	: Equipment Under Test
QP	: Quasi-Peak
CAV	: CISPR Average
AV	: Average
CDN	: Coupling Decoupling Network
SAC	: Semi-Anechoic Chamber
OATS	: Open Area Test Site
BW	: Bandwidth
AM	: Amplitude Modulation
PM	: Pulse Modulation
HCP	: Horizontal Coupling Plane
VCP	: Vertical Coupling Plane
U_N	: Nominal voltage
T_x	: Transmitter
R_x	: Receiver
N/A	: Not Applicable
N/M	: Not Measured

DOCUMENT HISTORY

Report nr.	Date	Description
4392250.56	2022-11-14	First release.

REMARKS AND COMMENTS

The equipment under test (EUT) does meet the essential requirements of the stated standard(s)/test(s).

1 GENERAL INFORMATION

1.1 General Description of the Item(s)

Description of the item	Bluetooth controllable dimmer
Trademark	Casambi
Model / Type number	CBU-TED-LR, CBU-TDP-LR
FCC/IC ID	FCC ID: 2ALA3-CBUTEDLR IC ID: 22496-CBUTEDLR
Ratings	85-240 Vac, 50-60 Hz
Manufacturer.....	Casambi Technologies Oy Alberga Business Park Bertel Jungin Aukio 1 C Espoo, Finland
Factory	Sanmina Corporation 312, Qing Yang South Road, Kunshan, 215300 Jiangsu, China

Rated power supply	Voltage and Frequency		Reference poles				
			L1	L2	L3	N	PE
	<input checked="" type="checkbox"/>	AC: 85-240 V, 50-60 Hz	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
	<input type="checkbox"/>	DC: 12 V, 24 V, 12 / 24 V					
Mounting position.....	<input type="checkbox"/>	Table top equipment					
	<input checked="" type="checkbox"/>	Wall/Ceiling mounted equipment					
	<input type="checkbox"/>	Floor standing equipment					
	<input type="checkbox"/>	Hand-held equipment					
	<input type="checkbox"/>	Other:					

Operating frequency range(s) – Tx :	2402-2480 MHz
Operating frequency range(s) – Rx :	2402-2480 MHz
Type of Modulation	GFSK
Data rate.....	1 Mbps, 2 Mbps (proprietary), 125 kbps, 500 kbps
Antenna type.....	Integral antenna
Antenna gain.....	0 dBi
Number of channel.....	40
Operating Temperature Range.....	-20 - 45 °C

Intended use of the Equipment Under Test (EUT)	
<p>The apparatus as supplied for the test is Bluetooth controllable dimmer which intended for residential use, the product contains electronic circuitry but without earth connection.</p> <p>According to manufacturer's declaration, models are identical except for the enclosure.</p> <p>Hence, model CBU-TED-LR was chosen for full test and the corresponding test data are also representative of the other model as well.</p>	

Copy of marking plate:
No provide.

1.2 Test data

Test Location	DEKRA Testing and Certification (Shanghai) Ltd. Guangzhou Branch Block 5, No.3, Qiyun Road, Huangpu District, Guangzhou, Guangdong, China FCC Designation Number: CN1324; ISED CAB identifier: CN0130
Date of receipt of test item	2022-07-08
Date (s) of performance of tests	2022-07-08 to 2022-08-03

1.3 The environment(s) in which the EUT is intended to be used

The equipment under test (EUT) is intended to be used in the following environment(s):

<input checked="" type="checkbox"/>	Residential (domestic) environment.
<input checked="" type="checkbox"/>	Commercial and light-industrial environment.
<input type="checkbox"/>	Industrial environment.

2 DESCRIPTION OF TEST SETUP

2.1 Operating mode(s) used for tests

During the tests the following operating mode(s) has(have) been used.

Operating mode	Operating mode description	Used for methods	
		Conducted	Radiated
1	Transmitting at 1 Mbit/s,	<input checked="" type="checkbox"/>	<input type="checkbox"/>
2	Transmitting at 2 Mbit/s,	<input checked="" type="checkbox"/>	<input type="checkbox"/>
3	Transmitting at 500 Kbit/s	<input checked="" type="checkbox"/>	<input type="checkbox"/>
4	Transmitting at 125 Kbit/s	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Supplemental information: ---			

2.2 Support / Auxiliary equipment / unit / software for the EUT

The EUT has been tested with the following auxiliary equipment / unit / software:

Auxiliary equipment / unit / software	Type / Version	Manufacturer	Supplied by
Laptop	Latitude 5488	DELL	DEKRA
Supplemental information: ---			

3 RF EXPOSURE EVALUATION

3.1 Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (Minutes)
(A) Limits for Occupational/ Control Exposures				
300-1500	--	--	F/300	6
1500-100,000	--	--	5	6
(B) Limits for General Population/ Uncontrolled Exposures				
300-1500	--	--	F/1500	6
1500-100,000	--	--	1	30

F= Frequency in MHz

Friis Formula

Friis transmission formula: $Pd = (Pout \cdot G) / (4 \cdot \pi \cdot r^2)$

Where

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

Pd is the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

3.2 Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

The temperature and related humidity: 18°C and 78% RH.

3.3 Test Result

Power Density:

The tune-up power is 1,0 dB, so the maximum conducted power for BLE we used to calculate RF exposure is 8,42 dBm.

Test Mode	Frequency Band (MHz)	Conducted RF Power Output (dBm)	Antenna Gain (dBi)	Maximum EIRP (dBm)	Maximum Power (mW)	Power Density at r = 20 cm (mW/cm ²)	Limit of Power Density S(mW/cm ²)
BLE	2400 ~ 2483.5	8,42	0	8,42	6,95	0,001	1

--- END ---