

# RF Exposure Evaluation

## FCC ID: 2ALAA-MBS14102

### 1. Client Information

<b>Applicant</b>	: SHENZHEN JIAXINGWEI DIGITAL TECHNOLOGY CO.LTD
<b>Address</b>	: 4F, 3Block, YuYe District, Zhoushi Road, XiXiang, BaoAn, Shenzhen, China
<b>Manufacturer</b>	: DongGuan JiaXing Electronic&Technology Co.,Ltd
<b>Address</b>	: No.4 Xing Sheng Road, HuangNiuPu Industri, HuangJiang, Town GongGuan, China

### 2. General Description of EUT

<b>EUT Name</b>	: BLUETOOTH SPEAKER	
<b>Models No.</b>	: MBS14102, SD-005B, SD-002	
<b>Model Difference</b>	: All these models are identical in the same PCB, layout and electrical circuit, the only difference is model name for commercial.	
<b>Product Description</b>	Operation Frequency:	Bluetooth V2.0+EDR: 2402~2480 MHz
	Number of Channel:	Bluetooth: 79 Channels See Note 2
	Max Peak Output Power:	Bluetooth: 0.814 dBm(GFSK)
	Antenna Gain:	0.94 dBi PCB Antenna
	Modulation Type:	GFSK 1Mbps(1 Mbps) $\pi$ /4-DQPSK(2 Mbps) 8-DPSK(3 Mbps)
<b>Power Supply</b>	: DC power by USB cable. DC power by Li-ion battery.	
<b>Power Rating</b>	: DC 5.0V by USB cable. DC 3.7V by 1200mAh Li-ion battery.	
<b>Connecting I/O Port(S)</b>	: Please refer to the User's Manual	

**Note:** More test information about the EUT please refer the RF Test Report.

## SAR Test Exclusion Calculations

1. FCC: According to KDB 447498 D01 Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies v06.

(1) Clause 4.3: General SAR test reduction and exclusion guidance

Sub clause 4.31: Standalone SAR test exclusion considerations

1) The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6GHz at test separation distance  $\leq 5$  mm are determined by:

$$\frac{[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation, mm})] * [\sqrt{f_{\text{GHz}}]} \leq 3.0 \text{ for 1-g SAR}$$

$$\frac{[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation, mm})] * [\sqrt{f_{\text{GHz}}]} \leq 7.5.0 \text{ for 10-g SAR}$$

2.  
Calculation:

Test separation: 5mm						
Bluetooth Mode (GFSK)						
Frequency (GHz)	Conducted Power (dBm)	Turn-up Power Tolerance (dB)	Max power of tune up tolerance (dbm)	Max power of tune up tolerance (mw)	Calculation Value	Threshold Value
2.402	0.814	0±1	1	1.259	0.390	3.0
2.441	0.590	0±1	1	1.259	0.393	3.0
2.480	0.112	0±1	1	1.259	0.397	3.0
Bluetooth Mode ( $\pi/4$ -DQPSK)						
Frequency (GHz)	Conducted Power (dBm)	Turn-up Power Tolerance (dB)	Max power of tune up tolerance (dbm)	Max power of tune up tolerance (mw)	Calculation Value	Threshold Value
2.402	0.199	0±1	1	1.259	0.390	3.0
2.441	-0.149	0±1	1	1.259	0.393	3.0
2.480	-0.587	0±1	1	1.259	0.397	3.0
Bluetooth Mode (8-DPSK)						
Frequency (GHz)	Conducted Power (dBm)	Turn-up Power Tolerance (dB)	Max power of tune up tolerance (dbm)	Max power of tune up tolerance (mw)	Calculation Value	Threshold Value
2.402	0.105	0±1	1	1.259	0.390	3.0
2.441	-0.259	0±1	1	1.259	0.393	3.0
2.480	-0.688	0±1	1	1.259	0.397	3.0

So standalone SAR measurements are not required.

-----END OF REPORT-----