

# FCC ID: 2ALAYSNDM-0013US

## Maximum Permissible Exposure (MPE)

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
<b>(A) Limits for Occupational/Controlled Exposure</b>				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f <sup>2</sup>	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
<b>(B) Limits for General Population/Uncontrolled Exposure</b>				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f <sup>2</sup>	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

f = frequency in MHz \* = Plane-wave equivalent power density

## MPE Calculation Method

$$E \text{ (V/m)} = \frac{\sqrt{30 * P * G}}{d} \qquad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric field (V/m)

P = Average RF output power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 * P * G}{377 * D^2}$$

From the EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained.

## 2.4G WIFI:

Operation Frequency: WIFI 2412-2462MHz for 802.11b/g/11n(HT20);  
 2422-2452MHz for 802.11n(HT40);  
 Power density limited:  $1\text{mW}/\text{cm}^2$

Antenna Type: FPC Antenna

antenna gain: 2dBi;

R=20cm

$\text{mW}=10^{(\text{dBm}/10)}$

antenna gain Numeric= $10^{(\text{dBi}/10)}=10^{(2/10)}=1.58$

Channel Freq. (MHz)	modulation	conducted power (dBm)	Tune-up power (dBm)	Max		Antenna		Evaluation result (mW/cm <sup>2</sup> )	Power density Limits (mW/cm <sup>2</sup> )
				tune-up power		Gain			
				(dBm)	(mW)	(dBi)	Numeric		
2412	802.11b	13.18	13±1	14	25.119	2.00	1.58	0.0079	1
2437		13.16	13±1	14	25.119	2.00	1.58	0.0079	1
2462		12.15	13±1	14	25.119	2.00	1.58	0.0079	1
2412	802.11g	12.23	12±1	13	19.953	2.00	1.58	0.0063	1
2437		11.61	12±1	13	19.953	2.00	1.58	0.0063	1
2462		11.42	12±1	13	19.953	2.00	1.58	0.0063	1
2412	802.11n H20	12.56	12±1	13	19.953	2.00	1.58	0.0063	1
2437		11.79	12±1	13	19.953	2.00	1.58	0.0063	1
2462		10.84	11.5±1	12.5	17.783	2.00	1.58	0.0056	1
2422	802.11n(H T40)	10.48	10±1	11	12.589	2.00	1.58	0.0040	1
2437		10.98	10±1	11	12.589	2.00	1.58	0.0040	1
2452		9.84	10±1	11	12.589	2.00	1.58	0.0040	1

**BT:**

Operation Frequency: 2402MHz~2480MHz

Power density limited: 1mW/ cm<sup>2</sup>

Antenna Type: FPC antenna

BT antenna gain:2 dBi ;

R=20cm

antenna gain Numeric = $10^{(dBi/10)}=10^{(2/10)}=1.58$ 

Channel Freq. (MHz)	modulation	conducted power (dBm)	Tune-up power (dBm)	Max		Antenna		Evaluation result (mW/cm <sup>2</sup> )	Power density (mW/cm <sup>2</sup> )
				tune-up power		Gain			
				(dBm)	(mW)	(dBi)	Numeric		
2402	GFSK	2.937	3±1	4	2.512	2.00	1.58	0.0008	1
2441		4.664	4±1	5	3.162	2.00	1.58	0.0010	1
2480		3.435	4±1	5	3.162	2.00	1.58	0.0010	1
2402	π/4-DQPSK	2.143	3±1	4	2.512	2.00	1.58	0.0008	1
2441		3.799	3±1	4	2.512	2.00	1.58	0.0008	1
2480		2.592	3±1	4	2.512	2.00	1.58	0.0008	1
2402	8-DPSK	2.628	3.5±1	4.5	2.818	2.00	1.58	0.0009	1
2441		4.24	3.5±1	4.5	2.818	2.00	1.58	0.0009	1
2480		2.952	3.5±1	4.5	2.818	2.00	1.58	0.0009	1
2402	BLE	-0.88	0±1	1	1.259	2.00	1.58	0.0004	1
2440		-0.92	0±1	1	1.259	2.00	1.58	0.0004	1
2480		-0.85	0±1	1	1.259	2.00	1.58	0.0004	1

**Conclusion:**For the max result :  $0.0079 \leq 1\text{mW/ cm}^2$  for Power density, compliance with RF exposure.

Note: This product does not support WIFI and Bluetooth simultaneous delivery.

**Signature:**

Date: 2022-09-26


**NAME AND TITLE** (Please print or type): alex li/Manager**COMPANY** (Please print or type): Shenzhen NTEK Testing Technology Co., Ltd./ 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street Bao'an District, Shenzhen P.R. China.