



FCC PART 22H, PART 24E
FCC PART 27
MEASUREMENT AND TEST REPORT

For

F&C Wireless Solution, Inc.

10883 NW 78th Terrace - Doral Florida 33178,USA

FCC ID: 2ALB7ETENO

Report Type: Original Report	Product Name: Mobile phone
Test Engineer: <u>Kevin Hu</u>	<i>Kevin hu</i>
Report Number: <u>RDG170424001D</u>	
Report Date: <u>2017-05-24</u>	
Reviewed By: <u>Henry Ding</u> EMC Leader	<i>Henry Ding</i>
Test Laboratory:	Bay Area Compliance Laboratories Corp. (Chengdu) No.5040, Huilongwan Plaza, No.1, Shawan Road, Jinniu District, Chengdu, Sichuan, China Tel: 028-65523123, Fax: 028-65525125 www.baclcorp.com

Note: This test report was prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Chengdu). Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. This report was valid only with a valid digital signature.

TABLE OF CONTENTS

GENERAL INFORMATION	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY	4
TEST FACILITY.....	5
SYSTEM TEST CONFIGURATION.....	6
JUSTIFICATION.....	6
EQUIPMENT MODIFICATIONS	6
SUPPORT EQUIPMENT LIST AND DETAILS	6
CONFIGURATION OF TEST SETUP.....	6
BLOCK DIAGRAM OF TEST SETUP	7
SUMMARY OF TEST RESULTS	8
FCC §1.1310 & §2.1093- RF EXPOSURE.....	9
APPLICABLE STANDARD.....	9
TEST RESULT	9
FCC §2.1047 - MODULATION CHARACTERISTIC.....	10
FCC § 2.1046, § 22.913 (A) & § 24.232 (C) & § 27.50 - RF OUTPUT POWER	11
APPLICABLE STANDARD.....	11
TEST PROCEDURE	11
TEST EQUIPMENT LIST AND DETAILS	16
TEST DATA	16
FCC §2.1049, §22.917, §22.905 & §24.238 & §27.53- OCCUPIED BANDWIDTH.....	23
APPLICABLE STANDARD.....	23
TEST PROCEDURE	23
TEST EQUIPMENT LIST AND DETAILS	23
TEST DATA	23
FCC §2.1051, §22.917(A) & §24.238(A) & §27.53- SPURIOUS EMISSIONS AT ANTENNA TERMINALS	38
APPLICABLE STANDARD.....	38
TEST PROCEDURE	38
TEST EQUIPMENT LIST AND DETAILS	38
TEST DATA	38
FCC §2.1053, §22.917 & §24.238 & §27.53- SPURIOUS RADIATED EMISSIONS	50
APPLICABLE STANDARD.....	50
TEST PROCEDURE	50
TEST EQUIPMENT LIST AND DETAILS	51
TEST DATA	51
FCC §22.917(A) & §24.238(A) & §27.53- BAND EDGES.....	54
APPLICABLE STANDARD.....	54
TEST PROCEDURE	54
TEST EQUIPMENT LIST AND DETAILS	55
TEST DATA	55
FCC §2.1055, §22.355 & §24.235 & §27.54 - FREQUENCY STABILITY	81
APPLICABLE STANDARD.....	81

TEST PROCEDURE	81
TEST EQUIPMENT LIST AND DETAILS	82
TEST DATA	82

FINAL

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The **F&C Wireless Solution, Inc.**'s product, model number: **GT17(FCC ID: 2ALB7ETENO)** (the "EUT") in this report was a **Mobile phone**, which was measured approximately: 14.0 cm (L) × 7.0 cm (W) × 0.8 cm (H), rated input voltage: DC3.8V battery or DC5V Charging from adapter.

Adapter Information:

INPUT: AC 100-240V, 50/60Hz, 0.15A

OUTPUT: DC 5V, 1A

**All measurement and test data in this report was gathered from final production sample, serial number: 170424001(assigned by the BACL, Chengdu). It may have deviation from any other sample. The EUT supplied by the applicant was received on 2017-04-24, and EUT conformed to test requirement.*

Objective

This report is prepared on behalf of **F&C Wireless Solution, Inc.** in accordance with: Part 2-Subpart J, Part 22-Subpart H, Part 24-Subpart E and part 27 of the Federal Communications Commission's rules.

The objective is to determine compliance with FCC rules for output power, modulation characteristic, occupied bandwidth, spurious emissions at antenna terminal, spurious radiated emission, frequency stability and band edge.

Related Submittal(s)/Grant(s)

FCC Part 15B JBP submissions with FCC ID: 2ALB7ETENO.

FCC Part 15C DTS submissions with FCC ID: 2ALB7ETENO.

FCC Part 15C DSS submissions with FCC ID: 2ALB7ETENO.

Test Methodology

All tests and measurements indicated in this document were performed in accordance with the Code of Federal Regulations Title 47 Part 2, Sub-part J, Part 22 Subpart H, Part 24 Subpart E and Part 27.

Applicable Standards: TIA/EIA 603-D-2010.

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Chengdu).

Test Facility

The test site used by BACL to collect test data is located in the No.5040, Huilongwan Plaza, No.1, Shawan Road, Jinniu District, Chengdu, Sichuan, China.

Test site at BACL has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on April 24, 2015. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2014.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 560332. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

FINAL

SYSTEM TEST CONFIGURATION

Justification

The EUT was configured for testing according to TIA/EIA-603-D-2010.

The test items were performed with the EUT operating at testing mode.


Equipment Modifications

No modification was made to the EUT.


Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
R&S	Universal Radio Communication Tester	CMU200	11-9435686-111
R&S	Universal Radio Communication Tester	CMW500	106891
N/A	ANTENNA	N/A	N/A

Configuration of Test Setup



Block Diagram of Test Setup



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§1.1310, §2.1093	RF Exposure	Compliance
§2.1046; § 22.913 (a); § 24.232 (c); §27.50	RF Output Power	Compliance
§ 2.1047	Modulation Characteristics	Not Applicable
§ 2.1049; § 22.905 § 22.917; § 24.238; §27.53	Occupied Bandwidth	Compliance
§ 2.1051, § 22.917 (a); § 24.238 (a); §27.53	Spurious Emissions at Antenna Terminal	Compliance
§ 2.1053 § 22.917 (a); § 24.238 (a); §27.53	Spurious Radiation Emissions	Compliance
§ 22.917 (a); § 24.238 (a); §27.53	Out of band emission, Band Edge	Compliance
§ 2.1055 § 22.355; § 24.235; §27.54	Frequency stability vs. temperature Frequency stability vs. voltage	Compliance

FCC §1.1310 & §2.1093- RF EXPOSURE

Applicable Standard

FCC§1.1310 and §2.1093.

Test Result

Compliant, please refer to the SAR report: RDG170424001-20.

FINAL

FCC §2.1047 - MODULATION CHARACTERISTIC

According to FCC § 2.1047(d), Part 22H & 24E, Part 27 there is no specific requirement for digital modulation, therefore modulation characteristic is not presented.

FINAL

FCC § 2.1046, § 22.913 (a) & § 24.232 (c) & § 27.50 - RF OUTPUT POWER

Applicable Standard

According to FCC §2.1046 and §22.913 (a), the ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 watts.

According to FCC §2.1046 and §24.232 (C), mobile and portable stations are limited to 2 watts EIRP and the equipment must employ a means for limiting power to the minimum necessary for successful communications..

According to FCC §2.1046 and §27.50 (d), (4) Fixed, mobile, and portable (hand-held) stations operating in the 1710-1755 MHz band and mobile and portable stations operating in the 1695-1710 MHz and 1755-1780 MHz bands are limited to 1 watt EIRP. Fixed stations operating in the 1710-1755 MHz band are limited to a maximum antenna height of 10 meters above ground. Mobile and portable stations operating in these bands must employ a means for limiting power to the minimum necessary for successful communications.

According to §24.232 (d) Power measurements for transmissions by stations authorized under this section may be made either in accordance with a Commission-approved average power technique or in compliance with paragraph (e) of this section. In both instances, equipment employed must be authorized in accordance with the provisions of §24.51. In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

Test Procedure

GSM/GPRS/EGPRS

Function: Menu select > GSM Mobile Station > GSM 850/1900
Press Connection control to choose the different menus
Press RESET > choose all the reset all settings
Connection Press Signal Off to turn off the signal and change settings
Network Support > GSM + GPRS or GSM + EGSM
Main Service > Packet Data
Service selection > Test Mode A – Auto Slot Config. off
MS Signal Press Slot Config Bottom on the right twice to select and change the number of time slots and power setting
> Slot configuration > Uplink/Gamma
> 33 dBm for GPRS 850
> 30 dBm for GPRS 1900
> 27 dBm for EGPRS 850
> 26 dBm for EGPRS 1900
BS Signal Enter the same channel number for TCH channel (test channel) and BCCH channel
Frequency Offset > + 0 Hz
Mode > BCCH and TCH
BCCH Level > -85 dBm (May need to adjust if link is not stable)
BCCH Channel > choose desire test channel [Enter the same channel number for TCH channel (test channel) and BCCH channel]
Channel Type > Off

P0 > 4 dB
 Slot Config > Unchanged (if already set under MS signal)
 TCH > choose desired test channel
 Hopping > Off
 Main Timeslot > 3
 Network Coding Scheme > CS4 (GPRS) and MCS5 (EGPRS)

Bit Stream > 2E9-1 PSR Bit Stream
 AF/RF Connection Enter appropriate offsets for Ext. Att. Output and Ext. Att. Input
 Press Signal on to turn on the signal and change settings

WCDMA-Release 99

The following tests were conducted according to the test requirements outlines in section 5.2 of the 3GPP TS34.121-1 specification. The EUT has a nominal maximum output power of 24dBm (+1.7/-3.7).

WCDMA General Settings	Loopback Mode	Test Mode 1
	Rel99 RMC	12.2kbps RMC
	Power Control Algorithm	Algorithm2
	β_c / β_d	8/15

WCDMA HSDPA

The following tests were conducted according to the test requirements outlines in section 5.2 of the 3GPP TS34.121-1 specification.

	Mode	HSDPA	HSDPA	HSDPA	HSDPA
	Subset	1	2	3	4
WCDMA General Settings	Loopback Mode	Test Mode 1			
	Rel99 RMC	12.2kbps RMC			
	HSDPA FRC	H-Set1			
	Power Control Algorithm	Algorithm2			
	β_c	2/15	12/15	15/15	15/15
	β_d	15/15	15/15	8/15	4/15
	β_d (SF)	64			
	β_c / β_d	2/15	12/15	15/8	15/4
	β_{hs}	4/15	24/15	30/15	30/15
	MPR(dB)	0	0	0.5	0.5
HSDPA Specific Settings	DACK	8			
	DNAK	8			
	DCQI	8			
	Ack-Nack repetition factor	3			
	CQI Feedback	4ms			
	CQI Repetition Factor	2			
	$A_{hs} = \beta_{hs} / \beta_c$	30/15			

WCDMA HSUPA

The following tests were conducted according to the test requirements outlines in section 5.2 of the 3GPP TS34.121-1 specification.

	Mode	HSUPA	HSUPA	HSUPA	HSUPA	HSUPA
	Subset	1	2	3	4	5
WCDMA General Settings	Loopback Mode	Test Mode 1				
	Rel99 RMC	12.2kbps RMC				
	HSDPA FRC	H-Set1				
	HSUPA Test	HSUPA Loopback				
	Power Control Algorithm	Algorithm2				
	β_c	11/15	6/15	15/15	2/15	15/15
	β_d	15/15	15/15	9/15	15/15	0
	β_{ec}	209/225	12/15	30/15	2/15	5/15
	β_c / β_d	11/15	6/15	15/9	2/15	-
	β_{hs}	22/15	12/15	30/15	4/15	5/15
	CM(dB)	1.0	3.0	2.0	3.0	1.0
MPR(dB)	0	2	1	2	0	
HSDPA Specific Settings	DACK	8				
	DNAK	8				
	DCQI	8				
	Ack-Nack repetition factor	3				
	CQI Feedback	4ms				
	CQI Repetition Factor	2				
	$A_{hs} = \beta_{hs} / \beta_c$	30/15				
HSUPA Specific Settings	DE-DPCCH	6	8	8	5	7
	DHARQ	0	0	0	0	0
	AG Index	20	12	15	17	21
	ETFCI	75	67	92	71	81
	Associated Max UL Data Rate kbps	242.1	174.9	482.8	205.8	308.9
	Reference E_FCIs	E-TFCI 11 E E-TFCI PO 4 E-TFCI 67 E-TFCI PO 18 E-TFCI 71 E-TFCI PO23 E-TFCI 75 E-TFCI PO26 E-TFCI 81 E-TFCI PO 27	E-TFCI 11 E-TFCI PO4 E-TFCI 92 E-TFCI PO 18	E-TFCI 11 E-TFCI PO 4 E-TFCI 67 E-TFCI PO 18 E-TFCI 71 E-TFCI PO23 E-TFCI 75 E-TFCI PO 26 E-TFCI 81 E-TFCI PO 27	E-TFCI 11 E E-TFCI PO 4 E-TFCI 67 E-TFCI PO 18 E-TFCI 71 E-TFCI PO23 E-TFCI 75 E-TFCI PO26 E-TFCI 81 E-TFCI PO 27	

HSPA+

The following tests were conducted according to the test requirements in Table C.11.1.4 of 3GPP TS 34.121-1

Sub-test	β_c (Note3)	β_d	β_{HS} (Note1)	β_{ec}	β_{ed} (2xSF2) (Note 4)	β_{ed} (2xSF4) (Note 4)	CM (dB) (Note 2)	MPR (dB) (Note 2)	AG Index (Note 4)	E-TFCI (Note 5)	E-TFCI (boost)
1	1	0	30/15	30/15	β_{ed1} : 30/15 β_{ed2} : 30/15	β_{ed3} : 24/15 β_{ed4} : 24/15	3.5	2.5	14	105	105

- Note 1: Δ_{ACK} , Δ_{NACK} and $\Delta_{CQI} = 30/15$ with $\beta_{HS} = 30/15 * \beta_c$.
- Note 2: CM = 3.5 and the MPR is based on the relative CM difference, MPR = MAX(CM-1,0).
- Note 3: DPDCH is not configured, therefore the β_c is set to 1 and $\beta_d = 0$ by default.
- Note 4: β_{ed} can not be set directly; it is set by Absolute Grant Value.
- Note 5: All the sub-tests require the UE to transmit 2SF2+2SF4 16QAM EDCH and they apply for UE using E-DPDCH category 7. E-DCH TTI is set to 2ms TTI and E-DCH table index = 2. To support these E-DCH configurations DPDCH is not allocated. The UE is signalled to use the extrapolation algorithm.

DC-HSDPA

The following tests were conducted according to the test requirements in Table C.8.1.12 of 3GPP TS 34.121-1

Table C.8.1.12: Fixed Reference Channel H-Set 12

Parameter	Unit	Value
Nominal Avg. Inf. Bit Rate	kbps	60
Inter-TTI Distance	TTI's	1
Number of HARQ Processes	Processes	6
Information Bit Payload (N_{INF})	Bits	120
Number Code Blocks	Blocks	1
Binary Channel Bits Per TTI	Bits	960
Total Available SML's in UE	SML's	19200
Number of SML's per HARQ Proc.	SML's	3200
Coding Rate		0.15
Number of Physical Channel Codes	Codes	1
Modulation		QPSK
<p>Note 1: The RMC is intended to be used for DC-HSDPA mode and both cells shall transmit with identical parameters as listed in the table.</p> <p>Note 2: Maximum number of transmission is limited to 1, i.e., retransmission is not allowed. The redundancy and constellation version 0 shall be used.</p>		

LTE (FDD):

The following tests were conducted according to the test requirements in 3GPP TS36.101

The following tests were conducted according to the test requirements outlined in section 6.2 of the 3GPP TS36.101 specification.

UE Power Class: 3 (23 +/- 2dBm). The allowed Maximum Power Reduction (MPR) for the maximum output power due to higher order modulation and transmit bandwidth configuration (resource blocks) is specified in Table 6.2.3-1 of the 3GPP TS36.101.

Table 6.2.3-1: Maximum Power Reduction (MPR) for Power Class 3

Modulation	Channel bandwidth / Transmission bandwidth (RB)						MPR (dB)
	1.4 MHz	3.0 MHz	5 MHz	10 MHz	15 MHz	20 MHz	
QPSK	> 5	> 4	> 8	> 12	> 16	> 18	≤ 1
16 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 1
16 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 2

The allowed A-MPR values specified below in Table 6.2.4.-1 of 3GPP TS36.101 are in addition to the allowed MPR requirements. All the measurements below were performed with A-MPR disabled, by using Network Signaling Value of "NS_01".

Table 6.2.4-1: Additional Maximum Power Reduction (A-MPR)

Network Signalling value	Requirements (sub-clause)	E-UTRA Band	Channel bandwidth (MHz)	Resources Blocks (N_{RB})	A-MPR (dB)
NS_01	6.6.2.1.1	Table 5.5-1	1.4, 3, 5, 10, 15, 20	Table 5.6-1	NA
NS_03	6.6.2.2.1	2, 4, 10, 23, 25, 35, 36	3	>5	≤ 1
			5	>6	≤ 1
			10	>6	≤ 1
			15	>8	≤ 1
			20	>10	≤ 1
NS_04	6.6.2.2.2	41	5	>6	≤ 1
			10, 15, 20	See Table 6.2.4-4	
NS_05	6.6.3.3.1	1	10,15,20	≥ 50	≤ 1
NS_06	6.6.2.2.3	12, 13, 14, 17	1.4, 3, 5, 10	Table 5.6-1	n/a
NS_07	6.6.2.2.3	13	10	Table 6.2.4-2	Table 6.2.4-2
	6.6.3.3.2				
NS_08	6.6.3.3.3	19	10, 15	> 44	≤ 3
NS_09	6.6.3.3.4	21	10, 15	> 40	≤ 1
				> 55	≤ 2
NS_10		20	15, 20	Table 6.2.4-3	Table 6.2.4-3
NS_11	6.6.2.2.1	23 ¹	1.4, 3, 5, 10	Table 6.2.4-5	Table 6.2.4-5
..					
NS_32	-	-	-	-	-

Note 1: Applies to the lower block of Band 23, i.e. a carrier placed in the 2000-2010 MHz region.

Radiated method:

ANSI/TIA 603-D section 2.2.17

Test Equipment List and Details

Manufacturer	Description	Model Number	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	100028	2016-12-02	2017-12-01
Sunol Sciences	Broadband Antenna	JB3	A121808	2016-04-10	2019-04-09
Rohde & Schwarz	Spectrum Analyzer	FSEM30	100018	2016-12-02	2017-12-01
ETS	Horn Antenna	3115	003-6076	2016-12-02	2017-12-01
Ducommun Technologies	Horn Antenna	ARH-4223-02	1007726-0113024	2014-06-16	2017-06-15
EMCO	Adjustable Dipole Antenna	3121C	9109-258	N/A	N/A
HP	Signal Generator	8648C	3623A04150	2016-05-23	2017-05-22
WILTRON	SWEPT FREQUENCY SYNTHESIZER	6737	213001	2016-05-23	2017-05-22
EMCT	Semi-Anechoic Chamber	966	966-1	2015-04-24	2018-04-23
Unknown	RF Cable (below 1GHz)	Unknown	NO.1	2016-11-10	2017-11-09
Unknown	RF Cable (below 1GHz)	Unknown	NO.4	2016-11-10	2017-11-09
Unknown	RF Cable (above 1GHz)	Unknown	NO.2	2016-11-10	2017-11-09
R&S	Universal Radio Communication Tester	CMU200	11-9435686-111	2016-07-28	2017-07-27
R&S	Wideband Radio Communication Tester	CMW500	106891	2016-11-23	2017-11-23

* **Statement of Traceability:** BACL(Chengdu) attests that all of the calibrations on the equipment items listed above were traceable to NIM or to another internationally recognized National Metrology Institute (NMI), and were compliant with the NIST HB 150-2016 Normative Annex B "Implementation of traceability policy in accredited laboratories".

Test Data

Environmental Conditions

Temperature:	25.2 °C
Relative Humidity:	49.9 %
ATM Pressure:	100.2 kPa

The testing was performed by Kevin Hu on 2017-05-09.

Conducted Power

Cellular Band (Part 22H) & PCS Band (Part 24E)

Band	Channel No.	Peak Output Power (dBm)								
		GSM	GPRS 1 TX Slot	GPRS 2 TX Slot	GPRS 3 TX Slot	GPRS 4 TX Slot	EDGE 1 TX Slot	EDGE 2 TX Slot	EDGE 3 TX Slot	EDGE 4 TX Slot
Cellular	128	32.37	32.39	31.25	29.33	28.42	26.04	24.80	22.90	21.91
	190	32.83	32.85	31.60	29.64	28.33	26.02	24.92	22.95	21.93
	251	33.30	33.29	32.02	30.01	28.97	26.32	25.11	23.20	22.16
PCS	512	28.6	28.60	27.45	25.61	24.68	24.15	23.20	21.83	20.25
	661	29.64	29.68	28.55	26.61	25.75	24.70	23.68	22.33	20.76
	810	30.4	30.41	29.56	27.78	26.90	25.63	24.54	22.95	21.88

WCDMA Band II

Mode	3GPP Sub Test	Average Output Power (dBm)					
		Low Channel (Ave. Power)	Low Channel (PAR)	Middle Channel (Ave. Power)	Middle Channel (PAR)	High Channel (Ave. Power)	High Channel (PAR)
Rel 99 (QPSK)	1	22.62	3.03	22.84	3.25	22.83	3.29
HSDPA (QPSK)	1	22.58	2.90	22.76	3.05	22.68	3.15
	2	22.60	3.00	22.77	3.22	22.73	3.17
	3	22.61	3.03	22.71	3.23	22.69	3.13
	4	22.44	2.88	22.70	3.22	22.82	3.25
HSUPA (QPSK)	1	22.51	2.97	22.80	3.24	22.76	3.09
	2	22.51	2.87	22.69	3.20	22.64	3.17
	3	22.47	2.90	22.65	3.16	22.71	3.20
	4	22.43	2.87	22.73	3.14	22.70	3.15
	5	22.57	3.02	22.73	3.19	22.71	3.25
DC-HSDPA (QPSK)	1	22.56	2.97	22.69	3.18	22.68	3.15
	2	22.46	2.85	22.66	3.17	22.66	3.23
	3	22.53	2.93	22.68	3.11	22.73	3.21
	4	22.45	3.02	22.79	3.25	22.76	3.14
HSPA+ (16QAM)	1	22.43	2.98	22.71	3.18	22.71	3.23

WCDMA Band IV

Mode	3GPP Sub Test	Average Output Power (dBm)					
		Low Channel (Ave. Power)	Low Channel (PAR)	Middle Channel (Ave. Power)	Middle Channel (PAR)	High Channel (Ave. Power)	High Channel (PAR)
Rel 99 (QPSK)	1	22.13	3.19	22.18	2.78	22.26	3.23
HSDPA (QPSK)	1	22.09	3.01	22.04	2.68	22.21	3.20
	2	22.12	3.18	22.10	2.71	22.06	3.15
	3	22.03	3.09	22.04	2.60	22.07	3.20
	4	21.96	3.11	21.98	2.64	22.07	3.21
HSUPA (QPSK)	1	22.10	3.12	22.05	2.62	22.13	3.13
	2	22.02	3.15	22.17	2.66	22.21	3.11
	3	22.04	3.12	22.18	2.59	22.19	3.13
	4	21.96	3.10	22.13	2.69	22.20	3.09
	5	22.03	3.13	22.16	2.69	22.22	3.20
DC-HSDPA (QPSK)	1	22.11	3.03	22.17	2.68	22.11	3.05
	2	22.06	3.18	22.10	2.63	22.08	3.15
	3	21.97	3.05	22.15	2.75	22.16	3.09
	4	21.99	3.07	22.16	2.59	22.06	3.17
HSPA+ (16QAM)	1	21.94	3.10	22.15	2.74	22.19	3.14

WCDMA Band V

Mode	3GPP Sub Test	Average Output Power (dBm)					
		Low Channel (Ave. Power)	Low Channel (PAR)	Middle Channel (Ave. Power)	Middle Channel (PAR)	High Channel (Ave. Power)	High Channel (PAR)
Rel 99 (QPSK)	1	21.89	3.46	22.33	3.16	22.20	3.67
HSDPA (QPSK)	1	21.82	3.40	22.25	3.06	22.09	3.63
	2	21.88	3.31	22.26	3.15	22.05	3.51
	3	21.70	3.31	22.21	3.10	22.09	3.65
	4	21.83	3.26	22.27	3.11	22.19	3.53
HSUPA (QPSK)	1	21.88	3.31	22.30	3.15	22.09	3.52
	2	21.78	3.27	22.21	3.07	22.10	3.58
	3	21.77	3.32	22.23	3.16	22.23	3.51
	4	21.82	3.33	22.17	3.09	22.17	3.50
	5	21.85	3.42	22.20	3.14	22.10	3.49
DC-HSDPA (QPSK)	1	21.75	3.44	22.29	2.99	22.13	3.51
	2	21.78	3.38	22.28	3.08	22.16	3.52
	3	21.86	3.29	22.20	3.06	22.23	3.62
	4	21.78	3.40	22.31	3.12	22.07	3.53
HSPA+ (16QAM)	1	21.87	3.40	22.27	3.00	22.16	3.59

LTE Band II

Channel Bandwidth	Modulation	Resource Block & RB offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
1.4MHz	QPSK	1#0	23.27	23.24	23.07
		1#3	23.30	23.20	22.94
		1#5	23.26	23.12	22.72
		3#0	23.22	23.33	22.66
		3#3	23.18	23.32	22.84
		6#0	23.22	23.28	23.00
	16QAM	1#0	22.30	22.37	22.82
		1#3	22.35	22.35	22.08
1#5		23.32	22.23	21.85	
6#0		23.28	22.19	21.76	
3 MHz	QPSK	1#0	23.25	22.97	22.62
		1#8	23.32	22.65	22.06
		1#14	23.26	22.72	22.00
		10#0	23.33	22.62	22.33
		10#5	22.85	22.68	22.22
		15#0	22.32	22.50	22.05
	16QAM	1#0	22.28	22.21	21.60
		1#8	22.32	22.55	22.21
		1#14	22.25	22.56	22.12
		15#0	22.26	22.48	22.18
5 MHz	QPSK	1#0	23.16	22.91	22.68
		1#13	23.15	22.93	22.66
		1#24	23.10	22.88	22.65
		10#0	23.08	22.75	22.68
		10#15	23.12	22.65	22.56
		25#0	23.10	22.50	22.52
	16QAM	1#0	22.05	21.77	21.24
		1#13	22.49	22.01	21.87
		1#24	22.50	21.88	21.86
		25#0	22.52	21.95	21.82

Channel Bandwidth	Modulation	Resource Block & RB offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
10 MHz	QPSK	1#0	22.70	22.47	22.06
		1#25	22.72	22.36	22.12
		1#49	22.66	22.32	22.02
		25#0	22.68	22.36	22.10
		25#25	22.75	22.42	22.05
		50#0	22.60	22.50	21.98
	16QAM	1#0	21.90	21.75	21.33
		1#25	21.91	22.07	21.21
1#49		21.95	22.10	21.20	
50#0		21.85	22.12	21.23	
15 MHz	QPSK	1#0	21.82	22.06	21.18
		1#38	21.93	22.02	21.12
		1#74	21.65	22.05	21.08
		36#0	21.14	20.85	20.82
		36#39	23.15	22.93	23.05
		75#0	23.16	22.95	23.10
	16QAM	1#0	23.12	22.90	23.05
		1#38	23.10	22.85	23.12
1#74		23.20	22.86	23.00	
75#0		23.02	22.80	22.96	
20 MHz	QPSK	1#0	22.65	22.10	21.97
		1#50	22.40	22.55	22.65
		1#99	22.43	22.50	22.60
		50#0	22.42	22.52	22.38
		50#50	22.38	22.48	22.35
		100#0	22.36	22.45	22.36
	16QAM	1#0	22.33	22.36	22.20
		1#50	22.00	21.83	21.36
		1#99	23.16	23.02	23.35
		100#0	23.15	23.08	23.37

PAR, Band II

Test Modulation		Channel Bandwidth	Low Channel PAR (dB)	Middle Channel PAR (dB)	High Channel PAR (dB)	Limit (dB)
QPSK	1 RB	20 MHz	3.72	4.64	3.48	13
	100 RB		6.28	6.36	6.20	13
16QAM	1 RB	20 MHz	4.04	5.16	3.76	13
	100 RB		6.96	7.12	6.84	13

Note: peak-to-average ratio (PAR) <13 dB.

ERP & EIRP

Part 22H

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBµV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			S.G. Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
GSM 850_Middle Channel								
836.600	H	109.41	32.3	0.0	0.6	31.7	38.5	6.8
836.600	V	108.53	33.5	0.0	0.6	32.9	38.5	5.6
EDGE 850_Middle Channel								
836.600	H	99.68	22.6	0.0	0.6	22.0	38.5	16.5
836.600	V	101.73	26.7	0.0	0.6	26.1	38.5	12.4
WCDMA Band V Middle Channel								
836.600	H	97.68	20.6	0.0	0.6	20.0	38.5	18.5
836.600	V	96.39	21.4	0.0	0.6	20.8	38.5	17.7

Part 24E

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBµV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			S.G. Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
PCS 1900_Middle Channel								
1880.000	H	94.58	21	8.0	0.9	28.1	33.0	4.9
1880.000	V	92.77	20.4	8.0	0.9	27.5	33.0	5.5
EDGE 1900_Middle Channel								
1880.000	H	91.67	18.1	8.0	0.9	25.2	33.0	7.8
1880.000	V	90.91	18.5	8.0	0.9	25.6	33.0	7.4
WCDMA Band II Middle Channel								
1880.000	H	89.39	15.8	8.0	0.9	22.9	33.0	10.1
1880.000	V	87.75	15.4	8.0	0.9	22.5	33.0	10.5

Part 27

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBµV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			S.G. Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
AWS Band_Middle Channel								
1732.600	H	90.35	14.9	7.9	0.9	21.9	30.0	8.1
1732.600	V	89.67	15.3	7.9	0.9	22.3	30.0	7.7

LTE Band II

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
QPSK 1.4M BW Middle Channel 1880.000 MHz								
1880.000	H	90.20	16.6	8.0	0.9	23.7	33.0	9.3
1880.000	V	82.40	10	8.0	0.9	17.1	33.0	15.9
16-QAM 1.4M BW Middle Channel 1880.000 MHz								
1880.000	H	90.10	16.5	8.0	0.9	23.6	33.0	9.4
1880.000	V	82.50	10.1	8.0	0.9	17.2	33.0	15.8
QPSK 3M BW Middle Channel 1880.000 MHz								
1880.000	H	90.40	16.8	8.0	0.9	23.9	33.0	9.1
1880.000	V	82.20	9.8	8.0	0.9	16.9	33.0	16.1
16-QAM 3M BW Middle Channel 1880.000 MHz								
1880.000	H	90.20	16.6	8.0	0.9	23.7	33.0	9.3
1880.000	V	82.10	9.7	8.0	0.9	16.8	33.0	16.2
QPSK 5M BW Middle Channel 1880.000 MHz								
1880.000	H	90.00	16.4	8.0	0.9	23.5	33.0	9.5
1880.000	V	82.60	10.2	8.0	0.9	17.3	33.0	15.7
16-QAM 5M BW Middle Channel 1880.000 MHz								
1880.000	H	89.90	16.3	8.0	0.9	23.4	33.0	9.6
1880.000	V	82.40	10	8.0	0.9	17.1	33.0	15.9
QPSK 10M BW Middle Channel 1880.000 MHz								
1880.000	H	89.60	16	8.0	0.9	23.1	33.0	9.9
1880.000	V	81.90	9.5	8.0	0.9	16.6	33.0	16.4
16-QAM 10M BW Middle Channel 1880.000 MHz								
1880.000	H	89.70	16.1	8.0	0.9	23.2	33.0	9.8
1880.000	V	82.10	9.7	8.0	0.9	16.8	33.0	16.2
QPSK 15M BW Middle Channel 1880.000 MHz								
1880.000	H	88.70	15.1	8.0	0.9	22.2	33.0	10.8
1880.000	V	81.00	8.6	8.0	0.9	15.7	33.0	17.3
16-QAM 15M BW Middle Channel 1880.000 MHz								
1880.000	H	88.70	15.1	8.0	0.9	22.2	33.0	10.8
1880.000	V	81.50	9.1	8.0	0.9	16.2	33.0	16.8
QPSK 20M BW Middle Channel 1880.000 MHz								
1880.000	H	88.00	14.4	8.0	0.9	21.5	33.0	11.5
1880.000	V	80.30	7.9	8.0	0.9	15.0	33.0	18.0
16-QAM 20M BW Middle Channel 1880.000 MHz								
1880.000	H	88.20	14.6	8.0	0.9	21.7	33.0	11.3
1880.000	V	80.40	8	8.0	0.9	15.1	33.0	17.9

FCC §2.1049, §22.917, §22.905 & §24.238 & §27.53- OCCUPIED BANDWIDTH


Applicable Standard

FCC §2.1049, §22.917, §22.905, §24.238 and §27.53.

Test Procedure

The RF output of the transmitter was connected to the simulator and the spectrum analyzer through sufficient attenuation.

The 26 dB & 99% bandwidth was recorded.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Signal Analyzer	FSIQ26	831929/005	2016-09-21	2017-09-20
Rohde & Schwarz	Spectrum Analyzer	FSEM30	100018	2016-12-02	2017-12-01
Unknown	RF Cable	Unknown	NO.3	Each Time	/
Unknown	Two-way Splitter	Unknown	OE0120121	Each Time	/

* **Statement of Traceability:** BACL(Chengdu) attests that all of the calibrations on the equipment items listed above were traceable to NIM or to another internationally recognized National Metrology Institute (NMI), and were compliant with the NIST HB 150-2016 Normative Annex B "Implementation of traceability policy in accredited laboratories".

Test Data

Environmental Conditions

Temperature:	26.7~29.5 °C
Relative Humidity:	32~50.1 %
ATM Pressure:	100.1 kPa

The testing was performed by Kevin Hu from 2017-05-11 to 2017-05-13.


Test Mode: Transmitting

Test Result: Compliant. Please refer to the following table and plots.


Band	Test Channel	Mode	99% Occupied Bandwidth (MHz)	26 dB Occupied Bandwidth (MHz)
Cellular	M	GSM	0.246	0.319
		EDGE	0.251	0.321
PCS		PCS	0.248	0.315
		EDGE	0.251	0.315
WCDMA Band II		Rel 99	4.208	4.870
		HSDPA	4.228	4.890
		HSUPA	4.228	4.910
WCDMA Band IV		Rel 99	4.228	4.910
		HSDPA	4.228	4.950
		HSUPA	4.228	4.890
WCDMA Band V	Rel 99	4.208	4.890	
	HSDPA	4.208	4.890	
	HSUPA	4.208	4.890	

Band	Test Modulation	Test Bandwidth (MHz)	Test Channel	99% Occupied Bandwidth (MHz)	26 dB Occupied Bandwidth (MHz)
LTE Band II	QPSK	1.4	M	1.112	1.311
		3		2.754	3.114
		5		4.549	5.070
		10		9.138	10.581
		15		13.587	15.307
		20		18.036	19.960
	16QAM	1.4	M	1.112	1.311
		3		2.778	3.126
		5		4.549	5.150
		10		9.138	10.501
		15		13.587	15.331
		20		18.116	20.200


GMSK 850 Cellular Band




GMSK PCS Band




EDGE 850 Cellular Band



EDGE PCS Band




REL99 Band II




Date: 13.MAY 2017 17:25:51

HSDPA Band II




Date: 13.MAY 2017 17:20:51

HSUPA Band II




Date: 13.MAY 2017 17:22:50

REL99 Band V




Date: 13.MAY 2017 17:33:05

HSDPA Band IV




Date: 13.MAY 2017 17:37:53

HSUPA Band IV




Date: 13.MAY 2017 17:35:49


REL99 Band IV



HSDPA Band V




HSUPA Band V




LTE Band II:

QPSK_1.4 MHz




Date: 11.MAY.2017 22:44:48

QPSK_3 MHz




Date: 11.MAY.2017 22:48:08


QPSK_5 MHz




QPSK_10 MHz




QPSK_15 MHz




QPSK_20 MHz




16QAM_1.4 MHz




16QAM_3 MHz




16QAM_5 MHz




16QAM_10 MHz



16QAM_15 MHz



16QAM_20 MHz



FCC §2.1051, §22.917(a) & §24.238(a) & §27.53- SPURIOUS EMISSIONS AT ANTENNA TERMINALS


Applicable Standard

FCC §2.1051, §22.917(a) , §24.238(a) and §27.53.

The spectrum was to be investigated to the tenth harmonics of the highest fundamental frequency as specified in § 2.1051.

Test Procedure

The RF output of the transceiver was connected to a spectrum analyzer and simulator through appropriate attenuation. Sufficient scans were taken to show any out of band emissions up to 10th harmonic.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Signal Analyzer	FSIQ26	831929/005	2016-09-21	2017-09-20
Rohde & Schwarz	Spectrum Analyzer	FSEM30	100018	2016-12-02	2017-12-01
Unknown	RF Cable	Unknown	NO.3	Each Time	/
Unknown	Two-way Splitter	Unknown	OE0120121	Each Time	/

* **Statement of Traceability:** BACL(Chengdu) attests that all of the calibrations on the equipment items listed above were traceable to NIM or to another internationally recognized National Metrology Institute (NMI), and were compliant with the NIST HB 150-2016 Normative Annex B "Implementation of traceability policy in accredited laboratories".



Test Data

Environmental Conditions


Temperature:	26.7~29.5 °C
Relative Humidity:	32 ~ 50.1 %
ATM Pressure:	100.1kPa

The testing was performed by Kevin Hu from 2017-05-11 to 2017-05-13.
Please refer to the following plots.


GSM850_Middle Channel




REL99 Band II_ Middle Channel




Fundamental





REL99 Band IV_ Middle Channel



Fundamental




REL99 Band V_ Middle Channel




LTE Band II (Middle Channel)

QPSK_1.4 MHz




Date: 11.MAY.2017 23:36:32

Fundamental




Date: 11.MAY.2017 23:37:41


QPSK_3 MHz




Fundamental




QPSK_5 MHz




Fundamental




QPSK_10 MHz




Fundamental




QPSK_15 MHz




Fundamental



QPSK_20 MHz



Fundamental



FCC §2.1053, §22.917 & §24.238 & §27.53- SPURIOUS RADIATED EMISSIONS

Applicable Standard

FCC § 2.1053, §22.917, § 24.238 and § 27.53.

Test Procedure

The transmitter was placed on a wooden turntable, and it was transmitting into a non-radiating load which was also placed on the turntable.

The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.

The frequency range up to tenth harmonic of the fundamental frequency was investigated.

Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution.

Spurious emissions in dB = $10 \lg(\text{TXpwr in Watts}/0.001)$ – the absolute level

Spurious attenuation limit in dB = $43 + 10 \text{Log}_{10}(\text{power out in Watts})$

Test Equipment List and Details

Manufacturer	Description	Model Number	Serial Number	Calibration Date	Calibration Due Date
Agilent	Amplifier	8447D	2944A10442	2016-12-02	2017-12-01
Rohde & Schwarz	EMI Test Receiver	ESCI	100028	2016-12-02	2017-12-01
Sunol Sciences	Broadband Antenna	JB3	A121808	2016-04-10	2019-04-09
Rohde & Schwarz	Spectrum Analyzer	FSEM30	100018	2016-12-02	2017-12-01
ETS	Horn Antenna	3115	003-6076	2016-12-02	2017-12-01
Ducommun Technologies	Horn Antenna	ARH-4223-02	1007726-0113024	2014-06-16	2017-06-15
EMCO	Adjustable Dipole Antenna	3121C	9109-258	N/A	N/A
HP	Signal Generator	8648C	3623A04150	2016-05-23	2017-05-22
WILTRON	SWEPT FREQUENCY SYNTHESIZER	6737	213001	2016-05-23	2017-05-22
Mini-circuits	Amplifier	ZVA-183-S+	771001215	2016-05-20	2017-05-19
HP	Amplifier	8449B	3008A00277	2016-12-02	2017-12-01
EMCT	Semi-Anechoic Chamber	966	966-1	2015-04-24	2018-04-23
Unknown	RF Cable (below 1GHz)	Unknown	NO.1	2016-11-10	2017-11-09
Unknown	RF Cable (below 1GHz)	Unknown	NO.4	2016-11-10	2017-11-09
Unknown	RF Cable (above 1GHz)	Unknown	NO.2	2016-11-10	2017-11-09
Ducommun Technologies	Horn Antenna	ARH-4223-02	1007726-011315	2016-08-18	2017-08-18
Ducommun Technologies	Horn Antenna	ARH-2823-02	1007726-011312	2016-08-18	2017-08-18

* **Statement of Traceability:** BACL(Chengdu) attests that all of the calibrations on the equipment items listed above were traceable to NIM or to another internationally recognized National Metrology Institute (NMI), and were compliant with the NIST HB 150-2016 Normative Annex B "Implementation of traceability policy in accredited laboratories".

Test Data

Environmental Conditions

Temperature:	23.1 °C
Relative Humidity:	61.9 %
ATM Pressure:	100.7kPa

The testing was performed by Kevin Hu on 2017-04-26.

EUT Operation Mode: Transmitting

Cellular Band

30MHz-10 GHz:

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBµV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			S.G. Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
GSM850, Frequency:836.600 MHz								
1673.200	H	53.53	-49.6	7.9	0.8	-42.5	-13.0	29.5
1673.200	V	48.83	-52.5	7.9	0.8	-45.4	-13.0	32.4
2509.800	H	60.72	-39	8.9	1.3	-31.4	-13.0	18.4
2509.800	V	50.90	-46.6	8.9	1.3	-39.0	-13.0	26.0
549.000	H	43.10	-65.9	0.0	0.4	-66.3	-13.0	53.3
417.000	V	46.10	-63.9	0.0	0.4	-64.3	-13.0	51.3
WCDMA Band V R99, Frequency:836.600 MHz								
1673.200	H	52.25	-50.9	7.9	0.8	-43.8	-13.0	30.8
1673.200	V	47.58	-53.8	7.9	0.8	-46.7	-13.0	33.7
2509.800	H	60.06	-39.7	8.9	1.3	-32.1	-13.0	19.1
2509.800	V	49.89	-47.6	8.9	1.3	-40.0	-13.0	27.0
437.500	H	42.29	-69.2	0.0	0.4	-69.6	-13.0	56.6
654.900	V	45.35	-60.2	0.0	0.5	-60.7	-13.0	47.7

PCS Band

30MHz-20GHz:

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBµV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			S.G. Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
GSM1900, Frequency:1880.000 MHz								
3760.000	H	53.12	-41.8	8.8	1.4	-34.4	-13.0	21.4
3760.000	V	49.78	-45.1	8.8	1.4	-37.7	-13.0	24.7
5640.000	H	46.00	-47.1	10.3	1.8	-38.6	-13.0	25.6
5640.000	V	47.58	-45.6	10.3	1.8	-37.1	-13.0	24.1
655.000	H	45.30	-60.8	0.0	0.5	-61.3	-13.0	48.3
736.000	V	44.20	-61.7	0.0	0.6	-62.3	-13.0	49.3
WCDMA Band II, R99, Frequency:1880.000 MHz								
3760.000	H	53.33	-41.5	8.8	1.4	-34.1	-13.0	21.1
3760.000	V	48.64	-46.2	8.8	1.4	-38.8	-13.0	25.8
5640.000	H	59.24	-33.9	10.3	1.8	-25.4	-13.0	12.4
5640.000	V	50.60	-42.5	10.3	1.8	-34.0	-13.0	21.0
439.800	H	43.31	-68.2	0.0	0.4	-68.6	-13.0	55.6
656.100	V	46.17	-59.4	0.0	0.5	-59.9	-13.0	46.9

AWS Band

30MHz-20GHz:

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			S.G. Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
WCDMA Band IV, R99, Frequency:1732.6.000 MHz								
3465.200	H	52.40	-44.2	8.8	1.3	-36.7	-13.0	23.7
3465.200	V	47.72	-49	8.8	1.3	-41.5	-13.0	28.5
5197.800	H	59.92	-33.3	10.0	1.7	-25.0	-13.0	12.0
5197.800	V	49.78	-43.3	10.0	1.7	-35.0	-13.0	22.0
439.800	H	43.19	-68.3	0.0	0.4	-68.7	-13.0	55.7
667.300	V	44.56	-61.3	0.0	0.5	-61.8	-13.0	48.8

LTE Band II (30MHz-20GHz):

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			S.G. Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
QPSK, Frequency: 1880.000 MHz								
3760.000	H	42.30	-52.6	8.8	1.4	-45.2	-13.0	32.2
3760.000	V	46.40	-48.5	8.8	1.4	-41.1	-13.0	28.1
5640.000	H	36.20	-56.9	10.3	1.8	-48.4	-13.0	35.4
5640.000	V	40.00	-53.1	10.3	1.8	-44.6	-13.0	31.6
435.500	H	43.31	-68.2	0.0	0.4	-68.6	-13.0	55.6
645.200	V	46.17	-59.1	0.0	0.5	-59.6	-13.0	46.6
16-QAM, Frequency: 1880.000 MHz								
3760.000	H	42.80	-52.1	8.8	1.4	-44.7	-13.0	31.7
3760.000	V	47.20	-47.7	8.8	1.4	-40.3	-13.0	27.3
5640.000	H	37.30	-55.8	10.3	1.8	-47.3	-13.0	34.3
5640.000	V	41.40	-51.7	10.3	1.8	-43.2	-13.0	30.2
435.500	H	43.31	-68.2	0.0	0.4	-68.6	-13.0	55.6
645.200	V	46.17	-59.1	0.0	0.5	-59.6	-13.0	46.6

Note:

- 1) The unit of Antenna Gain is dBd for frequency below 1GHz, and the unit of Antenna Gain is dBi for frequency above 1GHz.
- 2) Absolute Level = SG Level - Cable loss + Antenna Gain
- 3) Margin = Limit-Absolute Level

FCC §22.917(a) & §24.238(a) & §27.53- BAND EDGES

Applicable Standard

According to § 22.917(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

According to §24.238(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.


According to §27.53 (h), AWS emission limits—(1) General protection levels. Except as otherwise specified below, for operations in the 1695-1710 MHz, 1710-1755 MHz, 1755-1780 MHz, 1915-1920 MHz, 1995-2000 MHz, 2000-2020 MHz, 2110-2155 MHz, 2155-2180 MHz, and 2180-2200 bands, the power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) in watts by at least $43 + 10 \log_{10}(P)$ dB.

According to §27.53 (m), (4) For mobile digital stations, the attenuation factor shall be not less than $40 + 10 \log(P)$ dB on all frequencies between the channel edge and 5 megahertz from the channel edge, $43 + 10 \log(P)$ dB on all frequencies between 5 megahertz and X megahertz from the channel edge, and $55 + 10 \log(P)$ dB on all frequencies more than X megahertz from the channel edge, where X is the greater of 6 megahertz or the actual emission bandwidth as defined in paragraph (m)(6) of this section. In addition, the attenuation factor shall not be less than $43 + 10 \log(P)$ dB on all frequencies between 2490.5 MHz and 2496 MHz and $55 + 10 \log(P)$ dB at or below 2490.5 MHz. Mobile Satellite Service licensees operating on frequencies below 2495 MHz may also submit a documented interference complaint against BRS licensees operating on channel BRS Channel 1 on the same terms and conditions as adjacent channel BRS or EBS licensees.

Test Procedure

The RF output of the transmitter was connected to the input of the spectrum analyzer through sufficient attenuation.

The center of the spectrum analyzer was set to block edge frequency.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Signal Analyzer	FSIQ26	831929/005	2016-09-21	2017-09-20
Rohde & Schwarz	Spectrum Analyzer	FSEM30	100018	2016-12-02	2017-12-01
Unknown	RF Cable	Unknown	NO.3	Each Time	/
Unknown	Two-way Splitter	Unknown	OE0120121	Each Time	/

* **Statement of Traceability:** BACL(Chengdu) attests that all of the calibrations on the equipment items listed above were traceable to NIM or to another internationally recognized National Metrology Institute (NMI), and were compliant with the NIST HB 150-2016 Normative Annex B "Implementation of traceability policy in accredited laboratories".

Test Data

Environmental Conditions


Temperature:	26.7~29.5 °C
Relative Humidity:	32 ~ 50.1 %
ATM Pressure:	100.1 kPa

The testing was performed by Kevin Hu from 2017-05-11 to 2017-05-13.

Test Mode: Transmitting


Test Result: Compliant. Please refer to the following plots.

GSM 850, Left Band Edge




Date: 13.MAY 2017 18:51:42

GSM 850, Right Band Edge




Date: 13.MAY 2017 18:52:39


GSM 1900, Left Band Edge



GSM 1900, Right Band Edge




EDGE 850, Left Band Edge




Date: 13.MAY 2017 18:56:27

EDGE 850, Right Band Edge




Date: 13.MAY 2017 18:55:47

EDGE 1900, Left Band Edge




Date: 13.MAY 2017 18:44:33

EDGE 1900, Right Band Edge




Date: 13.MAY 2017 18:46:21


REL99 Band II, Left Band Edge




REL99 Band II, Right Band Edge




HSDPA Band II, Left Band Edge




HSDPA Band II, Right Band Edge



HSUPA Band II, Left Band Edge




HSUPA Band II, Right Band Edge




WCDMA Band IV

REL99 Band IV, Left Band Edge




Date: 13.MAY 2017 20:05:50

REL99 Band IV Right Band Edge




Date: 13.MAY 2017 20:08:12

HSDPA Band IV, Left Band Edge




HSDPA Band IV, Right Band Edge



HSUPA Band IV, Left Band Edge


Marker 1 [T1] RBW 100 kHz RF Att 30 dB
Ref Lvl -16.25 dBm VBW 300 kHz
34 dBm 1.71003096 GHz SWT 5 ms Unit dBm



Date: 13.MAY 2017 20:05:32

HSUPA Band IV, Right Band Edge


Marker 1 [T1] RBW 100 kHz RF Att 30 dB
Ref Lvl -16.97 dBm VBW 300 kHz
34 dBm 1.75498968 GHz SWT 5 ms Unit dBm



Date: 13.MAY 2017 20:07:55


WCDMA Band V

REL99 Band V, Left Band Edge




Date: 13.MAY 2017 20:14:15

REL99 Band V Right Band Edge




Date: 13.MAY 2017 20:12:27


HSDPA Band V, Left Band Edge



HSDPA Band V, Right Band Edge



HSUPA Band V, Left Band Edge




HSUPA Band V, Right Band Edge




LTE Band II


QPSK_1.4MHz_6 RB_Left




QPSK_1.4MHz_6 RB_Right




QPSK_3MHz_15 RB_ Left




QPSK_3MHz_15 RB_ Right




QPSK_5MHz_25 RB_ Left




QPSK_5MHz_25 RB_ Right




QPSK_10MHz_50 RB_Left




QPSK_10MHz_50 RB_Right




QPSK_15MHz_75 RB_ Left




QPSK_15MHz_75 RB_ Right




QPSK_20MHz_FULL RB_Left




QPSK_20MHz_FULL RB_Right




16QAM_1.4MHz_6 RB_Left




16QAM_1.4MHz_6 RB_Right




16QAM_3MHz_ 15 RB_ Left




16QAM_3MHz_ 15 RB_ Right




16QAM_5MHz_25 RB_ Left




16QAM_5MHz_25 RB_ Right




16QAM_10MHz_50 RB_ Left




16QAM_10MHz_50 RB_ Right




16QAM_15MHz_75 RB_ Left




16QAM_15MHz_75 RB_ Right



16QAM_20MHz_FULL RB_Left



16QAM_20MHz_FULL RB_Right



FCC §2.1055, §22.355 & §24.235 & §27.54 - FREQUENCY STABILITY

Applicable Standard

FCC § 2.1055 (a), § 2.1055 (d), §22.355, §24.235, §27.54

According to §22.355, the carrier frequency of each transmitter in the Public Mobile Services must be maintained within the tolerances given in Table below:

Frequency Tolerance for Transmitters in the Public Mobile Services

Frequency Range (MHz)	Base, fixed (ppm)	Mobile > 3 watts (ppm)	Mobile ≤ 3 watts (ppm)
25 to 50	20.0	20.0	50.0
50 to 450	5.0	5.0	50.0
450 to 512	2.5	5.0	5.0
821 to 896	1.5	2.5	2.5
928 to 929.	5.0	N/A	N/A
929 to 960.	1.5	N/A	N/A
2110 to 2220	10.0	N/A	N/A

According to §24.235, the frequency stability shall be sufficient to ensure that the fundamental emissions stays within the authorized frequency block.


According to §27.54, the frequency stability shall be sufficient to ensure that the fundamental emissions stay within the authorized bands of operation.

Test Procedure

Frequency Stability vs. Temperature: The equipment under test was connected to an external DC power supply and the RF output was connected to communication test set via feed-through attenuators. The EUT was placed inside the temperature chamber. The DC leads and RF output cable exited the chamber through an opening made for the purpose.

After the temperature stabilized for approximately 20 minutes, the frequency output was recorded from the communication test set.

Frequency Stability vs. Voltage: An external variable DC power supply was connected to the battery terminals of the equipment under test. The output frequency was recorded for each battery voltage.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
BACL	High Temperature Test Chamber	BTH-150	30024	2016-12-02	2017-12-01
FLUKE	Multimeter	1587	27870099	2016-12-30	2017-12-29
R&S	Universal Radio Communication Tester	CMU200	11-9435686-111	2016-07-28	2017-07-27
R&S	Wideband Radio Communication Tester	CMW500	106891	2016-11-23	2017-11-23
Unknown	RF Cable	Unknown	NO.3	Each Time	/

* **Statement of Traceability:** BACL(Chengdu) attests that all of the calibrations on the equipment items listed above were traceable to NIM or to another internationally recognized National Metrology Institute (NMI), and were compliant with the NIST HB 150-2016 Normative Annex B “Implementation of traceability policy in accredited laboratories”.

Test Data

Environmental Conditions

Temperature:	23.1 °C
Relative Humidity:	61.9 %
ATM Pressure:	100.7kPa

The testing was performed by Kevin Hu on 2017-04-26.

Cellular Band (Part 22H)

GMSK, Middle Channel, $f_c = 836.6$ MHz				
Temperature	Voltage	Frequency Error	Frequency Error	Limit
°C	V_{DC}	Hz	ppm	ppm
-30	3.8	-9	-0.011	2.5
-20	3.8	-9	-0.011	2.5
-10	3.8	-5	-0.006	2.5
0	3.8	-9	-0.011	2.5
10	3.8	2	0.002	2.5
20	3.8	2	0.002	2.5
30	3.8	-10	-0.012	2.5
40	3.8	-1	-0.001	2.5
50	3.8	-3	-0.004	2.5
25	3.6	-6	-0.007	2.5
25	4.3	1	0.001	2.5

Cellular Band (Part 22H)

EDGE, Middle Channel, $f_c = 836.6$ MHz				
Temperature	Voltage	Frequency Error	Frequency Error	Limit
°C	V_{DC}	Hz	ppm	ppm
-30	3.8	12	0.014	2.5
-20	3.8	-5	-0.006	2.5
-10	3.8	-1	-0.001	2.5
0	3.8	8	0.010	2.5
10	3.8	6	0.007	2.5
20	3.8	5	0.006	2.5
30	3.8	13	0.016	2.5
40	3.8	9	0.011	2.5
50	3.8	6	0.007	2.5
25	3.6	12	0.014	2.5
25	4.3	4	0.005	2.5

PCS Band (Part 24E)

GMSK, Middle Channel, $f_c = 1880.0$ MHz				
Temperature	Voltage	Frequency Error	Frequency Error	Result
°C	V _{DC}	Hz	ppm	
-30	3.8	6	0.003	Pass
-20	3.8	1	0.001	Pass
-10	3.8	-4	-0.002	Pass
0	3.8	-3	-0.002	Pass
10	3.8	4	0.002	Pass
20	3.8	2	0.001	Pass
30	3.8	-3	-0.002	Pass
40	3.8	5	0.003	Pass
50	3.8	1	0.001	Pass
25	3.6	5	0.003	Pass
25	4.3	-5	-0.003	Pass

PCS Band (Part 24E)

EDGE, Middle Channel, $f_c = 1880.0$ MHz				
Temperature	Voltage	Frequency Error	Frequency Error	Result
°C	V _{DC}	Hz	ppm	
-30	3.8	3	0.002	Pass
-20	3.8	-11	-0.006	Pass
-10	3.8	4	0.002	Pass
0	3.8	2	0.001	Pass
10	3.8	-9	-0.005	Pass
20	3.8	-13	-0.007	Pass
30	3.8	-5	-0.003	Pass
40	3.8	5	0.003	Pass
50	3.8	-10	-0.005	Pass
25	3.6	-10	-0.005	Pass
25	4.3	5	0.003	Pass

WCDMA Band IV :

Middle Channel, $f_c = 1732.6$ MHz				
Temperature	Voltage	Frequency Error	Frequency Error	Limit
°C	V _{DC}	Hz	ppm	ppm
-30	3.8	11	0.006	2.5
-20	3.8	-1	-0.001	2.5
-10	3.8	9	0.005	2.5
0	3.8	2	0.001	2.5
10	3.8	-1	-0.001	2.5
20	3.8	16	0.009	2.5
30	3.8	8	0.004	2.5
40	3.8	12	0.006	2.5
50	3.8	8	0.004	2.5
25	3.6	14	0.007	2.5
25	4.3	7	0.004	2.5

WCDMA Band V :

Middle Channel, $f_c = 836.6$ MHz				
Temperature	Voltage	Frequency Error	Frequency Error	Limit
°C	V _{DC}	Hz	ppm	ppm
-30	3.8	8	0.010	2.5
-20	3.8	16	0.019	2.5
-10	3.8	7	0.008	2.5
0	3.8	4	0.005	2.5
10	3.8	15	0.018	2.5
20	3.8	14	0.017	2.5
30	3.8	5	0.006	2.5
40	3.8	14	0.017	2.5
50	3.8	10	0.012	2.5
25	3.6	8	0.010	2.5
25	4.3	4	0.005	2.5

WCDMA Band II :

Middle Channel, $f_c = 1880.0$ MHz				
Temperature	Voltage	Frequency Error	Frequency Error	Result
°C	V _{DC}	Hz	ppm	
-30	3.8	2	0.001	Pass
-20	3.8	4	0.002	Pass
-10	3.8	1	0.001	Pass
0	3.8	9	0.005	Pass
10	3.8	7	0.004	Pass
20	3.8	1	0.001	Pass
30	3.8	6	0.003	Pass
40	3.8	8	0.004	Pass
50	3.8	6	0.003	Pass
25	3.6	-3	-0.002	Pass
25	4.3	-3	-0.002	Pass

LTE Band II:

QPSK, Channel Bandwidth:10MHz Middle Channel, $f_c = 1880$ MHz				
Temperature	Voltage	Frequency Error	Frequency Error	Result
°C	V _{DC}	Hz	ppm	
-30	3.8	-4.53	-0.0024	Pass
-20	3.8	-4.48	-0.0024	Pass
-10	3.8	-4.56	-0.0024	Pass
0	3.8	-4.52	-0.0024	Pass
10	3.8	-4.52	-0.0024	Pass
20	3.8	-4.49	-0.0024	Pass
30	3.8	-4.56	-0.0024	Pass
40	3.8	-4.53	-0.0024	Pass
50	3.8	-4.56	-0.0024	Pass
25	3.6	-4.51	-0.0024	Pass
25	4.3	-4.48	-0.0024	Pass

16QAM, Channel Bandwidth:10MHz Middle Channel, $f_c = 1880$ MHz				
Temperature	Voltage	Frequency Error	Frequency Error	Result
°C	V _{DC}	Hz	ppm	
-30	3.8	3.62	0.0019	Pass
-20	3.8	3.63	0.0019	Pass
-10	3.8	3.73	0.0020	Pass
0	3.8	3.66	0.0019	Pass
10	3.8	3.70	0.0020	Pass
20	3.8	3.65	0.0019	Pass
30	3.8	3.77	0.0020	Pass
40	3.8	3.64	0.0019	Pass
50	3.8	3.60	0.0019	Pass
25	3.6	3.63	0.0019	Pass
25	4.3	3.56	0.0019	Pass

Note: The fundamental emissions stay within the authorized bands of operation based on the frequency deviation measured is small, the extreme voltage was declared by applicant.

***** **END OF REPORT** *****