

Test Report Prepared By:

Electronics Test Centre
27 East Lake Hill
Airdrie, Alberta
Canada
T4A 2K3

sales@etc-mpbtech.com
<http://www.etc-mpb.com>

Telephone: 1-403-912-0037

ETC Report #: t29e23a158_Mob_DSS Release 2

Report date: May 2, 2023

EMC testing of the Tektelic Communication Inc. Pearl Mobile Gateway in accordance with FCC Part 15.247 and ANSI C63.10: 2013 as referenced by FCC OET KDB 558074 D01 15.247 Meas Guidance v05r02.

FCC ID: 2ALEPT0004437

Test Dates: 2023-03-07 to 2023-05-02

Test Personnel: Branden Van Hee, Janet Mijares, Imran Akram

Prepared for: Tektelic Communication Inc.

7657 10th Street NE
Calgary, Alberta
Canada
T2E 8X2

Telephone: 1-403-338-6910



Imran Akram
iakram@etc-mpbtech.com
EMC Technologist
Electronics Test Centre (Airdrie)



Marc Rousseau
marc.rousseau@mpbc.ca
QA Manager
Electronics Test Centre (Airdrie)

REVISION RECORD

ISSUE	DATE	AUTHOR	REVISIONS
DRAFT 1	2023-03-20	I. Akram	Initial draft submitted for review.
DRAFT 2	2023-04-13	I. Akram	Power/OBW measurements plots update with correct frequencies
Release 1	2023-04-26	I. Akram	Sign Off
Release 2	2023-04-26	I. Akram	Power/OBW measurements plots update after tuning up the output power Sign Off

TABLE OF CONTENTS

1.0	INTRODUCTION	4
1.1	Scope	4
1.2	Applicant	4
1.3	Test Sample Description	4
1.4	General Test Conditions	4
1.5	Reference Standards	5
1.6	Test Methodology	5
1.6.1	Variations in Test Methodology	5
1.6.2	Test Sample Verification, Configuration & Modifications	5
1.6.3	Uncertainty of Measurement	5
2.0	TEST CONCLUSION	6
2.1	AC Main Power Line Conducted Emissions: N/A	7
2.2	Occupied Bandwidth	8
2.2.1	Test Guidance: ANSI C63.10-2013, Clause 6.9.2 & 6.9.3/ FCC OET KDB 558074	8
2.2.2	Deviations From The Standard	8
2.2.3	Test Equipment	8
2.2.4	Test Sample Verification, Configuration & Modifications	9
2.2.5	Channel Occupied Bandwidth Data: DSS	9
2.3	Max Average Output Power	12
2.3.1	Test Guidance: ANSI C63.10-2013, Clause 11.9.2.2.2 Clause 7.8.5 / FCC OET KDB 558074	12
2.3.2	Deviations From The Standard	13
2.3.3	Test Equipment	13
2.3.4	Test Sample Verification, Configuration & Modifications	13
2.3.5	Max Output Power Data: DSS	13
2.4	EUT Positioning Assessment	16
2.5	Radiated Spurious Emissions within restricted band	17
2.5.1	Test Guidance: ANSI C63.10-2013, Clause 13.4.2	18
2.5.2	Deviations From The Standard	18
2.5.3	Test Equipment	18
2.5.4	Test Sample Verification, Configuration & Modifications	19
2.5.5	Radiated Emissions Data: FHSS (125 KHz)	20
2.6	Radiated Emissions (RX Mode)	24
2.6.1	Test Guidance	24
2.6.2	Deviations From The Standard	24
2.6.3	Test Equipment	25
2.6.4	Test Sample Verification, Configuration & Modifications	25
2.6.5	Radiated Emissions Data maximization	26
2.7	RF Exposure	29
3.0	TEST FACILITY	30
3.1	Location	30
3.2	Grounding Plan	30
3.3	Power Supply	30
	Appendix A – Test Setup Block Diagram	31

1.0 INTRODUCTION

1.1 Scope

The purpose of this report is to present the results of compliance testing performed in accordance with FCC Part 15.247 and ANSI C63.10-2013 to gain FCC Class II permissive change Authorization for Low-Power License-Exempt transmitters. All test procedures, limits, criteria, and results described in this report apply only to the Tektelic Communication Inc. Pearl Mobile Gateway test sample, referred to herein as the EUT (Equipment Under Test).

This report does not imply product endorsement by the Electronics Test Centre, A2LA, nor any Canadian Government agency.

1.2 Applicant

This test report has been prepared for Tektelic Communication Inc., located in Calgary, Alberta, Canada.

1.3 Test Sample Description

As provided to ETC (Airdrie) by Tektelic Communication Inc.:

Product Name:		Pearl Mobile Gateway
LoRa Radio	Frequency Band	902 – 928 MHz
	Frequency Range	912.31 – 927.0125 MHz
	Type of Modulation	FHSS 125KHz
	Max Transmit Power (Conducted)	0.151 W
Associated LoRa Antennas		Frequency = 896-940MHz Model# BMUF9115 Polarization = Vertical, linear, Gain 5dBi
Gateway (Pearl)	Model#	T0004437 Rev F
	Serial#	2307k0001
Power supply:		DC Powered

1.4 General Test Conditions

The EUT was set up and exercised using the configurations, modes of operation and arrangements defined in this report only. All inputs and outputs to and from other equipment associated with the EUT were adequately simulated.

Where relevant, the EUT was only tested using the monitoring methods and test criteria defined in this report.

The environmental conditions are recorded during each test, and are reported in the relevant sections of this document.

1.5 Reference Standards

Standards	Description
FCC, title 47 CFR § 15.247	Operation within the bands 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz.
FCC, title 47 CFR § 15.207	Conducted limits for an intentional radiator that is designed to be connected to the public utility (AC) power line.
FCC, title 47 CFR § 15.107	Conducted limits for equipment that is designed to be connected to the public utility (AC) power line.
FCC, title 47 CFR § 15.209	Radiated emission limits; general requirements
FCC, title 47 CFR § 15.109	Radiated emission limits; from unintentional radiators digital devices.
ANSI C63.10-2013	American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices
ANSI C63.4-2014	American National Standard for Methods of Measurement of Radio – Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 KHz to 40 GHz
558074 D01 15.247 Meas Guidance v05r02	Guidance For Compliance Measurements On Digital Transmission System, Frequency Hopping Spread Spectrum System, And Hybrid System Devices Operating Under Section 15.247 Of The FCC Rules

1.6 Test Methodology

Test methods are specified in the Basic Standard as referenced and/or modified by the Product Standard in the part of Section 2 of this report associated with each particular test case. Separate test report is provided to customer for RX mode under SDOC.

1.6.1 Variations in Test Methodology

Any variance in methodology or deviation from the reference Standard is documented in the part of Section 2 of this report associated with each particular Test Case.

1.6.2 Test Sample Verification, Configuration & Modifications

EUT setup, configuration, protocols for operation and monitoring of EUT functions, and any modifications performed in order to meet the requirements, are detailed in each Test Case of Section 2 of this report.

1.6.3 Uncertainty of Measurement:

The factors contributing to measurement uncertainty are identified and calculated in accordance with CISPR 16-4-2: 2011.

This uncertainty estimate represents an expended uncertainty expressed at approximately 95% confidence using a coverage factor of $k = 2$.

Test Method	Uncertainty
Radiated Emissions Level (9 KHz – 1 GHz)	±5.8 dB
Radiated Emissions Level (1 GHz – 18 GHz)	±4.9 dB
Radiated Emissions Level (18 GHz – 26.5 GHz)	±5.0 dB
Conducted Emissions Level (150 KHz – 30 MHz)	±3.0 dB
Uncertainty Conducted Power level	±0.5 dB
Uncertainty Conducted Spurious emission level	±0.6 dB
Uncertainty for Bandwidth test	±1.5 %

2.0 TEST CONCLUSION

STATEMENT OF COMPLIANCE

The customer equipment referred to in this report was found to comply with the requirements, as summarized below.

The EUT was subjected to the following tests. Compliance status is reported as **Compliant** or **Non-compliant**. **N/A** indicates the test was Not Applicable to the EUT.

The measurement uncertainty is not accounted for determination of the statement of compliance. The statement of compliance is based only on the measurement value recorded.

Note: Maintenance of compliance is the responsibility of the Manufacturer. Any modifications to the product should be assessed to determine their potential impact on the compliance status of the EUT with respect to the standards detailed in this test report.

The following table summarizes the tests performed in terms of the specification, class or performance criterion applied, and the EUT modification state.

Test Case	Test Type	Specification	Test Sample	Modifications	Config.	Result
2.1	AC Main Conducted Emissions	15.207 / 15.109	Pearl Mobile Gateway	none	see § 2.1	N/A
2.2	Occupied Bandwidth	15.247(a)(1) 15.247(2)(2)	Pearl Mobile Gateway	none	see § 2.2	Compliant
2.3	Max Output Average Power	15.247(b)	Pearl Mobile Gateway	none	see § 2.3	Compliant
2.4	EUT Position	ANSI C63.4	Pearl Mobile Gateway	none	see § 2.5	N/A Fix Position
2.5	Radiated Spurious Emission (Restricted Band)	15.205, 15.209 15.247(d)	Pearl Mobile Gateway	none	see § 2.6	Compliant
2.6	Radiated Emission	15.109	Pearl Mobile Gateway	none	see § 2.7	Compliant
2.7	RF Exposure	15.247(i)	Pearl Mobile Gateway	none	see § 2.8	Exempt

Refer to the test data for applicable test conditions.

2.1 AC Main Power Line Conducted Emissions: N/A

Test Lab: Electronics Test Centre, Airdrie	EUT: Pearl Mobile Gateway Standard: FCC Part 15.207, FCC Part 15.107 Basic Standard: ANSI C63.10: 2013 Basic Standard: ANSI C63.4: 2014
EUT status: N/A	
Comments: EUT is DC Powered. No Direct/indirect connection to AC main.	

2.2 Occupied Bandwidth

Test Lab: Electronics Test Centre, Airdrie	EUT: Pearl Mobile Gateway
Test Personnel: Imran Akram	Standard: FCC PART 15.247
Date: 2023-05-02 (21.4°C,22.3% RH)	Basic Standard: ANSI C63.10-2013 FCC OET KDB 558074
EUT status: Compliant	

Specification: FCC Part 15.247 (a, 1, i)

Criteria: The maximum allowed 20 dB bandwidth of the hopping channel is 250 kHz.

2.2.1 Test Guidance: ANSI C63.10-2013, Clause 6.9.2 & 6.9.3/ FCC OET KDB 558074

This measurement is performed at low, mid and high frequencies, with modulation.

The RF output of EUT with an antenna connector is fed to the input of the spectrum analyzer through appropriate attenuation. The loss from the cable and the attenuator were added on the analyzer as gain offset setting there by allowing direct measurements, without the need for any further corrections.

Use the following spectrum analyzer setting:	
Span	Between two time and five times the channel center frequency OBW
RBW	1% to 5% of the OBW
VBW	Approximately three times of RBW
Sweep	Auto Couple
Detector Function	Peak
Trace	Max Hold
Allow the trace to stabilize. The automated 99% BW function of the spectrum analyzer is engaged, 20dB bandwidth is measured with the X dB function.	

2.2.2 Deviations From The Standard:

There were no deviations from the EUT setup or methodology specified in the standard.

2.2.3 Test Equipment

Testing was performed with the following equipment:


Equipment	Manufacturer	Model #	Asset #	Cal. Date	Cal. Due
EMI receiver	Agilent	N9038A (FW A.25.05)	6130	2022-07-12	2023-07-12
Temp/Humidity	Extech	42270	5871	2022-05-09	2023-05-09
Attenuator	Fairview Microwave	SA18N5WA-10	6886	Cal. before each use	
Coaxial Cables (RF)	W.L. Gore	Pgr10R01036.0	-	Cal. before each use	

2.2.4 Test Sample Verification, Configuration & Modifications

The EUT was set to transmit continuously on a selected channel with test-specific software. The output was modulated as in normal operation. The EUT met the requirements without modification.

Test setup diagrams for Occupied Bandwidth testing:

Conducted:




2.2.5 Channel Occupied Bandwidth Data:


Mode of operation	Channel	Freq. [MHz]	Occupied BW [kHz]	20 dB BW [kHz]	Limit 20dB BW [KHz]
125KHz FHSS	Low	912.31	127.04	144.5	≤ 250
	Mid	919.51	126.81	141.4	
	High	927.0125	126.81	141.5	

FHSS (125 KHz) Mode


Screen Captures from the spectrum analyzer: Low Channel



Screen Captures from the spectrum analyzer: MID Channel



Screen Captures from the spectrum analyzer: High Channel



2.3 Max Average Output Power

Test Lab: Electronics Test Centre, Airdrie	EUT: Pearl Mobile Gateway
Test Personnel: Imran Akram	Standard: FCC PART 15.247
Date: : 2023-05-02 (21.4°C,22.3% RH)	Basic Standard: ANSI C63.10: 2013 FCC OET KDB 558074
EUT status: Compliant	

Specification: FCC Part 15.247(b, 2)

Criteria For frequency hopping systems operating in the 902-928 MHz band: 1 watt for systems employing at least 50 hopping channels
--

2.3.1 Test Guidance: ANSI C63.10-2013, Clause 11.9.2.2 Clause 7.8.5 / FCC OET KDB 558074

This measurement is performed at low, mid and high frequencies, with modulation.

The RF output of EUT with an antenna connector is fed to the input of the spectrum analyzer through appropriate attenuation. The loss from the cable and the attenuator were added on the analyzer as gain offset setting there by allowing direct measurements, without the need for any further corrections.

Output Power Method AVGSA-1 For DTS	
Span	≥ 1.5 times the OBW
RBW	1 – 5 % of the OBW, ≤ 1 MHz
VBW	≥ 3 x RBW
Number of Points in sweep	≥ 2 x Span / RBW
Sweep time	Auto Couple
Detector	RMS (Power Averaging)
Sweep trigger	Free Run (Duty Cycle ≥98%)
Trace Average	Minimum 100 traces in power Averaging (RMS)
Power measured	Integrated the spectrum across the OBW of the signal using the S/A band power measurement function, with band limit set equal to the OBW band edge.

2.3.2 Deviations From The Standard:

There were no deviations from the EUT setup or methodology specified in the standard.

2.3.3 Test Equipment

Testing was performed with the following equipment:

Equipment	Manufacturer	Model #	Asset #	Cal. Date	Cal. Due
EMI receiver	Agilent	N9038A (FW A.25.05)	6130	2022-07-12	2023-07-12
Temp/Humidity	Extech	42270	5871	2022-05-09	2023-05-09
Attenuator	Fairview Microwave	SA18N5WA-10	6886	Cal. before each use	
Coaxial Cables (RF)	W.L. Gore	Pgr10R01036.0	-	Cal. before each use	


2.3.4 Test Sample Verification, Configuration & Modifications

The EUT was set to a selected channel with test-specific software. The output was modulated as in normal operation.

The EUT met the requirements without modification.

Test setup diagrams for Peak Power testing:

Conducted:




2.3.5 Max Output Power Data: DSS


Mode of operation	Channel	Freq. [MHz]	Max Average Power [dBm]	Limit Power [dBm]
125KHz FHSS	Low	912.31	21.52	≤ 30 (1Watt)
	Mid	919.51	21.79	
	High	927.0125	21.07	

FHSS (125 KHz) Mode


Screen Captures from the spectrum analyzer Low Channel



Screen Captures from the spectrum analyzer: MID Channel



Screen Captures from the spectrum analyzer: High Channel



2.4 EUT Positioning Assessment

Test Lab: Electronics Test Centre, Airdrie

EUT: Pearl Mobile Gateway

Test Personnel:

Standard: FCC PART 15.247


Date:

Basic Standard: ANSI C63.4-2014

Comments: Not Applicable. EUT be mounted only in one fix position.

Specification: ANSI C63.4-2014, Clause 6.3.2.1

Portable, small, lightweight, or modular devices that may be handheld, worn on the body, or placed on a table during operation shall be positioned on a non-conducting platform, the top of which is 80 cm above the reference ground plane. The preferred area occupied by the EUT arrangement is 1 m by 1.5 m, but it may be larger or smaller to accommodate various sized EUTs (see Figure 6, Figure 7, and Figure 9). For testing purposes, ceiling- and wall-mounted devices also shall be positioned on a tabletop (see also 6.3.4 and 6.3.5). In making any tests involving handheld, body-worn, or ceiling-mounted equipment, it is essential to recognize that the measured levels may be dependent on the orientation (attitude) of the three orthogonal axes of the EUT. Thus, exploratory tests as specified in 8.3.1 shall be carried out for various axes orientations to determine the attitude having maximum or near-maximum emission level.



2.5 Radiated Spurious Emissions within restricted band

Test Lab: Electronics Test Centre, Airdrie	EUT: Pearl Mobile Gateway
Test Personnel: Janet Mijares/ Brendan Van Hee	Standard: FCC PART 15.247/15.209
Date: 2023-03-07/08 (19.9° C,6.4 % RH)	Basic Standard: ANSI C63.10-2013
EUT status: Compliant	

Specification: FCC PART 15.247(d)

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Restricted Bands of Operation:

MHz	MHz	MHz	MHz	MHz	GHz	GHz
0.090000 – 0.110000	8.291000 - 8.294000	16.804250 - 16.804750	162.01250 - 167.17000	1660.0000 – 1710.0000	3.6000000 – 4.4000000	14.470000 – 14.500000
0.4950000 - 0.5050000	8.3620000 - 8.3660000	25.500000 - 25.670000	167.72000 - 173.20000	1718.8000 – 1722.2000	4.5000000 – 5.1500000	15.350000 – 16.200000
2.1735000 - 2.1905000	8.3762500 - 8.3867500	37.500000 - 38.250000	240.00000 – 285.00000	2200.0000 – 2300.0000	5.3500000 – 5.4600000	17.700000 – 21.400000
4.1250000 - 4.1280000	8.4142500 - 8.4147500	73.000000 - 74.600000	322.00000 - 335.40000	2310.0000 – 2390.0000	7.2500000 – 7.7500000	22.010000 – 23.120000
4.1772500 - 4.1777500	12.290000 - 12.293000	74.800000 - 75.200000	399.90000 – 410.00000	2483.5000 – 2500.0000	8.0250000 – 8.5000000	23.600000 – 24.000000
4.2072500 - 4.2077500	12.519750 - 12.520250	108.00000 - 121.94000 **	608.00000 – 614.00000	2655.0000 – 2900.0000	9.0000000 – 9.2000000	31.200000 – 31.800000
5.6770000 - 5.6830000	12.576750 - 12.577250	123.00000 - 138.00000 **	960.00000 – 1240.00000 ***	3260.0000 – 3267.0000	9.3000000 – 9.5000000	36.430000 – 36.500000
6.2150000 - 6.2180000	13.360000 - 13.410000	149.90000 - 150.05000	1300.0000 – 1427.0000 ***	3332.0000 – 3339.0000	10.600000 – 12.700000	Above 38.600000
6.2677500 - 6.2682500	16.420000 - 16.423000	156.52475 - 156.52525	1435.0000 – 1626.5000	3345.8000 – 3358.0000	13.250000 – 13.400000	
6.3117500 - 6.3122500	16.694750 - 16.695250	156.70000 - 156.90000	1645.5000 – 1646.5000	3500.0000 – 3600.0000		

■ US only
 ■ Canada 108 – 138 MHz
 ■ Canada 960 – 1427 MHz
 ■ Canada only

2.5.1 Test Guidance: ANSI C63.10-2013, Clause 13.4.2

From 9 kHz to 150 kHz (resolution bandwidth of 200 Hz) and from 150 kHz to 30 MHz (resolution bandwidth 9 kHz) measurements are performed with a loop antenna (as per KDB 460108).

From 30 MHz to 1000 MHz, measurements are performed with a broadband biconilog antenna and a resolution bandwidth of 120 kHz.

Above 1000 MHz, measurements are performed with a DRG Horn antenna or a Standard Gain horn, and a resolution bandwidth of 1 MHz The EUT is raised to 150 cm above the ground plane, and the area between the EUT and the antenna mast is covered with RF absorbent material.

The scan is performed at discreet increments of turntable azimuth and antenna height, which are selected in accordance with the applicable standard in order to assure capture of frequencies of interest. Optimization is performed based on the scan data.

Frequencies having peak emissions within 10dB of the limits are optimized. The EUT is rotated in azimuth over 360 degrees and the direction of maximum emission is noted.

Antenna height is varied from 1 – 4 meters at this azimuth to obtain the maximum emission. Then the maximum level is measured with the appropriate detector and recorded. Up to 1 GHz, measurements are performed with a Quasi-Peak detector. Above 1 GHz, measurements are recorded with Peak and/or Average detectors, as applicable.

2.5.2 Deviations From The Standard:

There were no deviations from the EUT setup or methodology specified in the standard.

2.5.3 Test Equipment

Testing was performed with the following equipment:


Equipment	Manufacturer	Model #	Asset #	Cal. Date (yyyy-mm-dd)	Cal. Due (yyyy-mm-dd)
EMC Software	UL	Ver. 9.5	ETC-SW-EMC 2.1	N/A	
EMI receiver	Agilent	N9038A (FW A.25.05)	6130	2022-07-12	2023-07-12
Loop Antenna (9KHz – 30MHz)	EMCO	6502	10868	2021-05-11	2023-05-11
Biconilog Antenna (30 – 1000 MHz)	AR	JB1	6905	2021-10-29	2023-10-29
DRG Horn (1000 – 18000 MHz)	Tensor	4105	9588	2021-05-10	2023-05-10
Humidity/Temp Logger	Extech Ins. Corp.	42270	5892	2022-04-07	2023-04-07
Pre-Amplifier (30 – 1400 MHz)	HP	8447D	9291	2022-05-11	2023-05-11
Low Noise Amplifier (1 – 18 GHz)	MITEQ	JS43-01001800-21- 5P	4354	2022-05-11	2023-05-11
RE Cable below 1GHz	Insulated Wire Inc.	KPS-1501A-3600- KPA-01102006	4419	2022-05-11	2023-05-11
Re Cable Above 1 GHz	A.H. System Inc.	SAC-26G-8.23	6187	2022-05-11	2023-05-11
0.9GHz Notch Filter	Microtronics	BRM20784	6947	2022-05-11	2023-05-11
1.4GHz HPF	K & L	4DH21-R1793/6000-0/0	6952	2022-05-11	2023-05-11

2.5.4 Test Sample Verification, Configuration & Modifications


The EUT was set to a selected channel with test-specific software. The output was modulated as in normal operation. LoRa radio is transmitting at mid channel in single carrier configuration and high channel in dual carrier configurations.

The EUT met the requirements without modification.

Test setup diagram for Radiated Spurious Emissions testing (below 1GHz):



Test setup diagram for Radiated Spurious Emissions testing (above 1GHz):



2.5.5 Radiated Emissions Data: FHSS (125 KHz)

The emissions data are presented in tabular form, showing turntable azimuth, antenna height and polarization, the uncorrected spectrum analyzer reading, the correction factors applied, the net result, the value of the limit at the frequency investigated, and the Delta between the result and the limit.

**Meter Reading in dBμV + Antenna Factor in dB/m + Gain/Loss Factor in dB = Corrected Field Strength in dBμV/m.
 Delta = Field Strength – Limit**

Notes:

- When a preamp is used, the resulting gain is compensated, producing a negative value for the Cable Loss. Measurements reported are the result of adjusting the turntable azimuth and antenna height to obtain the maximum EUT emission. This may produce a different reading than the plot trace. The plot is a Peak Hold function obtained at discreet increments of height and azimuth, while the reported measurement is obtained with the appropriate Quasi Peak or Average detector after the height and azimuth have been adjusted for maximum emission. Preliminary scans were performed for all channels in Transmit modes. The MID band channel 919.5 MHz was selected as the worst-case condition for detailed examination. In Transmit mode, the EUT was assessed up to 10.0 GHz.

Negative values for Delta indicate compliance.

Freq. Marker	Freq. [MHz]	Raw reading [dBμv]	Det	Antenna Factor [dB/m]	Pre amp Gain [dB]	Corrected Reading [dBμv/m]	FCC 15.209 Limit [dBμv/m]	Delta [dB]	Azimuth [Deg]	Height [cm]	Polarization
1	*1091.4	28.35	AV	24.7	-35.6	1.45	54	-36.55	257	331	Horizontal
1	*1091.4	41.06	PK	24.7	-35.6	30.16	74	-43.84	257	331	Horizontal
2	*1349.8	40.85	AV	25.3	-35.1	31.05	54	-22.95	38	103	Horizontal
2	*1349.8	46.65	PK	25.3	-35.1	36.85	74	-37.15	38	103	Horizontal
3	*1071.0	42.13	AV	24.6	-35.6	31.13	54	-22.87	229	213	Vertical
3	*1071.0	48.84	PK	24.6	-35.6	37.84	74	-36.16	229	213	Vertical
4	*1349.8	40.18	AV	25.3	-35.1	30.38	54	-23.62	359	214	Vertical
4	*1349.8	46.35	PK	25.3	-35.1	36.55	74	-37.45	359	214	Vertical
5	*1521.7	28.47	AV	26	-34.8	19.67	54	-34.32	350	196	Vertical
5	*1521.7	41.4	PK	26	-34.8	32.6	74	-41.40	350	196	Vertical

PK: Peak Detector


AV: Average Detector.

*** Spurious Emission in Restricted Band**


Plot of Radiated Emissions:

< 30MHz Emission is more than 20dB below the limit.


Plot of Radiated Emissions: Horizontal polarization




Plot of Radiated Emissions: Vertical polarization



Plot of Radiated Emissions: Horizontal polarization



Plot of Radiated Emissions: Vertical polarization



2.6 Radiated Emissions (RX Mode)

Test Lab: Electronics Test Centre, Airdrie	EUT: Pearl Mobile Gateway
Test Personnel: Janet Mijares	Standard: FCC Part 15.109
Date: 2023-03-08 (19.9° C,6.4 % RH)	Basic Standard: ANSI C63.4: 2014
	Class: A

EUT status: Compliant

Frequency (MHz)	FCC Part 15.109 Class A Limit (3m)
30 – 88	49.54 (dB μ V/m)
88 – 216	53.98 (dB μ V/m)
216 – 960	56.90 (dB μ V/m)
Above 960	60 (dB μ V/m)

Criteria: The radiated emissions produced by a device, measured at a distance of 3 meters, shall not exceed the limits as specified.

2.6.1 Test Guidance:

From 30 MHz to 1000 MHz, measurements are performed with a broadband biconilog antenna and a resolution bandwidth of 120 kHz.

Above 1000 MHz, measurements are performed with a DRG Horn antenna or a Standard Gain horn, and a resolution bandwidth of 1 MHz.

The scan is performed at discreet increments of turntable azimuth and stepped antenna height, with peak detector and Max Hold function which are selected in accordance with the applicable standard in order to assure capture of frequencies of interest. Optimization is performed based on the scan data.

After the pre-scan is completed, the frequencies of interest are optimized. The EUT is rotated in azimuth over 360 degrees and the direction of maximum emission is noted.

Antenna height is varied from 1 – 4 meters at this azimuth to obtain the maximum emission. Then the maximum level is measured with the appropriate detector and recorded. This may produce a different reading than the pre scan trace. Up to 1 GHz, measurements are performed with a Quasi-Peak detector. Above 1 GHz, measurements are recorded with Peak and/or Average detectors, as applicable.

2.8.2 Deviations From The Standard:

There were no deviations from the EUT setup or methodology specified in the standard.

2.6.3 Test Equipment

Testing was performed with the following equipment:


Equipment	Manufacturer	Model #	Asset #	Calibration Date	Calibration Due
EMC Software	UL	Ver. 9.5	ETC-SW-EMC 2.1	N/A	
EMI receiver	Agilent	N9038A (FW A.25.05)	6130	2022-07-12	2023-07-12
Biconilog Antenna	SunAR RF Motion;	JB1	6905	2021-10-29	2023-10-29
DRG Horn	Tensor	4105	9588	2021-05-10	2023-05-10
T/H Logger	EXTECH Ins.	42270	5892	2022-04-07	2023-04-07
Pre- Amp	HP	8447D	9291	2022-05-11	2023-05-11
Low Noise Amplifier	MITEQ	JS43-01001800-21-5P	4354	2022-05-11	2023-05-11
RE Cable	Insulated Wire Inc.	KPS-1501A-3600-KPA-01102006	4419	2022-05-11	2023-05-11

2.6.4 Test Sample Verification, Configuration & Modifications

To cover the unintentional radiated emission. The EUT was configured in receive mode. Unit was placed at the center of turntable in semi-anechoic chamber 80cm above the ground plane and at a distance of 3m from the test receive antenna.

The EUT met the requirements without modification.

EUT RX configuration Block Diagram for Radiated Emissions testing:




2.6.5 Radiated Emissions Data maximization:

No Emission observed within 10 dB from the specified limit


Meter Reading in dB μ V + Antenna Factor in dB/m + Gain/Loss Factor in dB = Corrected Field Strength in db μ V/m.

- In receive mode, the EUT was assessed up to 5.0 GHz.


Plot of Radiated Emissions: Horizontal polarization




Plot of Radiated Emissions: Vertical polarization



Plot of Radiated Emissions: Horizontal polarization



Plot of Radiated Emissions: Vertical polarization



2.7 RF Exposure

Test Lab: Electronics Test Centre, Airdrie	EUT: Pearl Mobile Gateway
Test Personnel:	Standard: FCC PART 15.247
Date:	
EUT status: Compliant	

Compliant: RF exposure assessment to be provided in a separate Exhibit.

3.0 TEST FACILITY

3.1 Location

The Pearl Mobile Gateway was tested at the Electronics Test Centre laboratory located in Airdrie, Alberta, Canada. The Radio Frequency Anechoic Chamber (RFAC), identified as Chamber 1, has a usable working space measuring 10.6 m long x 7.3 m wide x 6.5 m high.

Measurements taken at this site are accepted by Industry Canada as evidence of conformity per registration file # 2046A. This site is also listed with the FCC under Registration Number CA2046.

The floor, walls and ceiling consist of annealed steel panels. The walls and ceiling are covered with ferrite tile, augmented by RF absorbant foam material on the end wall nearest the turntable, and on the adjacent walls and the ceiling. The chamber floor supports a 15 cm high internal floor, constructed of annealed steel panels, that forms the ground plane, and is bonded to the chamber walls.

The 3-m diameter turntable is flush-mounted with the floor. A sub-floor cable-way is provided to route cables between the turntable pit and EUT support equipment located in the Control Room. Cables reach the EUT through an opening in the centre of the turntable.

Test instrumentation and EUT support equipment is located in the Control Room, consisting of two shielded vestibules joined together at the side of the main room. Cables are routed through bulkhead panels between the rooms and the test chamber as required. Power feeds are routed into the main room and vestibules through line filters providing at least 100 dB of attenuation between 10 kHz and 10 GHz.

Either floor mounted or table-top equipment can be tested at this facility.

3.2 Grounding Plan


The Pearl Mobile Gateway was placed at the center of the test chamber turntable on top of an 80-cm high polystyrene foam table below 1GHz and at 1.5m high polystyrene foam table above 1 GHz for transmits mode and 80cm high for RX mode. Ground connection is provided as per customer specification.

3.3 Power Supply

All EUT power was supplied by DC Power Supply

Appendix A – Test Setup Block Diagram

TX MODE



End of Document