

Radio frequency radiation exposure evaluation: portable devices

RESULT :

Pass

Test Specification

Test item	: Golf Bluetooth Speaker
Identification / Type No.	: GB Voice XL
FCC ID	: 2ALG4GBVOICEXL
IC	: 27071-GBVOICEXL
Test standard	: CFR47 FCC Part 2: Section 2.1093 FCC KDB Publication 447498 D04 RSS-102 Issue 5

Calculation Method according to KDB 447498 D04

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}}(d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases} \quad (\text{B. 2})$$

where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right)$$

and f is in GHz, d is the separation distance (cm), and ERP20cm is per Formula (B.1). The example values shown in Table B.2 are for illustration only.

For FCC Measurement Record:

Test Mode	Conducted Power (dBm)	Conducted Power (mW)	Minimum Separation Distances (mm)	Limit (mW)
BLE	1.42	1.38	5	3
BR+EDR	2.27	1.68	5	3

For ISED Measurement Record:

Test Mode	Conducted Power (dBm)	E.I.R.P (dBm)	E.I.R.P (mW)	Minimum Separation Distances (mm)	Limit (mW)
BLE	1.42	0.84	1.21	5	4
BR+EDR	2.27	1.69	1.48	5	4

For ISED, output power level shall be the higher of the maximum conducted or effective isotropic radiated power (e.i.r.p.) source-based, time-averaged output power.

Hence the EUT is excluded from SAR evaluation if the distance between the antenna and the human body is equal or above one of the minimum distances depicted in the tables above, depending on the



wireless protocol in use, in accordance with FCC KDB Publication 447498 D04 Interim General RF Exposure Guidance v01 and RSS-102 Issue 5.