

# Maximum Permissible Exposure(MPE) Report

## 1. Applicable Standard

FCC Part §1.1310

## 2. Requirements

Limits For Maximum Permissible Exposure (MPE)				
Frequency range (MHz)	Electric field strength(V/m)	Magnetic field Strength(A/m)	Power density (mw/cm <sup>2</sup> )	Averaging time (minutes)
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f <sup>2</sup>	30
30-300	27.5	0.0173	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

## 3. MPE Calculation

Predication of MPE limit at a given distance

$$S = \frac{PG}{4\pi R^2}$$

S = Power density (In appropriate units, e.g., mW/cm<sup>2</sup>)

P = Power input to the antenna ( In appropriate units, e.g., mW)

G = Power gain og the antenna in the direction of interest relative to an isotropic radiator, the power gain factor,

Is normally numeric gain

R =Distance tp the center of radiation of the antenna(In appropriate units, e.g., cm

#### 4. Test Result

Operation Bands	Frequency (MHz)	Max. Output power(dBm)	Cable loss (dB)	Power to Antenna (mW)	Antenna gain	
					Isotropic	Numeric
UL698-716	702.00	22.12	3.5	72.78	8	6.31
UL776-787	780.70	19.76	3.7	40.36	8	6.31
DL728-746	736.46	6.71	1.3	3.48	6	3.98
DL746-757	750.99	8.55	1.3	5.31	5.5	3.55

Operation Bands	Power (mW)	Antenna gain(G)	Measure Distance(cm)	Power density (mW/cm <sup>2</sup> )	MPE limit (mW/cm <sup>2</sup> )
UL698-716	72.78	6.31	20	0.0914	0.468
UL776-787	40.36	6.31	20	0.0507	0.520
DL728-746	3.48	3.98	20	0.0028	0.491
DL746-757	5.31	3.55	20	0.0037	0.501

**Results: PASS**