

Maximum Permissible Exposure(MPE) Report

1. Applicable Standard

FCC Part §1.1310

2. Requirements

Limits For Maximum Permissible Exposure (MPE)				
Frequency range (MHz)	Electric field strength(V/m)	Magnetic field Strength(A/m)	Power density (mw/cm ²)	Averaging time (minutes)
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f ²	30
30-300	27.5	0.0173	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

3. MPE Calculation

Predication of MPE limit at a given distance

$$S = \frac{PG}{4\pi R^2}$$

S = Power density (In appropriate units, e.g., mW/cm²)

P = Power input to the antenna (In appropriate units, e.g., mW)

G = Power gain og the antenna in the direction of interest relative to an isotropic radiator, the power gain factor,

Is normally numeric gain

R =Distance tp the center of radiation of the antenna(In appropriate units, e.g., cm

4. Test Result

Operation Bands	Frequency (MHz)	Max. Output power(dBm)	Cable loss (dB)	Power to Antenna(mW)	Antenna gain	
					Isotropic	Numeric
UL698-716	702.38	18.28	3.6	29.38	8	6.31
DL728-746	737.92	6.47	1.2	3.37	6	3.98

Operation Bands	Power (mW)	Antenna gain(G)	Measure Distance(cm)	Power density (mW/cm ²)	MPE limit (mW/cm ²)
UL698-716	29.38	6.31	20	0.0369	0.47
DL728-746	3.37	3.98	20	0.0027	0.49

Results: PASS