

Maximum Permissible Exposure(MPE) Report

1. Applicable Standard

FCC Part §1.1310

2. Requirements

Limits For Maximum Permissible Exposure (MPE)				
Frequency range (MHz)	Electric field strength(V/m)	Magnetic field Strength(A/m)	Power density (mw/cm ²)	Averaging time (minutes)
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f ²	30
30-300	27.5	0.0173	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

3. MPE Calculation

Predication of MPE limit at a given distance

$$S = \frac{PG}{4\pi R^2}$$

S = Power density (In appropriate units, e.g., mW/cm²)

P = Power input to the antenna (In appropriate units, e.g., mW)

G = Power gain og the antenna in the direction of interest relative to an isotropic radiator, the power gain factor,

Is normally numeric gain

R =Distance tp the center of radiation of the antenna(In appropriate units, e.g., cm

4. Test Result

698 - 716 MHz

Operation Bands	Frequency(MHz)	Max. Output power(dBm)	Cable loss (dB)	Power to Antenna(mW)	Antenna gain	
					Isotropic	Numeric
UL698-716	708.440	18.86	3.5	34.36	8	6.31
DL728-746	743.048	10.92	1.2	9.38	6	3.98

Operation Bands	Power (mW)	Antenna gain(G)	Measure Distance(cm)	Power density (mW/cm ²)	MPE limit (mW/cm ²)
UL698-716	34.36	6.31	20	0.0432	0.47
DL728-746	9.38	3.98	20	0.0074	0.49

776 - 787 MHz

Operation Bands	Frequency(MHz)	Max. Output power(dBm)	Cable loss (dB)	Power to Antenna(mW)	Antenna gain	
					Isotropic	Numeric
UL776-787	783.942	21.11	3.8	53.83	8	6.31
DL746-757	753.150	10.25	1.4	7.67	6	3.98

Operation Bands	Power (mW)	Antenna gain(G)	Measure Distance(cm)	Power density (mW/cm ²)	MPE limit (mW/cm ²)
UL776-787	53.83	6.31	20	0.0676	0.524
DL746-757	7.67	3.98	20	0.0061	0.500

Results: PASS