



Outdoor:


Option 1: Yagi antenna with 15m 4D-FB cable to the Out Door port.

Frequency(MHz)	698-716	728-746
Gain(dBi)	6	6
Cable Loss(dB)	3.5	3.6
Photo		
Remark	Default Matching Antenna	

Option 2: Log periodic antenna with 15m 4D-FB cable to the Out Door port.


Frequency(MHz)	698-716	728-746
Gain(dBi)	8	8
Cable Loss(dB)	3.5	3.6
Photo		

Option 3: Tubular antenna with 15m 4D-FB cable to the Out Door port.

Frequency(MHz)	698-716	728-746
Gain(dBi)	3	3
Cable Loss(dB)	3.5	3.6
Photo		


Option 4: Plate antenna with 15m 4D-FB cable to the Out Door port.

Frequency(MHz)	698-716	728-746
----------------	---------	---------


Gain(dBi)	6	6
Cable Loss(dB)	3.5	3.6
Photo		

Indoor:


Option 1: Equipment "INDOOR" ports with right Angle antenna.

Frequency(MHz)	698-716	728-746
Gain(dBi)	2	2
Cable Loss(dB)	*	*
Photo		
Remark	Default Matching Antenna	

Option 2: INDOOR ports for suction dish antennas.

Frequency(MHz)	698-716	728-746
Gain(dBi)	3.5	4
Cable Loss(dB)	*	*
Photo		

Option 3: Omnidirectional roof suction antenna with 5 m 4D-FB cable and 'INDOOR' ports.

Frequency(MHz)	698-716	728-746
Gain(dBi)	1.5	2
Cable Loss(dB)	1.2	1.2
Photo		

Option 4: Panel antenna with 5 m 4D-FB cable and 'INDOOR' ports.

Frequency(MHz)	698-716	728-746
Gain(dBi)	6	6
Cable Loss(dB)	1.2	1.2
Photo	