

§1.1307 (b) (1) & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to subpart 1.1307 (b)(1), 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

Limits for General Population/Uncontrolled Exposure

Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (Minutes)
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

f = frequency in MHz

* = Plane-wave equivalent power density

Result

Calculated Formulary:

Predication of MPE limit at a given distance

$$S = \frac{PG}{4\pi R^2}$$

S = power density (in appropriate units, e.g. mW/cm²)

P = power input to the antenna (in appropriate units, e.g., mW).

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain.

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

For worst case:

Mode	Frequency (MHz)	Antenna Gain		Tune up conducted power		Evaluation Distance (cm)	Power Density (mW/cm ²)	MPE Limit (mW/cm ²)
		(dBi)	(numeric)	(dBm)	(mW)			
WCDMA B2	1850-1910	1.3	1.35	24.0	251.19	20	0.067	1
WCDMA B4	1710-1755	1.3	1.35	24.0	251.19	20	0.067	1
WCDMA B5	824-849	0.6	1.15	24.0	251.19	20	0.057	0.549
LTE B2	1850-1910	1.3	1.35	22.5	177.83	20	0.048	1
LTE B4	1710-1755	1.3	1.35	22.5	177.83	20	0.048	1
LTE B5	824-849	0.6	1.15	23.5	223.87	20	0.051	0.549
LTE B12	699-716	0.35	1.08	23.5	223.87	20	0.048	0.466
LTE B13	777-787	0.35	1.08	23.5	223.87	20	0.048	0.518
LTE B14	788-798	0.6	1.15	23.5	223.87	20	0.051	0.525
LTE B66	1710-1780	1.3	1.35	22.5	177.83	20	0.048	1
LTE B71	663-698	0.19	1.04	22.5	177.83	20	0.037	0.442

Note 1: The tune up conducted power was declared by the applicant.

Note: 2: The information about LTE B14, please refer to Report No. RTZ201211002-00C.

To maintain compliance with the FCC's RF exposure guidelines, place the equipment at least 20cm from nearby persons.

Result: Compliance