# Fieldpiece Instruments, Inc. 1636 WEST COLLINS AVE ORANGE, California United States 92867

Federal Communications Commission Authorization and Evaluation Division Equipment Authorization Branch 7435 Oakland Mills Road Columbia, MD 21046

## Applicant's declaration concerning RF Radiation Exposure

We hereby indicate that the product Product description: Wireless Module

Model No: 2ALHR004

The equipment complies with FCC RF radiation exposure limits set forth for an uncontrolled environment. The integral antennas used for this transmitter must not be co-located or operating in conjunction with any other antenna or transmitter within the host device.

A safety statement concerning minimum separation distances from enclosure of the Product: Wireless Module will be integrated in the user's manual to provide end-users with transmitter operating conditions for satisfying RF exposure compliance.

The appropriate information can be drawn from the test report no: W6M21710-17521-C-1 and the accompanying calculations.

Company: Fieldpiece Instruments, Inc.

Address: 1636 WEST COLLINS AVE ORANGE, California United States 92867

Date: 2017-12-01

Signature Zhond resh BUM

Registration number: W6M21710-17521-C-1

FCC ID: 2ALHR004

### 3.2 Equivalent isotropic radiated power

FCC Rule: 15.247(b)(3)

Test exclusion = max. conducted output power

Test exclusion = 12.23 dBm

Test equipment used: ETSTW-RE 055

#### 3.3 RF Exposure Compliance Requirements

FCC OET Bulletin 65 Edition 97.01 determines the equations for predicting RF fields and applicable limits.

The prediction for power density in the far-field but will over-predict power density in the near field, where it could be used for walking a "worst case" or conservative prediction.

$$S = \frac{PG}{4 \pi R^2}$$

S – Power Density

P – Output power ERP

R – Distance

D – Cable Loss

AG – Antenna Gain

Item	Unit	Value	Remarks
P	mW	16.7109	Peak value
D	dB	-	
AG	dBi	-1.44	
G		0.7178	Calculated Value
R	cm	20	Assumed value
S	mW/cm <sup>2</sup>	0.0024	Calculated value

#### Limits:

Limit for General Population / Uncontrolled Exposure		
Frequency (MHz)	Power Density (mW/cm <sup>2</sup> )	
1500 – 100.000	1.0	