

# RF EXPOSURE EVALUATION

## 1. PRODUCT INFORMATION

Product Description	Bluetooth Headset
Model Name	MZX008, MZX008-BLK-BUR, MZX008-RED-BUR, MZX008-WHT-BUR, MZX008-RYB-BUR, BT-1300, BT-1060F, BT-1090P, BT-1090, BT-1060, BT-1100F, BT-1300F, BT-2020, BT-685, BT-686, BT-1108, BT-261, BT-1066, BT-1069, BT-1070, BT-1080, BT-1050, BT-597, BT-680, BT-222, BT-222F, BT-235, BT-102
FCC ID	2ALHZBT-1300

## 2. EVALUATION METHOD

According to 447498 D01 General RF Exposure Guidance v05

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR.

Where  $f(\text{GHz})$  is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

## 3. CALCULATION

$P_t = -5.13\text{dBm} = 0.31\text{mW}$

The value of the Maximum output power  $P_t$  is referred to the test report of the CFR47 §15.247.

The result for RF exposure evaluation  $\text{SAR} = (0.31\text{mW} / 5\text{mm}) \cdot [\sqrt{2.441(\text{GHz})}] = 0.10 < 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR.

## 4. CONCLUSION

The SAR evaluation is not required.