



## SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

No. 1 Workshop, M-10, Middle section, Science & Technology Park,  
Shenzhen, Guangdong, China 518057

Telephone: +86 (0) 755 2601 2053  
Fax: +86 (0) 755 2671 0594  
Email: ee.shenzhen@sgs.com

Report No.: SZEM161201112702  
Page: 1 of 8

# TEST REPORT

**Application No.:** SZEM1612011127CR  
**Applicant:** XDynamics Limited  
**Address of Applicant:** Unites 216-217, Photonics Centre NO.2 Science Park East Avenue, Hong Kong  
**Manufacturer:** XDynamics Limited  
**Address of Manufacturer:** Unites 216-217, Photonics Centre NO.2 Science Park East Avenue, Hong Kong  
**Factory:** Vtech Communications Ltd  
**Address of Factory:** Vtech Holding, Liaobu Town, Dongguan, Guangdong  
**Equipment Under Test (EUT):**  
**EUT Name:** EVOLVE  
**Model No.:** EVOLVE Drone  
**FCC ID:** 2ALI6XD-D1-EVOLVE  
**Standard(s) :** 47 CFR Part 1.1307, Part 1.1310  
**Date of Receipt:** 2017-06-28  
**Date of Test:** 2017-07-22 to 2017-10-20  
**Date of Issue:** 2018-03-29

<b>Test Result:</b>	Pass*
---------------------	-------

\* In the configuration tested, the EUT complied with the standards specified above.



Keny Xu

EMC Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

<b>Revision Record</b>				
<b>Version</b>	<b>Chapter</b>	<b>Date</b>	<b>Modifier</b>	<b>Remark</b>
01		2018-03-29		Original

Authorized for issue by:			
		Hank Yan	
		Hank Yan /Project Engineer	
		Eric Fu	
		Eric Fu /Reviewer	

## 2 Contents

	Page
<b>1 COVER PAGE</b> .....	<b>1</b>
<b>2 CONTENTS</b> .....	<b>3</b>
<b>3 GENERAL INFORMATION</b> .....	<b>4</b>
3.1 DETAILS OF E.U.T.....	4
3.2 DESCRIPTION OF SUPPORT UNITS.....	4
3.3 TEST LOCATION.....	5
3.4 TEST FACILITY.....	5
3.5 DEVIATION FROM STANDARDS.....	5
3.6 ABNORMALITIES FROM STANDARD CONDITIONS .....	5
<b>4 RADIO SPECTRUM TECHNICAL REQUIREMENT</b> .....	<b>6</b>
4.1 RF EXPOSURE .....	6
4.1.1 <i>Test Requirement:</i> .....	6
4.1.2 <i>EUT RF Exposure Evaluation</i> .....	8

### 3 General Information

#### 3.1 Details of E.U.T.

Power supply:	DC 17.4V 6700mAH Li-ion battery			
<b>For 2.4G FHSS:</b>				
Operation Frequency:	2404MHz to 2467MHz			
Modulation Type:	GFSK			
Number of Channels:	43			
Channel Spacing:	1.5MHz			
Antenna Type:	Integral Antenna			
Antenna Gain:	2dBi			
<b>For 5G Certified module (FCC ID: VQSAAMNPTTX01):</b>				
Operation Frequency:	Band	Mode	Frequency Range(MHz)	Number of channels
	Band 1	10MHz Bandwidth	5175 ~ 5245	8
		20MHz Bandwidth	5180 ~ 5240	4
		40MHz Bandwidth	5190 ~ 5230	2
	Band 2A	10MHz Bandwidth	5255 ~ 5325	8
		20MHz Bandwidth	5260 ~ 5320	4
		40MHz Bandwidth	5270 ~ 5310	2
	Band 2C	10MHz Bandwidth	5495 ~ 5705	22
		20MHz Bandwidth	5540 ~ 5700	9
		40MHz Bandwidth	5510 ~ 5670	5
	Band 3	10MHz Bandwidth	5740 ~ 5820	9
		20MHz Bandwidth	5745 ~ 5825	5
		40MHz Bandwidth	5755 ~ 5795	2
Modulation Type:	OFDM, BPSK			
Channel Spacing:	10MHz Bandwidth: 10MHz 20MHz Bandwidth: 20MHz 40MHz Bandwidth: 40MHz			
Antenna Type:	PIFA Antenna			
Antenna Gain:	5dBi			

#### 3.2 Description of Support Units

The EUT has been tested as an independent unit.

### **3.3 Test Location**

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, Guangdong, China.  
518057.

Tel: +86 755 2601 2053      Fax: +86 755 2671 0594

No tests were sub-contracted.

### **3.4 Test Facility**

The test facility is recognized, certified, or accredited by the following organizations:

- CNAS (No. CNAS L2929)**

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

- A2LA (Certificate No. 3816.01)**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

- VCCI**

The 3m Fully-anechoic chamber for above 1GHz, 10m Semi-anechoic chamber for below 1GHz, Shielded Room for Mains Port Conducted Interference Measurement and Telecommunication Port Conducted Interference Measurement of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-20026, R-14188, C-12383 and T-11153 respectively.

- FCC –Designation Number: CN1178**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized as an accredited testing laboratory.

Designation Number: CN1178. Test Firm Registration Number: 406779.

- Industry Canada (IC)**

Two 3m Semi-anechoic chambers and the 10m Semi-anechoic chamber of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab have been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-1, 4620C-2, 4620C-3.

### **3.5 Deviation from Standards**

None

### **3.6 Abnormalities from Standard Conditions**

None

## 4 Radio Spectrum Technical Requirement

### 4.1 RF Exposure

#### 4.1.1 Test Requirement:

CFR 47 Part 1.1310, RSS-102 Issue 5, Section 3.2

Limit:

According to FCC Part1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in Part1.1307(b)

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
<b>(A) Limits for Occupational/Controlled Exposure</b>				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f <sup>2</sup>	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
<b>(B) Limits for General Population/Uncontrolled Exposure</b>				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f <sup>2</sup>	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

f = frequency in MHz

\* = Plane-wave equivalent power density

According to RSS-102 Issue 5 section 3.2 Table 4, the RF Field Strength Limits for Devices Used by the General Public is below:

**Table 4: RF Field Strength Limits for Devices Used by the General Public (Uncontrolled Environment)**

Frequency Range (MHz)	Electric Field (V/m rms)	Magnetic Field (A/m rms)	Power Density (W/m <sup>2</sup> )	Reference Period (minutes)
0.003-10	83	90	-	Instantaneous*
0.1-10	-	0.73/ $f$	-	6**
1.1-10	87/ $f^{0.5}$	-	-	6**
10-20	27.46	0.0728	-2	6
20-48	58.07/ $f^{0.25}$	0.1540/ $f^{0.25}$	8.944/ $f^{0.5}$	6
48-300	22.06	0.05852	1.291	6
300-6000	3.142 $f^{0.3417}$	0.008335 $f^{0.3417}$	0.02619 $f^{0.6834}$	6
6000-15000	61.4	0.163	10	6
15000-150000	61.4	0.163	10	616000/ $f^{1.2}$
150000-300000	0.158 $f^{0.5}$	4.21 x 10 <sup>-4</sup> $f^{0.5}$	6.67 x 10 <sup>-5</sup> $f$	616000/ $f^{1.2}$

Note:  $f$  is frequency in MHz.

\* Based on nerve stimulation (NS).

\*\* Based on specific absorption rate (SAR).

According to IEEE C95.3:2002 section 5.5.1.1, The power density S at a point on the axis at a distance d from a transmitting antenna is given by the Friis free-space transmission formula

$$S = \frac{PG}{4\pi d^2}$$

$S$  = power density (mW/cm<sup>2</sup>)

$P$  = the net power delivered to the antenna (mW)

$G$  = gain of the antenna in linear scale

$d$  = distance between observation point and center of the radiator (cm)

#### 4.1.2 EUT RF Exposure Evaluation

##### 1) exposure conditions for standalone operations

###### For 2.4G Band:

Antenna Gain: 1.5dBi

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 1.413 in linear scale.

Output Power into Antenna & RF Exposure Evaluation Distance:

Channel	Frequency (MHz)	Max Tune-up Output Power (dBm)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )	MPE Ratios	Result
Middle	2435.5	18.230	66.527	0.019	1.0	0.019	PASS

Note: The distance R (5th column) calculated from the Fries transmission formula is far greater than 20 cm separation requirement.

###### For 5.8G Band:

Antenna Gain: 5dBi

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 3.162 in linear scale.

Output Power into Antenna & RF Exposure Evaluation Distance:

Channel	Frequency (MHz)	Max Tune-up Output Power (dBm)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )	MPE Ratios	Result
Middle	5795.0	23.900	245.471	0.154	1.0	0.154	PASS

Note: The max output power is refer to the report of the RF module (FCC ID: VQSAMNPTTX01).

The distance R (5th column) calculated from the Fries transmission formula is far greater than 20 cm separation requirement.

##### 2) exposure conditions for simultaneous transmission operations

Simultaneous transmission MPE test is not required, because the Max. sum of the MPE ratios is  $0.019+0.154=0.173 < 1$

- End of the Report -