

# FCC RF Exposure

EUT Description: Tablet pc

Model No.: RNB V1

FCC ID: 2ALIJ-RNBV1

## 1. Limits

According to KDB 447498 D01 General RF Exposure Guidance v06 The 1 - g and 10 - g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:  

$$[(\text{max power of channel, including tune - up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$$
for 1 - g SAR and  $\leq 7.5$  for 10 - g extremity SAR,

Where:

Result= $P/D \cdot \sqrt{F}$

F= the RF channel transmit frequency in GHz

P=Maximum turn - up power in mw

D=Min. test separation distance in mm

## 2. Test Result of RF Exposure Evaluation

### 2.4G WiFi

	Output power (dBm)	Tune Up Power (dBm)	Max Tune Up power dBm/mW	Min test separation distance mm	Result	Limit (mW/cm <sup>2</sup> )	SAR Test Exclusion
802.11b	8.77	8 $\pm$ 1	9/7.94	5	2.479	3.0	Pass
802.11g	8.16	8 $\pm$ 1	9/7.94	5	2.466	3.0	Pass
802.11n(HT20)	7.61	7 $\pm$ 1	8/6.31	5	1.970	3.0	Pass
802.11n(HT40)	6.41	7 $\pm$ 1	8/6.31	5	1.970	3.0	Pass
Note: PK Output power= conducted power. Conducted power see the test report HUAK180809825-E, antenna gain=1dBi							

Note: Exclusion Thresholds Results= $[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}]$

$f(\text{GHz})$  is the RF channel transmit frequency in GHz

Distance=5mm