

COMPLIANCE WORLDWIDE INC. TEST REPORT 107-23

In Accordance with the Requirements of
FCC TITLE 47 CFR Part 15.519, Subpart F
Technical Requirements for Handheld UWB Systems
Class II Permissive Change

Issued to


**Ciholas, Inc.
3700 Bell Road
Newburgh, IN 47630**

**For the
MU202
UWB Module**

FCC ID: 2ALIR-MU202

Report Issued on February 22, 2023

Tested by



Sean P. Defelice

Sean P. Defelice

Reviewed by



Larry K. Stillings

Larry K. Stillings

This test report shall not be reproduced, except in full, without written permission from Compliance Worldwide, Inc.

Table of Contents

1. Scope.....	3
2. Product Details	3
2.1. Manufacturer	3
2.2. Model Number.....	3
2.3. Serial Number	3
2.4. Description	3
2.5. Power Source.....	3
2.6. Hardware Revision.....	3
2.7. Software Revision	3
2.8. Modulation Type.....	3
2.9. Operating Frequency	3
2.10. EMC Modifications	3
3. Product Configuration.....	3
3.1. Operational Characteristics & Software	3
3.2. EUT Hardware	3
3.3. EUT Cables/Transducers.....	3
3.4. Support Equipment	3
3.5. Test Setup.....	4
3.6. EUT Orientation Diagram.....	4
4. Measurements Parameters	5
4.1. Measurement Equipment Used to Perform Test	5
4.2. Measurement & Equipment Setup	6
4.3. Measurement Procedure	6
4.4. Measurement Uncertainty	6
5. Measurement Summary	7
6. Measurement Data	8
6.1. Antenna Requirement	8
6.2. Operational Requirements	9
6.3. UWB Bandwidth	11
6.4. Radiated Emissions below 960 MHz	13
6.5. Radiated Emissions above 960 MHz	22
6.6. Radiated Emissions in the GPS Bands.....	29
6.7. RMS Emissions of UWB Transmission.....	36
6.8. Peak Emissions in a 50 MHz Bandwidth	39
6.9. Conducted Emissions Test Setup	42
7. Test Site Description	43
8. Test Images	44
8.1. Spurious and Harmonic Emissions - 30 kHz to 1 GHz Front.....	44
8.2. Spurious and Harmonic Emissions - 30 kHz to 30 MHz Rear	45
8.3. Spurious and Harmonic Emissions - 30 MHz to 1 GHz Rear	46
8.4. Spurious and Harmonic Emissions - 1 to 18 GHz Front	47
8.5. Spurious and Harmonic Emissions - 1 to 18 GHz Rear.....	48
8.6. Spurious and Harmonic Emissions - 18 to 40 GHz Side	49

1. Scope

This test report certifies that the Ciholas MU202 Module as tested, meets the FCC Part 15, Subpart F requirements. The scope of this test report is limited to the test sample provided by the client, only in as much as that sample represents other production units. If any significant changes are made to the unit, the changes shall be evaluated and a retest may be required.

2. Product Details

2.1. Manufacturer:	Ciholas, Inc.
2.2. Model Numbers:	A02824
2.3. Serial Numbers:	109195
2.4. Description:	The MU202 is part of a wireless system that relies on ultra-wideband (UWB) pulses and time-stamp information to determine real-time location tracking data.
2.5. Power Source:	5 VDC via USB power
2.6. Hardware Revision:	1.0.1
2.7. Software Revision:	N/A
2.8. Modulation Type:	Pulse Modulation, Frequency Hopping
2.9. Operating Frequencies:	4.49 GHz Center Frequency Nominal (Channel 3 – 500 MHz BW)
2.10. EMC Modifications:	None

3. Product Configuration

3.1 Operational Characteristics & Software

Connect the MU202 to a laptop via a UWB cable. The laptop is used with the device's embedded firmware and serial port software to configure the radio module. The module was configured for transmitting at 16M and 64M PRFs at a 6.8 Mbps data rate.

The module was tested using a support PCB to provide connectivity from the USB interface to the module's M2 connector. No other circuitry on that support PCB was enabled during testing. The enclosure was used for convenience of orienting the module in its worst case orientation. The enclosure provides no shielding and is absent of any reflective surfaces that would impact the RF signal leaving the module's antenna.

3.2. EUT Hardware

Manufacturer	Model/Part # / Options	Serial Number	Input Volts	Freq (Hz)	Description/Function
Ciholas	MU202	109195	5	DC	UWB Module

3.3. EUT Cables/Transducers


Cable Type	Length	Shield	From	To
USB	10M	Yes	EUT	Laptop

3.4. Support Equipment

Manufacturer	Model/Part # / Options	Serial Number	Input Voltage	Freq (Hz)	Description/Function
Dell	XPS 13 – L321X	41647808737	120	60	For controlling the USB Dongle

3. Product Configuration (cont.)

3.5. Test Setup Diagram



4. Measurements Parameters

4.1. Measurement Equipment Used to Perform Test

Device	Manufacturer	Model No.	Serial No.	Cal Due	Interval
EMI Test Receiver, 9kHz - 7GHz ¹	Rohde & Schwarz	ESR7	101156	10/25/2023	2 Year
EMI Test Receiver, 10 Hz - 7GHz ¹	Rohde & Schwarz	ESR7	101770	7/23/2023	2 Year
Spectrum Analyzer, 2 Hz to 26.5 GHz ²	Rohde & Schwarz	FSW26	102057	6/24/2023	2 Years
Spectrum Analyzer, 9 kHz to 40 GHz ³	Rohde & Schwarz	FSV40	100899	8/12/2023	3 Years
Spectrum Analyzer 10 Hz – 40 GHz ⁴	Rohde & Schwarz	FSVR40	100909	9/18/2023	3 Years
Loop Antenna 9 kHz - 30 MHz	EMCO	6512	9309-1139	4/14/2025	3 Years
Biconilog Antenna, 30 MHz - 2 GHz	Sunol Sciences	JB1	A050913	7/1/2023	2 Years
Dbl Ridged Guide Antenna 1- 18 GHz	ETS-Lindgren	3117	00143292	5/11/2024	2 Years
Dbl Ridged Guide Antenna 1- 18 GHz	ETS-Lindgren	3117	00227631	4/21/2024	2 Years
Preamplifier 100 MHz to 7 GHz	Miteq	AFS3-00100200-10-15P-4	988773	3/31/2023	1 Year
Preamplifier 100 MHz to 18 GHz	Miteq	AMF-7D-00101800-30-10P	1953081	3/31/2023	1 Year
Preamplifier 2 to 12 GHz	JCA	JCA48-4111B1	7087S	3/31/2023	1 Year
Preamplifier, 1 GHz to 26.5 GHz	Hewlett Packard	8449B	3008A01323	11/30/2023	2 Years
Preamplifier 18 to 40 GHz	Miteq	JSD42-21004200-40-5P	649199/649219	3/31/2023	1 Year
Horn Antenna 18 to 40 GHz	Com Power	AH-840	101032	1/25/2024	2 Years
High Pass Filter 8 to 18 GHz	Micro-Tronics	HPM50107	G036	3/30/2023	1 Year
High Pass Filter 6.4 to 18 GHz	Micro-Tronics	HPM50112	14	3/30/2023	1 Year
Barometric Pressure/Humidity & Temp Datalogger	Extech Instruments	SD700	Q590483	10/14/2023	2 Years

¹ ESR7 Firmware revision: V3.48 SP3, Date installed: 09/30/2020

Previous V3.48 SP2, installed 07/23/2020.

² FSW26 Firmware revision: V4.71 SP1, Date installed: 11/16/2020

Previous V4.61, installed 08/11/2020.

³ FSV40 Firmware revision: V2.30 SP4, Date installed: 05/04/2016

Previous V2.30 SP1, installed 10/22/2014.

⁴ FSVR40 Firmware revision: V2.23 SP1, Date installed: 08/19/2016

Previous V2.23, installed 10/22/2014.

4. Measurements Parameters (continued)

4.2. Measurement & Equipment Setup

Test Dates:	11/30/2020, 1/10/2023, 2/14/2023
Test Engineers:	Sean Defelice
Normal Site Temperature (15 – 35°C):	21.6
Relative Humidity (20 -75%RH):	35
Frequency Range:	30 kHz to 40 GHz
Measurement Distance:	3 Meters
	200 Hz – 30 kHz to 150 kHz
EMI Receiver IF Bandwidth:	9 kHz – 150 kHz to 30 MHz 120 kHz - 30 MHz to 1 GHz 1 MHz - Above 1 GHz
EMI Receiver Avg Bandwidth:	>= 3 * RBW
Detector Function:	Peak, Quasi-Peak & Average

4.3. Measurement Procedure

Test measurements were made in accordance FCC Parts 15.209 Subpart C, 15.519 Subpart F requirements.

The test methods used to generate the data in this test report is in accordance with ANSI C63.10:2013, American National Standard for Testing Unlicensed Wireless Devices.

4.4. Measurement Uncertainty

The following uncertainties are expressed for an expansion/coverage factor of K=2.

RF Frequency (out of band)	± 1x10 ⁻⁸
Radiated Emission of Transmitter to 100 GHz	± 4.55 dB
Radiated Emission of Receiver	± 4.55 dB
Temperature	± 0.91° C
Humidity	± 5%

5. Measurements Summary

Test Requirement	FCC Rule Requirement	Test Report Section	Result	Comment
Antenna Requirement	15.203	6.1	Compliant	
Operational Requirements	15.519 (a) (1)	6.2	Compliant	
UWB Bandwidth	15.503 (a) (d) 15.519 (b)	6.3	Compliant	
Radiated Emissions below 960 MHz	15.209	6.4	Compliant	
Radiated Emissions above 960 MHz	15.519 (c) 15.521 (d)	6.5	Compliant	
Radiated Emissions in GPS Bands	15.519 (d)	6.6	Compliant	
RMS Emissions of UWB Transmission in a 1 MHz Bandwidth	15.519 (c) 15.521 (d)	6.7	Compliant	
Peak Emissions in a 50 MHz Bandwidth	15.519 (e) 15.521 (g)	6.8	Compliant	
Conducted Emissions	15.207	6.9	N/A	
99% Emission Bandwidth	N/A	6.10	Compliant	

6. Measurement Data

6.1. Antenna Requirement (15.203)

Requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply

Result: The antenna utilized by the device under test is an etched pcb type.

6. Measurement Data (continued)


6.2. Operational Requirements of the Device under Test (15.519 (a) (1))

Requirement: UWB device operating under the provisions of this section must be hand held, i.e., they are relatively small device that are primarily hand held while being operated and do not employ a fixed infrastructure. UWB devices operating under the provisions of this section may operate indoors or outdoors.

A UWB device operating under the provisions of this section shall transmit only when it is sending information to an associated receiver. The UWB intentional radiator shall cease transmission within 10 seconds unless it receives an acknowledgement from the associated receiver that its transmission is being received. An acknowledgment of reception must continue to be received by the UWB intentional radiator at least every 10 seconds or the UWB device must cease transmitting.

Result: Compliant, the EUT transmits a 0.247 mS burst of location information every 11.513 seconds to an associated receiver.


6.2.1 Plot of Transmission Period CH3 16M PRF On-Time



6. Measurement Data (continued)

6.2. Operational Requirements of the Device under Test (15.519 (a) (1))

6.2.2 Plot of Shutoff after receiver removed – CH3 16M PRF



6. Measurement Data (continued)


6.3. UWB Bandwidth (15.503 (a) (d), 15.519 (b))

Requirement: The UWB bandwidth of a device operating under the provisions of this section shall be contained between 3,100 MHz and 10,600 MHz and at any point in time and has a fractional bandwidth equal to or greater than 0.20 or has a UWB bandwidth equal to or greater than 500 MHz, regardless of the fractional bandwidth.

6.3.1. Measurement Data – Values in GHz

		CH3 16M
f_M	The highest emission peak	4.4880
f_L	10 dB below the highest peak	4.1633
f_H	10 dB above the highest peak	4.8387
f_C	Calculated: $(f_H + f_L) / 2$	4.5010
Bandwidth	Calculated: $(f_H - f_L)$	0.6754
Fractional BW	Calculated: $2 * (f_H - f_L) / (f_H + f_L)$	0.1501

6.3.2. Measurement Plot of 10 dB frequencies (Channel 3, 16M PRF)



11:32:12 30.11.2020


6. Measurement Data (continued)

6.3. UWB Bandwidth (15.503 (a) (d), 15.519 (b) continued)

6.3.3. Measurement Data – Values in GHz

		CH3 64M
f_M	The highest emission peak	4.4920
f_L	10 dB below the highest peak	4.1453
f_H	10 dB above the highest peak	4.8397
f_C	Calculated: $(f_H + f_L) / 2$	4.4925
Bandwidth	Calculated: $(f_H - f_L)$	0.6944
Fractional BW	Calculated: $2 * (f_H - f_L) / (f_H + f_L)$	0.1546

6.3.4. Measurement Plot of 10 dB frequencies (Channel 3, 64M PRF)



6. Measurement Data (continued)

6.4. Spurious Radiated Emissions below 960 MHz (15.519 (c), 15.209)

Requirement: The radiated emissions at or below 960 MHz from a device operating under the provisions of this section shall not exceed the emission levels in Section 15.209.

Radiated Emissions Field Strength Limits at 3 Meters (Section 15.209, RSS-220)

Frequency (MHz)	Field Strength (μ V/m)	Field Strength (dB μ V/m)
0.009 to 0.490	2,400/F (F in kHz)	128.5 to 93.8
0.490 to 1.705	24,000/F (F in kHz)	73.8 to 63
1.705 - 30	30	69.5
30 - 88	100	40
88 - 216	150	43.5
216 - 960	200	46

Test Notes: Refer to Section 4.1 for the test equipment used.

Frequency Range:	30 kHz to 960 MHz
Measurement Distance:	3 Meters
EMI Receiver IF Bandwidth:	200 Hz – 30 kHz to 150 kHz 9 kHz – 150 kHz to 30 MHz 120 kHz - 30 MHz to 960 MHz
EMI Receiver Avg Bandwidth:	$\geq 3 * RBW$ or IF(BW)
Detector Function:	Peak, Quasi-Peak & CISPR Average

Sample Calculation: Final Result (dB μ V/m) = Measurement Value (dB μ V) + Antenna Factor (dB/m) + Cable Loss (dB) – Pre-amplifier Gain (dB) Internal or External.

Note: All correction factors are loaded into the measurement instrument prior to testing to determine the final result.


6. Measurement Data (continued)

6.4. Spurious Radiated Emissions (15.209, continued)


6.4.1. 30 kHz to 960 MHz, measured at 3 Meters

The device was prescreened in our 3 Meter Semi-Anechoic Chamber. There were no measurable emissions below 960 MHz on our 3 Meter OATS.

6.4.1.1 Parallel Measurement Antenna – 30 to 150 kHz – CH3 16M



6.4.1.2 Perpendicular Measurement Antenna – 30 to 150 kHz – CH3 16M




6. Measurement Data (continued)

6.4. Spurious Radiated Emissions (15.209, continued)


6.4.1. 30 kHz to 960 MHz, measured at 3 Meters

The device was prescreened in our 3 Meter Semi-Anechoic Chamber. There were no measurable emissions below 960 MHz on our 3 Meter OATS.

6.4.1.3 Ground Parallel Measurement Antenna – 30 to 150 kHz – CH3 16M



6.4.1.4 Parallel Measurement Antenna – 30 to 150 kHz – CH3 64M




6. Measurement Data (continued)

6.4. Spurious Radiated Emissions (15.209, continued)


6.4.1. 30 kHz to 960 MHz, measured at 3 Meters

The device was prescreened in our 3 Meter Semi-Anechoic Chamber. There were no measurable emissions below 960 MHz on our 3 Meter OATS.

6.4.1.5 Perpendicular Measurement Antenna – 30 to 150 kHz – CH4 64M



6.4.1.6 Ground Parallel Measurement Antenna – 30 to 150 kHz – CH3 64M




6. Measurement Data (continued)

6.4. Spurious Radiated Emissions (15.209 continued)

6.4.1. 30 kHz to 960 MHz, measured at 3 Meters

The device was prescreened in our 3 Meter Semi-Anechoic Chamber. There were no measurable emissions below 960 MHz on our 3 Meter OATS.

6.4.1.7 Parallel Measurement Antenna – 150 kHz to 30 MHz – CH3 16M



6.4.1.8 Perpendicular Measurement Antenna – 150 kHz to 30 MHz – CH3 16M




6. Measurement Data (continued)

6.4. Spurious Radiated Emissions (15.209 continued)


6.4.1. 30 kHz to 960 MHz, measured at 3 Meters

The device was prescreened in our 3 Meter Semi-Anechoic Chamber. There were no measurable emissions below 960 MHz on our 3 Meter OATS.

6.4.1.9 Ground Parallel Measurement Antenna – 150 kHz to 30 MHz – CH3 16M



6.4.1.10 Parallel Measurement Antenna – 150 kHz to 30 MHz – CH3 64M




6. Measurement Data (continued)

6.4. Spurious Radiated Emissions (15.209 continued)


6.4.1. 30 kHz to 960 MHz, measured at 3 Meters

The device was prescreened in our 3 Meter Semi-Anechoic Chamber. There were no measurable emissions below 960 MHz on our 3 Meter OATS.

6.4.1.11 Perpendicular Measurement Antenna – 150 kHz to 30 MHz – CH3 64M



6.4.1.12 Ground Parallel Measurement Antenna – 150 kHz to 30 MHz – CH3 64M




6. Measurement Data (continued)

6.4. Spurious Radiated Emissions (15.209 continued)


6.4.1. 30 kHz to 960 MHz, measured at 3 Meters

The device was prescreened in our 3 Meter Semi-Anechoic Chamber. There were no measurable emissions below 960 MHz on our 3 Meter OATS.

6.4.1.13 Horizontal Polarity – 30 to 960 MHz – CH3 16M



6.4.1.14 Vertical Polarity – 30 to 960 MHz – CH3 16M




6. Measurement Data (continued)

6.4. Spurious Radiated Emissions (15.209 continued)


6.4.1. 30 kHz to 960 MHz, measured at 3 Meters

The device was prescreened in our 3 Meter Semi-Anechoic Chamber. There were no measurable emissions below 960 MHz on our 3 Meter OATS.

6.4.1.15 Horizontal Polarity – 30 to 960 MHz – CH3 64M



6.4.1.16 Vertical Polarity – 30 to 960 MHz – CH3 64M



6. Measurement Data (continued)

6.5. Spurious Radiated Emissions above 960 MHz (15.519 (c), 15.521 (d))

Requirement: The radiated emissions above 960 MHz from a device operating under the provisions of this section shall not exceed the following average limits when measured using a resolution bandwidth of 1 MHz:

The RMS average measurement is based on the use of a spectrum analyzer with a resolution bandwidth of 1 MHz, an RMS detector, and a 1 millisecond or less averaging time.

The EIRP in terms of dBm, can be converted to a field strength, in dB μ V/m at 3 Meters by adding 95.2.

Frequency (MHz)	EIRP (dBm)	EIRP at 3 Meters (dB μ V/m)
960 - 1610	-75.3	19.9
1610 - 1990	-63.3	31.9
1990 - 3100	-61.3	33.9
3100 - 10600	-41.3	53.9
Above 10600	-61.3	33.9

Frequency Range:

960 MHz to 40 GHz

Measurement Distance:

1 Meter and 0.3 Meter

EMI Receiver IF Bandwidth:

1 MHz

EMI Receiver Avg Bandwidth

10 MHz

Detector Function:

RMS 1 mS Average as defined in 15.521(d)

Notes: Measurements made from 960 MHz to 18 GHz were made in a semi-anechoic chamber at 1 Meter using a -9.54 dB distance offset was programmed into the spectrum analyzer.

Measurements made from 6.4 to 18 GHz were performed with the aid of a High Pass Filter before the low noise amplifier.

Measurements made from 18 to 40 GHz were performed at 0.3 meters and a -20.00 dB distance offset was programmed into the spectrum analyzer.


Sample Calculation: Final Result (dB μ V/m) = Measurement Value (dB μ V) + Antenna Factor (dB/m) + Cable Loss (dB) – Pre-amplifier Gain (dB) Internal or External.

Note: All correction factors are loaded into the measurement instrument prior to testing to determine the final result.

6. Measurement Data (continued)

6.5. Spurious Radiated Emissions (15.519 (c) continued)

6.5.1. 960 MHz to 6.4 GHz Horizontal at 1 Meter, CH3 16M



Date: 10.JAN.2023 11:45:41

6.5.2. 960 MHz to 6.4 GHz Vertical at 1 Meter, CH3 16M




Date: 10.JAN.2023 11:31:26


6. Measurement Data (continued)

6.5. Spurious Radiated Emissions (15.519 (c) continued)

6.5.3. 960 MHz to 6.4 GHz Horizontal at 1 Meter, CH3 64M




6.5.4. 960 MHz to 6.4 GHz Vertical at 1 Meter, CH3 64M




6. Measurement Data (continued)

6.5. Spurious Radiated Emissions (15.519 (c) continued)

6.5.5. 6.4 to 18 GHz Horizontal at 1 Meter, CH3 16M




6.5.6. 6.4 to 18 GHz Vertical at 1 Meter, CH3 16M




6. Measurement Data (continued)

6.5. Spurious Radiated Emissions (15.519 (c) continued)

6.5.7. 6.4 to 18 GHz Horizontal at 1 Meter, CH3 64M




6.5.8. 6.4 to 18 GHz Vertical at 1 Meter, CH3 64M




6. Measurement Data (continued)

6.5. Spurious Radiated Emissions (15.519 (c) continued)

6.5.9. 18 to 40 GHz Horizontal at 0.3 Meter, CH3 16M



6.5.10. 18 to 40 GHz Vertical at 0.3 Meter, CH3 16M



6. Measurement Data (continued)

6.5. Spurious Radiated Emissions (15.519 (c) continued)

6.5.11. 18 to 40 GHz Horizontal at 0.3 Meter, CH3 64M



Date: 10.JAN.2023 16:51:44

6.5.12. 18 to 40 GHz Vertical at 0.3 Meter, CH3 64M



Date: 10.JAN.2023 16:46:26

6. Measurement Data (continued)

6.6. Spurious Radiated Emissions in GPS Bands (15.519 (d))

Requirement: In addition to the radiated emission limits specified in the table in paragraph (d) of this section, UWB transmitters operating under the provisions of this section shall not exceed the following average limits when measured using a resolution bandwidth of no less than 1 kHz:

Frequency (MHz)	EIRP (dBm)	EIRP at 3 Meters (dB μ V/m)
1164 - 1240	-85.3	9.9
1559 - 1610	-85.3	9.9

6.6.1. Measurement & Equipment Setup

EMI Receiver IF Bandwidth: 1 kHz

EMI Receiver Avg Bandwidth: 10 kHz

Detector Functions: RMS Average, 1mS / point

6.6.2. 1164 to 1240 MHz & 1559 to 1610 MHz

There were no broadband emissions related to the UWB transmitter. Measured signals were narrowband and related to the microprocessor / clocks and do not fall under the requirements of this section. Measurements were made at 1.0 Meter with a -9.54 dB distance correction factor. The -85.3 dBm limit was converted to a field strength limit of 9.9 dB μ V/m using a factor of 95.2.

The narrowband spikes are due to clock / processor noise and are still present when the device was placed in receive only mode of operation as seen 6.6.3.5, 6.6.3.6, 6.6.3.11 & 6.6.3.12 and are subjected to different limits under Part 15.209.


Sample Calculation: Final Result (dB μ V/m) = Measurement Value (dB μ V) + Antenna Factor (dB/m) + Cable Loss (dB) – Pre-amplifier Gain (dB) Internal or External.

Note: All correction factors are loaded into the measurement instrument prior to testing to determine the final result.


6. Measurement Data (continued)

6.6. Spurious Radiated Emissions in GPS Bands (15.519 (d) continued)

6.6.3.1 Horizontal Measurement Polarity 1164 to 1240 MHz, CH3 16M, Tx On




6.6.3.2 Vertical Measurement Polarity 1164 to 1240 MHz, CH3 16M, Tx On




6. Measurement Data (continued)

6.6. Spurious Radiated Emissions in GPS Bands (15.519 (d) continued)

6.6.3.3 Horizontal Measurement Polarity 1164 to 1240 MHz, CH3 64M, Tx On




6.6.3.4 Vertical Measurement Polarity 1164 to 1240 MHz, CH3 64M, Tx On




6. Measurement Data (continued)

6.6. Spurious Radiated Emissions in GPS Bands (15.519 (d) continued)

6.6.3.5 Horizontal Measurement Polarity 1164 to 1240 MHz, CH3 Rx Only




6.6.3.6 Vertical Measurement Polarity 1164 to 1240 MHz, CH3 Rx Only




6. Measurement Data (continued)

6.6. Spurious Radiated Emissions in GPS Bands (15.519 (d) continued)

6.6.3.7 Horizontal Measurement Polarity 1559 to 1610 MHz, CH3 16M, Tx On




6.6.3.8 Vertical Measurement Polarity 1559 to 1610 MHz, CH3 16M, Tx On




6. Measurement Data (continued)

6.6. Spurious Radiated Emissions in GPS Bands (15.519 (d) continued)

6.6.3.9 Horizontal Measurement Polarity 1559 to 1610 MHz, CH3 64M, Tx On




6.6.3.10 Vertical Measurement Polarity 1559 to 1610 MHz, CH3 64M, Tx On



6. Measurement Data (continued)


6.6. Spurious Radiated Emissions in GPS Bands (15.519 (d) continued)

6.6.3.11 Horizontal Measurement Polarity 1559 to 1610 MHz, CH3 Rx Only



Date: 10.JAN.2023 14:54:27

6.6.3.12 Vertical Measurement Polarity 1559 to 1610 MHz, CH3 Rx Only



Date: 10.JAN.2023 14:44:28

6. Measurement Data (continued)**6.7. Radiated Emissions of UWB Transmission (15.519 (c), 15.521 (d))**

Requirement: The radiated emissions above 960 MHz from a device operating under the provisions of this section shall not exceed the following average limits when measured using a resolution bandwidth of 1 MHz:

The RMS average measurement is based on the use of a spectrum analyzer with a resolution bandwidth of 1 MHz, an RMS detector, and a 1 millisecond or less averaging time.

The EIRP in terms of dBm, can be converted to a field strength, in dB μ V/m at 3 Meters by adding 95.2.

Frequency (MHz)	EIRP (dBm)	EIRP at 3 Meters (dB μ V/m)
3100 - 10600	-41.3	53.9

Frequency Range:	4 to 5 GHz
Measurement Distance:	3 Meters
EMI Receiver IF Bandwidth:	1 MHz
EMI Receiver Avg Bandwidth	10 MHz
Detector Function:	RMS 1 mS Average as defined in 15.521(d)

Test Number: 107-23
Issue Date: 2/22/2023

6. Measurement Data (continued)

6.7. Spurious Radiated Emissions (15.519 (c), 15.521(d))

6.7.1. Plot of RMS Power at 3 Meters (CH3, 16M PRF)


Frequency (GHz)	Amplitude ¹	Limit	Margin	Ant Polarity	Ant Height	Turntable Azimuth	Result
	(dB μ V/m)	(dB μ V/m)	(dB)	H/V	cm	Deg	
4.493	51.57	53.90	-2.33	V	120	0	Compliant

Notes: ¹ Antenna Factor (AF), Cable Factor (CF) and External Preamplifier Gain (PAG) have been entered into the analyzer as transducer factors.

Equation (22) from ANSI C63.10-2013, $EIRP = E_{meas} + 20 \log (d_{meas}) - 104.7$; $d_{meas} = 3$

$EIRP$ (dBm) = E_{meas} (dB μ V/m) - 95.2

Frequency (GHz)	Amplitude ¹ (dBm)	Limit (dBm)	Margin	Ant Polarity	Ant Height	Turntable Azimuth	Result
	EIRP	EIRP	(dB)	H/V	cm	Deg	
4.493	-43.63	-41.30	-2.33	V	120	0	Compliant

301-20 Ciholas MU202 UWB


11:11:33 30.11.2020

6. Measurement Data (continued)

6.7. Spurious Radiated Emissions (15.519 (c), 15.521(d)) continued

6.7.2. Plot of RMS Power at 3 Meters (CH3, 64M PRF)

Frequency (GHz)	Amplitude ¹	Limit	Margin	Ant Polarity	Ant Height	Turntable Azimuth	Result
	(dB μ V/m)	(dB μ V/m)	(dB)	H/V	cm	Deg	
4.4271	53.60	53.90	-0.30	V	120	0	Compliant


Notes: ¹ Antenna Factor (AF), Cable Factor (CF) and External Preamplifier Gain (PAG) have been entered into the analyzer as transducer factors.

Equation (22) from ANSI C63.10-2013, $EIRP = E_{meas} + 20 \log (d_{meas}) - 104.7$; $d_{meas} = 3$

$EIRP$ (dBm) = E_{meas} (dB μ V/m) - 95.2

Frequency (GHz)	Amplitude ¹ (dBm)	Limit (dBm)	Margin	Ant Polarity	Ant Height	Turntable Azimuth	Result
	EIRP	EIRP	(dB)	H/V	cm	Deg	
4.4271	-41.60	-41.30	-0.30	V	120	0	Compliant

301-20 Ciholas MU202 UWB



11:42:23 30.11.2020

6. Measurement Data (continued)**6.8. Peak Emissions in a 50 MHz Bandwidth (15.519 (e), 15.521 (g))**

Requirement: There is a limit on the peak level of the emissions contained within a 50 MHz bandwidth centered on the frequency at which the highest radiated emission occurs, f_M . That limit is 0 dBm EIRP.

The EIRP in terms of dBm, can be converted to a field strength, in dB μ V/m at 3 Meters by adding 95.2. As used in this subpart, EIRP refers to the highest signal strength measured in any direction and at any frequency from the UWB device.

Frequency (MHz)	EIRP (dBm)	EIRP at 3 Meters (dB μ V/m)
3100 - 10600	0	95.2

Frequency Range: 4 to 5 GHz
Measurement Distance: 3 Meters
EMI Receiver IF Bandwidth: 50 MHz
EMI Receiver Avg Bandwidth 80 MHz
Detector Function: Peak, Max Held

6. Measurement Data (continued)

6.8. Peak Emissions in a 50 MHz Bandwidth (15.519 (e), 15.521 (g) continued)

6.8.1 Plot of Peak Power at 3 Meters (CH3, 16M PRF)


Frequency (GHz)	Amplitude ¹	Limit	Margin	Ant Polarity	Ant Height	Turntable Azimuth	Result
	(dB μ V/m)	(dB μ V/m)	(dB)	H/V	cm	Deg	
4.487	94.81	95.20	-0.39	V	120	0	Compliant

Notes: ¹ Antenna Factor (AF), Cable Factor (CF) and External Preamplifier Gain (PAG) have been entered into the analyzer as transducer factors.

Equation (22) from ANSI C63.10-2013, $EIRP = E_{meas} + 20 \log (d_{meas}) - 104.7$; $d_{meas} = 3$

$EIRP$ (dBm) = E_{meas} (dB μ V/m) - 95.2

Frequency (GHz)	Amplitude ¹ (dBm)	Limit (dBm)	Margin	Ant Polarity	Ant Height	Turntable Azimuth	Result
	EIRP	EIRP	(dB)	H/V	cm	Deg	
4.487	-0.39	0.00	-0.39	V	120	0	Compliant



11:08:32 30.11.2020

6. Measurement Data (continued)

6.8. Peak Emissions in a 50 MHz Bandwidth (15.519 (e), 15.521 (g) continued)

6.8.2 Plot of Peak Power at 3 Meters (CH3, 64M PRF)

Frequency (GHz)	Amplitude ¹	Limit	Margin	Ant Polarity	Ant Height	Turntable Azimuth	Result
	(dB μ V/m)	(dB μ V/m)	(dB)	H/V	cm	Deg	
4.491	93.80	95.20	-1.40	V	120	0	Compliant


Notes: ¹ Antenna Factor (AF), Cable Factor (CF) and External Preamplifier Gain (PAG) have been entered into the analyzer as transducer factors.

Equation (22) from ANSI C63.10-2013, $EIRP = E_{meas} + 20 \log (d_{meas}) - 104.7$; $d_{meas} = 3$

$EIRP$ (dBm) = E_{meas} (dB μ V/m) - 95.2

Frequency (GHz)	Amplitude ¹ (dBm)	Limit (dBm)	Margin	Ant Polarity	Ant Height	Turntable Azimuth	Result
	EIRP	EIRP	(dB)	H/V	cm	Deg	
4.491	-1.40	0.00	-1.40	V	120	0	Compliant

301-20 Ciholas MU202 UWB



11:46:54 30.11.2020

6. Measurement Data (continued)

6.9 Conducted Emissions Test Setup

6.9.1. Regulatory Limit: FCC Part 15, Class B, IC RSS-GEN

Frequency Range (MHz)	Limits (dB μ V)	
	Quasi-Peak	Average
0.15 to 0.50	66 to 56*	56 to 46*
0.50 to 5.0	56	46
5.0 to 30.0	60	50

* Decreases with the logarithm of the frequency.

6.9.2 Measurement Equipment and Software Used to Perform Test

Device	Manufacturer	Model No.	Serial No.	Cal Due
EMI Receiver	Rohde & Schwarz	ESR7	101156	10/25/2024
LISN	EMCO	3825/2	9109-1860	1/4/2023
Manufacturer	Software Description		Title/Model #	Rev.
Compliance Worldwide	Test Report Generation Software		Test Report Generator	1.0

6.9.3. Measurement & Equipment Setup

Test Date:	N/A
Test Engineer:	N/A
Site Temperature (°C):	N/A
Relative Humidity (%RH):	N/A
Frequency Range:	0.15 MHz to 30 MHz
EMI Receiver IF Bandwidth:	9 kHz
EMI Receiver Avg Bandwidth:	≥ 3 * RBW or IF(BW)
Detector Functions:	Peak, Quasi-Peak & CISPR Average

6.9.4. Test Procedure

Test measurements were made in accordance with ANSI C63.4-2014, Standard Methods of Measurement of Radio Noise Emissions from Low-Voltage Electrical and Electronics Equipment in the Range of 9 kHz to 40 GHz.

Sample Calculation: Final Result (dB μ V) = Measurement Value (dB μ V) + LISN Factor (dB) + Cable Loss (dB).

Note: All correction factors are loaded into the measurement instrument prior to testing to determine the final result.

7. Test Site Description

Compliance Worldwide is located at 357 Main Street in Sandown, New Hampshire. The test sites at Compliance Worldwide are used for conducted and radiated emissions testing in accordance with the Federal Communications Commission (FCC) and Industry Canada standards. Through our American Association for Laboratory Accreditation (A2LA) ISO Guide 17025 Accreditation our test sites are designated with the FCC (designation number **US1091**), Industry Canada (file number **IC 3023A-1**) and VCCI (Member number 3168) under registration number A-0274.

Compliance Worldwide is also designated as a Phase 1 CAB under APEC-MRA (US0132) for Australia/New Zealand AS/NZS CISPR 32, Chinese-Taipei (Taiwan) BSMI CNS 13438 and Korea (RRA) KN 11, KN 13, KN 14-1, KN 22, KN 32, KN 61000-6-3, KN 61000-6-4.

The radiated emissions test site is a 3 and 10 meter enclosed open area test site (OATS). Personnel, support equipment and test equipment are located in the basement beneath the OATS ground plane.

The conducted emissions site is part of a 16' x 20' x 12' ferrite tile chamber and uses one of the walls for the vertical ground plane. A second conducted emissions site is also located in the basement of the OATS site with a 2.3 x 2.5 meter ground plane and a 2.4 x 2.4 meter vertical wall.

The radiated emissions test site for measurements above 1GHz is a 3 Meter open area test site (OATS) with a 3.6 by 3.6 meter anechoic absorber floor patch to achieve a quasi-free space measurement environment per ANSI C63.4/C63.10 and CISPR 16-1-4 standards.

The sites are designed to test products or systems 1.5 meters W x 1.5 meters L x 2.0 meters H, floor standing or table top.

8. Test Images

8.1. Spurious and Harmonic Emissions – 30 kHz to 30 MHz Front



8. Test Images

8.2. Spurious and Harmonic Emissions – 30 kHz to 30 MHz Rear



8. Test Images

8.3. Spurious and Harmonic Emissions – 30 MHz to 1 GHz Rear



8. Test Images

8.4. Spurious and Harmonic Emissions – 1 to 18 GHz Front



8. Test Images

8.5. Spurious and Harmonic Emissions – 1 to 18 GHz Rear



8. Test Images

8.6. Spurious and Harmonic Emissions – 18 to 40 GHz Side View

