

TEST REPORT

FCC MPE Test for GCM6201NA
Certification

APPLICANT
GCT SEMICONDUCTOR, INC

REPORT NO.
HCT-RF-2410-FC001

DATE OF ISSUE
October 2, 2024

Tested by
Jae Ryang Do



Technical Manager
Jong Seok Lee



HCT CO., LTD.
Bongjai Huh
BongJai Huh / CEO

**HCT CO.,LTD.**

2-6, 73, 74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, Republic of Korea
Tel. +82 31 645 6300 Fax. +82 31 645 6401

TEST REPORT

REPORT NO.

HCT-RF-2410-FC001

DATE OF ISSUE

October 2, 2024

Applicant**GCT SEMICONDUCTOR, INC**

11F Construction Financial Building 15, Boramae-ro 5-gil, Dongjak-gu, Seoul,
07071, South Korea

Product Name

LTE Module

Model Name

GCM6201NA

Date of Test

August 19, 2024 ~ September 27, 2024

Location of Test☒ Permanent Testing Lab ☐ On Site Testing

(Address: 74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do,
Republic of Korea)

FCC ID

2ALIY-GCM6201NA

FCC Classification:

Licensed Non-Broadcast Station Transmitter (TNB)

Test Standard Used

FCC Rule Part(s) : § 1.1310, 2.1091

Test Results

PASS

REVISION HISTORY

The revision history for this test report is shown in table.

Revision No.	Date of Issue	Description
0	October 2, 2024	Initial Release

Notice

Content

The measurements shown in this report were made in accordance with the procedures specified in CFR47 section § 2.947. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them.

HCT CO., LTD. Certifies that no party to this application has subject to a denial of Federal benefits that includes FCC benefits pursuant to section 5301 of the Anti-Drug Abuse Act of 1998, 21 U.S.C. 853(a)

The results shown in this test report only apply to the sample(s), as received, provided by the applicant, unless otherwise stated.

The test results have only been applied with the test methods required by the standard(s).

The laboratory is not accredited for the test results marked *.

Information provided by the applicant is marked **.

Test results provided by external providers are marked ***.

When confirmation of authenticity of this test report is required, please contact www.hct.co.kr

The test results in this test report are not associated with the ((KS Q) ISO/IEC 17025) accreditation by KOLAS (Korea Laboratory Accreditation Scheme) / A2LA (American Association for Laboratory Accreditation) that are under the ILAC (International Laboratory Accreditation Cooperation) Mutual Recognition Agreement (MRA).

RF Exposure Statement

1. Limit

According to § 1.1310, § 2.1091 RF exposure is calculated.

(B) Limits for General Population/Uncontrolled Exposures

Frequency range (MHz)	Electric field Strength (V/m)	Magnetic field Strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
0.3 - 1.34.....	614	1.63	#(100)	30
1.34 - 30.....	824/f	2.19/f	#(180/ f ²)	30
30 - 300.....	27.5	0.073	0.2	30
300 - 1500.....			f/1500	30
1500 - 100.000.....			1.0	30

F = frequency in MHz

= Plane-wave equivalent power density

2. Maximum Permissible Exposure Prediction

Prediction of MPE limit at a given distance

$$S = PG/4\pi R^2$$

S = Power density

P = Power input to antenna

G = Power gain to the antenna in the direction of interest relative to an isotropic radiator

R = Distance to the center of radiation of the antenna

3. RESULTS

- LTE B24 -

Max output power at antenna input terminal	25.70	dBm
Max output power at antenna input terminal	371.54	mW
Prediction distance	20.00	cm
Prediction frequency	1626.5~1660.5	MHz
Antenna gain (typical)	4.00	dBi
Antenna gain (numeric)	2.512	-
Power density at prediction frequency (S)	0.1857	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	1.0000	mW/cm ²

- LTE B54-

Max output power at antenna input terminal	25.70	dBm
Max output power at antenna input terminal	371.54	mW
Prediction distance	20.00	cm
Prediction frequency	1670.0~1675.0	MHz
Antenna gain (typical)	4.00	dBi
Antenna gain (numeric)	2.512	-
Power density at prediction frequency (S)	0.1857	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	1.0000	mW/cm ²