


Site: AC1	Time: 2019/10/19 - 05:11
Limit: FCC_Part15.209(3m)	Engineer: Bacon Dong
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: HAN Access Point	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11VHT20 at Channel 2462MHz	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2457.280	111.715	79.358	N/A	N/A	32.357	PK
2		2483.500	66.497	34.082	-7.503	74.000	32.416	PK
3		2483.728	68.070	35.654	-5.930	74.000	32.416	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2019/10/19 - 05:10
Limit: FCC_Part15.209(3m)	Engineer: Bacon Dong
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: HAN Access Point	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11VHT20 at Channel 2462MHz	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2456.896	100.695	68.338	N/A	N/A	32.357	AV
2		2483.500	52.915	20.500	-1.085	54.000	32.416	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2019/10/19 - 05:13
Limit: FCC_Part15.209(3m)	Engineer: Bacon Dong
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: HAN Access Point	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11VHT20 at Channel 2462MHz	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2463.736	110.509	78.140	N/A	N/A	32.369	PK
2		2483.500	66.340	33.925	-7.660	74.000	32.416	PK
3		2483.632	68.733	36.317	-5.267	74.000	32.416	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2019/10/19 - 05:14
Limit: FCC_Part15.209(3m)	Engineer: Bacon Dong
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: HAN Access Point	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11VHT20 at Channel 2462MHz	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2464.264	99.721	67.351	N/A	N/A	32.370	AV
2		2483.500	52.987	20.572	-1.013	54.000	32.416	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2019/10/19 - 05:22
Limit: FCC_Part15.209(3m)	Engineer: Bacon Dong
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: HAN Access Point	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11VHT40 at Channel 2422MHz	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2386.758	68.340	35.921	-5.660	74.000	32.418	PK
2		2390.000	66.661	34.248	-7.339	74.000	32.413	PK
3	*	2416.920	108.731	76.352	N/A	N/A	32.378	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2019/10/19 - 05:20
Limit: FCC_Part15.209(3m)	Engineer: Bacon Dong
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: HAN Access Point	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11VHT40 at Channel 2422MHz	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2390.000	53.347	20.934	-0.653	54.000	32.413	AV
2	*	2417.052	98.234	65.856	N/A	N/A	32.378	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2019/10/19 - 05:23
Limit: FCC_Part15.209(3m)	Engineer: Bacon Dong
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: HAN Access Point	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11VHT40 at Channel 2422MHz	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2381.280	64.081	31.652	-9.919	74.000	32.428	PK
2		2390.000	61.957	29.544	-12.043	74.000	32.413	PK
3	*	2424.378	107.790	75.420	N/A	N/A	32.371	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2019/10/19 - 05:25
Limit: FCC_Part15.209(3m)	Engineer: Bacon Dong
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: HAN Access Point	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11VHT40 at Channel 2422MHz	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2390.000	50.282	17.869	-3.718	54.000	32.413	AV
2	*	2424.708	97.379	65.009	N/A	N/A	32.370	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2019/10/19 - 05:36
Limit: FCC_Part15.209(3m)	Engineer: Bacon Dong
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: HAN Access Point	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11VHT40 at Channel 2452MHz	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2446.926	107.375	75.037	N/A	N/A	32.338	PK
2		2483.500	64.477	32.062	-9.523	74.000	32.416	PK
3		2485.278	67.338	34.919	-6.662	74.000	32.419	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2019/10/19 - 05:33
Limit: FCC_Part15.209(3m)	Engineer: Bacon Dong
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: HAN Access Point	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11VHT40 at Channel 2452MHz	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2445.498	96.635	64.298	N/A	N/A	32.336	AV
2		2483.500	53.024	20.609	-0.976	54.000	32.416	AV
3		2484.156	53.138	20.721	-0.862	54.000	32.417	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2019/10/19 - 05:37
Limit: FCC_Part15.209(3m)	Engineer: Bacon Dong
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: HAN Access Point	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11VHT40 at Channel 2452MHz	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2453.726	104.690	72.339	N/A	N/A	32.351	PK
2		2483.500	64.525	32.110	-9.475	74.000	32.416	PK
3		2484.462	65.991	33.574	-8.009	74.000	32.417	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2019/10/19 - 05:38
Limit: FCC_Part15.209(3m)	Engineer: Bacon Dong
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: HAN Access Point	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11VHT40 at Channel 2452MHz	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2453.522	94.200	61.850	N/A	N/A	32.351	AV
2		2483.500	52.242	19.827	-1.758	54.000	32.416	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC2	Time: 2019/10/05 - 17:00
Limit: FCC_Part15.209(3m)	Engineer: Bacon Dong
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: HAN Access Point	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11ax-HE20 at Channel 2412MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			2389.520	63.395	33.535	-10.605	74.000	29.860	PK
2			2390.000	62.806	32.947	-11.194	74.000	29.859	PK
3		*	2406.488	113.700	83.883	N/A	N/A	29.817	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC2	Time: 2019/10/05 - 17:02
Limit: FCC_Part15.209(3m)	Engineer: Bacon Dong
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: HAN Access Point	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11ax-HE20 at Channel 2412MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			2390.000	49.611	19.752	-4.389	54.000	29.859	AV
2		*	2406.096	100.517	70.699	N/A	N/A	29.818	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC2	Time: 2019/10/05 - 17:04
Limit: FCC_Part15.209(3m)	Engineer: Bacon Dong
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: HAN Access Point	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11ax-HE20 at Channel 2412MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			2388.904	63.638	33.776	-10.362	74.000	29.862	PK
2			2390.000	62.645	32.786	-11.355	74.000	29.859	PK
3		*	2411.080	112.559	82.753	N/A	N/A	29.806	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC2	Time: 2019/10/05 - 17:04
Limit: FCC_Part15.209(3m)	Engineer: Bacon Dong
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: HAN Access Point	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11ax-HE20 at Channel 2412MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			2390.000	49.264	19.405	-4.736	54.000	29.859	AV
2		*	2410.128	98.495	68.687	N/A	N/A	29.808	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC2	Time: 2019/10/05 - 17:15
Limit: FCC_Part15.209(3m)	Engineer: Bacon Dong
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: HAN Access Point	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11ax-HE20 at Channel 2462MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		*	2461.096	112.034	82.298	N/A	N/A	29.736	PK
2			2483.500	66.586	36.812	-7.414	74.000	29.774	PK
3			2484.208	67.984	38.209	-6.016	74.000	29.775	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC2	Time: 2019/10/05 - 17:17
Limit: FCC_Part15.209(3m)	Engineer: Bacon Dong
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: HAN Access Point	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11ax-HE20 at Channel 2462MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		*	2456.368	98.369	68.638	N/A	N/A	29.731	AV
2			2483.500	52.547	22.773	-1.453	54.000	29.774	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC2	Time: 2019/10/05 - 17:14
Limit: FCC_Part15.209(3m)	Engineer: Bacon Dong
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: HAN Access Point	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11ax-HE20 at Channel 2462MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		*	2463.808	109.064	79.326	N/A	N/A	29.738	PK
2			2483.500	65.795	36.021	-8.205	74.000	29.774	PK
3			2483.776	66.585	36.811	-7.415	74.000	29.774	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC2	Time: 2019/10/05 - 17:13
Limit: FCC_Part15.209(3m)	Engineer: Bacon Dong
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: HAN Access Point	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11ax-HE20 at Channel 2462MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		*	2464.216	96.445	66.706	N/A	N/A	29.739	AV
2			2483.500	52.962	23.188	-1.038	54.000	29.774	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC2	Time: 2019/10/05 - 16:47
Limit: FCC_Part15.209(3m)	Engineer: Bacon Dong
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: HAN Access Point	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11ax-HE40 at Channel 2422MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			2389.398	70.434	40.574	-3.566	74.000	29.860	PK
2			2390.000	65.981	36.122	-8.019	74.000	29.859	PK
3		*	2426.424	110.142	80.372	N/A	N/A	29.770	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC2	Time: 2019/10/05 - 16:46
Limit: FCC_Part15.209(3m)	Engineer: Bacon Dong
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: HAN Access Point	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11ax-HE40 at Channel 2422MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			2386.692	53.465	23.598	-0.535	54.000	29.867	AV
2			2390.000	51.179	21.320	-2.821	54.000	29.859	AV
3		*	2426.490	97.574	67.804	N/A	N/A	29.770	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC2	Time: 2019/10/05 - 16:49
Limit: FCC_Part15.209(3m)	Engineer: Bacon Dong
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: HAN Access Point	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11ax-HE40 at Channel 2422MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			2388.540	66.575	36.712	-7.425	74.000	29.863	PK
2			2390.000	64.056	34.197	-9.944	74.000	29.859	PK
3		*	2430.978	108.134	78.375	N/A	N/A	29.759	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC2	Time: 2019/10/05 - 16:50
Limit: FCC_Part15.209(3m)	Engineer: Bacon Dong
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: HAN Access Point	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11ax-HE40 at Channel 2422MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			2390.000	50.005	20.146	-3.995	54.000	29.859	AV
2		*	2425.302	95.504	65.732	N/A	N/A	29.772	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC2	Time: 2019/10/05 - 16:55
Limit: FCC_Part15.209(3m)	Engineer: Bacon Dong
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: HAN Access Point	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11ax-HE40 at Channel 2452MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		*	2456.956	109.186	79.454	N/A	N/A	29.732	PK
2			2483.500	67.165	37.391	-6.835	74.000	29.774	PK
3			2486.876	68.198	38.418	-5.802	74.000	29.780	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC2	Time: 2019/10/05 - 16:54
Limit: FCC_Part15.209(3m)	Engineer: Bacon Dong
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: HAN Access Point	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11ax-HE40 at Channel 2452MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		*	2446.212	96.015	66.293	N/A	N/A	29.722	AV
2			2483.500	53.009	23.235	-0.991	54.000	29.774	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC2	Time: 2019/10/05 - 16:56
Limit: FCC_Part15.209(3m)	Engineer: Bacon Dong
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: HAN Access Point	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11ax-HE40 at Channel 2452MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		*	2440.058	106.882	77.145	N/A	N/A	29.737	PK
2			2483.500	66.362	36.588	-7.638	74.000	29.774	PK
3			2487.046	67.175	37.395	-6.825	74.000	29.780	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC2	Time: 2019/10/05 - 16:57
Limit: FCC_Part15.209(3m)	Engineer: Bacon Dong
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: HAN Access Point	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11ax-HE40 at Channel 2452MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		*	2435.468	93.200	63.452	N/A	N/A	29.748	AV
2			2483.500	52.936	23.162	-1.064	54.000	29.774	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

For Scan Antenna

Site: AC1	Time: 2019/10/29 - 20:54
Limit: FCC_Part15.209(3m)	Margin: 0
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: HAN Access Point	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11b at channel 2412MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			2380.448	59.799	27.369	-14.201	74.000	32.431	PK
2			2390.000	58.390	25.977	-15.610	74.000	32.413	PK
3		*	2412.032	100.905	68.521	N/A	N/A	32.384	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2019/10/29 - 20:56
Limit: FCC_Part15.209(3m)	Margin: 0
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: HAN Access Point	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11b at channel 2412MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			2390.000	45.163	12.750	-8.837	54.000	32.413	AV
2		*	2411.136	97.202	64.817	N/A	N/A	32.385	AV

Note: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2019/10/29 - 20:57
Limit: FCC_Part15.209(3m)	Margin: 0
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: HAN Access Point	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11b at channel 2412MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			2370.312	59.317	26.865	-14.683	74.000	32.452	PK
2			2390.000	58.101	25.688	-15.899	74.000	32.413	PK
3		*	2411.976	96.863	64.479	N/A	N/A	32.384	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2019/10/29 - 20:59
Limit: FCC_Part15.209(3m)	Margin: 0
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: HAN Access Point	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11b at channel 2412MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			2390.000	45.135	12.722	-8.865	54.000	32.413	AV
2		*	2411.136	93.227	60.842	N/A	N/A	32.385	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2019/10/29 - 21:00
Limit: FCC_Part15.209(3m)	Margin: 0
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: HAN Access Point	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11b at channel 2462MHz	



No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		*	2460.544	100.608	68.244	N/A	N/A	32.364	PK
2			2483.500	58.094	25.679	-15.906	74.000	32.416	PK
3			2485.984	59.869	27.449	-14.131	74.000	32.420	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2019/10/29 - 21:01
Limit: FCC_Part15.209(3m)	Margin: 0
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: HAN Access Point	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11b at channel 2462MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		*	2461.168	97.270	64.905	N/A	N/A	32.365	AV
2			2483.500	45.647	13.232	-8.353	54.000	32.416	AV

Note: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2019/10/29 - 21:02
Limit: FCC_Part15.209(3m)	Margin: 0
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: HAN Access Point	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11b at channel 2462MHz	



No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		*	2460.736	98.116	65.752	N/A	N/A	32.364	PK
2			2483.500	57.828	25.413	-16.172	74.000	32.416	PK
3			2491.504	60.017	27.586	-13.983	74.000	32.431	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2019/10/29 - 21:02
Limit: FCC_Part15.209(3m)	Margin: 0
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: HAN Access Point	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11b at channel 2462MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		*	2461.168	94.739	62.374	N/A	N/A	32.365	AV
2			2483.500	45.618	13.203	-8.382	54.000	32.416	AV

Note: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2019/10/29 - 21:03
Limit: FCC_Part15.209(3m)	Margin: 0
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: HAN Access Point	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11g at channel 2412MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			2321.368	59.953	27.327	-14.047	74.000	32.626	PK
2			2390.000	58.318	25.905	-15.682	74.000	32.413	PK
3		*	2416.512	99.300	66.921	N/A	N/A	32.379	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2019/10/29 - 21:04
Limit: FCC_Part15.209(3m)	Margin: 0
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: HAN Access Point	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11g at channel 2412MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			2390.000	45.297	12.884	-8.703	54.000	32.413	AV
2		*	2417.240	86.929	54.551	N/A	N/A	32.378	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2019/10/29 - 21:05
Limit: FCC_Part15.209(3m)	Margin: 0
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: HAN Access Point	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11g at channel 2412MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			2359.000	59.421	26.944	-14.579	74.000	32.477	PK
2			2390.000	57.940	25.527	-16.060	74.000	32.413	PK
3		*	2409.792	94.246	61.859	N/A	N/A	32.386	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2019/10/29 - 21:06
Limit: FCC_Part15.209(3m)	Margin: 0
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: HAN Access Point	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11g at channel 2412MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			2390.000	45.181	12.768	-8.819	54.000	32.413	AV
2		*	2414.272	81.961	49.579	N/A	N/A	32.382	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2019/10/29 - 21:06
Limit: FCC_Part15.209(3m)	Margin: 0
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: HAN Access Point	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11g at channel 2462MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		*	2458.144	102.474	70.115	N/A	N/A	32.359	PK
2			2483.500	60.894	28.479	-13.106	74.000	32.416	PK
3			2484.136	62.452	30.035	-11.548	74.000	32.417	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2019/10/29 - 21:08
Limit: FCC_Part15.209(3m)	Margin: 0
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: HAN Access Point	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11g at channel 2462MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		*	2466.016	89.109	56.734	N/A	N/A	32.375	AV
2			2483.500	47.144	14.729	-6.856	54.000	32.416	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2019/10/29 - 21:08
Limit: FCC_Part15.209(3m)	Margin: 0
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: HAN Access Point	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11g at channel 2462MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		*	2458.360	100.029	67.670	N/A	N/A	32.359	PK
2			2483.500	60.071	27.656	-13.929	74.000	32.416	PK
3			2484.232	60.827	28.410	-13.173	74.000	32.417	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2019/10/29 - 21:10
Limit: FCC_Part15.209(3m)	Margin: 0
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: HAN Access Point	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11g at channel 2462MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		*	2466.328	86.926	54.551	N/A	N/A	32.376	AV
2			2483.500	46.568	14.153	-7.432	54.000	32.416	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

For AP321e

Site: AC1	Time: 2019/10/18 - 02:20
Limit: FCC_Part15.209(3m)	Engineer: Bacon Dong
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: HAN Access Point	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11b at Channel 2412MHz	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2371.264	60.743	28.294	-13.257	74.000	32.449	PK
2		2390.000	59.664	27.251	-14.336	74.000	32.413	PK
3	*	2410.800	101.413	69.027	N/A	N/A	32.386	PK

Note: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2019/10/18 - 02:29
Limit: FCC_Part15.209(3m)	Engineer: Bacon Dong
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: HAN Access Point	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11b at Channel 2412MHz	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2390.000	47.120	14.707	-6.880	54.000	32.413	AV
2	*	2411.080	96.991	64.606	N/A	N/A	32.385	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2019/10/18 - 02:34
Limit: FCC_Part15.209(3m)	Engineer: Bacon Dong
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: HAN Access Point	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11b at Channel 2412MHz	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2374.568	61.286	28.844	-12.714	74.000	32.442	PK
2		2390.000	59.325	26.912	-14.675	74.000	32.413	PK
3	*	2412.032	114.807	82.423	N/A	N/A	32.384	PK

Note: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2019/10/18 - 02:37
Limit: FCC_Part15.209(3m)	Engineer: Bacon Dong
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: HAN Access Point	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11b at Channel 2412MHz	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2390.000	47.900	15.487	-6.100	54.000	32.413	AV
2	*	2411.136	111.555	79.170	N/A	N/A	32.385	AV

Note: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2019/10/18 - 02:38
Limit: FCC_Part15.209(3m)	Engineer: Bacon Dong
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: HAN Access Point	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11b at Channel 2462MHz	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2460.856	99.103	66.739	N/A	N/A	32.364	PK
2		2483.500	59.427	27.012	-14.573	74.000	32.416	PK
3		2485.504	61.230	28.811	-12.770	74.000	32.419	PK

Note: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2019/10/18 - 02:40
Limit: FCC_Part15.209(3m)	Engineer: Bacon Dong
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: HAN Access Point	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11b at Channel 2462MHz	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2461.384	95.873	63.508	N/A	N/A	32.365	AV
2		2483.500	47.426	15.011	-6.574	54.000	32.416	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2019/10/18 - 02:41
Limit: FCC_Part15.209(3m)	Engineer: Bacon Dong
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: HAN Access Point	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11b at Channel 2462MHz	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2460.856	115.648	83.284	N/A	N/A	32.364	PK
2		2483.500	60.160	27.745	-13.840	74.000	32.416	PK
3		2487.112	60.910	28.487	-13.090	74.000	32.422	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2019/10/18 - 02:42
Limit: FCC_Part15.209(3m)	Engineer: Bacon Dong
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: HAN Access Point	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11b at Channel 2462MHz	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2461.312	112.514	80.149	N/A	N/A	32.365	AV
2		2483.500	47.897	15.482	-6.103	54.000	32.416	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2019/10/18 - 02:54
Limit: FCC_Part15.209(3m)	Engineer: Bacon Dong
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: HAN Access Point	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11g at Channel 2412MHz	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2359.224	62.499	30.022	-11.501	74.000	32.477	PK
2		2390.000	61.109	28.696	-12.891	74.000	32.413	PK
3	*	2409.512	103.569	71.182	N/A	N/A	32.387	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2019/10/18 - 02:56
Limit: FCC_Part15.209(3m)	Engineer: Bacon Dong
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: HAN Access Point	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11g at Channel 2412MHz	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2390.000	49.792	17.379	-4.208	54.000	32.413	AV
2	*	2409.792	93.240	60.853	N/A	N/A	32.386	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2019/10/18 - 02:53
Limit: FCC_Part15.209(3m)	Engineer: Bacon Dong
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: HAN Access Point	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11g at Channel 2412MHz	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2387.112	69.010	36.592	-4.990	74.000	32.418	PK
2		2390.000	67.487	35.074	-6.513	74.000	32.413	PK
3	*	2417.296	115.084	82.706	N/A	N/A	32.378	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2019/10/18 - 02:49
Limit: FCC_Part15.209(3m)	Engineer: Bacon Dong
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: HAN Access Point	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11g at Channel 2412MHz	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2388.568	53.419	21.004	-0.581	54.000	32.416	AV
2		2390.000	53.249	20.836	-0.751	54.000	32.413	AV
3	*	2417.408	104.797	72.419	N/A	N/A	32.378	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2019/10/18 - 03:07
Limit: FCC_Part15.209(3m)	Engineer: Bacon Dong
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: HAN Access Point	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11g at Channel 2462MHz	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2459.536	102.834	70.472	N/A	N/A	32.362	PK
2		2483.500	61.936	29.521	-12.064	74.000	32.416	PK
3		2487.256	62.570	30.147	-11.430	74.000	32.422	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2019/10/18 - 03:08
Limit: FCC_Part15.209(3m)	Engineer: Bacon Dong
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: HAN Access Point	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11g at Channel 2462MHz	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2459.656	91.969	59.607	N/A	N/A	32.362	AV
2		2483.500	49.424	17.009	-4.576	54.000	32.416	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2019/10/18 - 03:05
Limit: FCC_Part15.209(3m)	Engineer: Bacon Dong
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: HAN Access Point	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11g at Channel 2462MHz	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2457.448	114.645	82.287	N/A	N/A	32.357	PK
2		2483.500	66.976	34.561	-7.024	74.000	32.416	PK
3		2483.728	67.238	34.822	-6.762	74.000	32.416	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2019/10/18 - 03:03
Limit: FCC_Part15.209(3m)	Engineer: Bacon Dong
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: HAN Access Point	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11g at Channel 2462MHz	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2458.480	104.381	72.021	N/A	N/A	32.359	AV
2		2483.500	53.469	21.054	-0.531	54.000	32.416	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2019/10/18 - 03:18
Limit: FCC_Part15.209(3m)	Engineer: Bacon Dong
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: HAN Access Point	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11n-HT20 at Channel 2412MHz	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2390.000	61.157	28.744	-12.843	74.000	32.413	PK
2	*	2406.936	102.847	70.457	N/A	N/A	32.390	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2019/10/18 - 03:22
Limit: FCC_Part15.209(3m)	Engineer: Bacon Dong
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: HAN Access Point	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11n-HT20 at Channel 2412MHz	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2390.000	49.136	16.723	-4.864	54.000	32.413	AV
2	*	2407.104	92.643	60.253	N/A	N/A	32.390	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2019/10/18 - 03:16
Limit: FCC_Part15.209(3m)	Engineer: Bacon Dong
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: HAN Access Point	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11n-HT20 at Channel 2412MHz	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2389.016	68.715	36.300	-5.285	74.000	32.414	PK
2		2390.000	67.278	34.865	-6.722	74.000	32.413	PK
3	*	2412.144	114.637	82.253	N/A	N/A	32.384	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2019/10/18 - 03:15
Limit: FCC_Part15.209(3m)	Engineer: Bacon Dong
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: HAN Access Point	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11n-HT20 at Channel 2412MHz	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2390.000	52.829	20.416	-1.171	54.000	32.413	AV
2	*	2412.928	104.407	72.024	N/A	N/A	32.383	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2019/10/18 - 03:47
Limit: FCC_Part15.209(3m)	Engineer: Bacon Dong
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: HAN Access Point	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11n-HT20 at Channel 2462MHz	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2464.840	100.981	68.609	N/A	N/A	32.372	PK
2		2483.500	61.840	29.425	-12.160	74.000	32.416	PK
3		2485.144	63.318	30.899	-10.682	74.000	32.419	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2019/10/18 - 03:48
Limit: FCC_Part15.209(3m)	Engineer: Bacon Dong
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: HAN Access Point	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11n-HT20 at Channel 2462MHz	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2457.760	91.037	58.679	N/A	N/A	32.359	AV
2		2483.500	49.177	16.762	-4.823	54.000	32.416	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2019/10/18 - 03:45
Limit: FCC_Part15.209(3m)	Engineer: Bacon Dong
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: HAN Access Point	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11n-HT20 at Channel 2462MHz	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2462.992	114.354	81.986	N/A	N/A	32.368	PK
2		2483.500	67.369	34.954	-6.631	74.000	32.416	PK
3		2484.640	67.839	35.421	-6.161	74.000	32.418	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2019/10/18 - 03:30
Limit: FCC_Part15.209(3m)	Margin: 0
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: HAN Access Point	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11n-HT20 at Channel 2462MHz	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2463.064	103.648	71.280	N/A	N/A	32.368	AV
2		2483.500	53.004	20.589	-0.996	54.000	32.416	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2019/10/18 - 04:01
Limit: FCC_Part15.209(3m)	Engineer: Bacon Dong
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: HAN Access Point	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11n-HT40 at Channel 2422MHz	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2373.756	62.868	30.424	-11.132	74.000	32.444	PK
2		2390.000	61.639	29.226	-12.361	74.000	32.413	PK
3	*	2428.074	100.858	68.492	N/A	N/A	32.366	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2019/10/18 - 04:02
Limit: FCC_Part15.209(3m)	Engineer: Bacon Dong
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: HAN Access Point	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11n-HT40 at Channel 2422MHz	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2390.000	49.106	16.693	-4.894	54.000	32.413	AV
2	*	2427.018	90.142	57.775	N/A	N/A	32.367	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2019/10/18 - 03:59
Limit: FCC_Part15.209(3m)	Engineer: Bacon Dong
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: HAN Access Point	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11n-HT40 at Channel 2422MHz	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2387.880	66.857	34.440	-7.143	74.000	32.416	PK
2		2390.000	65.903	33.490	-8.097	74.000	32.413	PK
3	*	2412.894	111.894	79.511	N/A	N/A	32.383	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2019/10/18 - 03:58
Limit: FCC_Part15.209(3m)	Engineer: Bacon Dong
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: HAN Access Point	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11n-HT40 at Channel 2422MHz	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2390.000	53.371	20.958	-0.629	54.000	32.413	AV
2	*	2412.564	100.965	68.581	N/A	N/A	32.384	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2019/10/18 - 04:55
Limit: FCC_Part15.209(3m)	Engineer: Bacon Dong
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: HAN Access Point	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11n-HT40 at Channel 2452MHz	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2458.452	97.873	65.513	N/A	N/A	32.359	PK
2		2483.500	61.589	29.174	-12.411	74.000	32.416	PK
3		2485.312	62.796	30.377	-11.204	74.000	32.419	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2019/10/18 - 04:56
Limit: FCC_Part15.209(3m)	Engineer: Bacon Dong
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: HAN Access Point	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11n-HT40 at Channel 2452MHz	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2446.926	87.304	54.966	N/A	N/A	32.338	AV
2		2483.500	49.115	16.700	-4.885	54.000	32.416	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2019/10/18 - 04:54
Limit: FCC_Part15.209(3m)	Engineer: Bacon Dong
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: HAN Access Point	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11n-HT40 at Channel 2452MHz	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2453.726	109.723	77.372	N/A	N/A	32.351	PK
2		2483.500	65.495	33.080	-8.505	74.000	32.416	PK
3		2484.394	67.936	35.519	-6.064	74.000	32.417	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2019/10/18 - 04:52
Limit: FCC_Part15.209(3m)	Engineer: Bacon Dong
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: HAN Access Point	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11n-HT40 at Channel 2452MHz	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2453.318	99.414	67.064	N/A	N/A	32.350	AV
2		2483.500	53.454	21.039	-0.546	54.000	32.416	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2019/10/18 - 05:05
Limit: FCC_Part15.209(3m)	Engineer: Bacon Dong
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: HAN Access Point	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11VHT20 at Channel 2412MHz	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2368.576	63.460	31.004	-10.540	74.000	32.455	PK
2		2390.000	61.645	29.232	-12.355	74.000	32.413	PK
3	*	2407.440	102.671	70.282	N/A	N/A	32.389	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2019/10/18 - 05:06
Limit: FCC_Part15.209(3m)	Engineer: Bacon Dong
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: HAN Access Point	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11VHT20 at Channel 2412MHz	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2390.000	49.114	16.701	-4.886	54.000	32.413	AV
2	*	2408.336	92.096	59.708	N/A	N/A	32.389	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2019/10/18 - 05:03
Limit: FCC_Part15.209(3m)	Engineer: Bacon Dong
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: HAN Access Point	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11VHT20 at Channel 2412MHz	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2388.848	67.181	34.766	-6.819	74.000	32.415	PK
2		2390.000	66.842	34.429	-7.158	74.000	32.413	PK
3	*	2412.984	115.299	82.916	N/A	N/A	32.383	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2019/10/18 - 05:01
Limit: FCC_Part15.209(3m)	Engineer: Bacon Dong
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: HAN Access Point	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11VHT20 at Channel 2412MHz	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2390.000	53.005	20.592	-0.995	54.000	32.413	AV
2	*	2413.768	104.089	71.707	N/A	N/A	32.382	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2019/10/18 - 05:13
Limit: FCC_Part15.209(3m)	Engineer: Bacon Dong
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: HAN Access Point	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11VHT20 at Channel 2462MHz	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2465.512	101.019	68.646	N/A	N/A	32.373	PK
2		2483.500	61.271	28.856	-12.729	74.000	32.416	PK
3		2485.720	63.564	31.144	-10.436	74.000	32.420	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2019/10/18 - 05:18
Limit: FCC_Part15.209(3m)	Engineer: Bacon Dong
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: HAN Access Point	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11VHT40 at Channel 2422MHz	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2390.000	66.484	34.071	-7.516	74.000	32.413	PK
2	*	2424.312	112.214	79.844	N/A	N/A	32.370	PK

Note: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2019/10/18 - 05:12
Limit: FCC_Part15.209(3m)	Engineer: Bacon Dong
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: HAN Access Point	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11VHT20 at Channel 2462MHz	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2463.592	114.457	82.088	N/A	N/A	32.369	PK
2		2483.500	67.272	34.857	-6.728	74.000	32.416	PK
3		2483.704	67.604	35.188	-6.396	74.000	32.416	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2019/10/18 - 05:10
Limit: FCC_Part15.209(3m)	Engineer: Bacon Dong
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: HAN Access Point	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11VHT20 at Channel 2462MHz	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2464.072	103.480	71.110	N/A	N/A	32.369	AV
2		2483.500	52.718	20.303	-1.282	54.000	32.416	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2019/10/18 - 05:26
Limit: FCC_Part15.209(3m)	Engineer: Bacon Dong
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: HAN Access Point	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11VHT40 at Channel 2422MHz	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2379.498	63.193	30.761	-10.807	74.000	32.432	PK
2		2390.000	62.400	29.987	-11.600	74.000	32.413	PK
3	*	2427.546	100.645	68.279	N/A	N/A	32.366	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2019/10/18 - 05:27
Limit: FCC_Part15.209(3m)	Engineer: Bacon Dong
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: HAN Access Point	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11VHT40 at Channel 2422MHz	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2390.000	49.246	16.833	-4.754	54.000	32.413	AV
2	*	2427.612	90.095	57.729	N/A	N/A	32.367	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2019/10/18 - 05:24
Limit: FCC_Part15.209(3m)	Engineer: Bacon Dong
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: HAN Access Point	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11VHT40 at Channel 2422MHz	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2384.844	66.978	34.556	-7.022	74.000	32.422	PK
2		2390.000	65.669	33.256	-8.331	74.000	32.413	PK
3	*	2423.850	111.845	79.474	N/A	N/A	32.371	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2019/10/18 - 05:19
Limit: FCC_Part15.209(3m)	Engineer: Bacon Dong
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: HAN Access Point	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11VHT40 at Channel 2422MHz	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2390.000	53.432	21.019	-0.568	54.000	32.413	AV
2	*	2423.322	101.276	68.905	N/A	N/A	32.371	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2019/10/18 - 05:36
Limit: FCC_Part15.209(3m)	Engineer: Bacon Dong
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: HAN Access Point	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11VHT40 at Channel 2452MHz	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2457.534	96.998	64.640	N/A	N/A	32.358	PK
2		2483.500	61.476	29.061	-12.524	74.000	32.416	PK
3		2485.380	62.830	30.411	-11.170	74.000	32.419	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2019/10/18 - 05:37
Limit: FCC_Part15.209(3m)	Engineer: Bacon Dong
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: HAN Access Point	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11VHT40 at Channel 2452MHz	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2447.402	87.118	54.779	N/A	N/A	32.338	AV
2		2483.500	49.082	16.667	-4.918	54.000	32.416	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2019/10/18 - 05:34
Limit: FCC_Part15.209(3m)	Engineer: Bacon Dong
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: HAN Access Point	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11VHT40 at Channel 2452MHz	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2463.144	109.603	77.235	N/A	N/A	32.368	PK
2		2483.500	65.898	33.483	-8.102	74.000	32.416	PK
3		2485.992	66.345	33.925	-7.655	74.000	32.420	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2019/10/18 - 05:33
Limit: FCC_Part15.209(3m)	Engineer: Bacon Dong
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: HAN Access Point	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11VHT40 at Channel 2452MHz	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2454.610	98.837	66.485	N/A	N/A	32.353	AV
2		2483.500	53.152	20.737	-0.848	54.000	32.416	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2019/10/18 - 07:06
Limit: FCC_Part15.209(3m)	Engineer: Bacon Dong
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: HAN Access Point	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11ax-HE20 at Channel 2412MHz	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2367.008	63.305	30.846	-10.695	74.000	32.459	PK
2		2390.000	61.771	29.358	-12.229	74.000	32.413	PK
3	*	2407.160	104.425	72.035	N/A	N/A	32.390	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2019/10/18 - 07:07
Limit: FCC_Part15.209(3m)	Engineer: Bacon Dong
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: HAN Access Point	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11ax-HE20 at Channel 2412MHz	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2390.000	49.045	16.632	-4.955	54.000	32.413	AV
2	*	2408.168	91.376	58.987	N/A	N/A	32.388	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2019/10/18 - 07:05
Limit: FCC_Part15.209(3m)	Engineer: Bacon Dong
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: HAN Access Point	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11ax-HE20 at Channel 2412MHz	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2389.240	68.491	36.077	-5.509	74.000	32.414	PK
2		2390.000	66.749	34.336	-7.251	74.000	32.413	PK
3	*	2413.544	117.174	84.792	N/A	N/A	32.382	PK

Note: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2019/10/18 - 07:03
Limit: FCC_Part15.209(3m)	Engineer: Bacon Dong
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: HAN Access Point	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11ax-HE20 at Channel 2412MHz	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2390.000	53.356	20.943	-0.644	54.000	32.413	AV
2	*	2412.872	103.552	71.169	N/A	N/A	32.383	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2019/10/18 - 07:13
Limit: FCC_Part15.209(3m)	Engineer: Bacon Dong
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: HAN Access Point	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11ax-HE20 at Channel 2462MHz	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2457.904	103.587	71.228	N/A	N/A	32.359	PK
2		2483.500	62.641	30.226	-11.359	74.000	32.416	PK
3		2485.312	63.006	30.587	-10.994	74.000	32.419	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2019/10/18 - 07:14
Limit: FCC_Part15.209(3m)	Engineer: Bacon Dong
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: HAN Access Point	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11ax-HE20 at Channel 2462MHz	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2458.168	90.474	58.115	N/A	N/A	32.359	AV
2		2483.500	49.075	16.660	-4.925	54.000	32.416	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2019/10/18 - 07:11
Limit: FCC_Part15.209(3m)	Engineer: Bacon Dong
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: HAN Access Point	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11ax-HE20 at Channel 2462MHz	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2463.160	116.694	84.326	N/A	N/A	32.368	PK
2		2483.500	66.800	34.385	-7.200	74.000	32.416	PK
3		2484.064	68.006	35.589	-5.994	74.000	32.417	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2019/10/18 - 07:10
Limit: FCC_Part15.209(3m)	Engineer: Bacon Dong
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: HAN Access Point	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11ax-HE20 at Channel 2462MHz	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2463.256	102.928	70.560	N/A	N/A	32.369	AV
2		2483.500	53.537	21.122	-0.463	54.000	32.416	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2019/10/18 - 07:19
Limit: FCC_Part15.209(3m)	Engineer: Bacon Dong
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: HAN Access Point	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11ax-HE40 at Channel 2422MHz	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2385.108	63.395	30.973	-10.605	74.000	32.422	PK
2		2390.000	61.535	29.122	-12.465	74.000	32.413	PK
3	*	2426.952	102.717	70.350	N/A	N/A	32.367	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2019/10/18 - 07:20
Limit: FCC_Part15.209(3m)	Engineer: Bacon Dong
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: HAN Access Point	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11ax-HE40 at Channel 2422MHz	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2390.000	49.116	16.703	-4.884	54.000	32.413	AV
2	*	2427.216	89.197	56.830	N/A	N/A	32.367	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2019/10/18 - 07:18
Limit: FCC_Part15.209(3m)	Engineer: Bacon Dong
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: HAN Access Point	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11ax-HE40 at Channel 2422MHz	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2387.286	67.431	35.013	-6.569	74.000	32.418	PK
2		2390.000	65.420	33.007	-8.580	74.000	32.413	PK
3	*	2432.298	114.404	82.045	N/A	N/A	32.359	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2019/10/18 - 07:17
Limit: FCC_Part15.209(3m)	Engineer: Bacon Dong
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: HAN Access Point	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11ax-HE40 at Channel 2422MHz	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2390.000	53.215	20.802	-0.785	54.000	32.413	AV
2	*	2423.652	100.543	68.172	N/A	N/A	32.371	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2019/10/18 - 07:29
Limit: FCC_Part15.209(3m)	Engineer: Bacon Dong
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: HAN Access Point	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11ax-HE40 at Channel 2452MHz	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2447.844	99.990	67.651	N/A	N/A	32.340	PK
2		2483.500	62.158	29.743	-11.842	74.000	32.416	PK
3		2489.256	62.986	30.559	-11.014	74.000	32.427	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2019/10/18 - 07:30
Limit: FCC_Part15.209(3m)	Engineer: Bacon Dong
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: HAN Access Point	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11ax-HE40 at Channel 2452MHz	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2447.096	86.620	54.282	N/A	N/A	32.338	AV
2		2483.500	49.071	16.656	-4.929	54.000	32.416	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2019/10/18 - 07:27
Limit: FCC_Part15.209(3m)	Engineer: Bacon Dong
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: HAN Access Point	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11ax-HE40 at Channel 2452MHz	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2442.234	112.589	80.247	N/A	N/A	32.342	PK
2		2483.500	67.393	34.978	-6.607	74.000	32.416	PK
3		2484.292	67.599	35.182	-6.401	74.000	32.417	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2019/10/18 - 07:25
Limit: FCC_Part15.209(3m)	Engineer: Bacon Dong
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: HAN Access Point	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11ax-HE40 at Channel 2452MHz	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2442.540	98.568	66.226	N/A	N/A	32.342	AV
2		2483.500	52.987	20.572	-1.013	54.000	32.416	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

7.8. AC Conducted Emissions Measurement


7.8.1. Test Limit

FCC Part 15 Subpart C Paragraph 15.207 Limits		
Frequency (MHz)	QP (dBuV)	AV (dBuV)
0.15 ~ 0.50	66 ~ 56	56 ~ 46
0.50 ~ 5.0	56	46
5.0 ~ 30	60	50

Note 1: The lower limit shall apply at the transition frequencies.


Note 2: The limit decreases linearly with the logarithm of the frequency in the range 0.15MHz to 0.5MHz.

7.8.2. Test Setup



7.8.3.Test Result

Site: SR2	Time: 2019/12/17 - 09:52
Limit: FCC_Part15.207_CE_AC Power	Engineer: Liz Yuan
Probe: ENV216_101683_Filter On	Polarity: Line
EUT: HAN Access Point	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11b at channel 2412MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV)	Factor (dB)	Type
1			0.150	48.169	37.001	-17.831	66.000	11.168	QP
2			0.150	29.512	18.344	-26.488	56.000	11.168	AV
3			0.170	48.351	38.273	-16.610	64.960	10.078	QP
4			0.170	38.306	28.229	-16.654	54.960	10.078	AV
5			0.358	44.946	34.895	-13.829	58.775	10.051	QP
6			0.358	29.858	19.807	-18.917	48.775	10.051	AV
7			0.407	48.091	38.000	-9.618	57.709	10.091	QP
8		*	0.407	43.291	33.200	-4.418	47.709	10.091	AV
9			3.710	38.798	28.853	-17.202	56.000	9.946	QP
10			3.710	30.297	20.351	-15.703	46.000	9.946	AV
11			8.394	37.138	26.968	-22.862	60.000	10.170	QP
12			8.394	30.690	20.520	-19.310	50.000	10.170	AV

Note: Measure Level (dBμV) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + LISN Factor (dB)

Site: SR2	Time: 2019/12/17 - 10:03
Limit: FCC_Part15.207_CE_AC Power	Engineer: Liz Yuan
Probe: ENV216_101683_Filter On	Polarity: Neutral
EUT: HAN Access Point	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11b at channel 2412MHz	



No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV)	Factor (dB)	Type
1			0.154	44.836	34.120	-20.946	65.781	10.716	QP
2			0.154	26.150	15.434	-29.632	55.781	10.716	AV
3			0.174	45.287	35.230	-19.481	64.767	10.057	QP
4			0.174	35.444	25.387	-19.324	54.767	10.057	AV
5			0.410	47.338	37.219	-10.310	57.648	10.119	QP
6		*	0.410	43.916	33.796	-3.733	47.648	10.119	AV
7			1.454	36.035	26.143	-19.965	56.000	9.892	QP
8			1.454	28.846	18.954	-17.154	46.000	9.892	AV
9			3.602	36.304	26.380	-19.696	56.000	9.924	QP
10			3.602	27.602	17.678	-18.398	46.000	9.924	AV
11			12.002	36.552	26.441	-23.448	60.000	10.111	QP
12			12.002	28.125	18.014	-21.875	50.000	10.111	AV

Note: Measure Level (dBμV) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + LISN Factor (dB)

8. CONCLUSION

The data collected relate only the item(s) tested and show that the unit is compliance with Part 15C of the FCC rules.

The End

Appendix A – Test Setup Photograph

Refer to “1909RSU036-UT” file.

Appendix B – EUT Photograph

Refer to “1909RSU036-UE” file.